

Submit 1 Copy To Appropriate District Office  
 District I - (575) 393-6161  
 1625 N. French Dr., Hobbs, NM 88240  
 District II - (575) 748-1283  
 811 S. First St., Artesia, NM 88210  
 District III - (505) 334-6178  
 1000 Rio Brazos Rd., Aztec, NM 87410  
 District IV - (505) 476-3460  
 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
 Energy, Minerals and Natural Resources

Form C-103  
 Revised August 1, 2011

OIL CONSERVATION DIVISION  
 1220 South St. Francis Dr.  
 Santa Fe, NM 87505

WELL API NO. 30-015-40953
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name WEST SHUGART 2 19 30 STATE
8. Well Number 2H
9. OGRID Number 4323
10. Pool name or Wildcat DELDWARE RIVER; BONE SPRING
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3517' GR

**SUNDRY NOTICES AND REPORTS ON WELLS**  
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well  Gas Well  Other


2. Name of Operator  
Chevron, U S A, Inc.

3. Address of Operator  
15 Smith Road  
Midland, TX 79705

4. Well Location  
 Unit Letter 1 : 1920' feet from the South line and 350' feet from the East line  
 Section 2 Township 19 S Range 30 E NMPM County EDDY

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

<b>NOTICE OF INTENTION TO:</b> PERFORM REMEDIAL WORK <input type="checkbox"/> PLUG AND ABANDON <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> MULTIPLE COMPL <input type="checkbox"/> DOWNHOLE COMMINGLE <input type="checkbox"/> OTHER: <input type="checkbox"/>	<b>SUBSEQUENT REPORT OF:</b> REMEDIAL WORK <input type="checkbox"/> ALTERING CASING <input type="checkbox"/> COMMENCE DRILLING OPNS. <input type="checkbox"/> PANDA <input type="checkbox"/> CASING/CEMENT JOB <input checked="" type="checkbox"/> OTHER: <input type="checkbox"/>
---	--



13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

ON 6/10/2013, DRILLED 12 1/4" HOLE TO 3536'. RAN 88 JTS 9.625 CSG, 40.0#, K-55, LTC AND SET @ 3536'. INSTALL CEMENT HEAD, PRESSURE TEST TO 3500 PSI, PUMP 20 BBL FW SPACER HEAD - 161 BBL, 500 SX, YIELD 1.81, 12.3 PPG, TAIL - 74 BBL, 300 SX, YIELD 1.38, @ 14.2 PPG (2 PPB CEMENT) SHUT DOWN, DROP DART WASH UP, DISPLACE WITH 126 BBL F/W, 138 BBL BW, (264 TOTAL), INSTALL CEMENT HEAD, FILL LINES, PRESSURE TEST TO 3000 PSI, 20 BBL FW SPACER, LEAD - 161 BBL, 500 SX, YIELD 1.81, 12.3 PPG, TAIL - 73 BBL, 300 SX, YIELD 1.38, @ 14.2 PPG (2 PPB CEMENT) SHUT DOWN, DROP DART WASH UP, WITH 126 BBL F/W, 138 BBL BW, (264 TOTAL), BUMP PLUG 500 OVER @ 1100 PSI, SET ACP W/ 2100 PSI, BLEED OFF PSI, DROP BOMB & WAIT 10 MINS. PSI UP TO 900 PSI AND OPEN DV TOOL CIRC BOTTOMS UP. CIRC 70 BBL CEMENT TO SURFACE. FULL RETURNS. CIRC THRU DV TOOL. PUMP 20 BBL FRESH WATER, PUMP LEAD (1300 SKS, 419 BBLS, YIELD 1.81, @ 12.3 PPG), TAIL - (250 SKS, 60 BBLS YIELD 1.35, @ 14.2 PPG), DISPLACE W/ 138 BBL F/W BUMP PLUG W/ 1500 OVER @ 2200 PSI AND CLOSE DV TOOL. BLEED 1.5 BBLS BACK, FLOAT HELD, 150 BBL CMT BACK TO PIT. FULL RETURNS. TEST BOPE TO 250 LOW, 5000 HIGH-TEST GOOD. TEST CASING TO 1500 PSI FOR 30 MINUTES-TEST GOOD. RESUME DRLG NEW FORMATION @ 1730 HOURS ON 6/13/2013.

Spud Date:  Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE *Bryan Arrant* TITLE Regulatory Specialist II DATE 6/20/2013

Type or print name Bryan Arrant (Agent) E-mail address: bryan.arrant@chk.com PHONE: (405)935-3782

**For State Use Only**

APPROVED BY *L Wade* TITLE Dist. P Supervisor DATE 6/20/2013

Conditions of Approval (if any):