Submit I Copy To Appropriate District Office	5) 393-6161 Energy, Minerals and Natural Resources Dr., Hobbs, NM 88240 5) 748-1283 OIL CONSERVATION DIVISION 05) 334-6178 1220 South St. Francis Dr.		Form C-103
<u>District I</u> – (575) 393-6161 1625 N. French Dr., Hobbs, NM 88240			Revised August 1, 2011 WELL API NO.
<u>District II</u> – (575) 748-1283 811 S. First St., Artesia, NM 88210			30-015-41307 5. Indicate Type of Lease
<u>District III</u> – (505) 334-6178 1000 Rio Brazos Rd., Aztec, NM 87410			STATE 🛛 FEE 🗌
<u>District IV</u> – (505) 476-3460 1220 S. St. Francis Dr., Santa Fe, NM	Santa Fe, NM 87505		6. State Oil & Gas Lease No.
87505 SUNDRY NOTICES AND REPORTS ON WELLS			7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)			Zircon 1 LI State
1. Type of Well: Oil Well Gas Well Other			8. Well Number 1H
2. Name of Operator Mewbourne Oil Company		9. OGRID Number 14744	
3. Address of Operator		10. Pool name or Wildcat	
PO Box 5270 Hobbs, NM 88241 4. Well Location			Turkey Track; Bone Spring 60660
Unit Letter_L :1350feet from theSouth line and120 feet from theWest line			
Section I Township 19S Range 29E NMPM Eddy County			
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3379' GL			
12 Charles	Annropriate Roy to Indicate N	otura of Notica I	Panort or Other Data
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data			
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING			
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. P AND A			
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐ CASING/CEMENT JOB ☐ DOWNHOLE COMMINGLE ☐			JOB 🖾
DOWNHOLE COMMININGLE [
OTHER: OTHER:			
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of			
proposed completion or recompletion.			
06/07/13 TD 12 ¼" hole @ 1410'. Ran 1410' of 9 ½" 36# J55 LT&C csg. Cemented with 300 sks EconoCem-HLC with additives. Mixed @ 12.6 /g w/ 2.02 yd. Tail w/200 sks HalCem-C w/2% CaCl2. Mixed @ 14.8/g w/1.35 yd. Plug down @ 11:30 PM 06/07/13.			
Circ 105 sks cement to pit. WOC. At 3:00 PM 06/08/13, tested BOPE & csg to 1500# for 30 minutes, held OK. Drilled out with 8 ¾"bit.			
,			RECEIVED
Spud Date: 06/04/2013 Rig Release Date:		JUL 2 3 2013	
		NMOCD ARTESIA	
I hereby certify that the information above is true and complete to the best of my knowledge and belief.			
SIGNATURE Pactic Lathan TITLE Hobbs Regulatory		DATE07/10/13	
Type or print name_Jackie Lathan E-mail address: jlathan@mewbourne.com_ PHONE: 575-393-5905 For State Use Only ### April 1975 For State Use Only			
APPROVED BY:	L TITLE	P. Sepenion	DATE 7/24/2013
Conditions of Approval (if any):		- april 5	DATE 1/0-1/0013

