

Submit 1 Copy To Appropriate District Office

District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised August 1, 2011

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505
REVISED

WELL API NO. 30-015-39958
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name RDX 16
8. Well Number 14H
9. OGRID Number 246289
10. Pool name or Wildcat WILDCAT G-03 S263016K; BONE SPRING
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3090' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well Gas Well Other

2. Name of Operator
RKI Exploration and Production, LLC

3. Address of Operator
210 Park Ave, Ste 900 OKC, OK 73102

4. Well Location
Unit Letter C : 330 feet from the North line and 1650 feet from the West line
Section 16 Township 26S Range 30E NMPM Eddy County

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

- PERFORM REMEDIAL WORK PLUG AND ABANDON
 TEMPORARILY ABANDON CHANGE PLANS
 PULL OR ALTER CASING MULTIPLE COMPL
 DOWNHOLE COMMINGLE

SUBSEQUENT REPORT OF:

- REMEDIAL WORK ALTERING CASING
 COMMENCE DRILLING OPNS. P AND A
 CASING/CEMENT JOB

OTHER:

OTHER:

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Spudded the well on 4/4/2013. On 4/5/2013 drilled 17-1/2 inch hole to 1003'. Ran 22 joints of 13-3/8 inch J-55, 54.5#, ST&C, 8RD, SHOE @ 996', F.C. @ 948'.

Cementing:

Lead: 610 sks of Class C (c+4%pf20+2%pf1+.125#pf29+.25#pf46), (13.5 ppg, 1.74 yield)
Tail: 200 sks of Class C (c+2%pf1) (14.8 ppg, 1.33 yield)
Spacer: H2O SPACER (20 volumes)
Displacement: Fresh water (147 volumes)

Circulated: 570 bbls/184 sks to pit. On 4/6/2013, tested surface casing to 3,000 psi=OK

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE [Signature] TITLE: Regulatory Analyst DATE: 8/28/2013

Type or print name: Robyn Lampley E-mail address: rlampley@rkixp.com PHONE: 405-996-5775

For State Use Only

APPROVED BY: [Signature] TITLE: **"Geologist"** DATE: 8/28/2013

Conditions of Approval (if any):