Submit 1 Copy To Appropriate District Office	State of New Me	Second Street Stre		Form C-103 Revised July 18, 2013
<u>District I</u> – (575) 393-6161 1625 N. French Dr., Hobbs, NM 88240 District II – (575) 748-1283	Energy, Minerals and Nam		WELL API NO.	Revised July 18, 2015
811 S. First St., Artesia, NM 88210	OIL CONSERVATION		30-015-41637 5. Indicate Type of L	ease
District III – (505) 334-6178 1000 Rio Brazos Rd., Aztec, NM 87410	1220 South St. Fra Santa Fe, NM88	OOD ARTESIA	STATE STATE	FEE
<u>District IV</u> – (505) 476-3460 1220 S. St. Francis Dr., Santa Fe, NM 87505	Sana I C, I	Grats Million	6. State Oil & Gas Le	ase No.
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)			7. Lease Name or Unit Agreement Name HORSESHOE STATE	
1. Type of Well: Oil Well 🛛 Gas Well 🗌 Other		8. Well Number #2		
2. Name of Operator LRE OPERATING, LLC			9. OGRID Number 2	81994
3. Address of Operator			10. Pool name or Wil	
c/o Mike Pippin LLC, 3104 N. Sullivan, Farmington, NM 87401			Red Lake, Glorieta-Y	eso NE (96836)
4. Well Location Unit Letter F :	1655 feet from the North	line and 2.	10 feet from the	West line
Section 30	Township 17-S	Range 28-E	NMPM Eddy	County
	11. Elevation (Show whether DR 3564' GL			
12. Check A	Appropriate Box to Indicate N	Jature of Notice. I	Report or Other Dat	a
			SEQUENT REPO	
	PLUG AND ABANDON	REMEDIAL WORK		
	CHANGE PLANS	COMMENCE DRIL		ND A
PULL OR ALTER CASING		CASING/CEMENT	JOB	
CLOSED-LOOP SYSTEM		OTHER: Comp		$\boxtimes$
	erations. (Clearly state all pertinent details, or Multiple Completions: Attach wellbore			tarting any proposed work).
On 11/1/13, PT 5-1/2" csg to 5000 p				20', 32', 40', 48', 64',
80', 96', 4310', 18', 30', 42', 50', 64				
w/3233 gal 15% HCL acid & 45 per linked gel.	f balls. Fraced lower Yeso w/87,8:	51# 16/30 Arizona &	19,066# 16/30 resin co	oated sand in 20# X-
Set 5-1/2" CBP @ 4120'. PT csg &				2'. 60'. 68'. 76'. 86'.
94', 4000', 06', 16', 26', 34', 40', 48	2' 54' 60' 66' 74' 80' w/1 0 41'	?? T		
$A^{\prime}$ northolds lineard $M^{\prime}A0^{\prime}2V^{\prime}H^{\prime}A^{\prime}$				
	30 Arizona & 15,351# 16/30 resin	coated sand in 20# >	-linked gel.	gal 15% HCL acid &
47 pert balls. Fraced w/49,383# 16/3 Set 5-1/2" CBP @ 3884'. PT csg to 3700', 10', 20', 30', 38', 46', 52', 60	30 Arizona & 15,351# 16/30 resin 3500 psi-OK. Perfed upper Yeso	coated sand in 20# > @ 3580', 92', 3600',	-linked gel. 10', 20', 32', 40', 50',	gal 15% HCL acid & 62' 72', 80', 87',
Set 5-1/2" CBP @ 3884'. PT csg to 3700', 10', 20', 30', 38', 46', 52', 60 w/2512 gal 15% HCL acid & 45 per	30 Arizona & 15,351# 16/30 resin 3500 psi-OK. Perfed upper Yeso 0', 69', 78', 94', 3808', 14', 20', 28 f balls. Fraced w/73,487# 16/30 A	coated sand in 20# > @ 3580', 92', 3600', 3', 38', 50', 56' w/1-0 rizona & 19,839# 16/	C-linked gel. 10', 20', 32', 40', 50', 0.41" spf. Total 30 hole 30 resin coated sand in	gal 15% HCL acid & 62' 72', 80', 87', es. Treated perfs 20# X-linked gel.
Set 5-1/2" CBP @ 3884'. PT csg to 3700', 10', 20', 30', 38', 46', 52', 60 w/2512 gal 15% HCL acid & 45 per Set 5-1/2" CBP @ 3560'. PT csg to	30 Arizona & 15,351# 16/30 resin 3500 psi-OK. Perfed upper Yeso 0', 69', 78', 94', 3808', 14', 20', 28 f balls. Fraced w/73,487# 16/30 A 3500 psi-OK. Perfed upper Yeso	coated sand in 20# > @ 3580', 92', 3600', 3', 38', 50', 56' w/1-0 rizona & 19,839# 16, @ 3280', 85', 90', 95	4-linked gel. 10', 20', 32', 40', 50', 41" spf. Total 30 hole 30 resin coated sand in ', 3300', 05', 10', 15',	gal 15% HCL acid & 62' 72', 80', 87', es. Treated perfs 20# X-linked gel. 20', 25', 30', 35', 40',
Set 5-1/2" CBP @ 3884'. PT csg to 3700', 10', 20', 30', 38', 46', 52', 60 w/2512 gal 15% HCL acid & 45 peri Set 5-1/2" CBP @ 3560'. PT csg to 45', 50', 55' 60', 65', 70', 75', 80', 8	30 Arizona & 15,351# 16/30 resin 3500 psi-OK. Perfed upper Yeso 9, 69', 78', 94', 3808', 14', 20', 28 f balls. Fraced w/73,487# 16/30 A 3500 psi-OK. Perfed upper Yeso 35', 90', 95', 3400', 05', 10', 15', 2	coated sand in 20# > @ 3580', 92', 3600', 3', 38', 50', 56' w/1-0 rizona & 19,839# 16, @ 3280', 85', 90', 95 20', 25', 30', 40', 48'	(-linked gel. 10', 20', 32', 40', 50', .41" spf. Total 30 hole 30 resin coated sand in ', 3300', 05', 10', 15', , 56', 64', 72', 80', 94'	gal 15% HCL acid & 62' 72', 80', 87', es. Treated perfs 20# X-linked gel. 20', 25', 30', 35', 40', , 3502', 10', 20', 34',
Set 5-1/2" CBP @ 3884'. PT csg to 3700', 10', 20', 30', 38', 46', 52', 60 w/2512 gal 15% HCL acid & 45 pert Set 5-1/2" CBP @ 3560'. PT csg to 45', 50', 55' 60', 65', 70', 75', 80', 8 40' w/1-0.41" spf. Total 43 holes. T 16/30 resin coated sand in 25# X-lind	30 Arizona & 15,351# 16/30 resin 3500 psi-OK. Perfed upper Yeso 1', 69', 78', 94', 3808', 14', 20', 28 f balls. Fraced w/73,487# 16/30 A 3500 psi-OK. Perfed upper Yeso 35', 90', 95', 3400', 05', 10', 15', 2 Freated perfs w/3363 gal 15% HCL ked gel.	coated sand in 20# > @ 3580', 92', 3600', 3', 38', 50', 56' w/1-0 rizona & 19,839# 16, @ 3280', 85', 90', 95 20', 25', 30', 40', 48' acid & 65 perf balls	C-linked gel. 10', 20', 32', 40', 50', 41'' spf. Total 30 hole 30 resin coated sand in ', 3300', 05', 10', 15', , 56', 64', 72', 80', 94' Fraced w/80,682# 16	gal 15% HCL acid & 62' 72', 80', 87', es. Treated perfs 20# X-linked gel. 20', 25', 30', 35', 40', , 3502', 10', 20', 34', /30 Arizona & 17,662#
Set 5-1/2" CBP @ 3884'. PT csg to 3700', 10', 20', 30', 38', 46', 52', 60 w/2512 gal 15% HCL acid & 45 pert Set 5-1/2" CBP @ 3560'. PT csg to 45', 50', 55' 60', 65', 70', 75', 80', 8 40' w/1-0.41" spf. Total 43 holes. T 16/30 resin coated sand in 25# X-lini On 11/8/13, MIRUSU. Drilled CBP	30 Arizona & 15,351# 16/30 resin 3500 psi-OK. Perfed upper Yeso 3,69', 78', 94', 3808', 14', 20', 28 f balls. Fraced w/73,487# 16/30 A 3500 psi-OK. Perfed upper Yeso 35', 90', 95', 3400', 05', 10', 15', 2 Freated perfs w/3363 gal 15% HCL ked gel. s @ 3560', 3884' & 4120' & CO to	coated sand in 20# > @ 3580', 92', 3600', 3', 38', 50', 56' w/1-0 rizona & 19,839# 16, @ 3280', 85', 90', 95 20', 25', 30', 40', 48' acid & 65 perf balls	C-linked gel. 10', 20', 32', 40', 50', 41'' spf. Total 30 hole 30 resin coated sand in ', 3300', 05', 10', 15', , 56', 64', 72', 80', 94' Fraced w/80,682# 16	gal 15% HCL acid & 62' 72', 80', 87', es. Treated perfs 20# X-linked gel. 20', 25', 30', 35', 40', , 3502', 10', 20', 34', /30 Arizona & 17,662#
Set 5-1/2" CBP @ 3884'. PT csg to 3700', 10', 20', 30', 38', 46', 52', 60 w/2512 gal 15% HCL acid & 45 pert Set 5-1/2" CBP @ 3560'. PT csg to 45', 50', 55' 60', 65', 70', 75', 80', 8 40' w/1-0.41" spf. Total 43 holes. T 16/30 resin coated sand in 25# X-lind	30 Arizona & 15,351# 16/30 resin 3500 psi-OK. Perfed upper Yeso 3,69', 78', 94', 3808', 14', 20', 28 f balls. Fraced w/73,487# 16/30 A 3500 psi-OK. Perfed upper Yeso 35', 90', 95', 3400', 05', 10', 15', 2 Freated perfs w/3363 gal 15% HCL ked gel. s @ 3560', 3884' & 4120' & CO to	coated sand in 20# > @ 3580', 92', 3600', 3', 38', 50', 56' w/1-0 rizona & 19,839# 16, @ 3280', 85', 90', 95 20', 25', 30', 40', 48' acid & 65 perf balls	C-linked gel. 10', 20', 32', 40', 50', 41'' spf. Total 30 hole 30 resin coated sand in ', 3300', 05', 10', 15', , 56', 64', 72', 80', 94' Fraced w/80,682# 16	gal 15% HCL acid & 62' 72', 80', 87', es. Treated perfs 20# X-linked gel. 20', 25', 30', 35', 40', , 3502', 10', 20', 34', /30 Arizona & 17,662#
Set 5-1/2" CBP @ 3884'. PT csg to 3700', 10', 20', 30', 38', 46', 52', 60 w/2512 gal 15% HCL acid & 45 pert Set 5-1/2" CBP @ 3560'. PT csg to 45', 50', 55' 60', 65', 70', 75', 80', 8 40' w/1-0.41" spf. Total 43 holes. T 16/30 resin coated sand in 25# X-lini On 11/8/13, MIRUSU. Drilled CBP Ran pump & rods. Released comple Spud Date: 10/24/13	30 Arizona & 15,351# 16/30 resin 3500 psi-OK. Perfed upper Yeso 7, 69', 78', 94', 3808', 14', 20', 28 f balls. Fraced w/73,487# 16/30 A 3500 psi-OK. Perfed upper Yeso 85', 90', 95', 3400', 05', 10', 15', 2 Freated perfs w/3363 gal 15% HCL ked gel. s @ 3560', 3884' & 4120' & CO t tion rig on 11/12/13. Drilling Ri	coated sand in 20# > @ 3580', 92', 3600', 3', 38', 50', 56' w/1-0 rizona & 19,839# 16, @ 3280', 85', 90', 95 20', 25', 30', 40', 48' acid & 65 perf balls o PBTD4872'. On 1 ig Release Date:	2-linked gel. 10', 20', 32', 40', 50', 0.41" spf. Total 30 hole 30 resin coated sand ir ', 3300', 05', 10', 15', 56', 64', 72', 80', 94' Fraced w/80,682# 16 1/11/13, landed 2-7/8" 10/30/13	gal 15% HCL acid & 62' 72', 80', 87', es. Treated perfs 20# X-linked gel. 20', 25', 30', 35', 40', , 3502', 10', 20', 34', /30 Arizona & 17,662#
Set 5-1/2" CBP @ 3884'. PT csg to 3700', 10', 20', 30', 38', 46', 52', 60 w/2512 gal 15% HCL acid & 45 pert Set 5-1/2" CBP @ 3560'. PT csg to 45', 50', 55' 60', 65', 70', 75', 80', 8 40' w/1-0.41" spf. Total 43 holes. T 16/30 resin coated sand in 25# X-lini On 11/8/13, MIRUSU. Drilled CBP Ran pump & rods. Released comple Spud Date: 10/24/13	30 Arizona & 15,351# 16/30 resin 3500 psi-OK. Perfed upper Yeso 7, 69', 78', 94', 3808', 14', 20', 28 f balls. Fraced w/73,487# 16/30 A 3500 psi-OK. Perfed upper Yeso 85', 90', 95', 3400', 05', 10', 15', 2 Freated perfs w/3363 gal 15% HCL ked gel. s @ 3560', 3884' & 4120' & CO t tion rig on 11/12/13. Drilling Ri	coated sand in 20# > @ 3580', 92', 3600', 3', 38', 50', 56' w/1-0 rizona & 19,839# 16, @ 3280', 85', 90', 95 20', 25', 30', 40', 48' acid & 65 perf balls o PBTD4872'. On 1 ig Release Date:	2-linked gel. 10', 20', 32', 40', 50', 0.41" spf. Total 30 hole 30 resin coated sand ir ', 3300', 05', 10', 15', 56', 64', 72', 80', 94' Fraced w/80,682# 16 1/11/13, landed 2-7/8" 10/30/13	gal 15% HCL acid & 62' 72', 80', 87', es. Treated perfs 20# X-linked gel. 20', 25', 30', 35', 40', , 3502', 10', 20', 34', /30 Arizona & 17,662#
Set 5-1/2" CBP @ 3884'. PT csg to   3700', 10', 20', 30', 38', 46', 52', 60   w/2512 gal 15% HCL acid & 45 period   Set 5-1/2" CBP @ 3560'. PT csg to   45', 50', 55' 60', 65', 70', 75', 80', 8   40' w/1-0.41" spf. Total 43 holes. T   16/30 resin coated sand in 25# X-lini   On 11/8/13, MIRUSU. Drilled CBP   Ran pump & rods. Released comple   Spud Date: 10/24/13   I hereby certify that the information   SIGNATURE M.La	30 Arizona & 15,351# 16/30 resin 3500 psi-OK. Perfed upper Yeso 3,69', 78', 94', 3808', 14', 20', 28 f balls. Fraced w/73,487# 16/30 A 3500 psi-OK. Perfed upper Yeso 35', 90', 95', 3400', 05', 10', 15', 2 Freated perfs w/3363 gal 15% HCL ked gel. s @ 3560', 3884' & 4120' & CO t tion rig on 11/12/13. Drilling Ri above is true and complete to the b V. J. J. J. TITLE Petro	coated sand in 20# > @ 3580', 92', 3600', 3', 38', 50', 56' w/1-0 rizona & 19,839# 16, @ 3280', 85', 90', 95 20', 25', 30', 40', 48' 2 acid & 65 perf balls o PBTD4872'. On 1 ig Release Date: pest of my knowledge	2-linked gel.   10', 20', 32', 40', 50',   20', 32', 40', 50',   30 resin coated sand in   ', 3300', 05', 10', 15',   , 56', 64', 72', 80', 94'   . Fraced w/80,682# 16   1/11/13, landed 2-7/8"   10/30/13   and belief.   entDATE1	gal 15% HCL acid & 62' 72', 80', 87', es. Treated perfs 20# X-linked gel. 20', 25', 30', 35', 40', , 3502', 10', 20', 34', /30 Arizona & 17,662# 6.5# J-55 tbg @ 4613'.
Set 5-1/2" CBP @ 3884'. PT csg to   3700', 10', 20', 30', 38', 46', 52', 60   w/2512 gal 15% HCL acid & 45 period   Set 5-1/2" CBP @ 3560'. PT csg to   45', 50', 55' 60', 65', 70', 75', 80', 8   40' w/1-0.41" spf. Total 43 holes. T   16/30 resin coated sand in 25# X-linil   On 11/8/13, MIRUSU. Drilled CBP   Ran pump & rods. Released comple   Spud Date: 10/24/13   I hereby certify that the information   SIGNATURE Mike Pipp	30 Arizona & 15,351# 16/30 resin 3500 psi-OK. Perfed upper Yeso 3,69', 78', 94', 3808', 14', 20', 28 f balls. Fraced w/73,487# 16/30 A 3500 psi-OK. Perfed upper Yeso 35', 90', 95', 3400', 05', 10', 15', 2 Freated perfs w/3363 gal 15% HCL ked gel. s @ 3560', 3884' & 4120' & CO t tion rig on 11/12/13. Drilling Ri above is true and complete to the b V. J. J. J. TITLE Petro	coated sand in 20# > @ 3580', 92', 3600', 3', 38', 50', 56' w/1-0 rizona & 19,839# 16, @ 3280', 85', 90', 95 20', 25', 30', 40', 48' 2 acid & 65 perf balls o PBTD4872'. On 1 ig Release Date: pest of my knowledge	2-linked gel.   10', 20', 32', 40', 50',   20', 32', 40', 50',   30 resin coated sand in   ', 3300', 05', 10', 15',   , 56', 64', 72', 80', 94'   . Fraced w/80,682# 16   1/11/13, landed 2-7/8"   10/30/13   and belief.   entDATE1	gal 15% HCL acid & 62' 72', 80', 87', es. Treated perfs 20# X-linked gel. 20', 25', 30', 35', 40', , 3502', 10', 20', 34', /30 Arizona & 17,662# 6.5# J-55 tbg @ 4613'.
Set 5-1/2" CBP @ 3884'. PT csg to 3700', 10', 20', 30', 38', 46', 52', 60 w/2512 gal 15% HCL acid & 45 pert Set 5-1/2" CBP @ 3560'. PT csg to 45', 50', 55' 60', 65', 70', 75', 80', 8 40' w/1-0.41" spf. Total 43 holes. T 16/30 resin coated sand in 25# X-lini On 11/8/13, MIRUSU. Drilled CBP Ran pump & rods. Released comple Spud Date: 10/24/13 I hereby certify that the information SIGNATURE Mike Pipp For State Use Only	30 Arizona & $15,351\# 16/30$ resin 3500 psi-OK. Perfed upper Yeso 1, 69', 78', 94', 3808', 14', 20', 28 f balls. Fraced w/73,487# 16/30 A 3500 psi-OK. Perfed upper Yeso 35', 90', 95', 3400', 05', 10', 15', 2 Freated perfs w/3363 gal 15% HCL ked gel. s @ 3560', 3884' & 4120' & CO to tion rig on 11/12/13. Drilling Ri above is true and complete to the b $V_{1}$ for the formation of th	coated sand in 20# > @ 3580', 92', 3600', 3', 38', 50', 56' w/1-0 rizona & 19,839# 16, @ 3280', 85', 90', 95 20', 25', 30', 40', 48' 2 acid & 65 perf balls o PBTD4872'. On 1 ig Release Date: pest of my knowledge	3-linked gel.   10', 20', 32', 40', 50',   0.41" spf. Total 30 hole   30 resin coated sand ir   ', 3300', 05', 10', 15',   , 56', 64', 72', 80', 94'   Fraced w/80,682# 16   1/11/13, landed 2-7/8"   10/30/13   and belief.   ent DATE 1   illc.com PHONI	gal 15% HCL acid & 62' 72', 80', 87', es. Treated perfs 20# X-linked gel. 20', 25', 30', 35', 40', , 3502', 10', 20', 34', /30 Arizona & 17,662# 6.5# J-55 tbg @ 4613'.
Set 5-1/2" CBP @ 3884'. PT csg to   3700', 10', 20', 30', 38', 46', 52', 60   w/2512 gal 15% HCL acid & 45 period   Set 5-1/2" CBP @ 3560'. PT csg to   45', 50', 55' 60', 65', 70', 75', 80', 8   40' w/1-0.41" spf. Total 43 holes. T   16/30 resin coated sand in 25# X-linil   On 11/8/13, MIRUSU. Drilled CBP   Ran pump & rods. Released comple   Spud Date: 10/24/13   I hereby certify that the information   SIGNATURE Mike Pipp	30 Arizona & 15,351# 16/30 resin 3500 psi-OK. Perfed upper Yeso 3,69', 78', 94', 3808', 14', 20', 28 f balls. Fraced w/73,487# 16/30 A 3500 psi-OK. Perfed upper Yeso 35', 90', 95', 3400', 05', 10', 15', 2 Freated perfs w/3363 gal 15% HCL ked gel. s @ 3560', 3884' & 4120' & CO t tion rig on 11/12/13. Drilling Ri above is true and complete to the b V. J. J. J. TITLE Petro	coated sand in 20# > @ 3580', 92', 3600', 3', 38', 50', 56' w/1-0 rizona & 19,839# 16, @ 3280', 85', 90', 95 20', 25', 30', 40', 48' 2 acid & 65 perf balls o PBTD4872'. On 1 ig Release Date: pest of my knowledge	2-linked gel.   10', 20', 32', 40', 50',   20', 32', 40', 50',   30 resin coated sand in   ', 3300', 05', 10', 15',   , 56', 64', 72', 80', 94'   . Fraced w/80,682# 16   1/11/13, landed 2-7/8"   10/30/13   and belief.   entDATE1	gal 15% HCL acid & 62' 72', 80', 87', es. Treated perfs 20# X-linked gel. 20', 25', 30', 35', 40', , 3502', 10', 20', 34', /30 Arizona & 17,662# 6.5# J-55 tbg @ 4613'.