

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-015-41638
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>		5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
2. Name of Operator LRE OPERATING, LLC		6. State Oil & Gas Lease No.
3. Address of Operator c/o Mike Pippin LLC, 3104 N. Sullivan, Farmington, NM 87401		7. Lease Name or Unit Agreement Name SOUTHERN UNION 30 G STATE
4. Well Location Unit Letter <u>G</u> : <u>1815</u> feet from the <u>North</u> line and <u>1650</u> feet from the <u>East</u> line Section <u>30</u> Township <u>17-S</u> Range <u>28-E</u> NMPM <u>Eddy</u> County		8. Well Number <u>#2</u>
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3574' GL		9. OGRID Number <u>281994</u>
		10. Pool name or Wildcat Red Lake, Glorieta-Yeso NE (96836)

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐
CLOSED-LOOP SYSTEM ☒
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐
OTHER: Completion ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work).
SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.
On 10/25/13, PT 5-1/2" csg to 5000 psi for 30 min-OK. Perfed lower Yeso @ MD4344', 54', 64', 70', 80', 90', 4400', 10', 20', 30', 40', 52', 60', 70', 80', 90', 4500', 10', 20', 30', 40', 50', 60', 70', 78', 90', 4600' w/1-0.41" spf. Total 27 holes. On 10/30/13, treated w/2600 gal 15% HCL acid & 41 perf balls. Fraced lower Yeso w/64,658# 16/30 Wisconsin White & 20,308# 16/30 resin coated sand in 20# X-linked gel.
Set 5-1/2" CBP @ MD4320'. PT csg & CBP to 4000 psi-OK. Perfed middle Yeso @ MD3962', 70', 80', 92', 4000', 10', 20', 34', 50', 60', 70', 80', 90', 4100', 10', 20', 32', 44', 52', 60', 73', 84', 4204', 18', 28', 38', 50', 60', 70', 80', 92' w/1-0.41" spf. Total 31 holes. Treated perfs w/3300 gal 15% HCL acid & 47 perf balls. Fraced w/95,892# 16/30 Wisconsin White & 19,620# 16/30 resin coated sand in 20# X-linked gel.
Set 5-1/2" CBP @ MD3920'. PT csg to 4000 psi-OK. Perfed upper Yeso @ MD3552', 60', 70', 80', 90', 3600', 10', 20', 36', 54', 76', 88', 3700', 10', 20', 30', 40', 50', 60', 70', 80', 90', 3800', 10', 20', 30', 38', 50', 60', 72', 82' w/1-0.41" spf. Total 31 holes. Treated perfs w/3300 gal 15% HCL acid & 37 perf balls. Fraced w/91,168# 16/30 Wisconsin White & 18,962# 16/30 resin coated sand in 20# X-linked gel.
Set 5-1/2" CBP @ MD3525'. PT csg to 4000 psi-OK. Perfed Glorieta/upper Yeso @ MD3220', 30', 40', 50', 60', 70', 80', 90', 3300', 05', 10', 15', 20', 25', 30', 35', 40', 45', 50', 55', 60', 65', 70', 75', 80', 85', 90', 95', 3400', 05', 10', 15', 20', 25', 30', 35', 40', 45', 50', 55', 60', 65', 70', 75', 80', 85', 90', 95', 3500', 06' w/1-0.41" spf. Total 50 holes. Treated perfs w/3839 gal 15% HCL acid & 75 perf balls. Fraced w/86,779# 16/30 Wisconsin White & 15,819# 16/30 resin coated sand in 25# X-linked gel.
On 11/1/13, MIRUSU. Drilled CBPs @ MD3525', 3920' & 4320' & CO to MDPBTD4845'. On 11/2/13, landed 2-7/8" 6.5# J-55 tbg @ MD4702'. Ran pump & rods. Released completion rig on 11/5/13.

Bottom Hole Location: 1659' FNL & 1647' FEL SEC. 30 T17S R28E

Spud Date: 10/15/13

Drilling Rig Release Date: 10/22/13

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Mike Pippin

TITLE Petroleum Engineer - Agent

DATE 11/16/13

Type or print name Mike Pippin

E-mail address: mike@pippinllc.com

PHONE: 505-327-4573

For State Use Only

APPROVED BY:

SR Dade

TITLE Dist. H. Spawson

DATE 11/20/2013

Conditions of Approval (if any):

RECEIVED

NOV 19 2013

NMOCD ARTESIA