

Submit 1 Copy To Appropriate District Office
District I- (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II- (575) 748-1283
1301 W. Grand Ave., Artesia, NM 88210
District III- (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV- (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-21064
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No. Fee
7. Lease Name or Unit Agreement Name Canal SWD <40393>
8. Well Number 1
9. OGRID Number 013837
10. Pool Name or Wildcat SWD; Bell Canyon, Cherry Canyon

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR, USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☐ Other SWD

2. Name of Operator
Mack Energy Corporation

3. Address of Operator
P.O. Box 960 Artesia, NM 88210

4. Well Location
Unit Letter L 2175 feet from the South line and 838 feet from the West line
Section 3 Township 23S Range 27E NMPM County Eddy

11. Elevation (Show whether DR, RKB, RT, GR etc.)
3114'

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐
CLOSED-LOOP SYSTEM ☐
OTHER: Re-Entry ☒


SUBSEQUENT REPORT OF:

REMEDIALWORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Mack Energy proposes to do the following re-entry procedure.

1. PU 8 3/4" bit, DC's and 2 7/8" tbg
2. Drill out cmt plugs @ surface, 300'-400', 2100'-2200'.
3. Continue in the hole to cmt plug @ 5369'.
4. TIH w/ CIBP. Set @ 4175'
5. PU 7" csg and run to 4150'
6. Cmt csg w/ Lead 200sx 12.6ppg 2.06yiel 35/65 Poz/H & 300sx 13ppg 1.48yield PVL cmt
7. Shoot 1st set of new perfs across Bell Canyon and Cherry Canyon interval 2145-4072'
8. Acid job w/ 2000gal 15% HCL and balls
9. RIH w/ plastic coated 2 7/8" tbg and 10k nickel plated arrow set pkr.
10. Turn over to disposal



Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Deana Weaver TITLE Production Clerk DATE 2.13.14

Type or print name Deana Weaver

E-mail address: dweaver@mec.com

PHONE: (575)748-1288

For State Use Only

APPROVED BY: T.C. Shepard TITLE "Geologist" DATE 2-14-2014

Conditions of Approval (if any):

BASED ON C-108 APPROVAL.