Form 3160-5	
(August 2007)	

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPRO	VED
OMB NO. 1004-	-0135
Expires: July 31	2010

SUNDRY NOTICES AND REPORTS ON WELLS

Lease Serial No. NMNM0428657

Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.

If Indian, Allottee or Tribe Name

·			
SUBMIT IN TRIPLICATE - Other instructions on reverse side.		7. If Unit or CA/Agreement, Name and/or No.	
Type of Well		8. Well Name and No. OXY RIBEYE FEDERAL 1	
Name of Operator CHI OPERATING INCORPORATED E-Mail: p	Contact: PAM CORBETT pamc@chienergyinc.com	9. API Well No. 30-015-30173-00-S1	
3a. Address MIDLAND, TX 79702	3b. Phone No. (include area code) Ph: 432-685-5001 Fx: 432-687-2662	10. Field and Pool, or Exploratory WINCHESTER	
4. Location of Well (Footage, Sec., T., R., M., or Survey I	Description)	11. County or Parish, and State	
Sec 34 T19S R28E SENW 1650FNL 1980FW	L	EDDY COUNTY, NM	
·		<u> </u>	

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

. TYPE OF SUBMISSION	TYPE OF ACTION			
□ Notice of Intent☑ Subsequent Report□ Final Abandonment Notice	☐ Acidize ☐ Alter Casing ☐ Casing Repair ☐ Change Plans ☐ Convert to Injection	☐ Deepen ☐ Fracture Treat ☐ New Construction ☑ Plug and Abandon ☐ Plug Back	☐ Production (Start/Resume) ☐ Reclamation ☐ Recomplete ☐ Temporarily Abandon ☐ Water Disposal	☐ Water Shut-Off ☐ Well Integrity ☐ Other

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof.

If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

DATE OF WORK:3/4-3/17/14

NM OIL CONSERVATION

ARTESIA DISTRICT

JUN 3 0 2014

Set CIBP @ 10,750' - dump bail 36' "H" cmt.
Set CIBP @ 8,900' - dump bail 36' "H" cmt.
Perf @ 6,200' - could not pump into - spot 45 sxs @ 6,250' - tag @ 6,039'.
Perf @ 4,700' - could not pump into - spot 45 sxs @ 4,750' - tag @ 4,503'.
Perf @ 3,245' - could not pump into - spot 125 sxs @ 3,287' - tag @ 2,573'.
Perf @ 1,420' - could not pump into - spot 30 sxs @ 1,479' - tag @ 1,313'.
Perf @ 480' - sqz 65 sxs - tag @ 353'.

Perf @ 60' - sqz 60 sxs to surface.

Cut and cap well & install dry hole marker.

URD 7-1-14

Accepted for Necotal

RECEIVED to plugging of the well bors. Liability under bond is retained until Surface restoration is completed.

14. I hereby certify that th	ne foregoing is true and correct. Electronic Submission #244072 verifie For CHI OPERATING INCORPO Committed to AFMSS for processing by LIND	ÞRÁTEI	D, sent to the Carlsbad	
Name (Printed/Typed)	SONNY MANN	Title	FIELD SUPERVISOR	
Signature	(Electronic Submission)	Date	05/01/2014	
	THIS SPACE FOR FEDERA	L OR	STATE OFFICE USE	
Approved By ACCEPTED		Title	AMES A AMOS SUPERVISOR EPS	Date 06/24/2014
certify that the applicant hol	ny, are attached. Approval of this notice does not warrant or lds legal or equitable title to those rights in the subject lease licent to conduct operations thereon.	Office	· Carlshad	

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

CHI Operating, inc.

Oxy Ribeye Federal No. 1 Eddy County, New Mexico

API: 30-015-30173

8-5/8" 32# K55 @ 2752' cmt w/1100 sx circulated to surface

CIBP @8900'

7" 26# AB STL FJ @ 9073' cmt w/300 sx

CIBP @10,750'

per @60' sqz 60 sxs to surface

13-3/8" 48# J55 @423'

cmt w/400 sx circulated

perf 480' sqz 65 sxs-TAG @ 353'

erf @ 1420' spot 30sxs @1479'-TAG @1313'

perf @ 3245' spot 125sxs @3287'-TAG @ 2573'

perf @ 4700' spot 45sxs @4750'-TAG @4503'

perf @ 6200' spot 45sxs@6250'-TAG 6039'

Perfs:

Wolfcamp: 8935-9026' (cement sqzd).

4-1/2 x 7" liner packer @ 8713'

Perfs: Morrow:

11098-11104' (BO w/CIBP @ 11,345' w/20' cmt on top)

10,774-10782, 10966-10976, 11003-11010

4-1/2"11.6# P110 @ 8724-11450' (BO w/CIBP @ 11,345' w/20' cmt on top) cmt w/300 sx