

Submit 1 Copy To Appropriate District Office  
District I – (575) 393-6161  
1625 N. French Dr., Hobbs, NM 88240  
District II – (575) 748-1283  
811 S. First St., Artesia, NM 88210  
District III – (505) 334-6178  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV – (505) 476-3460  
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
Revised August 1, 2011

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

<b>SUNDRY NOTICES AND REPORTS ON WELLS</b> (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-015-22904
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/> Injection Well <input type="checkbox"/>		5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
2. Name of Operator <b>Alamo Permian Resources, LLC</b>		6. State Oil & Gas Lease No. B-8318
3. Address of Operator <b>415 W. Wall Street, Suite 500, Midland, TX 79701</b>		7. Lease Name or Unit Agreement Name SPURCK
4. Well Location Unit Letter I : 2310 feet from the S line and 330 feet from the E line Section 24 Township 17S Range 27E NMPM County EDDY		8. Well Number 004
11. Elevation (Show whether DR, RKB, RT, GR, etc.)		9. OGRID Number 274841
		10. Pool name or Wildcat EMPIRE; YATES-SR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	P AND A <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	MULTIPLE COMPL <input type="checkbox"/>	CASING/CEMENT JOB <input type="checkbox"/>	
DOWNHOLE COMMINGLE <input type="checkbox"/>			
OTHER: <input type="checkbox"/>		OTHER: 9-16-14 <input type="checkbox"/>	

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

SEE ATTACHED

Approved for plugging of well bore only.  
Liability under bond is retained pending receipt  
of C-103 (Subsequent Report of Well Plugging)  
which may be found at OCD Web Page under  
Forms. [www.emnrd.state.nm.us/oed](http://www.emnrd.state.nm.us/oed).

NM OIL CONSERVATION  
ARTESIA DISTRICT  
OCT 14 2014  
RECEIVED

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Carie Stoker TITLE Regulatory Affairs Coordinator DATE 09/17/2014

Type or print name CARIE STOKER E-mail address: carie@stokeroilfield.com PHONE: 432.664.7659

APPROVED BY: [Signature] TITLE Dist. H. Supervisor DATE 10/14/2014

Conditions of Approval (if any):

\* Submit Subsequent C-103

<b><u>SPURCK #004</u></b>		
		Perfs: OH
API: 30-015-22904	Lease: B-8318	Spud: 05/01/79
I-24-17S-27E	2310 FSL & 330 FEL	<b>P&amp;A:</b>
Eddy Co., NM	Pool: 22230 – EMPIRE; Yates-Seven Rivers	

**OBJECTIVE: Plug and Abandon**

09/11/14

MIRU Aztec Rig #471. Unseat pump. ND. POOH w/junk ¾” rods, pump & polish rod. Dig out around wellhead. Prep for tubing. PU on 2-7/8” tubing. Tubing parted on 1<sup>st</sup> jt. Prep for BOP. SDFN.

Note: Plan to fish tubing in the AM.

09/12/14

MIRU kill truck & pump 3 BFW. Weld on 10-3/4” x 8-5/8” weld on swedge. Repair tbg drum brake handle. PU 5-3/4” overshot w/wall hook. RIH on 2-3/8” tbg. Worked overshot over parted tubing & POOH laying down junk 2-7/8” J55 EUE 8rd production tbg. NU BOP. SWI. SDFWE due to wind & rain.

09/13-14/14 SDFWE.

09/15/14

PU & tally 2-3/8” WS to 540’. Try to break circ without success. Pumped 50 sx Class C “Neat” cement w/1% CC from 540’ up to 436’. 180’. WOC 4 hrs. RIH, tag cmt @ 445’. Broke circ w/5 BFW. Mix & pump 190 sx Class C cement w/1% CC. Circ cmt to surface & POOH laying down WS. ND BOP. Top off cmt. SWI. SDFN.

09/16/14

Cleaned location. RDMO. Installed Dry Hole Marker; Cut anchors below surface. Well plugged.

<p>Approved for plugging of well bore only.          Liability under bond is retained pending receipt          of C-103 (Subsequent Report of Well Plugging)          which may be found at OCD Web Page under          Forms: <a href="http://www.emard.state.nm.us/oed">www.emard.state.nm.us/oed</a>.</p>
--