



**Additional data for EC transaction #245504 that would not fit on the form**

**32. Additional remarks, continued**

casing at 4,633 ft. Cemented with 1050 sacks 35:65:6 Poz C + 5 lb/sx D042 + 5 percent D044 + 0.3 percent D112 + 0.125 lb/sx D130 + 0.01 gal/sx D177 + 0.2 percent D046 + 4.5 percent D020 + 0.1 percent D65 (yld 1.97, wt 12.8). - Tailed in with 323 sacks 50/50 Poz C + 3 lb/sx D042 + 5 percent D044 + 0.125 lb/sx D130 + 0.06 percent D208 + 0.2 percent D46 + 0.5 percent D020 + 0.2 percent D65 (yld 1.36, wt 14.2). Circulated 279 sacks to surface.

4/20/14 - Tested casing to 1500 psi, ok. WOC 34 hours. Reduced hole to 8-3/4 inch and resumed drilling.

4/25/14 - Drilled to 10,098 ft KOP and continued drilling directional.

4/26/14 - Drilled to 10,896 ft and reduced hole to 8-1/2 inch and resumed drilling.

5/2/14 - Reached TD 8-1/2 inch hole to 15,235 ft.

5/4/14 - Notified Michael Balliett with BLM-Carlsbad on running and cementing production casing.

Set 5-1/2 inch 17# P-110 BT&C casing at 15,190 ft. Float collar at 15,142 ft. Circulated casing.

Cemented with 750 sacks LiteCrete + 2 percent D174 + 0.05 percent D208 + 0.7 percent D800 + 0.2 percent D46 + 0.5 percent D65 + 0.3 percent D167 (yld 2.46, wt 9.70). Tailed in with 1435 sacks PVL + 3 lb/sx D042 + 2 percent D174 + 0.5 percent D207 + 0.8 percent D800 + 0.2 percent D46 (yld 1.30, wt 13.5)

5/5/14 - Rig released at 11:00 am.