

1625 N. French Dr., Hobbs, NM 88249 ARTESIA DISTRICT

District II - (575) 748-1283

811 S. First St., Artesia, NM 88210

District III - (505) 334-6178

1000 Rio Brazos Rd., Aztec, NM 87410

District IV - (505) 476-3460

1220 S. St. Francis Dr., Santa Fe, NM 87505

JAN 27 2015

RECEIVED

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

WELL API NO. 42-015-26488
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. 16441
7. Lease Name or Unit Agreement Name Philly Federal
8. Well Number 2
9. OGRID Number 115970
10. Pool name or Wildcat Frontier Hills (Strawn)
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3338 GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well Gas Well Other

2. Name of Operator
Unit Petroleum Company

3. Address of Operator
P.O. Box 702500, Tulsa, OK 74170

4. Well Location
Unit Letter _____ : 1980 feet from the North _____ line and 1980 feet from the East _____ line
Section 21 Township 23S Range 26E NMPM Eddy County

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK PLUG AND ABANDON
 TEMPORARILY ABANDON CHANGE PLANS
 PULL OR ALTER CASING MULTIPLE COMPL
 DOWNHOLE COMMINGLE
 CLOSED-LOOP SYSTEM
 OTHER:

SUBSEQUENT REPORT OF:

REMEDIAL WORK ALTERING CASING
 COMMENCE DRILLING OPNS. P AND A
 CASING/CEMENT JOB
 OTHER:

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

- 7" CIBP @ 10,050' Dump Bale 7 sx of cement
- Spot 40 sx of cement from 8608' to 8428'
- Spot 40 sx of cement from 8036' to 7853'
- Spot 30 sx of cement from 5150' to 5000'
- Perf @ 2813' sqz 45 sx of cement from 2813' to 2682'
- Perf @ 1723' sqz 40 sx of cement from 1723' to 1613'
- Perf @ 415' sqz 60 sx of cement from 415' to 245'
- Perf @ 60' sqz 25 sx of cement from 60' to surface.
- Dig out cellar, cut off wellhead, top off w/3 sx of cement.
- Weld on dry hole marker. Dig up dead men, clean location.
- Date of plug 2/19/2014 by Griffin Plugging Services Inc.

DENIED

Accepted for record
RD NMOCD 2/11/2015

Approved for plugging of well bore only.
 Liability under bond is retained pending receipt
 of C-103 (Subsequent Report of Well Plugging)
 which may be found at OCD Web Page under
 Forms, www.cmrd.state.nm.us/ocd.

This is a Federal well - waiting on official/Signed BLM FORMS

Spud Date: 1/27/2014

Rig Release Date: 2/19/2014

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Helene Arnold TITLE Regulatory Tech DATE 1/26/2015

Type or print name Helene Arnold E-mail address: Helene.arnold@unitcorp.com PHONE: 918-477-4469

For State Use Only

APPROVED BY: _____ TITLE _____ DATE _____

Conditions of Approval (if any):

Accepted for record
DENIED
NMOCD