

Submit 1 Copy To Appropriate District Office  
District I - (575) 393-6161  
1625 N. French Dr., Hobbs, NM 88240  
District II - (575) 748-1283  
811 S. First St., Artesia, NM 88210  
District III - (505) 334-6178  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV - (505) 476-3460  
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
Revised July 18, 2013

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

|                                                                                                                                                                                                                |  |                                                                                          |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|------------------------------------------------------------------------------------------|
| <b>SUNDRY NOTICES AND REPORTS ON WELLS</b><br>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)  |  | WELL API NO.<br>30-015-05314                                                             |
| 1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input checked="" type="checkbox"/> Other <b>INJECTION</b>                                                                                         |  | 5. Indicate Type of Lease<br>STATE <input type="checkbox"/> FEE <input type="checkbox"/> |
| 2. Name of Operator<br>LINN OPERATING, INC.                                                                                                                                                                    |  | 6. State Oil & Gas Lease No.                                                             |
| 3. Address of Operator<br>600 TRAVIS, SUITE 5100, HOUSTON, TEXAS 77002                                                                                                                                         |  | 7. Lease Name or Unit Agreement Name<br>TURNER B                                         |
| 4. Well Location<br>Unit Letter <u>M</u> : <u>660</u> feet from the <u>S</u> line and <u>560</u> feet from the <u>W</u> line<br>Section <u>20</u> Township <u>17S</u> Range <u>31E</u> NMPM <u>EDDY</u> County |  | 8. Well Number <u>043</u>                                                                |
| 11. Elevation (Show whether DR, RKB, RT, GR, etc.)<br>3618' GL                                                                                                                                                 |  | 9. OGRID Number <u>269324</u>                                                            |
|                                                                                                                                                                                                                |  | 10. Pool name or Wildcat<br>GRAYBURG JACKSON;SR-Q-G-SA                                   |

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐  
DOWNHOLE COMMINGLE ☐  
CLOSED-LOOP SYSTEM ☐

OTHER: ☒ RU & IDENTIFY MECHANICAL ISSUE

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A ☐  
CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

DUE TO A FAILED MIT, LINN OPERATING, INC. RESPECTFULLY REQUESTS TO RIG UP AND IDENTIFY THE SOURCE OF PRESSURE LOSS. PLEASE SEE ATTACHED CURRENT WELLBORE DIAGRAM.

After well has been repaired, contact  
Richard Inge @ OCD for MIT witness

NM OIL CONSERVATION  
ARTESIA DISTRICT

JUN 19 2015

Spud Date:

Rig Release Date:

RECEIVED

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Laura A. Moreno TITLE REG COMPLIANCE ADVISOR DATE 6-18-2015

Type or print name LAURA A. MORENO E-mail address: lmoreno@linnenergy.com PHONE: 713-904-6657

For State Use Only

APPROVED BY: R.R. Soble TITLE Dist. H. Spewson DATE 6/23/

Conditions of Approval (if any):



## NM WBD

Well Name: TURNER B 43 INJ

|                       |                    |             |                   |                  |            |                   |                   |           |
|-----------------------|--------------------|-------------|-------------------|------------------|------------|-------------------|-------------------|-----------|
| API/UWI               | Field Name         | County      | State/Prov        | Section          | Township   | Range             | Survey            | Block     |
| 3001505314            | PBNM - PB-GRAYBURG | Eddy        | NM                | 20               | 017-S      | 031-E             |                   |           |
| Ground Elevation (ft) | Orig KB Elev (ft)  | KB-Grd (ft) | Initial Spud Date | Rig Release Date | TD Date    | Latitude (°)      | Longitude (°)     | Operated? |
| 3,618.00              | 3,620.00           | 2.00        | 9/2/1955          |                  | 10/10/1955 | 32° 48' 53.128" N | 103° 53' 54.12" W | Yes       |

Original Hole: 6/17/2015 5:21:20 PM

## Original Hole Data

| MD (ftKB) | Vertical schematic (actual)                       | Casing Strings                                                                  |
|-----------|---------------------------------------------------|---------------------------------------------------------------------------------|
| -3.9      |                                                   | Run Date: 9/6/1955, Casing Description: Surface, Set Depth (ftKB): 528.0        |
| 0.0       |                                                   | Run Date: 10/11/1955, Casing Description: Production, Set Depth (ftKB): 3,236.7 |
| 0.7       |                                                   | Cement Stages                                                                   |
| 2.0       |                                                   | Des, Top (ftKB), Btm (ftKB), Com                                                |
| 101.0     |                                                   | Surface Casing Cement, 101.0, 530.0, 50 sxs cmt, plug method used.              |
| 527.9     |                                                   | Production Casing Cement, 2,345.0, 3,241.0, 125 sxs cmt, plug method used.      |
| 529.9     |                                                   | Cement Squeeze, 1,400.0, 2,375.0                                                |
| 1,399.9   |                                                   | Tubing Strings                                                                  |
| 2,331.0   | 2 holes, Inactive - sqzd 5/20/81; 2,331.0-2,332.0 | Tubing Description, Run Date, Set Depth (ftKB)                                  |
| 2,332.0   |                                                   | Tubing, 1/11/1997, 2,760.7                                                      |
| 2,345.1   |                                                   | Other In Hole                                                                   |
| 2,375.0   |                                                   | Description, Top (ftKB), Btm (ftKB), OD (in), Run Date, Comment                 |
| 2,753.9   |                                                   | Formations                                                                      |
| 2,756.2   |                                                   | Formation, Drill Top MD (ftKB), Drill Btm MD (ftKB)                             |
| 2,760.5   |                                                   |                                                                                 |
| 2,821.9   | 1 hole; 2,822.0                                   |                                                                                 |
| 2,830.1   | 1 hole; 2,830.0                                   |                                                                                 |
| 2,873.0   | 1 hole; 2,873.0-2,875.0                           |                                                                                 |
| 2,875.0   | 1 hole; 2,875.0                                   |                                                                                 |
| 2,877.0   | 1 hole; 2,877.0                                   |                                                                                 |
| 2,878.9   | 1 hole; 2,879.0                                   |                                                                                 |
| 2,906.8   | 1 hole; 2,906.0                                   |                                                                                 |
| 2,910.1   | 1 hole; 2,910.0                                   |                                                                                 |
| 2,918.0   | 3 holes- 2918, 19, 20;                            |                                                                                 |
| 2,919.9   | 2,918.0-2,920.0                                   |                                                                                 |
| 2,923.9   | 1 hole; 2,924.0                                   |                                                                                 |
| 2,928.1   | 1 hole; 2,928.0                                   |                                                                                 |
| 2,930.1   | 1 hole; 2,930.0                                   |                                                                                 |
| 2,932.1   | 1 hole; 2,932.0                                   |                                                                                 |
| 2,934.1   | 1 hole; 2,934.0                                   |                                                                                 |
| 2,956.0   | 1 hole; 2,956.0                                   |                                                                                 |
| 2,962.9   | 1 hole; 2,963.0                                   |                                                                                 |
| 2,973.1   |                                                   |                                                                                 |
| 2,977.0   | 1 hole; 2,977.0                                   |                                                                                 |
| 2,994.1   | 1 hole; 2,994.0                                   |                                                                                 |
| 3,033.1   | 1 hole; 3,033.0                                   |                                                                                 |
| 3,035.1   | 1 hole; 3,035.0                                   |                                                                                 |
| 3,062.0   |                                                   |                                                                                 |
| 3,078.1   | 6 SPF; 3,062.0-3,078.0                            |                                                                                 |
| 3,115.2   | 2 holes; 3,115.0                                  |                                                                                 |
| 3,117.1   | 2 holes; 3,117.0                                  |                                                                                 |
| 3,127.0   | 2 holes; 3,127.0                                  |                                                                                 |
| 3,128.9   | 2 holes; 3,129.0                                  |                                                                                 |
| 3,148.0   | 4 holes, 2 SPF; 3,148.0                           |                                                                                 |
| 3,149.9   | 3,150.0                                           |                                                                                 |
| 3,151.9   | 4 holes, 2 SPF; 3,152.0                           |                                                                                 |
| 3,153.9   | 3,154.0                                           |                                                                                 |
| 3,155.8   | 14 holes, 2 SPF; 3,156.0                          |                                                                                 |
| 3,163.1   | 3,163.0                                           |                                                                                 |
| 3,200.1   | 20 holes, 2 SPF; 3,200.0                          |                                                                                 |
| 3,210.0   | 3,210.0                                           |                                                                                 |
| 3,236.5   |                                                   | Production Casing Cement; 2,345.0-3,241.0                                       |
| 3,241.1   |                                                   | Auto cement plug; 3,210.0-3,241.0                                               |
|           |                                                   | Wellbore; 3,241.0                                                               |