

**NM OIL CONSERVATION**

OCD ARTESIA DISTRICT

JUL 10 2015

Form 3160-3  
(March 2012)

FORM APPROVED  
OMB No. 1004-0137  
Expires October 31, 2014

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**R-111 POTASH  
RECEIVED**


**APPLICATION FOR PERMIT TO DRILL OR REENTER**

5a. Type of work: <input checked="" type="checkbox"/> DRILL <input type="checkbox"/> REENTER		7. If Unit or CA Agreement, Name and No. James Ranch Unit 70965X
5b. Type of Well: <input checked="" type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other <input checked="" type="checkbox"/> Single Zone <input type="checkbox"/> Multiple Zone		8. Lease Name and Well No. James Ranch Unit DI 1 #127H
2. Name of Operator BOPCO, L.P.		9. API Well No. 30-015-43231
3a. Address P.O. Box 2760 Midland, TX 79702	3b. Phone No. (include area code) 432-683-2277	10. Field and Pool, or Exploratory Quahada Ridge (Delaware)
4. Location of Well (Report location clearly and in accordance with any State requirements.)* At surface NENE, UL H, 1506' FNL & 1250' FEL, Lat: N32.380675, Lg:W103.881158 At proposed prod. zone UL A, Sec 23, T22S-R30E, 660' FNL & 330' FEL, Lat: N32.3829, Lg: W103.8434		11. Sec., T. R. M. or Blk. and Survey or Area Sec 21, T22S, R30E
14. Distance in miles and direction from nearest town or post office* 12 Miles Northeast of Loving		12. County or Parish Eddy County
15. Distance from proposed* location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any) 1250'		13. State NM
16. No. of acres in lease 1,400	17. Spacing Unit dedicated to this well 360	
18. Distance from proposed location* to nearest well, drilling, completed, applied for, on this lease, ft. 20'	19. Proposed Depth 18,014' MD / 7,191 TVD	20. BLM/BIA Bond No. on file COB000050
21. Elevations (Show whether DF, KDB, RT, GL, etc.) 3165' GL	22. Approximate date work will start* 07/01/2015	23. Estimated duration 30 days

**24. Attachments**

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No.1, must be attached to this form:

- |  |   |
|--|---|
| 1. Well plat certified by a registered surveyor.   | 4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above). |
| 2. A Drilling Plan.  | 5. Operator certification   |
| 3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office). | 6. Such other site specific information and/or plans as may be required by the BLM.             |

25. Signature 	Name (Printed/Typed) Whitney McKee	Date 7/2/14
Title Engineering Assistant		
Approved by (Signature) <i>/s/George MacDonell</i>	Name (Printed/Typed) George MacDonell	Date JUL - 6 2015
Title FIELD MANAGER		
Office CARLSBAD FIELD OFFICE		

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.  
Conditions of approval, if any, are attached.

**APPROVAL FOR TWO YEARS**

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Continued on page 2)

\*(Instructions on page 2)

Carlsbad Controlled Water Basin  
Carlsbad Controlled Water Basin

*APD*  
*7/07/15*

Approval Subject to General Requirements  
& Special Stipulations Attached

**SEE ATTACHED FOR  
CONDITIONS OF APPROVAL**

DISTRICT I  
1626 N. French Dr., Hobbs, NM 88240  
Phone (575) 393-6161 Fax: (575) 393-0720

DISTRICT II  
811 S. First St., Artesia, NM 88210  
Phone (575) 748-1283 Fax: (575) 748-9720

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410  
Phone (505) 334-8178 Fax: (505) 334-8170

DISTRICT IV  
1220 S. St. Francis Dr., Santa Fe, NM 87505  
Phone (505) 478-3460 Fax: (505) 478-3462

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-102  
Revised August 1, 2011

Submit one copy to appropriate  
District Office

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, New Mexico 87505

WELL LOCATION AND ACREAGE DEDICATION PLAT

AMENDED REPORT

API Number <b>30-015-43231</b>		Pool Code <b>97905-50470</b>	Pool Name <b>QUAHADA RIDGE (DELAWARE)</b>
Property Code <b>306407</b>	Property Name <b>JAMES RANCH UNIT D11</b>		Well Number <b>127H</b>
OGRID No. <b>260737</b>	Operator Name <b>BOPCO, L.P.</b>		Elevation <b>3165'</b>

Surface Location

UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
H	21	22 S	30 E		1506	NORTH	1250	EAST	EDDY

Bottom Hole Location If Different From Surface

UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
A	23	22 S	30 E		660	NORTH	330	EAST	EDDY

Dedicated Acres <b>360</b>	Joint or Infill	Consolidation Code	Order No.
-------------------------------	-----------------	--------------------	-----------

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

**SURFACE LOCATION**  
Lat - N 32°22'50.43"  
Long - W 103°52'52.17"  
NMSPCE - N 502500.0  
E 639590.7  
(NAD-27)

**PROPOSED BOTTOM HOLE LOCATION**  
Lat - N 32°22'58.53"  
Long - W 103°50'36.51"  
NMSPCE - N 503369.6  
E 651220.1  
(NAD-27)

**OPERATOR CERTIFICATION**

*I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.*

*Whitney McKee* 7/2/14  
Signature Date

330' Whitney McKee  
Printed Name  
wbmckee@basspet.com  
Email Address

---

**SURVEYOR CERTIFICATION**

*I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision and that the same is true and correct to the best of my belief.*


DATE SURVEYED: 7/2/13  
Signature: [Signature]  
Professional Surveyor  
7977

Certified to: [Signature] Jones 7977  
DRAIN SURVEYS

0' 1500' 3000' 4500' 6000'  
SCALE: 1" = 3000'  
WO Num.: D11 WELL PLATS


SECTION 21, TOWNSHIP 22 SOUTH, RANGE 30 EAST, N.M.P.M.,  
 EDDY COUNTY, NEW MEXICO.

BOPCO, L.P.  
 JAMES RANCH UNIT D11 127H  
 ELEV. - 3165'  
 Lat - N 32°22'50.43"  
 Long - W 103°52'52.17"  
 NMSPCE- N 502500.0  
 E 639590.7  
 (NAD-27)



SLOT 45 = JAMES RANCH UNIT D11 127H

LOVING, NM IS ±14 MILES TO THE SOUTHWEST OF LOCATION.



Directions to Location:



FROM THE JUNCTION OF HWY 128 AND CIMARRON,  
 GO NORTH ON CIMARRON FOR APPROX. 6.2 MILES  
 TO LEASE ROAD, ON LEASE ROAD GO  
 SOUTHWESTERLY 0.2 MILES TURNING NORTHWESTERLY  
 1.3 MILES TO PROPOSED WELL LOCATION.



P.O. Box 1786 (575) 393-7316 - Office  
 1120 N. West County Rd. (575) 392-2206 - Fax  
 Hobbs, New Mexico 88241 basinsurveys.com

<b>BOPCO, L.P.</b>
REF: JAMES RANCH UNIT D11 127H / WELL PAD TOPO
THE JAMES RANCH UNIT D11 127H LOCATED 1506' FROM THE NORTH LINE AND 1250' FROM THE EAST LINE OF SECTION 21, TOWNSHIP 22 SOUTH, RANGE 30 EAST, N.M.P.M., EDDY COUNTY, NEW MEXICO.

SECTION 21, TOWNSHIP 22 SOUTH, RANGE 30 EAST, N.M.P.M.,  
 EDDY COUNTY, NEW MEXICO.



**BOPCO, L.P.** 


REF: JAMES RANCH UNIT D11 127H / WELL PAD TOPO

THE JAMES RANCH UNIT D11 127H LOCATED 1506' FROM  
 THE NORTH LINE AND 1250' FROM THE EAST LINE OF  
 SECTION 21, TOWNSHIP 22 SOUTH, RANGE 30 EAST,  
 N.M.P.M., EDDY COUNTY, NEW MEXICO.

**basin surveys**  
 focused on excellence in the oilfield

P.O. Box 1786  
 1120 N. West County Rd.  
 Hobbs, New Mexico 88241

(575) 393-7316 - Office  
 (575) 392-2206 - Fax  
 basin-surveys.com




**JAMES RANCH UNIT D11 127H**

Located 1506' FNL and 1250' FEL  
 Section 21, Township 22 South, Range 30 East,  
 N.M.P.M., Eddy County, New Mexico.



focused on excellence  
 in the oilfield

P.O. Box 1786  
 1120 N. West County Rd.  
 Hobbs, New Mexico 88241  
 (575) 393-7316 - Office  
 (575) 392-2206 - Fax  
 basinsurveys.com




W.O. Number: JMS D11 WELL PLATS

Survey Date: 10-17-2013

YELLOW TINT - USA LAND  
 BLUE TINT - STATE LAND  
 NATURAL COLOR - FEE LAND



**BOPCO, L.P.**



**JAMES RANCH UNIT D11 127H**

Located 1506' FNL and 1250' FEL  
 Section 21, Township 22 South, Range 30 East,  
 N.M.P.M., Eddy County, New Mexico.

**basin surveys**  
 focused on excellence in the oilfield

P.O. Box 1786  
 1120 N. West County Rd.  
 Hobbs, New Mexico 88241  
 (575) 393-7316 - Office  
 (575) 392-2206 - Fax  
 basinsurveys.com


0 1 MI 2 MI 3 MI 4 MI  
 SCALE: 1" = 2 MILES

W.O. Number: JMS D11 WELL PLATS

Survey Date: 10-17-2013

YELLOW TINT - USA LAND  
 BLUE TINT - STATE LAND  
 NATURAL COLOR - FEE LAND

**BOPCO, L.P.**




**JAMES RANCH UNIT DI1 127H**

Located 1506' FNL and 1250' FEL  
 Section 21, Township 22 South, Range 30 East,  
 N.M.P.M., Eddy County, New Mexico.



P.O. Box 1786  
 1120 N. West County Rd.  
 Hobbs, New Mexico 88241  
 (575) 393-7316 - Office  
 (575) 392-2206 - Fax  
 basinsurveys.com



W.O. Number: JMS DI1 WELL PLATS  
 Survey Date: 10-17-2013  
 YELLOW TINT - USA LAND  
 BLUE TINT - STATE LAND  
 NATURAL COLOR - FEE LAND




**BOPCO, L.P.**

Exhibit "D"

RIG LAYOUT SCHEMATIC  
 INCLUSIVE OF CLOSED-LOOP DESIGN PLAN  
 Solids Control Equipment Legend

- 1) Roll Off Bin
- 2) Steel Tank
- 3) Mud Cleaner
- 4) Shaker
- 5) Centrifuge
- 6) Dewatering Unit
- 7) Catch Tank
- 8) Choke Manifold
- A) Bleed line from choke manifold



**JAMES RANCH UNIT DI1 127H**  
 Located 1506' FNL and 1250' FEL  
 Section 21, Township 22 South, Range 30 East,  
 N.M.P.M., Eddy County, New Mexico.



**basin surveys**  
 focused on excellence  
 in the oilfield

P.O. Box 1786  
 1120 N. West County Rd.  
 Hobbs, New Mexico 88241  
 (575) 393-7316 - Office  
 (575) 392-2206 - Fax  
 basinsurveys.com


SCALE: NONE

W.O. Number: JMS DI1 WELL PLATS


Survey Date: 10-17-2013

**BOPCO, L.P.**

# Access Road Diagram



# Flowline Route Diagram 4



**DRILLING PROGRAM  
BOPCO, L.P.**

**NAME OF WELL: James Ranch Unit DI 1 #127H.**

1. LEGAL DESCRIPTION - SURFACE: 1506' FNL, 1250' FEL, Sec 21-T22S-R30E. BHL: 1890' FSL, 2090' FEL, Sec 21-T25S-R30E. **The James Ranch Unit DI 1# 127H has a nonstandard surface location.**

2. Ground level elevation: 3165' KB elevation (estimated): 3191'

3. Proposed Drilling Depth: 18014' MD 7191' TVD

**4. WATER, OIL, GAS AND/OR MINERAL BEARING FORMATIONS:**

Formation Description	Est from KB (TVD)	BEARING
T/Fresh Water	131'	Fresh Water
T/Rustler	191'	Barren
T/Salado	556'	Barren
T/Lamar	3536'	Barren
Ramsey	3581'	Oil/Gas
Cherry Canyon	4459'	Oil/Gas
Brushy Canyon	5784'	Oil/Gas
T/Delaware Lower U Sand	6986'	Oil/Gas
TD Horizontal Hole (In Delaware lower U Sand)	7191'	Oil/Gas

5. Possible mineral bearing formation: Shown above

**6. Casing Program**

Casing	Set Depth MD	Set Depth (Deepest) TVD	Casing Size	Hole Size	Casing Weight	Casing Grade	Thread	Condition	Tension SF	Collapse SF	Burst SF
Surface	0-536'	536'	13-3/8"	17-1/2"	48 #	H-40	ST&C	New	14.56	2.82	1.13
Intermediate	0-3561'	3561'	9-5/8"	12-1/4"	40 #	J-55	LT&C	New	5.24	1.25	1.99
Production	0-7454'	7053'	7"	8-3/4"	26 #	N-80	LT&C	New	3.29	1.40	1.85
Completion System/Liner	7404- <del>18014</del> 18,526	7191'	4-1/2"	6-1/8"	11.6 #	HCP-110	LT&C	New	3.88	2.26	2.66

\* Depending on availability. *7304' must tie back 100'*

**DESIGN CRITERIA AND CASING LOADING ASSUMPTIONS:**

SURFACE CASING - (13-3/8")

**Tension** A 1.6 design factor utilizing the effects of buoyancy (9.2 ppg).

**Collapse** A 1.0 design factor with full internal evacuation and a collapse force equal to the mud gradient in which the casing will be run (0.48 psi/ft). The effects of axial load on collapse will be considered.

**Burst** A 1.3 design factor with a surface pressure equal to the fracture gradient at setting depth less a gas gradient to the surface. Internal burst force at the shoe will be fracture pressure at that depth. Backup pressure will be formation pore pressure. In all cases a conservative fracture pressure will be used such that it represents the upper limit of potential fracture resistance up to a 1.0 psi/ft gradient. The effects of tension on burst will not be utilized.

PROTECTIVE CASING - (9-5/8")

- Tension A 1.6 design factor utilizing the effects of buoyancy (10.2 ppg).
- Collapse A 1.125 design factor with full internal evacuation and a collapse force equal to the mud gradient in which the casing will be run (0.52 psi/ft). The effects of axial load on collapse will be considered.

In the case of development drilling, collapse design should be analyzed using internal evacuation equal to 1/3 the proposed total depth of the well. This criterion will be used when there is absolutely no potential of the protective string being used as a production casing string.

- Burst A 1.0 surface design factor and a 1.3 downhole design factor with a surface pressure equivalent to the fracture gradient at setting depth less a gas gradient to the surface. Internal burst force at the shoe will be fracture pressure at that depth. Back pressure will be formation pore pressure. In all cases a conservative fracture pressure will be used such that it represents the upper limit of potential fracture resistance up to a 1.0 psi/ft gradient.

Production CASING - (7")

- Tension A 1.6 design factor utilizing the effects of buoyancy (9.0 ppg).
- Collapse A 1.125 design factor with full internal evacuation and a collapse force equal to the mud gradient in which the casing will be run (0.48 psi/ft). The effects of axial load on collapse will be considered.
- Burst A 1.25 design factor with anticipated maximum tubing pressure (5000 psig) on top of the maximum anticipated packer fluid gradient. (0.433 psi/ft) Backup on production strings will be formation pore pressure. (0.433 psi/ft) The effects of tension on burst will not be utilized.

Completion System - (4-1/2")

- Tension A 1.6 design factor utilizing the effects of buoyancy (9.2 ppg).
- Collapse A 1.125 design factor with full internal evacuation and a collapse force equal to the mud gradient in which the casing will be run (0.48 psi/ft). The effects of axial load on collapse will be considered.
- Burst A 1.25 design factor with anticipated maximum tubing pressure (5000 psig) on top of the maximum anticipated packer fluid gradient. (0.433 psi/ft) Backup on production strings will be formation pore pressure. (0.433 psi/ft) The effects of tension on burst will not be utilized.

**7. CEMENT**

Surface	Sacks	Weight (ppg)	Yield (FT <sup>3</sup> /SX)	GALS/SX	Cement Blend
Lead	190	13.50	1.75	8.69	Class C +2% CACL + 4% Bentonite + 0.25 LB/SK Cello Flake + 3 lb/sk LCM-1
Tail	340	14.80	1.35	6.35	Class C + 2% CACL + 0.25 LB/SK CF, 0.25LB/SK Cello Flake +3 lb/sk LCM-1

**TOC: 0' 100% Excess**

Intermediate	Sacks	Weight (ppg)	Yield (FT <sup>3</sup> /SX)	GALS/SX	Cement Blend
Lead	680	12.90	1.85	9.32	EconoCEM HLC + 5% CaCl + 5#/sk Gilsonite
Tail	190	14.80	1.33	6.34	HalCem C

**TOC: 0' 30% Excess**

Production Stage 1	Sacks	Weight (ppg)	Yield (FT <sup>3</sup> /SX)	GALS/SX	Cement Blend
Lead	120	11.0	2.64	14.87	Tuned Light + 0.125 pps Poly-E-Flake
Tail	200	12.00	2.03	11.41	Class "H" + 0.5% Halad-344 + 0.25% CFR-3 + 0.5% Econolite

TOC: 5000'

50% Excess

DV Tool @ 5000'

Production Stage 2	Sacks	Weight (ppg)	Yield (FT <sup>3</sup> /SX)	GALS/SX	Cement Blend
Lead	410	11.0	2.35	11.70	Tuned Light + 0.125 pps Poly-E-Flake

TOC: 0'

10% Excess inside casing, 50% excess in open hole

Cement volumes will be adjusted proportionately for depth changes of the multi stage tool.

### COMPLETIONS SYSTEM

A 4-1/2" completion system with open hole packers will be run in the producing lateral to a depth of 18014'. The top of the Completion System will be set at approximately 7404'. Cement will not be required for this system.

### 8. PRESSURE CONTROL EQUIPMENT (SEE ATTACHED DIAGRAM A, B, C or Z)

After running the 13-3/8" surface casing, a 13-5/8" BOP/BOPE system with a minimum rating of 3M will be installed on the Cameron Multi-Bowl System wellhead. The BOP/BOPE will be pressure tested to 250 psi low and 3000 psi high after installation on the surface casing which will cover testing requirements for the duration of the well as per Onshore Order #2. The 9-5/8" intermediate casing and 7" production casing will be run with a mandrel hanger through the 13-5/8" BOP/BOPE system without breaking any connections on the BOP/BOPE system and thus not requiring a pressure test. Please find attached wellhead schematic. The field reports from the Cameron representative and the BOP test information will be provided in a subsequent report.

These tests will be performed:

- Upon installation
- After any component changes
- Thirty days after a previous test
- As required by well conditions
- Any time a seal is broken within a system

A function test to insure that the preventers are operating correctly will be performed on each trip

BOPCO, L.P. would like to request a variance to use an armored, 3" flex hose for the choke line in the drilling of the well if the rig is equip with hose. (See specification for hose that might be used, attached with APD exhibits). **If an armored flex hose is utilized, the company man will have all of the proper certified paper work for that hose available on location.**

### 9. MUD PROGRAM

DEPTH	MUD TYPE	Weight	FV	PV	YP	Ph
0-536'	FW Spud Mud	8.5 - 9.2	38-70	NC	NC	9.5 - 10.5
536' - 3561'	Brine Water	9.8 - 10.2	28-30	NC	NC	9.5 - 10.5
3561' - 7454'	FW/Gel	8.7 - 9.0	28-36	NC	NC	9.5 - 10.5
7454'-18014'	Synthetic OBM	8.7 - 9.2	36-55	16-30	16-30	NA

**NOTE: Sufficient mud materials will be kept on location at all times in order to combat lost circulation or control unexpected kicks. May increase vis for logging purposes only.**

The mud monitoring system installed on the rig is an electronic Pason, which satisfies onshore order 1 requirements.

## 10. Drilling Plan

KOP: 6088'                      EOC: 8214' MD (7191' TVD)

Set surface and intermediate casing strings. Drill production hole to KOP, continue drilling curve. Set and cement production casing at the end of a 70 degree, 200' tangent (in curve). Drill completion hole to TD. Run completions system.

## 11. TECHNICAL STAGES OF OPERATION

### A) TESTING

None anticipated.

### B) LOGGING

Run #1: GR with MWD during drilling of build and horizontal portions of 8-3/4" and 6-1/8" hole.

Run #2: Shuttle log w/GR, PE, Density, Neutron, Resistivity in lateral leg open hole are possible.

Mud Logger: Rigged up at 100'

### C) CONVENTIONAL CORING

None anticipated

## 12. H<sub>2</sub>S SAFETY EQUIPMENT

H<sub>2</sub>S monitors shall be installed prior to drilling out the surface shoe. If H<sub>2</sub>S is encountered in quantities greater than 10 PPM, the well will be shut in and H<sub>2</sub>S equipment will be installed, including a flare line that will be extended pursuant to Onshore Oil and Gas Order #6. **(Please refer to diagram B, or C for choke manifold and closed loop system layout when H<sub>2</sub>S is present) Please refer to H<sub>2</sub>S location diagram for location of important H<sub>2</sub>S safety items.**

## 13. ANTICIPATED RESERVOIR CONDITIONS

Normal pressures are anticipated throughout Delaware section. A BHP of 3440 psi (max) or MWE of 9.2 ppg is expected. Lost circulation may exist in the Delaware Section from 3,581'-7,191' TVD.

## 14. OTHER PERTINENT INFORMATION

### A) Auxiliary Equipment

Upper and lower kelly cocks. Full opening stab in valve on the rig floor.

### B) Anticipated Starting Date

Upon approval

30 days drilling operations

14 days completion operations




BTC



# BOPCO, LP

Location: Eddy County, NM  
 Field: JRU NAD27  
 Facility: JRU Drilling Island 1

Slot: JRU DI1 #127H  
 Well: JRU DI1 #127H  
 Wellbore: JRU DI1 #127H PWB



BGGM (1945.0 to 2015.0) Dip: 60.21° Field: 48427 nT  
 Magnetic North is 7.56 degrees East of True North (at 10/21/2013)  
 Grid North is 0.24 degrees East of True North  
 To correct azimuth from True to Grid subtract 0.24 degrees  
 To correct azimuth from Magnetic to Grid add 7.32 degrees

Plot reference wellpath is Rev-C.0	
True vertical depths are referenced to Rig on No.35H SHL (KB)	Grid System: NAD27 / TM New Mexico SP, Eastern Zone (3001), US feet
Measured depths are referenced to Rig on No.35H SHL (KB)	North Reference: Grid north
Rig on No.35H SHL (KB) to Mean Sea Level: 3191 feet	Scale: True distance
Mean Sea Level to Mud line (At Slot: JRU DI1 #127H): 0 feet	Depths are in feet
Coordinates are in feet referenced to Slot	Created by: bumranj on 6/30/2014

Well Profile Data								
Design Comment	MD (ft)	Inc (°)	Az (°)	TVD (ft)	Local N (ft)	Local E (ft)	DLS (°/100ft)	VS (ft)
Tie On	26.00	0.000	48.000	26.00	0.00	0.00	0.00	0.00
Est KOP	6088.00	0.000	48.000	6088.00	0.00	0.00	0.00	0.00
70° Curve	7254.67	70.000	48.000	6985.34	420.43	466.94	6.00	494.46
200' Tangent	7454.67	70.000	48.000	7053.74	546.19	606.60	0.00	642.36
EOC	8214.26	90.000	90.000	7191.00	798.52	1288.16	6.02	1339.50
TL	8216.30	90.000	90.041	7191.00	798.52	1290.19	2.00	1341.54
DI1 #127H PBHL	18526.46	90.000	90.041	7191.00	791.18	11600.35	0.00	11627.30

DI1 #127H PBHL: 90.00° Inc, 18526.46ft MD, 7191.00ft TVD, 11627.30ft VS

Azimuth 86.10° with reference 0.00 N, 0.00 E

Scale 1 inch = 1200 ft



# Planned Wellpath Report

Rev-C.0  
Page n of nn



REFERENCE WELLPATH IDENTIFICATION			
Operator	BOPCO, LP	Slot	JRU D11 #127H
Area	Eddy County, NM	Well	JRU D11 #127H
Field	JRU NAD27	Wellbore	JRU D11 #127H PWB
Facility	JRU Drilling Island 1		

REPORT SETUP INFORMATION			
Projection System	NAD27 / TM New Mexico SP, Eastern Zone (3001), US feet	Software System	WellArchitect@ 4.0.0
North Reference	Grid	User	Burnranj
Scale	0.999931	Report Generated	6/30/2014 at 4:30:18 PM
Convergence at slot	0.24° East	Database/Source file	WA_MIDLAND/C:\Users\burnranj\AppData\Roaming\Well Explorer\temp\BOPCO, LP JRU D11 #127H (Rev-C.0).xml

WELLPATH LOCATION						
	Local coordinates		Grid coordinates		Geographic coordinates	
	North[ft]	East[ft]	Easting[US ft]	Northing[US ft]	Latitude	Longitude
Slot Location	-55.10	570.66	639590.70	502500.00	32°22'50.435"N	103°52'52.165"W
Facility Reference Pt			639020.08	502555.10	32°22'51.004"N	103°52'58.816"W
Field Reference Pt			652495.44	494904.92	32°21'34.711"N	103°50'22.090"W

WELLPATH DATUM			
Calculation method	Minimum curvature	Rig on No.35H SHL (KB) to Facility Vertical Datum	3191.00ft
Horizontal Reference Pt	Slot	Rig on No.35H SHL (KB) to Mean Sea Level	3191.00ft
Vertical Reference Pt	Rig on No.35H SHL (KB)	Rig on No.35H SHL (KB) to Mud Line at Slot (JRU D11 #127H)	3191.00ft
MD Reference Pt	Rig on No.35H SHL (KB)	Section Origin	N 0.00, E 0.00 ft
Field Vertical Reference	Mean Sea Level	Section Azimuth	86.10°



# Planned Wellpath Report

Rev-C.0  
Page n of nn



REFERENCE WELLPATH IDENTIFICATION			
Operator	BOPCO, LP	Slot	JRU D11 #127H
Area	Eddy County, NM	Well	JRU D11 #127H
Field	JRU NAD27	Wellbore	JRU D11 #127H PWB
Facility	JRU Drilling Island 1		

WELLPATH DATA (142 stations) † = interpolated/extrapolated station								
MD [ft]	Inclination [°]	Azimuth [°]	TVD [ft]	Vert Sect [ft]	North [ft]	East [ft]	DLS [°/100ft]	Comments
0.00†	0.000	48.000	0.00	0.00	0.00	0.00	0.00	
26.00	0.000	48.000	26.00	0.00	0.00	0.00	0.00	Tie On
131.00†	0.000	48.000	131.00	0.00	0.00	0.00	0.00	Fresh Water
191.00†	0.000	48.000	191.00	0.00	0.00	0.00	0.00	T/Rustler
556.00†	0.000	48.000	556.00	0.00	0.00	0.00	0.00	Salado
3283.00†	0.000	48.000	3283.00	0.00	0.00	0.00	0.00	B/Salt
3536.00†	0.000	48.000	3536.00	0.00	0.00	0.00	0.00	Lamar
3581.00†	0.000	48.000	3581.00	0.00	0.00	0.00	0.00	Ramsey
4459.00†	0.000	48.000	4459.00	0.00	0.00	0.00	0.00	Cherry Canyon
5784.00†	0.000	48.000	5784.00	0.00	0.00	0.00	0.00	Brushy Canyon
6088.00	0.000	48.000	6088.00	0.00	0.00	0.00	0.00	Est KOP
6100.00†	0.720	48.000	6100.00	0.06	0.05	0.06	6.00	
6200.00†	6.720	48.000	6199.74	5.16	4.39	4.88	6.00	
6300.00†	12.720	48.000	6298.26	18.44	15.68	17.42	6.00	
6400.00†	18.720	48.000	6394.48	39.75	33.80	37.54	6.00	
6500.00†	24.720	48.000	6487.34	68.86	58.55	65.03	6.00	
6600.00†	30.720	48.000	6575.82	105.45	89.66	99.58	6.00	
6700.00†	36.720	48.000	6658.96	149.12	126.79	140.82	6.00	
6800.00†	42.720	48.000	6735.84	199.39	169.53	188.29	6.00	
6900.00†	48.720	48.000	6805.62	255.70	217.42	241.47	6.00	
7000.00†	54.720	48.000	6867.55	317.45	269.92	299.78	6.00	
7100.00†	60.720	48.000	6920.93	383.95	326.47	362.58	6.00	
7200.00†	66.720	48.000	6965.18	454.48	386.43	429.18	6.00	
7254.67	70.000	48.000	6985.34	494.46	420.43	466.94	6.00	70° Curve
7300.00†	70.000	48.000	7000.83	527.99	448.94	498.59	0.00	
7400.00†	70.000	48.000	7035.05	601.94	511.81	568.43	0.00	
7454.67	70.000	48.000	7053.74	642.36	546.19	606.60	0.00	200' Tangent
7500.00†	70.989	50.697	7068.88	676.60	574.02	639.02	6.02	
7554.23†	72.222	53.881	7086.00	719.35	605.49	679.73	6.02	Delaware Lower U Sand
7600.00†	73.303	56.533	7099.56	756.86	630.42	715.62	6.02	
7700.00†	75.777	62.225	7126.24	842.92	679.46	798.53	6.02	
7800.00†	78.382	67.791	7148.62	933.82	720.60	886.84	6.02	
7900.00†	81.092	73.252	7166.44	1028.56	753.38	979.57	6.02	
8000.00†	83.880	78.631	7179.53	1126.11	777.43	1075.70	6.02	
8100.00†	86.721	83.954	7187.73	1225.37	792.51	1174.17	6.02	
8200.00†	89.590	89.246	7190.95	1325.27	798.43	1273.89	6.02	
8214.26	90.000	90.000	7191.00	1339.50	798.52	1288.16	6.02	EOC
8216.30	90.000	90.041	7191.00	1341.54	798.52	1290.19	2.00	TL
8300.00†	90.000	90.041	7191.00	1425.04	798.46	1373.89	0.00	
8400.00†	90.000	90.041	7191.00	1524.80	798.39	1473.89	0.00	
8500.00†	90.000	90.041	7191.00	1624.57	798.32	1573.89	0.00	
8600.00†	90.000	90.041	7191.00	1724.33	798.25	1673.89	0.00	
8700.00†	90.000	90.041	7191.00	1824.09	798.18	1773.89	0.00	
8800.00†	90.000	90.041	7191.00	1923.86	798.10	1873.89	0.00	
8900.00†	90.000	90.041	7191.00	2023.62	798.03	1973.89	0.00	



# Planned Wellpath Report

Rev-C.0  
Page n of nn



REFERENCE WELLPATH IDENTIFICATION			
Operator	BOPCO, LP	Slot	JRU D11 #127H
Area	Eddy County, NM	Well	JRU D11 #127H
Field	JRU NAD27	Wellbore	JRU D11 #127H PWB
Facility	JRU Drilling Island 1		

WELLPATH DATA (142 stations) † = Interpolated/extrapolated station								
MD [ft]	Inclination [°]	Azimuth [°]	TVD [ft]	Vert Sect [ft]	North [ft]	East [ft]	DLS [%/100ft]	Comments
9000.00†	90.000	90.041	7191.00	2123.38	797.96	2073.89	0.00	
9100.00†	90.000	90.041	7191.00	2223.15	797.89	2173.89	0.00	
9200.00†	90.000	90.041	7191.00	2322.91	797.82	2273.89	0.00	
9300.00†	90.000	90.041	7191.00	2422.67	797.75	2373.89	0.00	
9400.00†	90.000	90.041	7191.00	2522.44	797.68	2473.89	0.00	
9500.00†	90.000	90.041	7191.00	2622.20	797.61	2573.89	0.00	
9600.00†	90.000	90.041	7191.00	2721.96	797.53	2673.89	0.00	
9700.00†	90.000	90.041	7191.00	2821.73	797.46	2773.89	0.00	
9800.00†	90.000	90.041	7191.00	2921.49	797.39	2873.89	0.00	
9900.00†	90.000	90.041	7191.00	3021.25	797.32	2973.89	0.00	
10000.00†	90.000	90.041	7191.00	3121.02	797.25	3073.89	0.00	
10100.00†	90.000	90.041	7191.00	3220.78	797.18	3173.89	0.00	
10200.00†	90.000	90.041	7191.00	3320.54	797.11	3273.89	0.00	
10300.00†	90.000	90.041	7191.00	3420.31	797.04	3373.89	0.00	
10400.00†	90.000	90.041	7191.00	3520.07	796.96	3473.89	0.00	
10500.00†	90.000	90.041	7191.00	3619.83	796.89	3573.89	0.00	
10600.00†	90.000	90.041	7191.00	3719.60	796.82	3673.89	0.00	
10700.00†	90.000	90.041	7191.00	3819.36	796.75	3773.89	0.00	
10800.00†	90.000	90.041	7191.00	3919.12	796.68	3873.89	0.00	
10900.00†	90.000	90.041	7191.00	4018.89	796.61	3973.89	0.00	
11000.00†	90.000	90.041	7191.00	4118.65	796.54	4073.89	0.00	
11100.00†	90.000	90.041	7191.00	4218.42	796.47	4173.89	0.00	
11200.00†	90.000	90.041	7191.00	4318.18	796.40	4273.89	0.00	
11300.00†	90.000	90.041	7191.00	4417.94	796.32	4373.89	0.00	
11400.00†	90.000	90.041	7191.00	4517.71	796.25	4473.89	0.00	
11500.00†	90.000	90.041	7191.00	4617.47	796.18	4573.89	0.00	
11600.00†	90.000	90.041	7191.00	4717.23	796.11	4673.89	0.00	
11700.00†	90.000	90.041	7191.00	4817.00	796.04	4773.89	0.00	
11800.00†	90.000	90.041	7191.00	4916.76	795.97	4873.89	0.00	
11900.00†	90.000	90.041	7191.00	5016.52	795.90	4973.89	0.00	
12000.00†	90.000	90.041	7191.00	5116.29	795.83	5073.89	0.00	
12100.00†	90.000	90.041	7191.00	5216.05	795.75	5173.89	0.00	
12200.00†	90.000	90.041	7191.00	5315.81	795.68	5273.89	0.00	
12300.00†	90.000	90.041	7191.00	5415.58	795.61	5373.89	0.00	
12400.00†	90.000	90.041	7191.00	5515.34	795.54	5473.89	0.00	
12500.00†	90.000	90.041	7191.00	5615.10	795.47	5573.89	0.00	
12600.00†	90.000	90.041	7191.00	5714.87	795.40	5673.89	0.00	
12700.00†	90.000	90.041	7191.00	5814.63	795.33	5773.89	0.00	
12800.00†	90.000	90.041	7191.00	5914.39	795.26	5873.89	0.00	
12900.00†	90.000	90.041	7191.00	6014.16	795.19	5973.89	0.00	
13000.00†	90.000	90.041	7191.00	6113.92	795.11	6073.89	0.00	
13100.00†	90.000	90.041	7191.00	6213.68	795.04	6173.89	0.00	
13200.00†	90.000	90.041	7191.00	6313.45	794.97	6273.89	0.00	
13300.00†	90.000	90.041	7191.00	6413.21	794.90	6373.89	0.00	
13400.00†	90.000	90.041	7191.00	6512.97	794.83	6473.89	0.00	



# Planned Wellpath Report

Rev-C.0

Page n of nn



REFERENCE WELLPATH IDENTIFICATION			
Operator	BOPCO, LP	Slot	JRU D11 #127H
Area	Eddy County, NM	Well	JRU D11 #127H
Field	JRU NAD27	Wellbore	JRU D11 #127H PWB
Facility	JRU Drilling Island I		

WELLPATH DATA (142 stations) † = interpolated/extrapolated station								
MD [ft]	Inclination [°]	Azimuth [°]	TVD [ft]	Vert Sect [ft]	North [ft]	East [ft]	DLS [°/100ft]	Comments
13500.00†	90.000	90.041	7191.00	6612.74	794.76	6573.89	0.00	
13600.00†	90.000	90.041	7191.00	6712.50	794.69	6673.89	0.00	
13700.00†	90.000	90.041	7191.00	6812.26	794.62	6773.89	0.00	
13800.00†	90.000	90.041	7191.00	6912.03	794.54	6873.89	0.00	
13900.00†	90.000	90.041	7191.00	7011.79	794.47	6973.89	0.00	
14000.00†	90.000	90.041	7191.00	7111.55	794.40	7073.89	0.00	
14100.00†	90.000	90.041	7191.00	7211.32	794.33	7173.89	0.00	
14200.00†	90.000	90.041	7191.00	7311.08	794.26	7273.89	0.00	
14300.00†	90.000	90.041	7191.00	7410.84	794.19	7373.89	0.00	
14400.00†	90.000	90.041	7191.00	7510.61	794.12	7473.89	0.00	
14500.00†	90.000	90.041	7191.00	7610.37	794.05	7573.89	0.00	
14600.00†	90.000	90.041	7191.00	7710.13	793.98	7673.89	0.00	
14700.00†	90.000	90.041	7191.00	7809.90	793.90	7773.89	0.00	
14800.00†	90.000	90.041	7191.00	7909.66	793.83	7873.89	0.00	
14900.00†	90.000	90.041	7191.00	8009.42	793.76	7973.89	0.00	
15000.00†	90.000	90.041	7191.00	8109.19	793.69	8073.89	0.00	
15100.00†	90.000	90.041	7191.00	8208.95	793.62	8173.89	0.00	
15200.00†	90.000	90.041	7191.00	8308.71	793.55	8273.89	0.00	
15300.00†	90.000	90.041	7191.00	8408.48	793.48	8373.89	0.00	
15400.00†	90.000	90.041	7191.00	8508.24	793.41	8473.89	0.00	
15500.00†	90.000	90.041	7191.00	8608.00	793.33	8573.89	0.00	
15600.00†	90.000	90.041	7191.00	8707.77	793.26	8673.89	0.00	
15700.00†	90.000	90.041	7191.00	8807.53	793.19	8773.89	0.00	
15800.00†	90.000	90.041	7191.00	8907.29	793.12	8873.89	0.00	
15900.00†	90.000	90.041	7191.00	9007.06	793.05	8973.89	0.00	
16000.00†	90.000	90.041	7191.00	9106.82	792.98	9073.89	0.00	
16100.00†	90.000	90.041	7191.00	9206.58	792.91	9173.89	0.00	
16200.00†	90.000	90.041	7191.00	9306.35	792.84	9273.89	0.00	
16300.00†	90.000	90.041	7191.00	9406.11	792.76	9373.89	0.00	
16400.00†	90.000	90.041	7191.00	9505.87	792.69	9473.89	0.00	
16500.00†	90.000	90.041	7191.00	9605.64	792.62	9573.89	0.00	
16600.00†	90.000	90.041	7191.00	9705.40	792.55	9673.89	0.00	
16700.00†	90.000	90.041	7191.00	9805.16	792.48	9773.89	0.00	
16800.00†	90.000	90.041	7191.00	9904.93	792.41	9873.89	0.00	
16900.00†	90.000	90.041	7191.00	10004.69	792.34	9973.89	0.00	
17000.00†	90.000	90.041	7191.00	10104.45	792.27	10073.89	0.00	
17100.00†	90.000	90.041	7191.00	10204.22	792.20	10173.89	0.00	
17200.00†	90.000	90.041	7191.00	10303.98	792.12	10273.89	0.00	
17300.00†	90.000	90.041	7191.00	10403.74	792.05	10373.89	0.00	
17400.00†	90.000	90.041	7191.00	10503.51	791.98	10473.89	0.00	
17500.00†	90.000	90.041	7191.00	10603.27	791.91	10573.89	0.00	
17600.00†	90.000	90.041	7191.00	10703.03	791.84	10673.89	0.00	
17700.00†	90.000	90.041	7191.00	10802.80	791.77	10773.89	0.00	
17800.00†	90.000	90.041	7191.00	10902.56	791.70	10873.89	0.00	
17900.00†	90.000	90.041	7191.00	11002.32	791.63	10973.89	0.00	



# Planned Wellpath Report

Rev-C.0  
Page n of nn



## REFERENCE WELLPATH IDENTIFICATION

Operator	BOPCO, LP	Slot	JRU D11 #127H
Area	Eddy County, NM	Well	JRU D11 #127H
Field	JRU NAD27	Wellbore	JRU D11 #127H PWB
Facility	JRU Drilling Island 1		

## WELLPATH DATA (142 stations) † = interpolated/extrapolated station


MD [ft]	Inclination [°]	Azimuth [°]	TVD [ft]	Vert Sect [ft]	North [ft]	East [ft]	DLS [°/100ft]	Comments
18000.00†	90.000	90.041	7191.00	11102.09	791.55	11073.89	0.00	
18100.00†	90.000	90.041	7191.00	11201.85	791.48	11173.89	0.00	
18200.00†	90.000	90.041	7191.00	11301.61	791.41	11273.89	0.00	
18300.00†	90.000	90.041	7191.00	11401.38	791.34	11373.89	0.00	
18400.00†	90.000	90.041	7191.00	11501.14	791.27	11473.89	0.00	
18500.00†	90.000	90.041	7191.00	11600.90	791.20	11573.89	0.00	
18526.46	90.000	90.041	7191.00†	11627.30	791.18	11600.35	0.00	D11 #127H PBHL

## TARGETS

Name	MD [ft]	TVD [ft]	North [ft]	East [ft]	Grid East [US ft]	Grid North [US ft]	Latitude	Longitude	Shape
1) JRU Pad No.35H PBHL		7191.00	869.66	11630.22	651220.10	503369.60	32°22'58.534"N	103°50'36.507"W	point


## SURVEY PROGRAM - Ref Wellbore: JRU D11 #127H PWB Ref Wellpath: Rev-C.0

Start MD [ft]	End MD [ft]	Positional Uncertainty Model	Log Name/Comment	Wellbore
26.00	18014.27	NaviTrak (Standard)		JRU D11 #127H PWB




**13-5/8" X 3-M BOPE (2 Rams and Rotating Head) & Closed Loop System Equipment Schematic Diagram A**

Note: all valves & lines on choke manifold are 3" unless otherwise noted. Exact manifold configuration may vary.



**13-5/8" X 3-M BOPE (2 Rams and Rotating Head) & Closed Loop System Equipment Schematic H2S contingency Diagram B**

Note: all valves & lines on choke manifold are 3" unless otherwise noted. Exact manifold configuration may vary.



Fill up line

Closed Loop Equipment \ Roll off Bins & Track

Vent to edge of location

Rotating Head

Mud

Volume

Process

Shakers

Mud/Gas Separator

Annular

Flowline to Shakers

A remote operated choke will be installed in an H2S situation

2" minimum Line to Shakers and or mud/gas separator

Latshaw 18 additional line to Mud pits, used to bypass mud/gas separator if necessary

Pipe Rams

Hand adjustable choke 3000 psi WP or above

Blind Rams

2" Kill Line

1-2" valve \ w check valve

3" minimum choke line or flex hose

4" VALVE w \ gauge

B U F F E R T A N K

3" minimum Panic line to half Frac. Located 100' from well outside designated H2S areas. Not connected to buffer tank

Hand adjustable choke 3000 psi WP or above

Latshaw 4 closed loop system, with Latshaw 18 addition "clouded."

**Latshaw 13-5/8" X 3-M BOPE (2 Rams and Rotating Head) & Closed Loop System Equipment Schematic Diagram C**

Note: all valves & lines on choke manifold are 3" unless otherwise noted. Exact manifold configuration may vary.

Note: Dimensional information reflected on this drawing are estimated measurements only.





Diagram Z



BOPCO  
Project: South East New Mexico





Midwest Hose & Specialty, Inc.

### Internal Hydrostatic Test Graph

April 4, 2012

Customer: Latshaw


Pick Ticket #: 81610

#### Hose Specifications

<u>Hose Type</u>	<u>Length</u>
D	30'
<u>I.D.</u>	<u>O.D.</u>
3"	4 15/32
<u>Working Pressure</u>	<u>Burst Pressure</u>
5000 PSI	Standard Safety Multiplier Applies

#### Verification

<u>Type of Fitting</u>	<u>Coupling Method</u>
41/16 SK	Swage
<u>Die Size</u>	<u>Final O.D.</u>
5.12"	5.16"
<u>Hose Serial #</u>	<u>Hose Assembly Serial #</u>
6884	81610



<u>Test Pressure</u> 10000 PSI	<u>Time Held at Test Pressure</u> 6 1/4 Minutes	<u>Actual Burst Pressure</u>	<u>Peak Pressure</u> 10195 PSI
-----------------------------------	--	------------------------------	-----------------------------------

Comments: Hose assembly pressure tested with water at ambient temperature.

Tested By: Donnie Mclemore

Approved By: Bobby Fink

**MIDWEST  
HOSE AND SPECIALTY INC.**

INTERNAL HYDROSTATIC TEST REPORT		
Customer: LATSHAW DRILLING		P.O. Number: RIG#4
HOSE SPECIFICATIONS		
Type: CHOKER LINE	Length: 30'	
I.D. 3" INCHES	O.D. 6" INCHES	
WORKING PRESSURE 5,000 PSI	TEST PRESSURE 10,000 PSI	BURST PRESSURE PSI
COUPLINGS		
Type of End Fitting 4 1/16 5K FLANGE		
Type of Coupling: SWEDGED	MANUFACTURED BY MIDWEST HOSE & SPECIALTY	
PROCEDURE		
<i>Hose assembly pressure tested with water at ambient temperature.</i>		
TIME HELD AT TEST PRESSURE 1 MIN.	ACTUAL BURST PRESSURE: 0 PSI	
COMMENTS: SO#81610 Hose is covered with stainless steel armour cover and wrapped with fire resistant vermiculite coated fiberglass insulation rated for 1500 degrees complete with lifting eyes		
Date: 3/2/2011	Tested By: BOBBY FINK	Approved: MENDI JACKSON

## **TABLE OF CONTENTS**

### **I. H<sub>2</sub>S Contingency Plan**

- A. Scope
- B. Objective
- C. Discussion of Plan

### **II. Emergency Procedures**

- A. Emergency Procedures and Public Protection
- B. Emergency Procedures Implementation
- C. Simulated Blowout Control Drills

### **III. Ignition Procedures**

- A. Responsibility
- B. Instructions

### **IV. Training Requirements**

### **V. Emergency Equipment**

### **VI. Evacuation Plan**

- A. General Plan
- B. Emergency Phone Lists

### **VII. General Information**

- A. H<sub>2</sub>S Toxicity Table
- B. Respirator Use
- C. Emergency Rescue

## H<sub>2</sub>S CONTINGENCY PLAN SECTION

### **Scope:**

This contingency plan provides an organized plan of action for alerting and protecting the public within an area of exposure prior to an intentional release, or following the accidental release of a potentially hazardous volume of hydrogen sulfide. The plan establishes guidelines for all personnel whose work activity may involve exposure to Hydrogen Sulfide Gas (H<sub>2</sub>S).

### **Objective:**

Prevent any and all accidents, and prevent the uncontrolled release of H<sub>2</sub>S into the atmosphere.

Provide proper evacuation procedures to cope with emergencies.

Provide immediate and adequate medical attention should an injury occur.

### **Discussion of Plan:**

#### ***Suspected Problem Zones:***

***Implementation:*** This plan, with all details, is to be fully implemented 500' above or three days prior to drilling into the first known sour zone

***Emergency Response and Public Protection Procedure:*** This section outlines the conditions and denotes steps to be taken in the event of an emergency.

***Emergency Equipment and Procedure:*** This section outlines the safety and emergency equipment that will be required for the drilling of this well.

***Training Provisions:*** This section outlines the training provisions that must be adhered to 500 feet above or three days prior to drilling into the first known sour zone.

***Emergency call lists:*** Included are the telephone numbers of all persons that would need to be contacted should an H<sub>2</sub>S emergency occur.

***Briefing:*** This section deals with the briefing of all persons involved with the drilling of this well.

***Public Safety:*** Public Safety Personnel will be made aware of the drilling of this well.

## EMERGENCY PROCEDURES AND PUBLIC PROTECTION SECTION

- I. In the event of any evidence of H<sub>2</sub>S levels above 10 ppm, take the following steps immediately:
  - A. Secure breathing apparatus.
  - B. Order non-essential personnel out of the danger zone.
  - C. Take steps to determine if the H<sub>2</sub>S level can be corrected or suppressed, and if so, proceed with normal operations.
- II. If uncontrollable conditions occur, proceed with the following:
  - A. Take steps to protect and/or remove any public downwind of the rig, including partial evacuation or isolation. Notify necessary public safety personnel and the New Mexico Oil & Gas of the situation.
  - B. Isolate area and prevent entry by unauthorized persons into the 100 ppm ROE.
  - C. Remove all personnel to the Safe Briefing Area.
  - D. Notify public safety personnel for help with maintaining roadblocks and implementing evacuation. Phone number list attached.
  - E. Determine and proceed with the best possible plan to regain control of the well. Maintain tight security and safety measures.
- III. Responsibility:
  - A. The Company Approved Supervisor shall be responsible for the total implementation of the plan.
  - B. The Company Approved Supervisor shall be in complete command during any emergency.
  - C. The Company Approved Supervisor shall designate a back up Supervisor in the event that he/she is not available.

## ***EMERGENCY PROCEDURE IMPLEMENTATION***

### **I. Drilling or Tripping**

#### **A. All Personnel**

1. When alarm sounds, don escape unit and report to upwind Safe Briefing Area.
2. Check status of other personnel (buddy system).
3. Secure breathing apparatus.
4. Wait for orders from supervisor.

#### **B. Drilling Foreman**

1. Report to the upwind Safe Briefing Area.
2. Don Breathing Apparatus and return to the point of release with the Tool Pusher or Driller (buddy system).
3. Determine the concentration of H<sub>2</sub>S.
4. Assess the situation and take appropriate control measures.

#### **C. Tool Pusher**

1. Report to the upwind Safe Briefing Area.
2. Don breathing apparatus and return to the point of release with the Drilling Foreman or the Driller (buddy system).
3. Determine the concentration.
4. Assess the situation and take appropriate control measures.

#### **D. Driller**

1. Check the status of other personnel (in a rescue attempt, always use the buddy system).
2. Assign the least essential person to notify the Drilling Foreman and Tool Pusher, in the event of their absence.

3. Assume the responsibility of the Drilling Foreman and the Tool Pusher until they arrive, in the event of their absence.

E. **Derrick Man and Floor Hands**

1. Remain in the upwind Safe Briefing Area until otherwise instructed by a supervisor.

F. **Mud Engineer**

1. Report to the upwind Safe Briefing Area.
2. When instructed, begin check of mud for pH level and H<sub>2</sub>S level.

G. **On-site Safety Personnel**

1. Don Breathing Apparatus.
2. Check status of all personnel.
3. Wait for instructions from Drilling Foreman or Tool Pusher.

**II. Taking a Kick**

- A. All personnel report to the upwind Safe Briefing Area.
- B. Follow standard BOP procedures.

**III. Open Hole Logging**

- A. All unnecessary personnel should leave the rig floor.
- B. Drilling Foreman and Safety Personnel should monitor the conditions and make necessary safety equipment recommendations.

**IV. Running Casing or Plugging**

- A. Follow "Drilling or Tripping" procedures.
- B. Assure that all personnel have access to protective equipment.

## **SIMULATED BLOWOUT CONTROL DRILLS**

All drills will be initiated by activating alarm devices (air horn). Use one long blast on the air horn for ACTUAL and SIMULATED Blowout Control Drills. This operation will be performed by the Drilling Foreman or Tool Pusher at least one time per week for each of the following conditions, with each crew:

Drill # 1      Bottom Drilling

Drill # 2      Tripping Drill Pipe

In each of these drills, the initial reaction time to shutting in the well shall be timed as well as the total time for the crew to complete its entire pit drill assignment. The times must be recorded on the IADC Driller's Log as "Blowout Control Drill".

Drill No.:			
Reaction Time to Shut-In:	minutes,	seconds.	
Total Time to Complete Assignment:	minutes,	seconds.	

### **I. Drill Overviews**

#### **A. Drill No. 1- Bottom Drilling**

1. Sound the alarm immediately.
2. Stop the rotary and hoist kelly joint above the rotary table.
3. Stop the circulatory pump.
4. Close the drill pipe rams.
5. Record casing and drill pipe shut-in pressures and pit volume increases.

#### **B. Drill No. 2 – Tripping Drill Pipe**

1. Sound the alarm immediately.
2. Position the upper tool joint just above the rotary table and set the slips.

3. Install a full opening valve or inside blowout preventor tool in order to close the drill pipe.
4. Close the drill pipe rams.
5. Record the shut-in annular pressure.

## II. Crew Assignments

### A. Drill No. 1 – Bottom Drilling

1. Driller
  - a) Stop the rotary and hoist kelly joint above the rotary table.
  - b) Stop the circulatory pump.
  - c) Check flow.
  - d) If flowing, sound the alarm immediately.
  - e) Record the shut-in drill pipe pressure.
  - f) Determine the mud weight increase needed or other courses of action.
2. Derrickman
  - a) Open choke line valve at BOP.
  - b) Signal Floor Man # 1 at accumulator that choke line is open.
  - c) Close choke and upstream valve after pipe tams have been closed.
  - d) Read the shut-in annular pressure and report readings to Driller.
3. Floor Man # 1
  - a) Close the pipe rams after receiving the signal from the Derrickman.
  - b) Report to Driller for further instructions.

4. Floor Man # 2
  - a) Notify the Tool Pusher and Operator Representative of the H<sub>2</sub>S alarms.
  - b) Check for open fires and, if safe to do so, extinguish them.
  - c) Stop all welding operations.
  - d) Turn-off all non-explosion proof lights and instruments.
  - e) Report to Driller for further instructions.
5. Tool Pusher
  - a) Report to the rig floor.
  - b) Have a meeting with all crews.
  - c) Compile and summarize all information.
  - d) Calculate the proper kill weight.
  - e) Ensure that proper well procedures are put into action.
6. Operator Representative
  - a) Notify the Drilling Superintendent.
  - b) Determine if an emergency exists and if so, activate the contingency plan.

**B. Drill No. 2 – Tripping Pipe**

1. Driller
  - a) Sound the alarm immediately when mud volume increase has been detected.
  - b) Position the upper tool joint just above the rotary table and set slips.
  - c) Install a full opening valve or inside blowout preventor tool to close the drill pipe.
  - d) Check flow.

- e) Record all data reported by the crew.
- f) Determine the course of action.

2. Derrickman

- a) Come down out of derrick.
- b) Notify Tool Pusher and Operator Representative.
- c) Check for open fires and, if safe to do so, extinguish them.
- d) Stop all welding operations.
- e) Report to Driller for further instructions.

3. Floor Man # 1

- a) Pick up full opening valve or inside blowout preventor tool and stab into tool joint above rotary table (with Floor Man # 2).
- b) Tighten valve with back-up tongs.
- c) Close pipe rams after signal from Floor Man # 2.
- d) Read accumulator pressure and check for possible high pressure fluid leaks in valves or piping.
- e) Report to Driller for further instructions.

4. Floor Man # 2

- a) Pick-up full opening valve or inside blowout preventor tool and stab into tool joint above rotary table (with Floor Man # 1).
- b) Position back-up tongs on drill pipe.
- c) Open choke line valve at BOP.
- d) Signal Floor Man # 1 at accumulator that choke line is open.
- e) Close choke and upstream valve after pipe rams have been closed.
- f) Check for leaks on BOP stack and choke manifold.

- g) Read annular pressure.
- h) Report readings to the Driller.

5. Tool Pusher

- a) Report to the rig floor.
- b) Have a meeting with all of the crews.
- c) Compile and summarize all information.
- d) See that proper well kill procedures are put into action.

6. Operator Representative

- a) Notify Drilling Superintendent
- b) Determine if an emergency exists, and if so, activate the contingency plan.

## IGNITION PROCEDURES

### Responsibility:

The decision to ignite the well is the responsibility of the DRILLING FOREMAN in concurrence with the STATE POLICE. The State Police shall be the Incident Command on the scene of any major release. Intentional ignition must be coordinated with the NMOCD and local officials. In the event the Drilling Foreman is incapacitated, it becomes the responsibility of the RIG TOOL PUSHER. This decision should be made only as a last resort and in a situation where it is clear that:

1. Human life and property are endangered.
2. There is no hope of controlling the blowout under the prevailing conditions.

If time permits, notify the main office, but do not delay if human life is in danger. Initiate the first phase of the evacuation plan.

### Instructions for Igniting the Well:

1. Two people are required for the actual igniting operation. Both men must wear self-contained breathing apparatus and must use a full body harness and attach a retrievable safety line to the D-Ring in the back. One man must monitor the atmosphere for explosive gases with the LEL monitor, while the Drilling Foreman is responsible for igniting the well.
2. The primary method to ignite is a 25mm flare gun with a range of approximately 500 feet.
3. Ignite from upwind and do not approach any closer than is warranted.
4. Select the ignition site best suited for protection and which offers an easy escape route.
5. Before igniting, check for the presence of combustible gases.
6. After igniting, continue emergency actions and procedures as before.
7. All unassigned personnel will limit their actions to those directed by the Drilling Foreman.

**NOTE:** After the well is ignited, burning Hydrogen Sulfide will convert to Sulfur Dioxide (SO<sub>2</sub>), which is also highly toxic. Do not assume the area is safe after the well is ignited.

## TRAINING REQUIREMENTS

When working in an area where Hydrogen Sulfide ( $H_2S$ ) might be encountered, definite training requirements must be carried out. The Company Supervisor will ensure that all personnel at the well site, whether regularly assigned, contracted, or employed on an unscheduled basis, have had adequate training by a qualified instructor in the following:

1. Hazards and Characteristics of Hydrogen Sulfide and Sulfur Dioxide.
2. Physicals effects of Hydrogen Sulfide on the human body.
3. Toxicity of Hydrogen Sulfide and Sulfur Dioxide.
4.  $H_2S$  detection, emergency alarm and sensor location.
5. Emergency rescue.
6. First aid and artificial resuscitation.
7. The effects of Hydrogen Sulfide on metals.
8. Location safety.

In addition, Supervisory Personnel will be trained in the following areas:

1. If high tensile tubular are to be used, personnel will be trained in their special maintenance requirements.
2. Corrective action and shut-in procedures when drilling or reworking a well as well as blowout prevention and well control procedures.
3. The contents and requirements of the  $H_2S$  Drilling Operations Contingency Plan and the Public Protection Plan.

Service company personnel and visiting personnel must be notified if the zone contains  $H_2S$ , and each service company must provide adequate training and equipment for their employees before they arrive at the well site.

## EMERGENCY EQUIPMENT

As stated in the BLM Onshore Order 6, for wells located in a known H<sub>2</sub>S areas, H<sub>2</sub>S equipment will be rigged up after setting surface casing. For wells located inside known H<sub>2</sub>S areas, the flare pit will be located 150' from the location and for wells located outside known H<sub>2</sub>S areas, the flare pit will be located 100' away from the location. (See page 6 of Survey plat package and diagram B or C.)

**It is not anticipated that any H<sub>2</sub>S is in the area, however in the event that H<sub>2</sub>S is encountered, the attached H<sub>2</sub>S Contingency Plan will be implemented.** (Please refer to diagrams B or C for choke manifold and closed loop system layout.) See H<sub>2</sub>S location layout diagram for location of all H<sub>2</sub>S equipment on location.

All H<sub>2</sub>S safety equipment and systems will be installed, tested and be operational when drilling reaches a depth of 500' above, or three days prior to penetrating a known formation containing H<sub>2</sub>S.

### **Lease Entrance Sign:**

Caution signs should be located at all roads providing direct access to the location. Signs shall have a yellow background with black lettering and contain the words "CAUTION" and "POISON GAS" that is legible from a distance of at least 50 feet.

**LEASE NAME  
CAUTION – POTENTIAL POISON GAS  
HYDROGEN SULFIDE  
NO ADMITTANCE WITHOUT AUTHORIZATION**

### **Windsocks or Wind Streamers:**

- A minimum of two 10" windsocks located at strategic locations so that they may be seen from any point on location.
- Wind streamers (if preferred) should be placed at various locations on the well site to ensure wind consciousness at all times. (Corners of location)

### **Hydrogen Sulfide Detector and Alarms:**

- H<sub>2</sub>S monitors with alarms will be located on the rig floor, at the cellar, and at the mud pits. These monitors will be set to alarm at 10 PPM with a red light and to alarm at 15 PPM with a red light and audible alarm.

### **Well Condition Flags:**

The Well Condition flags should be located at all roads providing direct access to the location. It should have three (3) color coded flags (green, yellow and red) that will be used to denote the following location conditions:

GREEN – Normal Operating Conditions

YELLOW – Potential Danger

RED – Danger, H<sub>2</sub>S Gas Present

### **Respiratory Equipment:**

- Fresh air breathing equipment should be placed at the company supervision trailer and the safe briefing areas and should include the following:
  - A minimum of two SCBA's at each briefing area and the supervisor company supervision trailer.
  - Enough air line units to operate safely; anytime the H<sub>2</sub>S concentration reaches the IDLH level (100 PPM).
  - Cascade system with enough breathing air hose and manifolds to reach the rig floor, the derrickman and the other operation areas.

### **Fire Extinguishers:**

Adequate fire extinguishers shall be located at strategic locations.

### **Mud Program:**

The mud program has been designed to minimize the volume of H<sub>2</sub>S circulated to the surface. Proper mud weight, safe drilling practices and the use of H<sub>2</sub>S scavengers will minimize hazards when penetrating H<sub>2</sub>S bearing zones.

### **Metallurgy:**

All drill strings, casing, tubing, wellhead; blowout preventer, drilling spools, kill lines, choke manifold and lines, and valves shall be suitable for H<sub>2</sub>S service.

### **Well Control Equipment:**

- Flare Line (See page 6 of survey plat package for flare line reference).
- Choke manifold (See diagram B or C and refer to H2S location diagram for location of important H2S safety items ).
- Blind rams and pipe rams to accommodate all pipe sizes with properly sized closing units.
- Auxiliary equipment may include, if applicable, annular preventer & rotating head.

### **Communication Equipment:**

- Proper communication equipment such as cell phones or 2 – way radios should be available for communication between the company man's trailer, rig floor and tool pusher's trailer.

### **Well Testing:**

- There will be no drill stem testing.

### **Evacuation Plan:**

- Evacuation routes should be established prior to spudding the well.
- Should be discussed with all rig personnel.

### **Designated Areas:**

#### ***Parking and Visitor area:***

- All vehicles are to be parked at a pre-determined safe distance from the wellhead.
- A smoking area will be designated at a pre-determined safe distance from the wellhead and any other possible flammable areas.

#### ***Safe Briefing Areas:***

- Two Safe Briefing Areas shall be designated on either side of the location at the maximum allowable distance from the well bore so they offset prevailing winds or they are at a 180 degree angle if wind directions tend to shift in the area.

- Personal protective equipment should be stored at both briefing areas or if a moveable cascade trailer is used, it should be kept upwind of existing winds. When wind is from the prevailing direction, both briefing areas should be accessible.

**NOTE:**

- Additional equipment will be available at Indian Fire and Safety in Hobbs, NM or at Total Safety in Hobbs, NM.

## **EVACUATION PLAN**

### **General Plan**

The direct lines of action to protect the public from hazardous gas situations are as follows:

1. When the company approved supervisor (Drilling Foremen, Tool Pusher or Driller) determine that Hydrogen Sulfide gas cannot be limited to the well location, and the public will be involved, he will activate the evacuation plan. Escape routes are noted on the Area Map.
2. Company safety personnel or designee will notify the appropriate local government agency that a hazardous condition exists and evacuation needs to be implemented.
3. Company approved safety personnel that have been trained in the use of the proper emergency equipment will be utilized.
4. Law enforcement personnel (State Police, Local Police Department, Fire Department, and the Sheriff's Department) will be called to aid in setting up and maintaining road blocks. Also, they will aid in evacuation of the public if necessary.

NOTE: Law enforcement personnel will not be asked to come into a contaminated area. Their assistance will be limited to uncontaminated areas. Constant radio contact will be maintained with them.

5. After the discharge of gas has been controlled, Company approved safety personnel will determine when the area is safe for re-entry.

**See Emergency Action Plan**

### **Contacting Authorities**

BOPCO L.P. personnel must liaison with local and state agencies to ensure a proper response to a major release. Additionally, the OCD must be notified of the release as soon as possible but no later than 4 hours. Agencies will ask for information such as type and volume of release, wind direction, location of release, etc. Be prepared with all information available including directions to site. The following call list of essential and potential responders has been prepared for use during a release. (Operator Name)'s response must be in coordination with the State of New Mexico's "Hazardous Materials Emergency Response Plan" (HMER).

**H<sub>2</sub>S CONTINGENCY PLAN EMERGENCY CONTACTS**  
BOPCO L.P. Midland Office 432-683-2277

Key Personnel

<u>Name</u>	<u>Title</u>	<u>Cell Phone Number</u>
Stephen Martinez	Drilling & Completions Manager	432-556-0262
Charles Warne	Division Engineer	432-312-4431
Don Wood	Division Drilling Specialist	432-266-2674
Leo Bojorquez	Area Drilling Superintendent	702-280-4424
Chris Giese	Engineer	432-661-7328
Chris Volek	Engineer	785-979-2643
Brian Braun	Engineer	210-683-9849
Jeremy Braden	Engineering Assistant	432-312-1113

Artesia

Ambulance	911
State Police	575-746-2703
City Police	575-746-2703
Sheriff's Office	575-746-9888
Fire Department	575-746-2701
Local Emergency Planning Committee	575-746-2122
New Mexico Oil Conservation Division	575-748-1283

Carlsbad

Ambulance	911
State Police	575-885-3137
City Police	575-885-2111
Sheriff's Office	575-887-7551
Fire Department	575-887-3798
Local Emergency Planning Committee	575-887-6544
US Bureau of Land Management	575-887-6544

New Mexico Emergency Response Commission (Santa Fe)	505-476-9600
24 Hour	505-827-9126
New Mexico State Emergency Operations Center	505-476-9635
National Emergency Response Center (Washington, DC)	800-424-8802

Other

Wild Well Control	432-550-6202 (Permian Basin)
Cudd PressureControl	432-580-3544 or 432-570-5300 (Permian Basin)
Flight For Life – 4000 24 <sup>th</sup> St. Lubbock, Texas	806-743-9911
Aerocare – R3, Box 49F, Lubbock, Texas	806-747-8923
Med Flight Air Amb – 2301 Yale Blvd SE #D3, Albuquerque, NM	505-842-4433
S B Air Med Service – 2505 Clark Carr Loop SE, Albuquerque, NM	505-842-4949
Indian Fire and Safety – 3317 NW Cnty Rd, Hobbs, NM	575-393-3093



## TOXIC EFFECTS OF HYDROGEN SULFIDE

Hydrogen Sulfide is extremely toxic. The acceptable ceiling concentration for eight-hour exposure is 10 PPM, which is .001% by volume. Hydrogen Sulfide is heavier than air (specific gravity = 1.192) and colorless. It forms an explosive mixture with air between 4.3 and 46.0 percent by volume. Hydrogen sulfide is almost as toxic as hydrogen cyanide and is between five and six times more toxic than carbon monoxide. Toxicity data for hydrogen sulfide and various other gases are compared in Table I. Physical effects at various Hydrogen Sulfide exposure levels are shown in Table II.

**Table I - TOXICITY OF VARIOUS GASES**

Common Name	Chemical Formula	Specific Gravity (SC=1)	Threshold Limit (1)	Hazardous Limit (2)	Lethal Concentration (3)
Hydrogen Cyanide	HCN	0.94	10 PPM	150 PPM/HR	300 PPM
Hydrogen Sulfide	H <sub>2</sub> S	1.18	10 PPM	250 PPM/HR	600 PPM
Sulfur Dioxide	SO <sub>2</sub>	2.21	5 PPM	--	1000 PPM
Chlorine	CL <sub>2</sub>	2.45	1 PPM	4 PPM/HR	1000 PPM
Carbon Monoxide	CO	0.97	50 PPM	400 PPM/HR	1000 PPM
Carbon Dioxide	CO <sub>2</sub>	1.52	5000 PPM	5%	10%
Methane	CH <sub>4</sub>	0.55	90,000 PPM	Combustible in air	Above 5%

- 1) **Threshold Limit** – Concentration at which it is believed that all worker may be repeatedly exposed day after day without adverse effects.
- 2) **Hazardous Limit** – Concentration that will cause death with short-term exposure.
- 3) **Lethal Concentration** – Concentration that will cause death with short-term exposure.

**Table II – PHYSICAL EFFECTS OF HYDROGEN SULFIDE**

<b>Percent (%)</b>	<b>PPM</b>	<b>Concentration Grains 100 STD. FT3*</b>	<b>Physical Effects</b>
<b>0.001</b>	<b>&lt; 10</b>	<b>00.65</b>	<b>Obvious &amp; unpleasant odor.</b>
<b>0.002</b>	<b>10</b>	<b>01.30</b>	<b>Safe for 8 hours of exposure.</b>
<b>0.010</b>	<b>100</b>	<b>06.48</b>	<b>Kills smell in 3-15 minutes. May sting eyes &amp; throat.</b>
<b>0.020</b>	<b>200</b>	<b>12.96</b>	<b>Kills smell shortly; stings eyes &amp; throat.</b>
<b>0.050</b>	<b>500</b>	<b>32.96</b>	<b>Dizziness; Breathing ceases in a few minutes. Needs prompt artificial respiration.</b>
<b>0.070</b>	<b>700</b>	<b>45.36</b>	<b>Unconscious quickly; Death will result if not rescued promptly.</b>
<b>0.100</b>	<b>1000</b>	<b>64.30</b>	<b>Unconscious at once; Followed by death within minutes.</b>

- At 15.00 PSIA and 60° F.

## USE OF SELF-CONTAINED BREATHING APPARATUS

1. Anyone who uses an SCBA shall: Be approved by a physician or licensed health care practitioner; Pass a fit test; Be trained in donning and doffing, proper use, including how to ensure a proper face seal, conducting an inspection of the SCBA, and conduct proper maintenance.
2. Such items as facial hair (beard or sideburns) and eyeglasses will not allow a proper face mask seal.
3. Anyone reasonably expected to wear SCBA's shall have these items removed before entering a toxic atmosphere.
4. A special mask with a mount for prescription glasses must be obtained for anyone who must wear eyeglasses in order to see while using an SCBA.
5. SCBA's should be worn in H<sub>2</sub>S concentrations above 10 PPM.

## RESCUE & FIRST AID FOR H<sub>2</sub>S POISONING


DO NOT PANIC – REMAIN CALM – THINK

1. Hold your breath – do not inhale first.
2. Put on SCBA.
3. Remove victim(s) to fresh air as quickly as possible. Go upwind from source or at right angle to the wind. Do not go downwind.
4. Briefly apply chest pressure – using arm lift method of artificial respiration to clean victim's lungs and to avoid inhaling any toxic gas directly from victim's lungs.
5. Provide artificial respiration if needed.
6. Provide for prompt transportation to the hospital and continue giving artificial respiration if needed.
7. Inform hospital/medical facilities of the possibility of H<sub>2</sub>S gas poisoning before they treat.

Besides basic first aid, everyone on location should have a good working knowledge of artificial respiration and CPR, as well as first aid for eyes and skin contact with liquid H<sub>2</sub>S.

# Proposed H2S Safety Schematic

- 1) Location of windsocks.
- 2) Location of H2S alarms
- 3) Location of briefing areas.
- 4) Terrain of surrounding area (Please refer to page 2 of survey plat package also see point 11 of multi-surface use plan)
- 5) Location of flare line(s) and pit(s) (Please refer to diagram 2 choke manifold diagram and or page six of survey plat packet)
- 6) Location of caution and/or danger signs.
- 7) Location of Breathing Equipment



## Location On-Site Notes

Location on-site conducted by Cecil Watkins-BOPCO L.P., Stephen Martinez-BOPCO L.P., Carlos Cruz-BOPCO, L.P., Bill Franks-BOPCO, L.P., Cody Layton-BLM, and Robert Gomez-Basin Survey on 3/20/2012. The James Ranch Unit 12 Pad added additional footage to the east and west sides of existing location. Surface footage calls are at 1506' FNL & 1250' FEL of Section 21, T22S-R30E. Location layout is as follows: v-door will face the west, frac pad will be on northeast corner, access road will enter location from the east corner and topsoil will be stockpiled to the north side of location.

## MULTI-POINT SURFACE USE PLAN

**NAME OF WELL: James Ranch Unit DI 1 #127H**

SURFACE: 1506' FNL, 1250' FEL, Section 21, T22S, R30E, Eddy County, NM.  
BHL: 660' FNL, 330' FEL, Section 23, T22S, R30E, Eddy County, NM.

### POINT 1: EXISTING ROADS

A) Proposed Well Site Location:

See Form C-102 (Survey Plat).

B) Existing Roads:

From the junction of Hwy 128 and Cimarron, go north on Cimarron for approximately 6.2 miles to lease road. On lease road go southwesterly 0.2 miles turning northwesterly 1.3 miles to proposed well location.

C) Existing Road Maintenance or Improvement Plan:

Existing roads will be maintained and kept in the same or better condition than before operations began. See the Well Pad Layout and Topo Map of the survey plat (Sheet 1 and 2 of plat package)

### POINT 2: NEW PLANNED ACCESS ROUTE

A) Route Location:

No new lease road will be built. (See the Well Pad Layout of the survey plat (Sheet 1 of plat package).

B) Width

14' wide

C) Maximum Grade

Grade to match existing topography or as per BLM requirements.

D) Turnout Ditches

As required by BLM stipulations

E) Culverts, Cattle Guards, and Surfacing Equipment

If required, culverts and cattle guards will be set per BLM Specs.

**POINT 3: LOCATION OF EXISTING WELLS**

The following wells are located within a one-mile radius of the location site. See the One-Mile Radius Map (Sheet 5 of the plat package).

Existing wells..... 4 (Four)  
Water wells..... 3 (Three)

**POINT 4: LOCATION OF EXISTING OR PROPOSED FACILITIES**

A) Existing facilities operated by BOPCO, L.P. are located within one mile of the James Ranch Unit DI 1 127H.

B) New Facilities in the Event of Production:

James Ranch Unit DI1 127H will pipe production to JRU Legg Battery (located in Sec 21, T22S, R30E). A new 3-1/2" in diameter steel flowline is to be run above ground, approx. 8550 feet in length. The flowline is expected to carry oil, water, and gas.

C) Rehabilitation of Disturbed Areas Unnecessary for Production:

See Point 10

**POINT 5: LOCATION AND TYPE OF WATER SUPPLY**

A) Location and Type of Water Supply

Fresh water will be hauled from Johnson Station 50 miles east of Carlsbad, New Mexico or other commercial facilities. Brine water will be hauled from commercial facilities.

B) Water Transportation System

Water hauling to the location will be over the existing and proposed roads.

**POINT 6: SOURCE OF CONSTRUCTION MATERIALS**

A) Materials

On-site caliche will be used. If this is not sufficient, caliche will be hauled from a BLM approved pit.

B) Land Ownership

Federally Owned

C) Materials Foreign to the Site

No construction materials foreign to this area are anticipated for this drill site

D) Access Roads

See the Well Pad Layout and Aerial Map of the survey plat (Sheet 1 and 4 of plat package)

**POINT 7: METHODS FOR HANDLING WASTE MATERIAL**

A) Cuttings

Cuttings will be contained in the roll off bins and disposed at R360 Environmental Services, Inc. located in Lea county, NM.

B) Drilling Fluids

Drilling fluids will be contained in the steel pits, frac tanks and disposed at licensed disposal sites.

C) Produced Fluids

Water production will be contained in the steel pits.

Hydrocarbon fluid or other fluids that may be produced during testing will be retained in test tanks. Prior to cleanup operations, any hydrocarbon material in the reserve pit will be removed by skimming or burning as the situation would dictate.

D) Sewage

Current laws and regulations pertaining to the disposal of human waste will be complied with.

E) Garbage

Portable containers will be utilized for garbage disposal during the drilling of this well.

F) Cleanup of Well Site

Upon release of the drilling rig, the surface of the drilling pad will be graded to accommodate a completion rig if electric log analysis indicate potential productive zones. Reasonable cleanup will be performed prior to the final restoration of the site.

**POINT 8: ANCILLARY FACILITIES**

None required.

## POINT 9: WELL SITE LAYOUT

### A) Rig Orientation and Layout

The "Rig Layout Schematic" (Sheet 6 of plat package) shows the dimensions of the well pad, closed loop system, and the location of major rig components. Only minor leveling of the well site will be required. No significant cuts or fills will be necessary. **The top soil will be stockpiled on the East side of the location.**

### B) Locations of Access Road

See the Well Pad Layout, Topo Map, and Vicinity Map of the survey plat (Sheet 1, 2, and 3 of plat package).

### C) Closed loop system.

## POINT 10: PLANS FOR RESTORATION OF THE SURFACE

### A) Closed loop drilling fluid system will be used

### B) Restoration Plans - Production Developed

BOPCO, L.P. has no plans for interim reclamation to allow for additional wells to be drilled on this pad

### C) Restoration Plans - No Production Developed

BOPCO, L.P. has no plans for interim reclamation to allow for additional wells to be drilled on this pad

## POINT 11: OTHER INFORMATION

### A) On-Site

Location on-site conducted by Cecil Watkins-BOPCO L.P., Stephen Martinez-BOPCO L.P., Carlos Cruz-BOPCO, L.P., Bill Franks-BOPCO, L.P., Cody Layton-BLM, and Robert Gomez-Basin Survey on 3/20/2012. The James Ranch Unit 12 Pad added additional footage to the east and west sides of existing location. Surface footage calls are at 1506' FNL & 1250' FEL of Section 21, T22S-R30E. Location layout is as follows: v-door will face the west, frac pad will be on northeast corner, access road will enter location from the east corner and topsoil will be stockpiled to the north side of location.

### B) Soil

Caliche and sand.

### C) Vegetation

Sparse, primarily grasses and mesquite with very little grass.

D) Surface Use

Primarily grazing.

E) Surface Water

There are no ponds, lakes, streams or rivers within several miles of the wellsite.

F) Water Wells

There are three water wells located within a 1 mile radius of the proposed location. These wells are listed by the New Mexico Office of the State Engineer and found on the "Point of Diversion by Location" database.

G) Residences and Buildings

None in the immediate vicinity.

H) Historical Sites

None observed.

I) Archeological Resources

No independent archeological survey has been done. This pad location is located in the area covered by Memorandum of Agreement – Permian Basin. The James Ranch 12 Pad is covered by a blanketed MOA for the entire Drilling Island. Any location or construction conflicts will be resolved before construction begins. Please see diagram 4 for flowline route.

J) Surface Ownership

The well site is on federally owned land. There will be no new access roads required for this location.

K) Well signs will be posted at the drilling site.

L) Open Pits

No open pits will be used for drilling or production. Any open top tanks will be netted.

M) Terrain

Slightly rolling hills.

**POINT 12: OPERATOR'S FIELD REPRESENTATIVE**

(Field personnel responsible for compliance with development plan for surface use).

**DRILLING**

Stephen Martinez  
Box 2760  
Midland, Texas 79702  
(432) 683-2277

**PRODUCTION**

Gary Fletcher  
3104 East Green Street  
Carlsbad, New Mexico 88220  
(575) 887-7329

Carlos Cruz  
Box 2760  
Midland, Texas 79702  
(432) 683-2277

BTC

**OPERATOR'S CERTIFICATION**

APPLICATION FOR PERMIT TO DRILL  
JAMES RANCH UNIT DI 1 #127H  
1,506' FNL, 1,250' FEL, Sec. 21, T22S, R30E, Eddy County, NM

In reference to the above captioned well, I hereby certify that I, or someone under my direct supervision, have inspected the drill site and access route proposed herein; that I am familiar with the conditions which currently exist; that I have full knowledge of state and Federal laws applicable to this operation; that the statements made in the APD package are, to the best of my knowledge, true and correct; and that the work associated with the operations proposed herein will be performed in conformity with this APD package and the terms and conditions under which it is approved. I also certify that I, or the company I represent, am responsible for the operations conducted under this application. These statements are subject to the provisions of 18 U.S.C. 1001 for the filing of false statements.

Executed this 2nd day of July, 2014.

If you have any questions regarding the accuracy of the plan provided herein, please do not hesitate to contact me at (432) 683-2277.

Sincerely,

*Whitney McKee*

Whitney McKee  
Engineering Assistant

*DM 7-6-15  
per email  
from W. McKee  
-attached-*



McKinney, Deborah <dmckinne@blm.gov>

---

## JRU DI1 #127H Certification page

1 message

---

McKee, Whitney B. <WBMcKee@basspet.com>

Mon, Jul 6, 2015 at 8:13 AM

To: "dmckinne@blm.gov" <dmckinne@blm.gov>

I, Whitney McKee, give Debbie McKinney permission to sign and date the certification page for the James Ranch Unit DI1 #127H.

*Thank you,*

*Whitney McKee*

*Engineering Assistant*

*BOPCO, LP*

*PO BOX 2760*

*Midland, TX 79702*

*Direct: 432-221-7353*

*Office: 432-683-2277*

*Email: [wbmckee@basspet.com](mailto:wbmckee@basspet.com)*

Form NM 8140-9  
(March 2008)

United States Department of the Interior  
Bureau of Land Management  
New Mexico State Office

Permian Basin Cultural Resource Mitigation Fund

The company shown below has agreed to contribute funding to the Permian Basin Cultural Resource Fund in lieu of being required to conduct a Class III survey for cultural resources associated with their project. This form verifies that the company has elected to have the Bureau of Land Management (BLM) follow the procedures specified within the Memorandum of Agreement (MOA) concerning improved strategies for managing historic properties within the Permian Basin, New Mexico, for the undertaking rather than the Protocol to meet the agency's Section 106 obligations.

Company Name: BOPCO, L.P.

Address: P. O. Box 2760

Midland, Texas 79702

Project description: James Ranch Unit DII #127H

T, 22S, R 30E, Section 21 NMPM, Eddy County, New Mexico

Amount of contribution: \$ MOA was covered in a blanket contribution for the entire island

Provisions of the MOA:

- A. No new Class III inventories are required of industry within the Project Area for those projects where industry elects to contribute to the mitigation fund.
- B. The amount of funds contributed was derived from the rate schedule established within Appendix B of the MOA. The amount of the funding contribution acknowledged on this form reflects those rates.
- C. The BLM will utilize the funding to carry out a program of mitigation at high-priority sited whose study is needed to answer key questions identified within the Regional Research Design.
- D. Donating to the fund is voluntary. Industry acknowledges that it is aware it has the right to pay for Class III survey rather than contributing to the mitigation fund, and that it must avoid or fund data recovery at those sites already recorded that are eligible for nomination to the National Register or whose eligibility is unknown and that any such payments are independent of the mitigation funds established by this MOA.
- E. Previously recorded archeological sites determined eligible for nomination to the National Register or whose eligibility remains undetermined must be avoided or mitigated.
- F. If any skeletal remains that might be human or funerary objects are discovered by any activities, the land-use applicant will cease activities in the area of discovery, protect the remains, and notify the BLM within 24 hours. The BLM will determine the appropriate treatment of the remains in consultation with culturally affiliated Indian Tribe(s) and lineal descendents. Applicants will be required to pay for treatment of the cultural items independent and outside of the mitigation fund.



\_\_\_\_\_  
Company-Authorized Officer

7/2/14

\_\_\_\_\_  
Date

\_\_\_\_\_  
BLM-Authorized Officer

\_\_\_\_\_  
Date

# PECOS DISTRICT CONDITIONS OF APPROVAL

<b>OPERATOR'S NAME:</b>	<b>BOPCO, L.P.</b>
<b>LEASE NO.:</b>	<b>NMLC-064827A</b>
<b>WELL NAME &amp; NO.:</b>	<b>James Ranch Unit DI 1 127H</b>
<b>SURFACE HOLE FOOTAGE:</b>	<b>1506' FNL &amp; 1250' FEL</b>
<b>BOTTOM HOLE FOOTAGE:</b>	<b>0660' FNL &amp; 0330' FEL Sec. 23, T. 22 S., R 30 E.</b>
<b>LOCATION:</b>	<b>Section 21, T. 22 S., R 30 E., NMPM</b>
<b>COUNTY:</b>	<b>Eddy County, New Mexico</b>

## TABLE OF CONTENTS

Standard Conditions of Approval (COA) apply to this APD. If any deviations to these standards exist or special COAs are required, the section with the deviation or requirement will be checked below.

- General Provisions**
- Permit Expiration**
- Archaeology, Paleontology, and Historical Sites**
- Noxious Weeds**
- Special Requirements**
  - Cave/Karst Mitigations**
  - Commercial Well Determination
  - Unit Well Sign Specs
- Construction**
  - Notification
  - Topsoil
  - Closed Loop System
  - Federal Mineral Material Pits
  - Well Pads
  - Roads
- Road Section Diagram**
- Drilling**
  - Cement Requirements
  - H2S Requirements
  - R-111-P-Potash
  - High Cave/Karst
  - Logging Requirements
  - Waste Material and Fluids
- Production (Post Drilling)**
  - Well Structures & Facilities
- Interim Reclamation**
- Final Abandonment & Reclamation**

## **I. GENERAL PROVISIONS**

The approval of the Application For Permit To Drill (APD) is in compliance with all applicable laws and regulations: 43 Code of Federal Regulations 3160, the lease terms, Onshore Oil and Gas Orders, Notices To Lessees, New Mexico Oil Conservation Division (NMOCD) Rules, National Historical Preservation Act As Amended, and instructions and orders of the Authorized Officer. Any request for a variance shall be submitted to the Authorized Officer on Form 3160-5, Sundry Notices and Report on Wells.

## **II. PERMIT EXPIRATION**

If the permit terminates prior to drilling and drilling cannot be commenced within 60 days after expiration, an operator is required to submit Form 3160-5, Sundry Notices and Reports on Wells, requesting surface reclamation requirements for any surface disturbance. However, if the operator will be able to initiate drilling within 60 days after the expiration of the permit, the operator must have set the conductor pipe in order to allow for an extension of 60 days beyond the expiration date of the APD. (Filing of a Sundry Notice is required for this 60 day extension.)

## **III. ARCHAEOLOGICAL, PALEONTOLOGY & HISTORICAL SITES**

Any cultural and/or paleontological resource discovered by the operator or by any person working on the operator's behalf shall immediately report such findings to the Authorized Officer. The operator is fully accountable for the actions of their contractors and subcontractors. The operator shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery shall be made by the Authorized Officer to determine the appropriate actions that shall be required to prevent the loss of significant cultural or scientific values of the discovery. The operator shall be held responsible for the cost of the proper mitigation measures that the Authorized Officer assesses after consultation with the operator on the evaluation and decisions of the discovery. Any unauthorized collection or disturbance of cultural or paleontological resources may result in a shutdown order by the Authorized Officer.

## **IV. NOXIOUS WEEDS**

The operator shall be held responsible if noxious weeds become established within the areas of operations. Weed control shall be required on the disturbed land where noxious weeds exist, which includes the roads, pads, associated pipeline corridor, and adjacent land affected by the establishment of weeds due to this action. The operator shall consult with the Authorized Officer for acceptable weed control methods, which include following EPA and BLM requirements and policies.

## V. SPECIAL REQUIREMENT(S)

### **Cave/Karst Surface Mitigation**

The following stipulations will be applied to minimize impacts during construction, drilling and production.

#### **Construction:**

In the advent that any underground voids are opened up during construction activities, construction activities will be halted and the BLM will be notified immediately.

#### **No Blasting:**

No blasting will be utilized for pad construction. The pad will be constructed and leveled by adding the necessary fill and caliche.

#### **Pad Berming:**

The entire perimeter of the well pad will be bermed to prevent oil, salt, and other chemical contaminants from leaving the well pad.

- The compacted berm shall be constructed at a minimum of 12 inches high with impermeable mineral material (e.g. caliche).
- No water flow from the uphill side(s) of the pad shall be allowed to enter the well pad.
- The topsoil stockpile shall be located outside the bermed well pad.
- Topsoil, either from the well pad or surrounding area, shall not be used to construct the berm.
- No storm drains, tubing or openings shall be placed in the berm.
- If fluid collects within the bermed area, the fluid must be vacuumed into a safe container and disposed of properly at a state approved facility.
- The integrity of the berm shall be maintained around the surfaced pad throughout the life of the well and around the downsized pad after interim reclamation has been completed.
- Any access road entering the well pad shall be constructed so that the integrity of the berm height surrounding the well pad is not compromised. (Any access road crossing the berm cannot be lower than the berm height.)

#### **Tank Battery Liners and Berms:**

Tank battery locations and all facilities will be lined and bermed. A 20 mil permanent liner will be installed with a 4 oz. felt backing to prevent tears or punctures. Tank battery berms must be large enough to contain 1 ½ times the content of the largest tank.

#### **Leak Detection System:**

A method of detecting leaks is required. The method could incorporate gauges to measure loss, siting valves and lines so they can be visually inspected, or installing electronic sensors to alarm when a leak is present. Leak detection plan will be submitted to BLM for approval.

**Automatic Shut-off Systems:**

Automatic shut off, check valves, or similar systems will be installed for pipelines and tanks to minimize the effects of catastrophic line failures used in production or drilling.

**Cave/Karst Subsurface Mitigation**

The following stipulations will be applied to protect cave/karst and ground water concerns:

**Rotary Drilling with Fresh Water:**

Fresh water will be used as a circulating medium in zones where caves or karst features are expected. SEE ALSO: Drilling COAs for this well.

**Directional Drilling:**

Kick off for directional drilling will occur at least 100 feet below the bottom of the cave occurrence zone. SEE ALSO: Drilling COAs for this well.

**Lost Circulation:**

ALL lost circulation zones from the surface to the base of the cave occurrence zone will be logged and reported in the drilling report.

Regardless of the type of drilling machinery used, if a void of four feet or more and circulation losses greater than 70 percent occur simultaneously while drilling in any cave-bearing zone, the BLM will be notified immediately by the operator. The BLM will assess the situation and work with the operator on corrective actions to resolve the problem.

**Abandonment Cementing:**

Upon well abandonment in high cave karst areas additional plugging conditions of approval may be required. The BLM will assess the situation and work with the operator to ensure proper plugging of the wellbore.

**Pressure Testing:**

Annual pressure monitoring will be performed by the operator on all casing annuli and reported in a sundry notice. If the test results indicated a casing failure has occurred, remedial action will be undertaken to correct the problem to the BLM's approval.

**Drilling:**

**Commercial Well Determination**

A commercial well determination shall be submitted after production has been established for at least six months.

**Unit Wells**

The well sign for a unit well shall include the unit number in addition to the surface and bottom hole lease numbers. This also applies to participating area numbers. If a participating area has not been established, the operator can use the general unit designation, but will replace the unit number with the participating area number when the sign is replaced.

## **VI. CONSTRUCTION**

### **A. NOTIFICATION**

The BLM shall administer compliance and monitor construction of the access road and well pad. Notify the Carlsbad Field Office at (575) 234-5909 at least 3 working days prior to commencing construction of the access road and/or well pad.

When construction operations are being conducted on this well, the operator shall have the approved APD and Conditions of Approval (COA) on the well site and they shall be made available upon request by the Authorized Officer.

### **B. TOPSOIL**

The operator shall strip the top portion of the soil (root zone) from the entire well pad area and stockpile the topsoil along the edge of the well pad as depicted in the APD. The root zone is typically six (6) inches in depth. All the stockpiled topsoil will be redistributed over the interim reclamation areas. Topsoil shall not be used for berming the pad or facilities. For final reclamation, the topsoil shall be spread over the entire pad area for seeding preparation.

Other subsoil (below six inches) stockpiles must be completely segregated from the topsoil stockpile. Large rocks or subsoil clods (not evident in the surrounding terrain) must be buried within the approved area for interim and final reclamation.

### **C. CLOSED LOOP SYSTEM**

Tanks are required for drilling operations: No Pits.

The operator shall properly dispose of drilling contents at an authorized disposal site.

### **D. FEDERAL MINERAL MATERIALS PIT**

Payment shall be made to the BLM prior to removal of any federal mineral materials. Call the Carlsbad Field Office at (575) 234-5972.

### **E. WELL PAD SURFACING**

Surfacing of the well pad is not required.

If the operator elects to surface the well pad, the surfacing material may be required to be removed at the time of reclamation. The well pad shall be constructed in a manner which creates the smallest possible surface disturbance, consistent with safety and operational needs.

### **F. EXCLOSURE FENCING (CELLARS & PITS)**

**Exclosure Fencing**

The operator will install and maintain exclosure fencing for all open well cellars to prevent access to public, livestock, and large forms of wildlife before and after drilling operations until the pit is free of fluids and the operator initiates backfilling. (For examples of exclosure fencing design, refer to BLM's Oil and Gas Gold Book, Exclosure Fence Illustrations, Figure 1, Page 18.)

**G. ON LEASE ACCESS ROADS****Road Width**

The access road shall have a driving surface that creates the smallest possible surface disturbance and does not exceed fourteen (14) feet in width. The maximum width of surface disturbance, when constructing the access road, shall not exceed twenty-five (25) feet.

**Surfacing**

Surfacing material is not required on the new access road driving surface. If the operator elects to surface the new access road or pad, the surfacing material may be required to be removed at the time of reclamation.

Where possible, no improvements should be made on the unsurfaced access road other than to remove vegetation as necessary, road irregularities, safety issues, or to fill low areas that may sustain standing water.

The Authorized Officer reserves the right to require surfacing of any portion of the access road at any time deemed necessary. Surfacing may be required in the event the road deteriorates, erodes, road traffic increases, or it is determined to be beneficial for future field development. The surfacing depth and type of material will be determined at the time of notification.

**Crowning**

Crowning shall be done on the access road driving surface. The road crown shall have a grade of approximately 2% (i.e., a 1" crown on a 14' wide road). The road shall conform to Figure 1; cross section and plans for typical road construction.

**Ditching**

Ditching shall be required on both sides of the road.

**Turnouts**


Vehicle turnouts shall be constructed on the road. Turnouts shall be intervisible with interval spacing distance less than 1000 feet. Turnouts shall conform to Figure 1; cross section and plans for typical road construction.

**Drainage**

Drainage control systems shall be constructed on the entire length of road (e.g. ditches, sidehill outsloping and insloping, lead-off ditches, culvert installation, and low water crossings).

A typical lead-off ditch has a minimum depth of 1 foot below and a berm of 6 inches above natural ground level. The berm shall be on the down-slope side of the lead-off ditch.

### Cross Section of a Typical Lead-off Ditch



All lead-off ditches shall be graded to drain water with a 1 percent minimum to 3 percent maximum ditch slope. The spacing interval are variable for lead-off ditches and shall be determined according to the formula for spacing intervals of lead-off ditches, but may be amended depending upon existing soil types and centerline road slope (in %);

### Formula for Spacing Interval of Lead-off Ditches

Example - On a 4% road slope that is 400 feet long, the water flow shall drain water into a lead-off ditch. Spacing interval shall be determined by the following formula:

$$400 \text{ foot road with } 4\% \text{ road slope: } \frac{400'}{4\%} + 100' = 200' \text{ lead-off ditch interval}$$

### Cattleguards

An appropriately sized cattleguard sufficient to carry out the project shall be installed and maintained at fence/road crossings. Any existing cattleguards on the access road route shall be repaired or replaced if they are damaged or have deteriorated beyond practical use. The operator shall be responsible for the condition of the existing cattleguards that are in place and are utilized during lease operations.

### Fence Requirement

Where entry is granted across a fence line, the fence shall be braced and tied off on both sides of the passageway prior to cutting. The operator shall notify the private surface landowner or the grazing allotment holder prior to crossing any fences.

### Public Access

Public access on this road shall not be restricted by the operator without specific written approval granted by the Authorized Officer.

**Construction Steps**

1. Salvage topsoil
2. Construct road

3. Redistribute topsoil
4. Revegetate slopes




Figure 1. Cross-sections and plans for typical road sections representative of BLM resource or FS local and higher-class roads.

## VII. DRILLING

### A. DRILLING OPERATIONS REQUIREMENTS

The BLM is to be notified in advance for a representative to witness:

- a. Spudding well (minimum of 24 hours)
- b. Setting and/or Cementing of all casing strings (minimum of 4 hours)
- c. BOPE tests (minimum of 4 hours)

**Eddy County**

Call the Carlsbad Field Office, 620 East Greene St., Carlsbad, NM 88220,  
(575) 361-2822

1. **Hydrogen Sulfide (H<sub>2</sub>S) monitors shall be installed prior to drilling out the surface shoe. If H<sub>2</sub>S is encountered in quantities greater than 10 PPM the well shall be shut in and H<sub>2</sub>S equipment shall be installed and flare line must be extended pursuant to Onshore Oil and Gas Order #6. Report measured values and formation to the BLM. After detection, the Hydrogen Sulfide area must meet Onshore Order 6 requirements, which includes equipment and personnel/public protection items.**
2. Unless the production casing has been run and cemented or the well has been properly plugged, the drilling rig shall not be removed from over the hole without prior approval. **If the drilling rig is removed without approval – an Incident of Non-Compliance will be written and will be a “Major” violation.**
3. Floor controls are required for 3M or Greater systems. These controls will be on the rig floor, unobstructed, readily accessible to the driller and will be operational at all times during drilling and/or completion activities. Rig floor is defined as the area immediately around the rotary table; the area immediately above the substructure on which the draw works is located, this does not include the dog house or stairway area.
4. **The record of the drilling rate along with the GR/N well log run from TD to surface (horizontal well – vertical portion of hole) shall be submitted to the BLM office as well as all other logs run on the borehole 30 days from completion. If available, a digital copy of the logs is to be submitted in addition to the paper copies. The Rustler top and top and bottom of Salt are to be recorded on the Completion Report.**

## B. CASING

Changes to the approved APD casing program need prior approval if the items substituted are of lesser grade or different casing size or are Non-API. The Operator can exchange the components of the proposal with that of superior strength (i.e. changing from J-55 to N-80, or from 36# to 40#). Changes to the approved cement program need prior approval if the altered cement plan has less volume or strength or if the changes are substantial (i.e. Multistage tool, ECP, etc.). The initial wellhead installed on the well will remain on the well with spools used as needed.

Centralizers required on surface casing per Onshore Order 2.III.B.1.f.

### Wait on cement (WOC) for Potash Areas:

After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi for all cement blends, 2) until cement has been in place at least 24 hours. WOC time will be recorded in the driller's log.

No pea gravel permitted for remedial or fall back remedial without prior authorization from the BLM engineer.

### R-111-P-Potash

#### High Cave/Karst

Possibility of water flows in the Salado and Castile.

Possibility of lost circulation in the Red Beds, Rustler, and Delaware.

**A MINIMUM OF TWO CASING STRINGS CEMENTED TO SURFACE IS REQUIRED IN HIGH CAVE/KARST AREAS. THE CEMENT MUST BE IN A SOLID SHEATH. THEREFORE, ONE INCH OPERATIONS ARE NOT SUFFICIENT TO PROTECT CAVE KARST RESOURCES. A CASING DESIGN THAT HAS A ONE INCH JOB PERFORMED DOES NOT COUNT AS A SOLID SHEATH. IF THE PRIMARY CEMENT JOB ON THE SURFACE CASING DOES NOT CIRCULATE, THEN THE NEXT TWO CASING STRINGS MUST BE CEMENTED TO SURFACE.**

1. The 13-3/8 inch surface casing shall be set at approximately 536 feet (a minimum of 25 feet into the Rustler Anhydrite and above the salt) and cemented to the surface. **If salt is encountered, set casing at least 25 feet above the salt.**
  - a. If cement does not circulate to the surface, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic type temperature survey with surface log readout will be used or a cement bond log shall be run to verify the top of the cement. Temperature survey will be run a minimum of six hours after pumping cement and ideally between 8-10 hours after completing the cement job.
  - b. **Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry.**
  - c. Wait on cement (WOC) time for a remedial job will be a minimum of 4 hours after bringing cement to surface or 500 pounds compressive strength, whichever is greater.
  - d. If cement falls back, remedial cementing will be done prior to drilling out that string.
2. The minimum required fill of cement behind the 9-5/8 inch intermediate casing is:
  - Cement to surface. If cement does not circulate see B.1.a, c-d above. **Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry due to cave/karst and potash.**

**Centralizers required through the curve and a minimum of one every other joint.**

3. The minimum required fill of cement behind the 7 inch production casing is:

**Operator has proposed DV tool at depth of 5000', but will adjust cement proportionately if moved. DV tool shall be set a minimum of 50' below previous shoe and a minimum of 200' above current shoe. Operator shall submit sundry if DV tool depth cannot be set in this range.**

- a. First stage to DV tool:
  - Cement to circulate. If cement does not circulate, contact the appropriate BLM office before proceeding with second stage cement job. Operator should have plans as to how they will achieve circulation on the next stage.
- b. Second stage above DV tool:
  - Cement to surface. If cement does not circulate, contact the appropriate BLM office. **Excess calculates to 23% - Additional cement may be required.**

4. Cement not required on the 4-1/2" casing. **Packer system being used. Liner must tie back a minimum of 100' into 7" casing.**
5. If hardband drill pipe is rotated inside casing, returns will be monitored for metal. If metal is found in samples, drill pipe will be pulled and rubber protectors which have a larger diameter than the tool joints of the drill pipe will be installed prior to continuing drilling operations.
6. Whenever a casing string is cemented in the R-111-P potash area, the NMOCD requirements shall be followed.

### **C. PRESSURE CONTROL**

1. All blowout preventer (BOP) and related equipment (BOPE) shall comply with well control requirements as described in Onshore Oil and Gas Order No. 2 and API 53.
2. Variance approved to use flex line from BOP to choke manifold. Check condition of flexible line from BOP to choke manifold, replace if exterior is damaged or if line fails test. Line to be as straight as possible with no hard bends and is to be anchored according to Manufacturer's requirements. The flexible hose can be exchanged with a hose of equal size and equal or greater pressure rating. **Anchor requirements, specification sheet and hydrostatic pressure test certification matching the hose in service, to be onsite for review. These documents shall be posted in the company man's trailer and on the rig floor.** If the BLM inspector questions the straightness of the hose, a BLM engineer will be contacted and will review in the field or via picture supplied by inspector to determine if changes are required (operator shall expect delays if this occurs).
3. **Operator has proposed a multi-bowl wellhead assembly. This assembly will only be tested when installed on the surface casing. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be 3000 (3M) psi.**
  - a. **Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.**
  - b. **If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.**
  - c. **Manufacturer representative shall install the test plug for the initial BOP test.**
  - d. **Operator shall perform the 9-5/8" and 7" casing integrity tests to 70% of the casing burst. This will test the multi-bowl seals.**
  - e. **If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.**

4. The appropriate BLM office shall be notified a minimum of 4 hours in advance for a representative to witness the tests.
- a. In potash areas, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. For all casing strings, casing cut-off and BOP installation can be initiated at twelve hours after bumping the plug. However, **no tests** shall commence until the cement has had a minimum of 24 hours setup time.
  - b. The tests shall be done by an independent service company utilizing a test plug **not a cup or J-packer**.
  - c. The test shall be run on a 5000 psi chart for a 2-3M BOP/BOP, on a 10000 psi chart for a 5M BOP/BOPE and on a 15000 psi chart for a 10M BOP/BOPE. If a linear chart is used, it shall be a one hour chart. A circular chart shall have a maximum 2 hour clock. If a twelve hour or twenty-four hour chart is used, tester shall make a notation that it is run with a two hour clock.
  - d. The results of the test shall be reported to the appropriate BLM office.
  - e. All tests are required to be recorded on a calibrated test chart. **A copy of the BOP/BOPE test chart and a copy of independent service company test will be submitted to the appropriate BLM office.**
  - f. The BOP/BOPE test shall include a low pressure test from 250 to 300 psi. The test will be held for a minimum of 10 minutes if test is done with a test plug and 30 minutes without a test plug. This test shall be performed prior to the test at full stack pressure.

#### **D. DRILL STEM TEST**

If drill stem tests are performed, Onshore Order 2.III.D shall be followed.

#### **E. WASTE MATERIAL AND FLUIDS**

All waste (i.e. drilling fluids, trash, salts, chemicals, sewage, gray water, etc.) created as a result of drilling operations and completion operations shall be safely contained and disposed of properly at a waste disposal facility. No waste material or fluid shall be disposed of on the well location or surrounding area.

Porto-johns and trash containers will be on-location during fracturing operations or any other crew-intensive operations.

**JAM 070115**

## VIII. PRODUCTION (POST DRILLING)

### A. WELL STRUCTURES & FACILITIES

#### **Placement of Production Facilities**

Production facilities should be placed on the well pad to allow for maximum interim recontouring and revegetation of the well location.

#### **Exclosure Netting (Open-top Tanks)**

Immediately following active drilling or completion operations, the operator will take actions necessary to prevent wildlife and livestock access, including avian wildlife, to all open-topped tanks that contain or have the potential to contain salinity sufficient to cause harm to wildlife or livestock, hydrocarbons, or Resource Conservation and Recovery Act of 1976-exempt hazardous substances. At a minimum, the operator will net, screen, or cover open-topped tanks to exclude wildlife and livestock and prevent mortality. If the operator uses netting, the operator will cover and secure the open portion of the tank to prevent wildlife entry. The operator will net, screen, or cover the tanks until the operator removes the tanks from the location or the tanks no longer contain substances that could be harmful to wildlife or livestock. Use a maximum netting mesh size of 1 ½ inches. The netting must not be in contact with fluids and must not have holes or gaps.

#### **Chemical and Fuel Secondary Containment and Exclosure Screening**

The operator will prevent all hazardous, poisonous, flammable, and toxic substances from coming into contact with soil and water. At a minimum, the operator will install and maintain an impervious secondary containment system for any tank or barrel containing hazardous, poisonous, flammable, or toxic substances sufficient to contain the contents of the tank or barrel and any drips, leaks, and anticipated precipitation. The operator will dispose of fluids within the containment system that do not meet applicable state or U. S. Environmental Protection Agency livestock water standards in accordance with state law; the operator must not drain the fluids to the soil or ground. The operator will design, construct, and maintain all secondary containment systems to prevent wildlife and livestock exposure to harmful substances. At a minimum, the operator will install effective wildlife and livestock exclosure systems such as fencing, netting, expanded metal mesh, lids, and grate covers. Use a maximum netting mesh size of 1 ½ inches.

#### **Open-Vent Exhaust Stack Exclosures**

The operator will construct, modify, equip, and maintain all open-vent exhaust stacks on production equipment to prevent birds and bats from entering, and to discourage perching, roosting, and nesting. (*Recommended exclosure structures on open-vent exhaust stacks are in the shape of a cone.*) Production equipment includes, but may not be limited to, tanks, heater-treaters, separators, dehydrators, flare stacks, in-line units, and compressor mufflers.

#### **Containment Structures**

Proposed production facilities such as storage tanks and other vessels will have a secondary containment structure that is constructed to hold the capacity of 1.5 times the

largest tank, plus freeboard to account for precipitation, unless more stringent protective requirements are deemed necessary.

**Painting Requirement**

All above-ground structures including meter housing that are not subject to safety requirements shall be painted a flat non-reflective paint color, **Shale Green** from the BLM Standard Environmental Color Chart (CC-001: June 2008).

**VRM Facility Requirement**

Low-profile tanks not greater than eight-feet-high shall be used.

## **IX. INTERIM RECLAMATION**

During the life of the development, all disturbed areas not needed for active support of production operations should undergo interim reclamation in order to minimize the environmental impacts of development on other resources and uses.

Within six (6) months of well completion, operators should work with BLM surface management specialists (Jim Amos: 575-234-5909) to devise the best strategies to reduce the size of the location. Interim reclamation should allow for remedial well operations, as well as safe and efficient removal of oil and gas.

During reclamation, the removal of caliche is important to increasing the success of revegetating the site. Removed caliche that is free of contaminants may be used for road repairs, fire walls or for building other roads and locations. In order to operate the well or complete workover operations, it may be necessary to drive, park and operate on restored interim vegetation within the previously disturbed area. Disturbing revegetated areas for production or workover operations will be allowed. If there is significant disturbance and loss of vegetation, the area will need to be revegetated. Communicate with the appropriate BLM office for any exceptions/exemptions if needed.

All disturbed areas after they have been satisfactorily prepared need to be reseeded with the seed mixture provided below.

Upon completion of interim reclamation, the operator shall submit a Sundry Notices and Reports on Wells, Subsequent Report of Reclamation (Form 3160-5).

## **X. FINAL ABANDONMENT & RECLAMATION**

At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land are restored.

Earthwork for final reclamation must be completed within six (6) months of well plugging. All pads, pits, facility locations and roads must be reclaimed to a satisfactory

revegetated, safe, and stable condition, unless an agreement is made with the landowner or BLM to keep the road and/or pad intact.

After all disturbed areas have been satisfactorily prepared, these areas need to be revegetated with the seed mixture provided below. Seeding should be accomplished by drilling on the contour whenever practical or by other approved methods. Seeding may need to be repeated until revegetation is successful, as determined by the BLM.

Operators shall contact a BLM surface protection specialist prior to surface abandonment operations for site specific objectives (Jim Amos: 575-234-5909).

## SEED MIXTURE 1 (LOAMY LOCATIONS)

The holder shall seed all disturbed areas with the seed mixture listed below. The seed mixture shall be planted in the amounts specified in pounds of pure live seed (PLS)\* per acre. There shall be no primary or secondary noxious weeds in the seed mixture. Seed will be tested and the viability testing of seed will be done in accordance with State law(s) and within nine months prior to purchase. Commercial seed will be certified or registered seed. The seed container will be tagged in accordance with State law(s) and available for inspection by the authorized officer.

Seed will be planted using a drill equipped with a depth regulator to ensure proper depth of planting where drilling is possible. The seed mixture will be evenly and uniformly planted over the disturbed area (smaller/heavier seeds have a tendency to drop to the bottom of the drill and are planted first; the holder shall take appropriate measures to ensure this does not occur). Where drilling is not possible, seed will be broadcast and the area shall be raked or chained to cover the seed. When broadcasting the seed, the pounds per acre are to be double the amounts listed below. The seeding will be repeated until a satisfactory stand is established as determined by the authorized officer. Evaluation of growth will not be made before completion of at least one full growing season after seeding.

Species to be planted in pounds of pure live seed\* per acre (**note: if broadcasting seed, amounts are to be doubled**):

Species	Pound/acre
Plains Lovegrass ( <i>Eragrostis intermedia</i> )	0.5
Sand Dropseed ( <i>Sporobolus cryptandrus</i> )	1.0
Sideoats grama ( <i>Bouteloua curtipendula</i> )	5.0

\* Pounds of pure live seed = (Pounds of seed) x (Percent purity) x (Percent germination)