

Date : 4/14/2015

Apache Corporation – Washington 33 State #6

Wellbore Diagram – Existing

API: 30-015-30138



Spud Date: 8/8/1998

GL = 3,667'

KB = 3,674

Surface Location

790' FNL & 1650' FWL
Sec 33, T17S, R28E
Eddy County, NM

Hole Size
12 1/4"

Hole Size
7 7/8"

Surface Casing

8 5/8" 24# @ 530' w/ 325sx circ to surface

Production Casing

5 1/2" 15.5# @ 4,000' w/ 760sx circ to surface

Existing:

1380'-1405', 1457'-1480', 1717'-1735',
1916'-1950', 2020'-2030'(San Andres
Shallow Sands) '07

2826-2295'(San Andres) '98

PBTD @ 3,952'

TD @ 4,000'

Date : 4/14/2015

Apache Corporation – Washington 33 State #6

Wellbore Diagram – Proposed

API: 30-015-30138



Spud Date: 8/8/1998

GL = 3,667'

KB = 3,674'

Surface Location

790' FNL & 1650' FWL
Sec 33, T17S, R28E
Eddy County, NM

Hole Size
12 1/4"

Hole Size
7 7/8"

Surface Casing

8 5/8" 24# @ 530' w/ 325sx circ to surface

Production Casing

5 1/2" 15.5# @ 4,000' w/ 760sx circ to surface

Existing: Proposed to squeeze

1380'-1405', 1457'-1480', 1717'-1735',

1916'-1950', 2020'-2030'(San Andres
Shallow Sands) '07

2295'-2826'(San Andres) '98

Proposed:

Perfs @ 3,400'-3,800' (Yeso)

PBTD @ 3,952'

TD @ 4,000'