

N.M. Oil Cons. DIV-Dist. 2  
UNITED STATES DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT  
1301 W. Grand Avenue  
Albuquerque, NM 88210

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

5. Lease Designation and Serial No.

NMNM-0560378

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

O'Neill Federal #1

9. API Well No.

30-015-22977

10. Field and Pool, or Exploratory Area

Henshaw Q-G-SA

11. County or Parish, State

Eddy, NM

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

RECEIVED

NOV 09 2005

OOD-ARTESIA

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Mack Energy Corporation

3. Address and Telephone No.

P.O. Box 960, Artesia, NM 88211-0960

(505)748-1288

4. Location of Well (Footage, Sec., T. R., M. or Survey Description)

1980 FSL & 660 FEL, Sec. 15 T16S R30E

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent  
☐ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☐ Other

- ☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13 Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work)\*

1. Notify BLM 24 hours prior to starting plugging operations.
2. Set CIBP @ 2404' w/35' cement cap above perfs at 2504' and circ hole with mud.
3. Set 45 sx cement plug 50' above and below 8 5/8" csg from 516' - 416'. + TAG PLUG
4. Set cement plug from 60' to surface.
5. Install dry hole marker.

APPROVAL SUBJECT TO  
GENERAL REQUIREMENTS AND  
SPECIAL STIPULATIONS ATTACHED

APPROVED

NOV - 8 2005

LES BABYAK  
PETROLEUM ENGINEER

14. I hereby certify that the foregoing is true and correct.

Signed Gary W. Sherrill

Title Production Clerk

Date 10/21/2005

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

•See Instruction on Reverse Side

MACK ENERGY CORPORATION  
O'NEIL FEDERAL #1  
Sec 15 T16S R30E 1980FSL 660FEL

1. Notify BLM 24 hrs. prior to any work done.
2. Circ hole with mud gel.
3. Set CIBP @ 2404' w/35'cmt cap
4. Set 100' cmt plug 45' below and above shoe joint
5. Set 60' cmt plug at surface
6. Install Dry Hole Marker

