Submit 3 Copies To Appropriate District State of New Mexico Form C-103 Office May 27, 2004 Energy, Minerals and Natural Resources District I WELL API NO. 1625 N. French Dr., Hobbs, NM 88240 30-015-31148 District II OIL CONSERVATION DIVISION 1301 W. Grand Ave., Artesia, NM 88210 5. Indicate Type of Lease District III 1220 South St. Francis Dr. STATE 🖂 1000 Rio Brazos Rd., Aztec, NM 87410 Santa Fe, NM 87505 6. State Oil & Gas Lease No. District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505 V-5667 7. Lease Name or Unit Agreement Name SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH Tumbledink AVK State Com PROPOSALS.) 8. Well Number 1. Type of Well: Oil Well Gas Well RECEIVED 2. Name of Operator 9. OGRID Number Yates Petroleum Corporation 025575 NOV 1 6 2005 3. Address of Operator 10. Pool name or Wildcat OCD-MATERIA 105 S. 4th Street, Artesia, NM 88210 Richard Knob Atoka-Morrow 4. Well Location 660 feet from the North line and 660 Unit Letter feet from the East line Section 16 Township 18S Range **NMPM** Eddy County 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3537'GR Pit or Below-grade Tank Application 🔲 or Closure 🔲 Pit type _____ Depth to Groundwater ____ Distance from nearest fresh water well _____ Distance from nearest surface water Below-Grade Tank: Volume Pit Liner Thickness: bbls; Construction Material 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐ REMEDIAL WORK □ ALTERING CASING □ TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS.□ PLUG AND ABANDON PULL OR ALTER CASING MULTIPLE COMPL \Box CASING/CEMENT JOB OTHER: Perforate Atoka and stimulate OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 10/18/05 - Set 7" 23# composite plug at 8500'. Perforate Atoka 8370'-8382' (73) and 8392'-8402' (61). Acidize with 1500g 7-1/2% MSA. 10/19/05 – Tagged composite plug at 8500'. Set packer above composite plug and attempt to test plug. Plug would not hold pressure. TOH with tubing and packer. 10/20/05 - Set 7" 23# CIBP at 8490' with 10' cement on top. 10/21/05 - Re-acidize Atoka 8370'-8402' with 1500g MSA. 11/1/05 - Frac Atoka 8370'-8402' with CO2 foam frac with 373 bbls fluid, 116 tons CO2, 50,000# 20/40 PRC Premium sand. AS-1 packer with 2.25" on/off tool at 8162'. I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or belowgrade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit or an (attached) alternative OCD-approved plan . SIGNATURE (1 TITLE <u>Regulatory Compliance Supervisor</u> DATE <u>November 14, 2005</u> Type or print name Tina Huerta E-mail address: tinah@ypcnm.com Telephone No. 505-748-1471 For State Use Only FOR RECORDS ONLY

TITLE

DATE

Conditions of Approval (if any):

APPROVED BY: