

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised May 08, 2003

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 015-34249
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. 34967
7. Lease Name or Unit Agreement Name: 1625 State Com
8. Well Number 218885
9. OGRID Number 281
10. Pool name or Wildcat Cottonwood Creek-Wolfcamp
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3546' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
Oil Well ☐ Gas Well ☒ Other ☐
2. Name of Operator
LCX Energy, LLC
3. Address of Operator
110 N. Marienfeld, Ste. 200, Midland, TX 79701

4. Well Location
Unit Letter M : 660 feet from the North line and 760 feet from the West line
Section 28 Township 16S Range 25E NMPM County Eddy

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3546' GR

12. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☒
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

11/24/05 Spud well @ 11:00 pm w/ 17-1/2" hole.

Ran 9 jts 13-3/8" 48# H-40 ST&C casing. Casing set at 387'.

Cemented casing as follows: Pump 10 bbls FW spacer, 490 sx of Class "C" cement with 2% CaCl₂ & .25#/sk celloflake. Displaced with 55 bbls of FW. Bumped plug to 350' & float held. Circulated 41 sx to reserve pit.

Heat & weld 13-3/8" wellhead. Test good to 500 psi for 30 mins.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Sharon Hindman TITLE Regulatory Agent DATE 11/29/2005

Type or print name Sharon Hindman Telephone No. 432 687-1575

(This space for State use) **FOR RECORDS ONLY**

APPROVED BY _____ TITLE _____ DATE _____

Conditions of approval, if any:

NOV 30 2005