

Submit 3 Copies To Appropriate District Office
 District I
 1625 N. French Dr., Hobbs, NM 88240
 District II
 1301 W. Grand Ave., Artesia, NM 88210
 District III
 1000 Rio Brazos Rd., Aztec, NM 87410
 District IV
 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
 Energy, Minerals and Natural Resources

Form C-103
 Revised March 25, 1999

OIL CONSERVATION DIVISION
 1220 South St. Francis Dr.
 Santa Fe, NM 87505

WELL API NO.
 30-015-34331
 5. Indicate Type of Lease
 STATE FEE
 6. State Oil & Gas Lease No.
 VB0158

SUNDRY NOTICES AND REPORTS ON WELLS
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)
 1. Type of Well:
 Oil Well Gas Well Other

7. Lease Name or Unit Agreement Name:
 Forty Niner Ridge Unit

2. Name of Operator
 Mewbourne Oil Company 14744

8. Well No.
 #101

3. Address of Operator
 PO Box 5270 Hobbs, NM 88241

9. Pool name or Wildcat
 Forty Niner Ridge: Morrow 76800

4. Well Location
 Unit Letter N : 660 feet from the South line and 1980 feet from the West line
 Section 16 Township 23S Range 30E NMPM Eddy County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)
 3159' GL

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	MULTIPLE COMPLETION <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER: <input type="checkbox"/>		OTHER: Spud, casing job and Ran 1" pipe <input checked="" type="checkbox"/>	

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

12/27/05...MI and spud 17 1/2" hole. TD'ed 17 1/2" hole @ 474'. Ran 474' 13 3/4" 48# H40 ST&C Csg. Cemented with 180 sks Class H Thixsad with additives. Mixed @ 14.6 /g w/ 1.52 yd. Followed with 200 sks (35:65:6) BJ Lite Class C with additives. Mixed @ 12.5 /g w/ 1.96 yd. Tail with 400 sks Class C with 2% CaCl2. Mixed @ 14.8 #/g w/ 1.34 yd. Did not circulate. Ran Temp Survey. TOC at 340'. Ran 1" pipe. Tag at 228'.

- Cmt 1st plug with 25 sks Class "C" with 3% CaCl2. WOC. Tagged @ 228'.
- Cmt 2nd plug with 25 sks Class "C" with 3% CaCl2. WOC. Tagged @ 228'.
- Cmt 3rd plug with 25 sks Class "C" with 3% CaCl2. WOC. Tagged @ 258'.
- Cmt 4th plug with 20 sks Class "C" with 3% CaCl2. WOC. Tagged @ 228'.
- Cmt 5th plug with 25 sks Class "C" with 3% CaCl2. WOC. Tagged @ 228'.
- Cmt 6th plug with 25 sks Class "C" with 3% CaCl2. WOC.
- Cmt 7th plug with 25 sks Class "C" with 4% CaCl2. WOC. Tagged @ 135'.
- Cmt 8th plug with 25 sks Class "C" with 4% CaCl2. WOC. Tagged @ 135'.
- Cmt 9th plug with 25 sks Class "C" with 4% CaCl2. WOC. Tagged @ 135'.
- Cmt 10th plug with 25 sks Class "C" with 4% CaCl2. WOC. Tagged @ 112'.
- Cmt 11th plug with 25 sks Class "C" with 4% CaCl2. WOC. Tagged @ 45'.
- Cmt 12th plug with 35 sks Class "C" with 4% CaCl2. WOC. Circ 10 sks to pit.

At 3:00 pm 12/30/05, tested casing & BOPE to 1250#, held OK. Drilled out with 12 1/4" bit.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.
 SIGNATURE Kristi Green TITLE Hobbs Regulatory DATE 01/03/06

Type or print name Kristi Green Telephone No. 505-393-5905

(This space for State use)
 APPROVED BY _____ TITLE _____ DATE JAN 05 2006

Conditions of approval, if any:

FOR RECORDS ONLY