Submit 3 Copies To Appropriate District Office	State of New Mo		Form C-103 May 27, 2004	
District I	Energy, Minerals and Natural Resources		WELL API NO.	
1625 N. French Dr., Hobbs, NM 87240 District II	OIL CONSERVATION DIVISION		30-015-34477	
1301 W. Grand Ave., Artesia, NM 88210	1220 South St. Francis Dr.		5. Indicate Type of I	Lease
District III 1000 Rio Brazos Rd., Aztec, NM 87410	Santa Fe, NM 87505		STATE	FEE 🗷
District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505			6. State Oil & Gas I	ease No.
SUNDRY NOTICES AND REPORTS ON WELLS I(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A			7. Lease Name or U	Init Agreement Name:
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		Yellow A 7 Fee		
1. Type of Well:		RECEIVED	8. Well Number	
Oil Well Gas Well	Other		1H	
2. Name of Operator		JAN 2 7 2006	9. OGRID Number	
EOG Resources Inc.		CU-ARTEDIA	737	
3. Address of Operator			10. Pool name or W	
P.O. Box 2267 Midland, Tex 4. Well Location	<u>ras 79702</u>		Cottonwood Creek	; Wolfcamp, West Gas
4. Well Location				
Unit Letter A ::	feet from the No.	rth line and	852 feet from	the East line
Section 7		Range 25E	NMPM	County Eddy
	11. Elevation (Show whether 35	DR, RKB, RT, GR, etc 5 14 G R	2.)	The second secon
Pit or Below-grade Tank Application	or Closure			
Pit type Depth to Groundwater Distance from nearest fresh water well Distance from nearest surface water				
Pit Liner Thickness: mil Below-Grade Tank: Volumebbls; Construction Material				
NOTICE OF INTERPRETATION TEMPORARILY ABANDON DULL OR ALTER CASING			SEQUENT REP	
OTHER:		OTHER:		П
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.				
1/21/06 Spud @ 2:45 PM 1/23/06 Ran 21 jts 8 5/8", 32 #, J-55 surface casing set @ 925'. Cemented w/ 200 sx Class C, 9.5 ppg, 7.65 yield; 100 sx Prem Plus, 14.0 ppg, 1.53 yield; 122 sx Halliburton Lite Prem Plus + 2% CaCl2, 12.4 ppg, 2.04 yield; 370 sx Prem Plus + 2% CaCl2, 14.8 ppg, 1.35 yield. CIRC 200 sx 1st slurry, 100 sx 2nd slurry, 190 sx 3rd slurry to surface. WOC 27 hrs. 1/24/06 Tested casing to 2000 psi for 30 min. Test good.				
I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-				
grade tank has been/will be constructed or closed according to NMOCD guidelines, a general permit or an (attached) alternative OCD-approved plan				
SIGNATURE Slame	Nogre-TIT	LE Regulator	ry Analyst [DATE1/24/06
Type or print name Stan Wagner	E-r	nail address:	Teleph	one No. 432 686 3689
For State Use Only			•	IAM O D DOOD

_ TITLE_

FOR RECORDS ONLY

APPROVED BY_

Conditions of Approval, if any:

JAN 3 0 2006

__ DATE `