SUNDRY I Do not use this abandoned well SUBMIT IN TRIF 1. Type of Well Oil Well S Gas Well Oth 2. Name of Operator BEPCO LP 3a. Address MIDLAND, TX 79702	Contact:	RTS ON WELLS drill or to re-enter an D) for such proposals.	5. Lease Serial No. NMNM06818 6. If Indian, Allottee 7. If Unit or CA/Age	or Tribe Name	
abandoned well SUBMIT IN TRIF 1. Type of Well Oil Well S Gas Well Oth 2. Name of Operator BEPCO LP 3a. Address MIDLAND, TX 79702	I. Use form 3160-3 (API PLICATE - Other instruc er Contact:	D) for such proposals.		or Tribe Name	
<ol> <li>Type of Well</li> <li>Oil Well Gas Well Oth</li> <li>Name of Operator BEPCO LP</li> <li>Address</li> <li>MIDLAND, TX 79702</li> </ol>	er Contact:	tions on reverse side.	7. If Unit or CA/Agr		
Oil Well Gas Well Oth C. Name of Operator BEPCO LP Gas. Address MIDLAND, TX 79702	Contact:			7. If Unit or CA/Agreement, Name and/or No	
2. Name of Operator BEPCO LP 3a. Address MIDLAND, TX 79702	Contact:		8. Well Name and No BIG EDDY 8	ວ.	
3a. Address MIDLAND, TX 79702		TRACIE J CHERRY	9. API Well No.		
MIDLAND, TX 79702	E-Mail: tjcherry@b	asspet.com 3b. Phone No. (include area code)	30-015-10775 10. Field and Pool, c		
	Ph: 432-		BIG EDDY		
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)			11. County or Parish, and State		
Sec 30 T20S R31E NENW	660' FAIL	€ 1980 Fil	EDDY COUNT	ΓΥ, NM	
12. CHECK APPR	OPRIATE BOX(ES) TO	) INDICATE NATURE OF 1	I NOTICE, REPORT, OR OTHI	ER DATA	
TYPE OF SUBMISSION	TYPE OF ACTION				
Notice of Intent	Acidize	Deepen	Production (Start/Resume)	Water Shut-Of	
Subsequent Report	Alter Casing	Fracture Treat		U Well Integrity	
	Casing Repair	New Construction	Recomplete	🗖 Other	
Final Abandonment Notice	Change Plans Convert to Injection	🔀 Plug and Abandon 🗂 Plug Back	Temporarily Abandon Water Disposal		
BOPCO, LP respectfully subm well. The plugging proceedure 1. MIRU pulling unit and plugg psi manual BOP for 2-7/8" tubi	e is as follows: ging equipment. Set open ing. POOH with existing 2	top steel pit for plugging. ND 2-7/8" and 2-3/8" tbg string.	RECI	LAMATION PROCED ATTACHED	
2. RIH with work string, circula					
3. Tag cmt @ 8,843'. Pump a			SEE ATTACH		
<ol> <li>POOH with work string, RII</li> </ol>	H with CIBP on WL. Set C	Accepted for record MOCD 9/3	CONDITIONS	OF APPROV	
14. I hereby certify that the foregoing is	Electronic Submission #	315438 verified by the BLM We	I Information System	OIL CONSERV	
Ci	For E ommitted to AFMSS for pro	BEPCO LP, sent to the Carlsba ocessing by JAMES AMOS on I	d 09/17/2015 (15JA0353SE)		
Name (Printed/Typed) TRACIE J	CHERRY ,	Title REGUL	ATORY ANALYST	SEP 30 201	
Signature (Electronic S	-	Date 09/03/2	015	RECEIVE	
		OR FEDERAL OR STATE			
_Approved Byamos	a. amo-	Title St	ET	9-17-, Date	
Conditions of approva, if any, are attached certify that the applicant holds legal or equivient which would entify the applicant to condu	itable title to those rights in the		$\mathcal{D}$		
Title 8 U.S.C Section 1001 and Title 43 States any false, fictitious or fraudulent s	U.S.C. Section 1212, make it a statements or representations as	crime for any person knowingly and to any matter within its jurisdiction	willfully to make to any department	or agency of the United	

ſ

#### Additional data for EC transaction #315438 that would not fit on the form

#### 32. Additional remarks, continued

5. RIH with workstring, tag CIBP @ 8,290 making sure CIBP did not slip downhole below the perfs. Spot 25 sxs Class H cmt on top of CIBP. (Perf Plug) Addie add from L Cont. fo cover Sq2 ed perfs @
6. POOH with tbg, RIH with WL and perforating gun. Perf 4spf at 7,075'. POOH with WL. RIH with packer. Using 50 sxs class C cmt squeeze perfs, spot plug from 2,075' to 6,060'. (T/BS Plug). 7205 - 7035.

7. ND BOP and WH Flange. Install lift nipple for 5-1/2" csg, jet cut same at +/-3,875. (Only cut C 3952 attempt one casing cut. If casing will not pull contact BLM). RIH with tubing. Circulate out with 9.5# salt gel mud. Pull 5-1/2" casing. NU BOP and WH Flange.

8. RIH with workstring to 3969', spot 125 sxs Class C cmt from 3,960' to 3,625'. WOC & Tag no 4002 - 3625' lower than 3625'. (T/Del & 8-5/8" Shoe Plug)

9. PUH to 2,677', spot 575 sxs Class C cmt from 2,677' to 750'. WOC & Tag no lower than 750'. Fluid used to mix the cement for the Salt section of this plug shall be saturated with the salts common to the section and in suitable proportions. Note: Well is in the Potash Area so it will need a solid plug from B/Salt to T/Salt. (DV Tool, 11-3/4" Shoe, B/Salt, 16" Shoe and T/Salt Plug)

10. PUH to 100', spot 30 sxs Class C cmt from 100' to surface. Verify to surface. (Surface Plug)

11. ND BOP, cut off wellhead 5' below surface.

12. Set P&A marker.

13. Use steel tank and haul all fluids

## BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

# Permanent Abandonment of Federal Wells Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within <u>ninety (90)</u> days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90<sup>th</sup> day provide this office, prior to the 90<sup>th</sup> day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

2. <u>Notification:</u> Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.

3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.

4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of **brine** water. Minimum nine (9) pounds per gallon.

5. <u>Cement Requirement</u>: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. **Before pumping or bailing** cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

6. <u>Dry Hole Marker</u>: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The BLM is to be notified a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 10<sup>th</sup> day, the BLM is to be contacted with justification to receive an extension for completing the cut off.

The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement, unless otherwise noted in COA (requirements will be attached). The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).

7. <u>Subsequent Plugging Reporting</u>: Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. **Show date well was plugged.** 

8. <u>Trash</u>: All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation procedure.

J. Amos 3/6/11



# **United States Department of the Interior**

BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 E. Greene St. Carlsbad, New Mexico 88220-6292 www.blm.gov/nm



In Reply Refer To: 1310

### **Reclamation Objectives and Procedures**

**Reclamation Objective:** Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land and water are restored.

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration, including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its predisturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives will be reached through natural processes.

To achieve these objectives, remove any and all contaminants, scrap/trash, equipment, pipelines and powerlines. Strip and remove caliche, contour the location to blend with the surrounding landscape, redistribute the native soils, provide erosion control as needed, rip and seed as specified in the original APD COA. This will apply to well pads, facilities, and access roads. Barricade access road at the starting point. If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to how you propose to provide adequate restoration of the pit area.

- The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of Operations must include adequate measures for stabilization and reclamation of disturbed lands. Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD process as per Onshore Oil and Gas Order No. 1.
- 2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation is to be completed within 6 months.
- 3. The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the plugging of a well.
- 4. Previous instruction had you waiting for a BLM specialist to inspect the location and provide you with reclamation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with reclamation as per approved APD. If you have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation

equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.

- 5. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
- 6. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.
- 7. At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved, releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

If there are any questions, please feel free to contact any of the following specialists:

Jim Amos Supervisory Petroleum Engineering Tech 575-234-5909, 575-361-2648 (Cell)

Arthur Arias Environmental Protection Specialist 575-234-6230

Linda Denniston Environmental Protection Specialist 575-234-5974

Henryetta Price Environmental Protection Specialist 575-234-5951

Dara Glass Environmental Protection Specialist 575-234-5924

Shelly Tucker Environmental Protection Specialist 575-234-5979