BI	UNITED STATES PARTMENT OF THE II UREAU OF LAND MANA	S NM OIL CONSERVA NTERIOR ARTEBIA DESIGNERIC GEMENT OCT 19 201		FORM APPROVED DMB NO. 1004-0135 xpires: July 31, 2010			
		5. Lease Serial NMLC065	5. Lease Serial No. NMLC065014				
Do not use thi abandoned wel	6. If Indian, Al	6. If Indian, Allottee or Tribe Name					
SUBMIT IN TRI	7. If Unit or Ca	7. If Unit or CA/Agreement, Name and/or N					
1. Type of Well Soli Well Gas Well Oth		8. Well Name and No. MAX FRIESS					
2. Name of Operator LINN OPERATING INCORPO		9. API Well No. 30-015-26656-00-S1					
3a. Address 600 TRAVIS STREET SUITE HOUSTON, TX 77002		10. Field and Pool, or Exploratory GRAYBURG					
4. Location of Well (Footage, Sec., T	, R., M., or Survey Description	Fx: 832-209-4338	11. County or l	Parish, and State			
Sec 30 T17S R31E NENE 127	70FNL 100FEL		EDDY CC	OUNTY; NM			
12. CHECK APPI	ROPRIATE BOX(ES) TO	DINDICATE NATURE OF	NOTICE, REPORT, OR C	THER DATA			
TYPE OF SUBMISSION		ТҮРЕ О	FACTION				
□ Notice of Intent	□ Acidize	Deepen	Production (Start/Result	me) 🔲 Water Shut-(
_	Alter Casing	Fracture Treat	Reclamation	🗖 Well Integrit			
🛛 Subsequent Report	Casing Repair	New Construction	🗋 Recomplete	Other			
Final Abandonment Notice	Change Plans	🛛 Plug and Abandon	Temporarily Abandon				
	Convert to Injection	Plug Back	Water Disposal				
testing has been completed. Final At determined that the site is ready for fi Subsequent sundry for shallow	inal inspection.)			pleted, and the operator has $(0,0,0)$			
from lim Amos The well was	plugged according to the	i hole. Received verbal appro following:	val to plug well	()) () () () () () () () () () () () ()			
from Jim Amos. The well was	plugged according to the	following:		NMOOD			
from Jim Amos. The well was 1/30/15 - MIRU plugging equip ring on wireline. Tagged at 14	plugged according to the	following:		NMOCD			
from Jim Amos. The well was 1/30/15 - MIRU plugging equip	plugged according to the oment. Dug out cellar. NL 05'. POH. 350', got communication v 0H w/ packer. RIH open e < of Class C cement at 14	following: J BOP. POH w/ 16 jts of tubin when started pumping. Isolate nded and tag fish at 1405'. Pi 105' - 1158'. (per Jim Amos at	g. RIH w/ gauge d holes in umped 35 bbls of BLM). POH w/ Accepted as to pi	ond is retained until			
from Jim Amos. The well was 1/30/15 - MIRU plugging equip ring on wireline. Tagged at 14 2/2/15 - Set 5 1/2 packer at 13 casing. (1260' and below). PC mud laden fluid. Spotted 25 so tbg. RIH and set packer at 110	plugged according to the pment. Dug out cellar. NL 05'. POH. 350', got communication v DH w/ packer. RIH open e k of Class C cement at 14 00', pressured up to 400 p strue and correct.	following: J BOP. POH w/ 16 jts of tubin when started pumping. Isolate nded and tag fish at 1405'. Pr 105' - 1158'. (per Jim Amos at osi. SI well.	g. RIH w/ gauge ed holes in umped 35 bbls of BLM). POH w/ Accepted as to pi Liability under b Surface restoretic	ond is retained until an i s co mpleted.			
from Jim Amos. The well was 1/30/15 - MIRU plugging equip ring on wireline. Tagged at 14 2/2/15 - Set 5 1/2 packer at 13 casing. (1260' and below). PC mud laden fluid. Spotted 25 sy tbg. RIH and set packer at 110	plugged according to the oment. Dug out cellar. NL 05'. POH. 350', got communication v H w/ packer. RIH open e c of Class C cement at 14 00', pressured up to 400 p s true and correct. Electronic Submission # For LINN OPERA mmitted to AFMSS for pro	following: J BOP. POH w/ 16 jts of tubin when started pumping. Isolate nded and tag fish at 1405'. Pr 105' - 1158'. (per Jim Amos at osi. SI well. 292685 verified by the BLM We TING INCORPORATED, sent to cessing by MARISSA KLEIN or	g. RIH w/ gauge ed holes in umped 35 bbls of BLM). POH w/ Accepted as to pi Liability under b Surface restoretic surface restoretic the Carlsbad	ond is retained until an i s co mpleted.			
from Jim Amos. The well was 1/30/15 - MIRU plugging equip ring on wireline. Tagged at 14 2/2/15 - Set 5 1/2 packer at 13 casing. (1260' and below). PC mud laden fluid. Spotted 25 so tbg. RIH and set packer at 110	plugged according to the oment. Dug out cellar. NL 05'. POH. 350', got communication v H w/ packer. RIH open e c of Class C cement at 14 00', pressured up to 400 p s true and correct. Electronic Submission # For LINN OPERA mmitted to AFMSS for pro	following: J BOP. POH w/ 16 jts of tubin when started pumping. Isolate nded and tag fish at 1405'. Pr 105' - 1158'. (per Jim Amos at osi. SI well. 292685 verified by the BLM We TING INCORPORATED, sent to cessing by MARISSA KLEIN or	g. RIH w/ gauge ed holes in umped 35 bbls of BLM). POH w/ Accepted as to pi Liability under b Surface restoretic	ond is retained until an i s co mpleted.			
from Jim Amos. The well was 1/30/15 - MIRU plugging equip ring on wireline. Tagged at 14 2/2/15 - Set 5 1/2 packer at 13 casing. (1260' and below). PC mud laden fluid. Spotted 25 so tbg. RIH and set packer at 110 14. Thereby certify that the foregoing is Co Name (Printed/Typed) ALEX BO	plugged according to the oment. Dug out cellar. NL 05'. POH. 350', got communication v OH w/ packer. RIH open e of Class C cement at 14 00', pressured up to 400 p strue and correct. Electronic Submission # For LINN OPERA mmitted to AFMSS for pro LANOS	following: J BOP. POH w/ 16 jts of tubin when started pumping. Isolate nded and tag fish at 1405'. Pr 105' - 1158'. (per Jim Amos at osi. SI well. 292685 verified by the BLM We TING INCORPORATED, sent to cessing by MARISSA KLEIN or Title AUTHO Date 02/23/2	g. RIH w/ gauge ad holes in umped 35 bbls of BLM). POH w/ Accepted as to pi Liability under be Surface restoretic surface restoretic the Carlsbad 06/17/2015 (15JA0196SE), DRIZED SIGNATURE	ond is retained until an is completed WOLAMATE SUR <u><u>8-3-/5</u></u>			
from Jim Amos. The well was 1/30/15 - MIRU plugging equip ring on wireline. Tagged at 14 2/2/15 - Set 5 1/2 packer at 13 casing. (1260' and below). PC mud laden fluid. Spotted 25 sy tbg. RIH and set packer at 110 14. Thereby certify that the foregoing is Co Name (<i>Printed/Typed</i>) ALEX BO	plugged according to the oment. Dug out cellar. NL 05'. POH. 350', got communication v OH w/ packer. RIH open e of Class C cement at 14 00', pressured up to 400 p strue and correct. Electronic Submission # For LINN OPERA mmitted to AFMSS for pro LANOS	following: J BOP. POH w/ 16 jts of tubin when started pumping. Isolate nded and tag fish at 1405'. Pr 105' - 1158'. (per Jim Amos at osi. SI well. 292685 verified by the BLM We TING INCORPORATED, sent to cessing by MARISSA KLEIN or Title AUTHO	g. RIH w/ gauge ad holes in umped 35 bbls of BLM). POH w/ Accepted as to pi Liability under be Surface restoretic surface restoretic the Carlsbad 06/17/2015 (15JA0196SE), DRIZED SIGNATURE	ond is retained until an is completed WOLAMATE			
from Jim Amos. The well was 1/30/15 - MIRU plugging equip ring on wireline. Tagged at 14 2/2/15 - Set 5 1/2 packer at 13 casing. (1260' and below). PC mud laden fluid. Spotted 25 sy tbg. RIH and set packer at 110 14. Thereby certify that the foregoing is Co Name (Printed/Typed) ALEX BO Signature (Electronic S	plugged according to the oment. Dug out cellar. NL 05'. POH. 350', got communication v OH w/ packer. RIH open e of Class C cement at 14 00', pressured up to 400 p strue and correct. Electronic Submission # For LINN OPERA mmitted to AFMSS for pro LANOS	following: J BOP. POH w/ 16 jts of tubin when started pumping. Isolate nded and tag fish at 1405'. Pr 105' - 1158'. (per Jim Amos at osi. SI well. 292685 verified by the BLM We TING INCORPORATED, sent to cessing by MARISSA KLEIN or Title AUTHO Date 02/23/2 DR FEDERAL OR STATE	g. RIH w/ gauge ad holes in umped 35 bbls of BLM). POH w/ Accepted as to pi Liability under be Surface restoretic surface restoretic the Carlsbad 06/17/2015 (15JA0196SE), DRIZED SIGNATURE	NCLAMATY CLAMATY CE_ <u>\$'3-/5</u>			
from Jim Amos. The well was 1/30/15 - MIRU plugging equip ring on wireline. Tagged at 14 2/2/15 - Set 5 1/2 packer at 13 casing. (1260' and below). PC mud laden fluid. Spotted 25 sy tbg. RIH and set packer at 110 14. Thereby certify that the foregoing is Co Name (<i>Printed/Typed</i>) ALEX BO	plugged according to the oment. Dug out cellar. NL 05'. POH. 350', got communication v H w/ packer. RIH open e c of Class C cement at 14 00', pressured up to 400 p strue and correct. Electronic Submission # For LINN OPERA mmitted to AFMSS for pro LANOS Submission) THIS SPACE FO	following: J BOP. POH w/ 16 jts of tubin when started pumping. Isolate nded and tag fish at 1405'. Pri 105' - 1158'. (per Jim Amos at osi. SI well. 292685 verified by the BLM We TING INCORPORATED, sent ti cessing by MARISSA KLEIN or Title AUTHO Date 02/23/2 DR FEDERAL OR STAT	g. RIH w/ gauge ad holes in umped 35 bbls of BLM). POH w/ Accepted as to pi Liability under by Surface restoretic surface restoretic the Carlsbad 06/17/2015 (15JA0196SE), DRIZED SIGNATURE 20/13 OF OF OF OF OF OF OF Arce USE OF OF OF OF OF Arce USE OF OF OF OF	ond is retained until an is completed WOLAMATE SUR <u><u>8-3-/5</u></u>			
from Jim Amos. The well was 1/30/15 - MIRU plugging equip ring on wireline. Tagged at 14 2/2/15 - Set 5 1/2 packer at 13 casing. (1260' and below). PC mud laden fluid. Spotted 25 sy tbg. RIH and set packer at 110 14. Thereby certify that the foregoing is Co Name (<i>Printed/Typed</i>) ALEX BO Signature (Electronic S Approved By	plugged according to the oment. Dug out cellar. NL 05'. POH. 350', got communication v OH w/ packer. RIH open e x of Class C cement at 14 00', pressured up to 400 p s true and correct. Electronic Submission # For LINN OPERA mmitted to AFMSS for pro LANOS Submission) THIS SPACE F(d. Approval of this notice does uitable title to those rights in th act operations thereon. U.S.C. Section 1212, make it a	following: J BOP. POH w/ 16 jts of tubin when started pumping. Isolate nded and tag fish at 1405'. Pr 105' - 1158'. (per Jim Amos at osi. SI well. 292685 verified by the BLM We TING INCORPORATED, sent to cessing by MARISSA KLEIN or Title AUTHO Date 02/23/2 DR FEDERAL OR STAT CR FEDERAL OR STAT Title S not warrant or e subject lease Office	g. RIH w/ gauge ed holes in umped 35 bbls of BLM). PAtterfted as to pil Liability under by Surface restoration of the Carlsbad 06/17/2015 (15JA0196SE) DRIZED SIGNATURE DISCOUNTING OCT 132 OCT 132 OCT 132 OCT 132	A RECORD Date MOLAMATI NOLAMATI NOLAMATI NOLAMATI NOLAMATI Date Date Date			

Additional data for EC transaction #292685 that would not fit on the form

32. Additional remarks, continued

2/3/15 - POH w/ packer. RIH w/ tbg and tagged at 1200'. POH, Set packer at 30' and pressured up on casing to 500 psi, held ok. POH w/ packer. RIH and spotted 25 sx of Class C cement from 650' - 403'. (per Jim Amos) POH and WOC. Tagged plug at 400'. POH, RIH and Perforated casing at 375'. Set packer at 30' and pressured up on perfs to 600 psi. Spotted 25 sx of Class C Cement from 400' - 153', POH WOC.

2/4/15 - RIH and tag cement at 160'. Perforate casing at 60', Set packer at 10' and pressured up on perfs to 600 psi. ND BOP. Spotted 20 sx of Class C Cement at 110' to surface with Kent Caffal from BLM. Rigged down and moved off.

2/9/15 - Moved in backhoe and welder, dug out cellar, cut off wellhead. Kent Caffal instructed to pump cement between 12 1/4 and 8 5/8 annulus.

2/13/15 - Moved in cemented. Ran 1" hose to 47' down annulus. Spotted 10 sx of Class C cement to surface. RDMO. Moved in backhoe and welder. Welded on below ground dry hole marker. Backfilled cellar and removed deadmen. Cleaned location and moved off.

LINN Edgy Well Name: FRIESS MAX M A 5

NM P&A Schemat	IC
----------------	----

AP/UW 30015	1 526656	Field Name PBNM - F	B-GRAYBU	County RG Eddy			State/Pro			Townshi 017-S		inge 31-E	Survey	E	Block	
Ground	Elevation (ft) Orig KB 3,613.00	Elev (fl) 3,626.00	KB-Grd (ft) 13.0	Initial Spud Da		Rig Release [Date	TD Dat	<u> </u>	Latit	ude (*) 32° 48	3' 33.552"	Longitude (N 10	(*) 3° 53' 59.	964" \	Operated N Yes
Original Hole, 2/19/2015 2:12:05 PM									C	Driginal	Hole Dat	ta		•		
MD tKB),	างและเรางรักษณ์ษระบบไฟน ตาม Vertical schematic (actual) การ เหมาะ และ และ ประชาภาพสาย เกมาะ							Wellbores of the State State of Courses of the state of t								
131 -							Lintun Kinati	North-South Distance (ft) INS Flag East-West Distance (ft) EW Flag								
29.9 ·	Production Casing Cement; 13.0-30.0							Casing Strings Csg Des [Set Dept.,]OD Nom [ID Nom [W/Len (I]String Grade] Run Date								
109.9		<u> </u>		Cement Plug; 12 3/4; Surfac			50		urface	s	325.0	12 3/4 NomID N		.50 J-55 1 (I., String G	Fade	3/12/199 Run Date
160.1				-Wellbore; 17	1/2; 13.0	0-333.0			oduction g Des		1.391.0 et Dept OD			.00 J-55 (I String G	irade	3/14/199 Run Date
325.1 ·· 333.0 ··	Surface Casing Cement; 13.0-325.0						Lii	Corport Set Deput OD Nom: Worm Weter (m. Sump chabe Num chabe Liner 3,810.0 5 1/2 4.892 17.00 J-55 3/20/199 Cement Stages 3/20/199 3/20/199 3/20/199 3/20/199 3/20/199								
375.0 .			数 ————————————————————————————————————					De	scription urface Ca			8tm (ftKB)	Eval Method	Comment		"C" cmt. c
399 9 549 9	%		×.	 Cement Plug; Cement Plug; 				Ce	ement					180 sx t		
649 9 .				8 5/8; Product Wellbore; 11;	tion; Ca	sing; 13.0-	1,391.0	J. Pr	scription oduction			Btm (ftKB) 1,391.0	Eval Method			. LW + 30
1,200.1 - 1,344.2 -			×					Ca	asing Cen	nent				150 sx t		omt. Circ
1,391.1				Production Ca 1,391.0	Ũ)_	Pr	scription oduction		Top (ftKB) 13.0	8tm (ftK8) 30.0	Eval Method	Comment Spot 10 sks cmt to		
1,404.9 ·			<u></u>	-Cement Plug;	.1,200.0	0-1,405.0		Ca	asing Cen	nent	.			surface P&A)	(Requ	uired for
1,494.1	²		 		<u> </u>				scription ner Ceme	nt	Top (ftKB) 13.0	Btm (ftKB) 3,810.0	Eval Method			. LW+850
1,858.9				5 1/2; Liner; C -Fish; 1,405.0-	3,592.0	; 2 7/8								sx. Clas 120 sx t		omt. Circ
2,896.2	č			Wellbore; 7 7	/8; 1,440	0.0-3,810.0)		scription ement Plu	ıg	Top (ftKB) 1,200.0	Btm (ftKB) 1,405.0	Eval Method			mt @ 140
3,036.1 - 3,037.1 -			 					De	scription		Top (ftKB)	Btm (ftKB)	Eval Method	1200' (ta Comment	ag TO	IC)
3,070 9 -			 1					-	ement Plu	g	400.0			400' (tag		mt @ 650 2)
3,071.9 - 3,092.8 - 3,094.2 -					•'				scription ement Plu	9	Top (ftKB) 160.0	Btm (ftKB) 400.0	Eval Method	Comment Spot 25 160' (tag		mt @ 400))
3,183.1 3,184.1 -			 →				,		scription ement Plu	g	Тор (ftKB) 13.0	Btm (ftKB) 110.0	Eval Method	Comment Spot 20 to surface		mt @ 110
3,185 0								Other In Hole								
3,207.0 · 3,208.0								- i	sh				3/15/2011	Tubing,	rods a	and pump ag fish @
3,2090 -														1405'.		• •
3,213 9 3,219 2					•				ormation:	3	Final Top		Comment			J. 4
3,2201			-						ALT mation		550.0 Final Top	1,344.0 Final Btm	Comment			
3,221.1 3,248.0			- -					Fo	ATES		1,494.0 Final Top	1,859.0 Final Btm	Comment	•		
3,251.0									EVEN RIN	/ERS	1,859.0 Final Top	2,492.0 Final Btm	Comment			
3,258.9 · 3,310 0 ·	Ň					•		- Fo	UEEN mation		2,492.0 Final Top		Comment			
3,347.1			F					Fo	RAYBUR		2,886.0 Final Top	3,310.0 Final Btm	Comment			
3,349.1 3,351.0			- -					S/	AN ANDR	ES	3,310.0					
3,353.0 ·			 -													
3,532.2 - 3,536.1 ·			- -													
3,537.1			-							•						
3,538.1 · 3,539.0			 -													
3,540.0 -			F													
3,591 9 · ·	~~~~~				- 19:0 C											
3,810.0			. <i>Î</i>	Liner Cement Wellbore; 3,8		,01U.U			•							
	peloton.com						Page 1	/1					Re	port Prin	ited [,]	2/19/201

.