

NM OIL CONSERVATION

ARTESIA DISTRICT

Form 3160-4
(August 2007)UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENTAUG 3 2015
OCD ArtesiaFORM APPROVED
OMB No. 1004-0137
Expires: July 31, 2010

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

RECEIVED

5. Lease Serial No.
NMNM113943

6. If Indian, Allottee or Tribe Name

7. Unit or CA Agreement Name and No.

8. Lease Name and Well No.
SKEEN 23 26 26 FEDERAL 6H9. API Well No.
30-015-4288310. Field and Pool, or Exploratory
WELCH; BONE SPRING11. Sec., T., R., M., or Block and Survey
or Area Sec 23 T26S R26E Mer NMP12. County or Parish
EDDY13. State
NM17. Elevations (DF, KB, RT, GL)*
3431 GL1a. Type of Well ☒ Oil Well ☐ Gas Well ☐ Dry ☐ Other
b. Type of Completion ☒ New Well ☐ Work Over ☐ Deepen ☐ Plug Back ☐ Diff. Resvr.
Other2. Name of Operator
CHEVRON U.S.A. INC. Contact: BRITANY CORTEZ
E-Mail: bcortez@chevron.com3. Address 15 SMITH ROAD
MIDLAND, TX 797053a. Phone No. (include area code)
Ph: 432-687-7415

4. Location of Well (Report location clearly and in accordance with Federal requirements)*

At surface 330FSL 660 FWL

At top prod interval reported below 503FNL 636FWL

At total depth 503FNL 636FWL

14. Date Spudded
03/22/201515. Date T.D. Reached
04/12/201516. Date Completed
☐ D & A ☒ Ready to Prod.
05/10/201518. Total Depth: MD
TVD 1212219. Plug Back T.D.: MD
TVD 1190520. Depth Bridge Plug Set: MD
TVD21. Type Electric & Other Mechanical Logs Run (Submit copy of each)
CCL22. Was well cored? ☒ No ☐ Yes (Submit analysis)
Was DST run? ☒ No ☐ Yes (Submit analysis)
Directional Survey? ☐ No ☒ Yes (Submit analysis)

23. Casing and Liner Record (Report all strings set in well)

Hole Size	Size/Grade	Wt. (#/ft.)	Top (MD)	Bottom (MD)	Stage Cementer Depth	No. of Sk. & Type of Cement	Slurry Vol. (BBL)	Cement Top*	Amount Pulled
17.500	13.375 H40	48.0		382		490		0	
12.250	9.625 HCK55	40.0		1915		760		0	
8.750	5.500 HCP110	17.0		12093		1950		647	

24. Tubing Record

Size	Depth Set (MD)	Packer Depth (MD)	Size	Depth Set (MD)	Packer Depth (MD)	Size	Depth Set (MD)	Packer Depth (MD)
2.875	6661	6668						

25. Producing Intervals

26. Perforation Record

Formation	Top	Bottom	Perforated Interval	Size	No. Holes	Perf. Status
A) BONE SPRING	7700	11835	7700 TO 11835			SEE WBD
B)						
C)						
D)						

27. Acid, Fracture, Treatment, Cement Squeeze, Etc.

Depth Interval	Amount and Type of Material
7700 TO 11835	CLEAN VOLUME: 2,162,161 GALS; TOTAL PROP: 4,188,835 LBS

28. Production - Interval A

Date First Produced	Test Date	Hours Tested	Test Production	Oil BBL	Gas MCF	Water BBL	Oil Gravity Corr. API	Gas Gravity	Production Method
05/29/2015	06/01/2015	24	→	36.0	44.0	1464.0			FLOWERS FROM WELL
Choke Size	Tbg. Press. Flwg.	Csg. Press.	24 Hr. Rate	Oil BBL	Gas MCF	Water BBL	Gas Oil Ratio	Well Status	
48/64	SI 225	0.0	→	36	44	1464		POW	

28a. Production - Interval B

Date First Produced	Test Date	Hours Tested	Test Production	Oil BBL	Gas MCF	Water BBL	Oil Gravity Corr. API	Gas Gravity	Production Method
			→						
Choke Size	Tbg. Press. Flwg.	Csg. Press.	24 Hr. Rate	Oil BBL	Gas MCF	Water BBL	Gas Oil Ratio	Well Status	
	SI		→						


(See Instructions and spaces for additional data on reverse side)

ELECTRONIC SUBMISSION #306808 VERIFIED BY THE BLM WELL INFORMATION SYSTEM

** OPERATOR-SUBMITTED ** OPERATOR-SUBMITTED ** OPERATOR-SUBMITTED **

Reclamation

Date: 12/1/15



AB

28b. Production - Interval C

Date First Produced	Test Date	Hours Tested	Test Production →	Oil BBL	Gas MCF	Water BBL	Oil Gravity Corr. API	Gas Gravity	Production Method
Choke Size	Tbg. Press. Flwg. SI	Csg. Press	24 Hr. Rate →	Oil BBL	Gas MCF	Water BBL	Gas Oil Ratio	Well Status	

28c. Production - Interval D

Date First Produced	Test Date	Hours Tested	Test Production →	Oil BBL	Gas MCF	Water BBL	Oil Gravity Corr. API	Gas Gravity	Production Method
Choke Size	Tbg. Press. Flwg. SI	Csg. Press	24 Hr. Rate →	Oil BBL	Gas MCF	Water BBL	Gas Oil Ratio	Well Status	

29. Disposition of Gas(Sold, used for fuel, vented, etc.)
SOLD

30. Summary of Porous Zones (Include Aquifers):

Show all important zones of porosity and contents thereof: Cored intervals and all drill-stem tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures and recoveries.

31. Formation (Log) Markers

Formation	Top	Bottom	Descriptions, Contents, etc.	Name	Top Meas. Depth
CHERRY CANYON	2832	4013	SANDSTONE		
BRUSHY CANYON	4014	5515	SANDSTONE		
BONE SPRING LIME	5516	6428	LIMESTONE		
1ST BONE SPRING SAND	6429	7125	SANDSTONE		
2ND BONE SPRING SAND	7126		SANDSTONE		

32. Additional remarks (include plugging procedure):

33. Circle enclosed attachments:

1. Electrical/Mechanical Logs (1 full set req'd.) 2. Geologic Report 3. DST Report 4. Directional Survey
5. Sundry Notice for plugging and cement verification 6. Core Analysis 7. Other:

34. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records (see attached instructions):

Electronic Submission #306808 Verified by the BLM Well Information System.
For CHEVRON U.S.A. INC., sent to the Carlsbad
Committed to AFMSS for processing by DEBORAH HAM on 07/10/2015 ()

Name (please print) BRITANY CORTEZ

Title REGULATORY SPECIALIST

Signature (Electronic Submission)

Date 06/25/2015

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

**** ORIGINAL ** ORIGINAL ** ORIGINAL ** ORIGINAL ** ORIGINAL ** ORIGINAL ** ORIGINAL ****

PathFinder -- a Schlumberger company

Survey Report

CHEVRON USA INC.
SKEEN 23 26 26 FEDERAL #6H
EDDY COUNTY, NM
API#: 30-015-42883 Rig: Nabors M51
PathFinder Office Supervisor: Qun Xu
PathFinder Field Engineers: T.Cramer
S.Amador

Survey Horiz. Reference: WELLHEAD
Ref Coordinates: LAT:32.17.1724 N LON:104.16.10.0884 W
GRID Reference: NAD27 new mexico east Transverse Mercator
Ref GRID Coord. X: 519793.0000 Y: 371531.0000
North Aligned To: GRID NORTH
Total Magnetic Correction: 7.57° EAST TO GRID
Vertical Section Plane: 0.05
Survey Vert. Reference: 22.00' Rotary Table To Ground
Altitude: 3431.00' Ground To MSL

Survey Calculations by RX4 using Minimum Curvature

Measured Depth (ft)	Incl (deg)	Drift Dir. (deg)	TVD (ft)	Course Length (ft)	Vertical Section (ft)	Rectangular Offsets (ft)	TOTAL (ft)	Closure Dist Dir (ft) (deg)	DLS (dg/100ft)
ORIGIN OF WELL AT SURFACE.									
THE FOLLOWING ARE PATHFINDER MWD SURVEYS.									
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00@ 0.00	0.00
427.00	3.08	193.04	426.79	427.00	-11.18	11.18 S	2.59 W	11.47@ 193.04	0.72
522.00	2.20	192.39	521.69	95.00	-15.45	15.45 S	3.56 W	15.85@ 192.97	0.93
609.00	1.67	186.95	608.64	87.00	-18.34	18.34 S	4.07 W	18.78@ 192.51	0.64
702.00	1.67	187.86	701.60	93.00	-21.03	21.02 S	4.42 W	21.48@ 191.87	0.03
795.00	1.67	188.92	794.56	93.00	-23.71	23.70 S	4.81 W	24.19@ 191.48	0.03
889.00	0.88	197.36	888.54	94.00	-25.75	25.75 S	5.24 W	26.27@ 191.50	0.86
980.00	0.70	199.58	979.53	91.00	-26.94	26.94 S	5.64 W	27.52@ 191.82	0.20
1079.00	0.79	204.24	1078.52	99.00	-28.13	28.13 S	6.12 W	28.79@ 192.27	0.11
1171.00	0.79	200.50	1170.51	92.00	-29.31	29.30 S	6.60 W	30.04@ 192.69	0.06
1266.00	0.79	162.02	1265.51	95.00	-30.54	30.54 S	6.63 W	31.25@ 192.25	0.55
1362.00	1.06	128.49	1361.49	96.00	-31.72	31.72 S	5.73 W	32.23@ 190.24	0.62
1457.00	1.14	127.27	1456.48	95.00	-32.84	32.84 S	4.29 W	33.12@ 187.44	0.09
1552.00	1.93	115.25	1551.44	95.00	-34.10	34.09 S	2.09 W	34.16@ 183.51	0.89
1647.00	2.81	104.61	1646.36	95.00	-35.36	35.36 S	1.61 E	35.40@ 177.39	1.03
1743.00	2.64	102.89	1742.25	96.00	-36.44	36.45 S	6.04 E	36.95@ 170.59	0.20
1838.00	2.46	103.35	1837.16	95.00	-37.40	37.41 S	10.16 E	38.76@ 164.81	0.19
1941.00	2.02	102.63	1940.08	103.00	-38.30	38.32 S	14.08 E	40.82@ 159.82	0.43
2036.00	1.76	95.92	2035.03	95.00	-38.82	38.83 S	17.17 E	42.46@ 156.15	0.36
2227.00	1.76	90.59	2225.94	191.00	-39.15	39.17 S	23.02 E	45.43@ 149.56	0.09
2418.00	1.41	318.53	2416.90	191.00	-37.41	37.43 S	24.39 E	44.68@ 146.91	1.52
2608.00	1.41	318.76	2606.85	190.00	-33.91	33.93 S	21.30 E	40.06@ 147.87	0.00
2799.00	1.41	312.69	2797.79	191.00	-30.55	30.56 S	18.03 E	35.49@ 149.47	0.08
2990.00	1.41	304.34	2988.73	191.00	-27.63	27.65 S	14.36 E	31.15@ 152.55	0.11

PathFinder – a Schlumberger company

Survey Report

CHEVRON USA INC.
SKEEN 23 26 26 FEDERAL #6H
EDDY COUNTY, NM
API#: 30-015-42883 Rig: Nabors M51

Page 02/05

Measured Depth (ft)	Incl (deg)	Drift Dir. (deg)	TVD (ft)	Course Length (ft)	Vertical Section (ft)	TOTAL Rectangular Offsets (ft)	Closure Dist Dir (ft) (deg)	DLS (dg/100ft)
3181.00	1.32	305.31	3179.68	191.00	-25.04	25.05 S 10.63 E	27.21@ 157.01	0.05
3371.00	1.32	299.88	3369.63	190.00	-22.69	22.69 S 6.94 E	23.73@ 162.99	0.07
3562.00	1.41	293.85	3560.57	191.00	-20.64	20.65 S 2.89 E	20.85@ 172.05	0.09
3752.00	1.41	295.94	3750.51	190.00	-18.68	18.68 S 1.36 W	18.73@ 184.15	0.03
3943.00	1.32	282.12	3941.46	191.00	-17.19	17.19 S 5.62 W	18.08@ 198.10	0.18
4133.00	1.06	287.64	4131.42	190.00	-16.21	16.20 S 9.43 W	18.74@ 210.22	0.15
4324.00	1.85	348.42	4322.37	191.00	-12.65	12.64 S 11.74 W	17.25@ 222.87	0.85
4514.00	1.67	353.29	4512.28	190.00	-6.90	6.89 S 12.68 W	14.43@ 241.48	0.12
4705.00	1.58	350.52	4703.20	191.00	-1.54	1.53 S 13.43 W	13.52@ 263.52	0.06
4895.00	1.41	352.92	4893.13	190.00	3.36	3.38 N 14.15 W	14.55@ 283.42	0.10
4991.00	0.88	184.32	4989.13	96.00	3.80	3.81 N 14.36 W	14.85@ 284.88	2.38
5086.00	5.35	170.76	5083.96	95.00	-1.30	1.29 S 13.70 W	13.76@ 264.63	4.74
5182.00	6.41	165.30	5179.46	96.00	-10.90	10.89 S 11.62 W	15.92@ 226.86	1.25
5277.00	6.23	171.20	5273.88	95.00	-21.12	21.11 S 9.49 W	23.15@ 204.19	0.71
5373.00	5.74	167.60	5369.36	96.00	-30.96	30.95 S 7.66 W	31.88@ 193.90	0.64
5468.00	5.52	173.41	5463.90	95.00	-40.13	40.13 S 6.11 W	40.59@ 188.66	0.64
5563.00	5.63	174.43	5558.45	95.00	-49.31	49.30 S 5.14 W	49.57@ 185.95	0.16
5754.00	4.46	171.54	5748.71	191.00	-65.98	65.98 S 3.13 W	66.05@ 182.72	0.63
5849.00	3.78	174.24	5843.46	95.00	-72.75	72.74 S 2.28 W	72.78@ 181.79	0.74
6040.00	4.56	174.61	6033.96	191.00	-86.57	86.57 S 0.93 W	86.57@ 180.62	0.41
6230.00	3.78	170.48	6223.45	190.00	-100.26	100.26 S 0.81 E	100.27@ 179.54	0.44
6326.00	3.43	173.27	6319.26	96.00	-106.24	106.24 S 1.67 E	106.25@ 179.10	0.41
6516.00	6.01	175.10	6508.60	190.00	-121.79	121.79 S 3.19 E	121.84@ 178.50	1.36
6612.00	5.04	177.99	6604.15	96.00	-131.01	131.02 S 3.77 E	131.07@ 178.35	1.05
6675.00	4.84	174.47	6666.92	63.00	-136.42	136.43 S 4.12 E	136.49@ 178.27	0.58
6703.00	4.66	174.36	6694.82	28.00	-138.73	138.74 S 4.35 E	138.80@ 178.21	0.64
6735.00	2.90	166.93	6726.75	32.00	-140.81	140.82 S 4.66 E	140.89@ 178.11	5.70
6767.00	1.58	22.27	6758.74	32.00	-141.19	141.20 S 5.01 E	141.29@ 177.97	13.40

PathFinder -- a Schlumberger company

Survey Report

CHEVRON USA INC.
SKEEN 23 26 26 FEDERAL #6H
EDDY COUNTY, NM
API#: 30-015-42883 Rig: Nabors M51

Page 03/05

Measured Depth (ft)	Incl (deg)	Drift Dir. (deg)	TVD (ft)	Course Length (ft)	Vertical Section (ft)	TOTAL Rectangular Offsets (ft)	Closure Dist Dir (ft) (deg)	DLS (dg/100ft)
6798.00	5.89	6.59	6789.67	31.00	-139.22	139.22 S	139.32@ 177.80	14.16
6830.00	10.55	1.57	6821.33	32.00	-134.65	134.66 S	134.78@ 177.61	14.72
6862.00	14.07	0.39	6852.59	32.00	-127.83	127.84 S	127.97@ 177.43	11.03
6894.00	16.53	1.90	6883.46	32.00	-119.39	119.40 S	119.54@ 177.17	7.79
6926.00	19.35	1.60	6913.90	32.00	-109.54	109.55 S	109.72@ 176.76	8.82
6957.00	22.34	0.41	6942.86	31.00	-98.51	98.52 S	98.73@ 176.29	9.74
6989.00	24.45	358.41	6972.23	32.00	-85.81	85.82 S	86.04@ 175.84	7.04
7021.00	25.94	357.73	7001.19	32.00	-72.20	72.20 S	72.43@ 175.42	4.74
7053.00	28.05	358.37	7029.70	32.00	-57.68	57.69 S	57.93@ 174.75	6.66
7085.00	29.63	358.24	7057.73	32.00	-42.25	42.26 S	42.53@ 173.47	4.94
7117.00	30.25	358.60	7085.46	32.00	-26.29	26.29 S	26.66@ 170.50	2.02
7148.00	31.48	358.62	7112.07	31.00	-10.39	10.39 S	11.14@ 158.89	3.97
7180.00	33.41	359.14	7139.07	32.00	6.77	6.77 N	7.70@ 28.54	6.09
7212.00	36.67	0.02	7165.27	32.00	25.14	25.14 N	25.39@ 8.04	10.31
7243.00	39.31	0.16	7189.70	31.00	44.22	44.22 N	44.36@ 4.63	8.52
7275.00	41.94	0.55	7213.98	32.00	65.05	65.05 N	65.16@ 3.27	8.26
7307.00	45.11	1.63	7237.18	32.00	87.08	87.08 N	87.18@ 2.72	10.17
7339.00	48.98	2.49	7258.99	32.00	110.49	110.48 N	110.59@ 2.58	12.25
7370.00	52.14	2.49	7278.68	31.00	134.40	134.40 N	134.53@ 2.57	10.19
7402.00	56.01	2.51	7297.45	32.00	160.29	160.28 N	160.44@ 2.56	12.09
7434.00	59.97	2.53	7314.41	32.00	187.39	187.38 N	187.57@ 2.55	12.37
7466.00	63.93	2.11	7329.45	32.00	215.60	215.59 N	215.80@ 2.52	12.43
7497.00	68.24	0.83	7342.02	31.00	243.93	243.92 N	244.13@ 2.40	14.41
7529.00	72.63	0.54	7352.73	32.00	274.07	274.06 N	274.26@ 2.21	13.75
7561.00	76.59	0.57	7361.22	32.00	304.91	304.90 N	305.10@ 2.04	12.37
7592.00	81.16	0.49	7367.20	31.00	335.32	335.31 N	335.50@ 1.90	14.74
7624.00	85.56	0.48	7370.90	32.00	367.10	367.09 N	367.27@ 1.78	13.75
7656.00	89.60	358.99	7372.25	32.00	399.06	399.05 N	399.21@ 1.62	13.45

PathFinder -- a Schlumberger company

Survey Report

CHEVRON USA INC.
SKEEN 23 26 26 FEDERAL #6H
EDDY COUNTY, NM
API#: 30-015-42883

Rig: Nabors M51

Page 04/05

Measured Depth (ft)	Incl (deg)	Drift Dir. (deg)	TVD (ft)	Course Length (ft)	Vertical Section (ft)	TOTAL Rectangular Offsets (ft)	Closure Dist Dir (ft) (deg)	DLS (dg/100ft)
7752.00	92.95	358.31	7370.11	96.00	495.00	9.01 E	495.07@ 1.04	3.56
7847.00	89.96	357.36	7367.70	95.00	589.88	5.42 E	589.90@ 0.53	3.30
7942.00	91.63	357.25	7366.38	95.00	684.76	0.96 E	684.76@ 0.08	1.76
8037.00	91.54	358.85	7363.76	95.00	779.66	2.27 W	779.67@ 359.83	1.69
8132.00	91.28	358.91	7361.42	95.00	874.61	4.13 W	874.63@ 359.73	0.28
8228.00	91.63	358.46	7358.98	96.00	970.56	6.33 W	970.58@ 359.63	0.59
8323.00	91.19	358.35	7356.64	95.00	1065.49	1065.50 N	1065.53@ 359.52	0.48
8418.00	91.89	358.81	7354.09	95.00	1160.42	1160.43 N	1160.49@ 359.44	0.88
8513.00	87.85	0.63	7354.31	95.00	1255.40	1255.41 N	1255.46@ 359.46	4.66
8608.00	89.34	1.35	7356.63	95.00	1350.35	1350.36 N	1350.40@ 359.57	1.74
8704.00	89.34	0.45	7357.74	96.00	1446.33	1446.34 N	1446.37@ 359.66	0.94
8799.00	88.99	359.84	7359.13	95.00	1541.32	1541.33 N	1541.35@ 359.69	0.74
8894.00	90.66	359.33	7359.42	95.00	1636.32	1636.32 N	1636.35@ 359.68	1.84
8989.00	88.64	358.87	7360.00	95.00	1731.30	1731.31 N	1731.34@ 359.65	2.18
9084.00	91.01	359.11	7360.29	95.00	1826.27	1826.28 N	1826.32@ 359.62	2.51
9179.00	90.04	0.85	7359.42	95.00	1921.26	1921.28 N	1921.31@ 359.63	2.10
9274.00	92.07	0.70	7357.67	95.00	2016.23	2016.24 N	2016.27@ 359.69	2.14
9370.00	90.13	1.96	7355.82	96.00	2112.19	2112.20 N	2112.21@ 359.76	2.41
9465.00	89.87	2.50	7355.82	95.00	2207.12	2207.12 N	2207.13@ 359.87	0.63
9560.00	89.60	3.25	7356.26	95.00	2302.00	2302.00 N	2302.00@ 359.99	0.84
9655.00	89.78	1.84	7356.78	95.00	2396.91	2396.90 N	2396.91@ 0.09	1.50
9751.00	88.90	0.70	7357.88	96.00	2492.88	2492.87 N	2492.88@ 0.14	1.50
9846.00	88.81	0.70	7359.78	95.00	2587.85	2587.85 N	2587.86@ 0.16	0.09
9941.00	88.37	0.79	7362.12	95.00	2682.81	2682.81 N	2682.82@ 0.18	0.47
10036.00	88.46	0.25	7364.75	95.00	2777.77	2777.77 N	2777.78@ 0.19	0.58
10131.00	88.64	0.40	7367.15	95.00	2872.74	2872.74 N	2872.75@ 0.20	0.25
10227.00	86.35	0.18	7371.35	96.00	2968.64	2968.64 N	2968.65@ 0.20	2.40
10322.00	88.11	359.81	7375.94	95.00	3063.53	3063.52 N	3063.54@ 0.19	1.89

PathFinder – a Schlumberger company

Survey Report

CHEVRON USA INC.
SKEEN 23 26 26 FEDERAL #6H
EDDY COUNTY, NM
API#: 30-015-42883 Rig: Nabors M51


Page 05/05

Measured Depth (ft)	Incl (deg)	Drift Dir. (deg)	TVD (ft)	Course Length (ft)	Vertical Section (ft)	Rectangular Offsets (ft)	TOTAL (ft)	Closure Dist Dir (ft) (deg)	DLS (dg/100ft)
10417.00	89.87	359.67	7377.61	95.00	3158.51	3158.50 N	9.87 E	3158.52@ 0.18	1.86
10513.00	86.88	359.77	7380.33	96.00	3254.46	3254.45 N	9.40 E	3254.46@ 0.17	3.12
10608.00	89.78	359.48	7383.10	95.00	3349.40	3349.40 N	8.78 E	3349.41@ 0.15	3.07
10703.00	90.13	359.23	7383.18	95.00	3444.40	3444.39 N	7.71 E	3444.40@ 0.13	0.45
10798.00	90.48	359.71	7382.67	95.00	3539.39	3539.39 N	6.83 E	3539.39@ 0.11	0.63
10894.00	90.31	359.84	7382.01	96.00	3635.39	3635.38 N	6.45 E	3635.39@ 0.10	0.22
10989.00	89.96	359.48	7381.78	95.00	3730.38	3730.38 N	5.89 E	3730.39@ 0.09	0.53
11084.00	89.25	359.78	7382.44	95.00	3825.38	3825.38 N	5.28 E	3825.38@ 0.08	0.81
11179.00	88.55	359.11	7384.26	95.00	3920.36	3920.35 N	4.36 E	3920.36@ 0.06	1.02
11274.00	90.75	358.85	7384.84	95.00	4015.33	4015.33 N	2.66 E	4015.33@ 0.04	2.33
11370.00	88.81	358.62	7385.21	96.00	4111.30	4111.30 N	0.55 E	4111.30@ 0.01	2.03
11465.00	89.16	358.72	7386.89	95.00	4206.26	4206.26 N	1.66 W	4206.26@ 359.98	0.38
11560.00	89.34	357.68	7388.14	95.00	4301.20	4301.20 N	4.64 W	4301.21@ 359.94	1.11
11655.00	89.87	358.04	7388.79	95.00	4396.13	4396.14 N	8.19 W	4396.14@ 359.89	0.67
11750.00	89.25	356.45	7389.52	95.00	4491.01	4491.02 N	12.76 W	4491.04@ 359.84	1.80
11845.00	89.87	357.47	7390.25	95.00	4585.86	4585.88 N	17.79 W	4585.92@ 359.78	1.26
11940.00	89.78	358.95	7390.54	95.00	4680.81	4680.83 N	20.76 W	4680.88@ 359.75	1.56
12036.00	91.89	357.68	7389.14	96.00	4776.75	4776.77 N	23.58 W	4776.83@ 359.72	2.57



Wellbore Schematic

Well Name SKEEN 23-26-26 FED 006H	Lease Skeen 22-26-26 Fed	Field Name Delaware River	Business Unit Mid-Continent
--------------------------------------	-----------------------------	------------------------------	--------------------------------



Job Details						
Job Category			Start Date		Rig/Unit End Date	
Completion			4/23/2015		5/20/2015	
Completion			5/26/2015		5/28/2015	
Completion			6/22/2015			
Casing Strings						
Csg Des	OD (in)	Wt/Len (lb/ft)	Grade	Top Thread	Set Depth (MD) (ftKB)	
Conductor	20	94.00	H-40		80	
Surface	13 3/8	48.00	H-40	ST&C	382	
Intermediate Casing 1	9 5/8	40.00	HCK55	LTC	1,915	
Production Casing	5 1/2	17.00	HCP-110	CDC	12,093	
Tubing Strings						
Versa Set packer set at 6,682.4ftKB on 5/23/2014 17:30						
Tubing Description			Run Date	String Length (ft)	Set Depth (MD) (ftKB)	
Versa Set packer			5/23/2014	21.39	6,682.4	
Item Des	Jts	OD (in)	Wt (lb/ft)	Grade	Len (ft)	Btm (ftKB)
Packer	1	4.61			8.35	6,669.4
Tubing	1	2 7/8	6.50	L-80	6.28	6,675.6
XN - Nipple	1	3.28			1.73	6,677.4
Tubing	1	2 7/8	6.50	L-80	4.28	6,681.6
Wireline Guide	1	3.7			0.75	6,682.4
Tubing - Production set at 6,661.0ftKB on 5/27/2015 12:00						
Tubing Description			Run Date	String Length (ft)	Set Depth (MD) (ftKB)	
Tubing - Production			5/27/2015	6,639.18	6,661.0	
Item Des	Jts	OD (in)	Wt (lb/ft)	Grade	Len (ft)	Btm (ftKB)
Tubing	1	2 7/8	6.50	L-80	32.68	54.5
Tubing Pup Joint	3	2 7/8	6.50	L-80	12.00	66.5
Tubing	49	2 7/8	6.50	L-80	1,600.04	1,666.5
Gas Lift Mandrel	1	2 7/8			4.10	1,670.6
Tubing	23	2 7/8	6.50	L-80	748.56	2,419.2
Gas Lift Mandrel	1	2 7/8			4.10	2,423.3
Tubing	19	2 7/8	6.50	L-80	619.80	3,043.1
Gas Lift Mandrel	1	2 7/8			4.10	3,047.2
Tubing	18	2 7/8	6.50	L-80	587.68	3,634.9
Gas Lift Mandrel	1	2 7/8			4.10	3,639.0
Tubing	18	2 7/8	6.50	L-80	587.71	4,226.7
Gas Lift Mandrel	1	2 7/8			4.10	4,230.8
Tubing	18	2 7/8	6.50	L-80	587.92	4,818.7
Gas Lift Mandrel	1	2 7/8			4.10	4,822.8
Tubing	19	2 7/8	6.50	L-80	618.04	5,440.9
Gas Lift Mandrel	1	2 7/8			4.10	5,445.0
Tubing	18	2 7/8	6.50	L-80	585.09	6,030.0
Gas Lift Mandrel	1	2 7/8			4.10	6,034.1
Tubing	18	2 7/8	6.50	L-80	587.84	6,622.0
Gas Lift Mandrel	1	2 7/8			4.10	6,626.1
Tubing	1	2 7/8	6.50	L-80	32.72	6,658.8
On-Off Tool	1	2 7/8			2.20	6,661.0
Perforations						
Date	Top (ftKB)	Btm (ftKB)	Shot Dens (shots/ft)	Entered Shot Total	Zone & Completion	
5/10/2015	7,700.0	7,702.0	6.0	12	2n bone springs, Original Hole	
5/10/2015	7,760.0	7,762.0	6.0	12	2n bone springs, Original Hole	
5/10/2015	7,835.0	7,837.0	6.0	12	2n bone springs, Original Hole	
5/10/2015	7,924.0	7,926.0	6.0	12	2n bone springs, Original Hole	
5/10/2015	7,991.0	7,993.0	6.0	12	2n bone springs, Original Hole	
5/10/2015	8,058.0	8,060.0	6.0	12	2n bone springs, Original Hole	
5/10/2015	8,125.0	8,127.0	6.0	12	2n bone springs, Original Hole	
5/10/2015	8,192.0	8,194.0	6.0	12	2n bone springs, Original Hole	

