

Submit 1 Copy To Appropriate District Office  
 District I - (575) 393-6161  
 1625 N. French Dr., Hobbs, NM 88240  
 District II - (575) 748-1283  
 811 S. First St., Artesia, NM 88210  
 District III - (505) 334-6178  
 1000 Rio Brazos Rd., Aztec, NM 87410  
 District IV - (505) 476-3460  
 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
 Energy, Minerals and Natural Resources

Form C-103  
 Revised August 1, 2011

OIL CONSERVATION DIVISION  
 1220 South St. Francis Dr.  
 Santa Fe, NM 87505

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-015-03553
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>		5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
2. Name of Operator <b>WS OIL AND GAS OPERATING. LLC</b>		6. State Oil & Gas Lease No. B-7950
3. Address of Operator <b>PO BOX 5375, Midland, TX 79704</b>		7. Lease Name or Unit Agreement Name: TURKEY TRACK SEC 3 UNIT
4. Well Location Unit Letter K : 2310 feet from the S line and 2310 feet from the W line Section 3 Township 19S Range 29E NMPM County EDDY		8. Well Number 013
9. OGRID Number <b>370922</b>		10. Pool name or Wildcat Turkey Track 7 RVRs QU GB SA
11. Elevation (Show whether DR, RKB, RT, GR, etc.)		

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

<b>NOTICE OF INTENTION TO:</b> PERFORM REMEDIAL WORK <input type="checkbox"/> PLUG AND ABANDON <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> MULTIPLE COMPL <input type="checkbox"/> DOWNHOLE COMMINGLE <input type="checkbox"/>  OTHER: <input type="checkbox"/>		<b>SUBSEQUENT REPORT OF:</b> REMEDIAL WORK <input type="checkbox"/> ALTERING CASING <input type="checkbox"/> COMMENCE DRILLING OPNS. <input type="checkbox"/> P AND A <input type="checkbox"/> CASING/CEMENT JOB <input type="checkbox"/>  OTHER: RETURN TO PRODUCTION <input checked="" type="checkbox"/>	
---	--	---	--

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

SEE ATTACHED

**NM OIL CONSERVATION**  
 ARTESIA DISTRICT  
 JAN 19 2016  
 RECEIVED

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Carie Stoker TITLE Regulatory Affairs Coordinator DATE: 1/13/2016

Type or print name Carie Stoker E-mail address: carie@stokeroilfield.com PHONE: 432.664.7659

APPROVED BY: R Wade TITLE Dist Engineer DATE 1/20/2016  
 Conditions of Approval (if any):

12/11/15

MIRU. UNHANG WELL, UNSEATED PUMP AND POOH WITH PUMP AND RODS. RD WELLHEAD. NU BOP. PU 3 JOINTS AND TAGGED FILL. POOH LAYING DOWN TUBING. SWISDOWE.

NOTE: TAGGED FILL @ 3123.51'

12/14/15

OFF LOADED 101 JTS 2-3/8" EUE 8RD BLUE BAND TUBING AND TALLY. PU 3-7/8" BIT, 4-1/2" CASING SCRAPER ON 2-3/8" TUBING, SCRAPER WORKING FROM 2650' DOWN TO 3042'. TUBING TAKING WEIGHT AND TRYING TO STICK @ 3072'. MIRU DOUBLE R KILL TRUCK, INSTALL TUBING SWIVEL AND BROKE CIRCULATION WITH 68 BBLS FW. CIRCULATED AND ROTATED BIT AND SCRAPER TO 3158'. CIRCULATED 30 MINS FOR CLEAN UP. RD KILL TRUCK AND SWIVEL. RELEASED VAC TRUCK. POOH WITH BIT AND SCRAPER. PU 2-3/8" SEATING NIPPLE AND 97 JOINTS OF 2-3/8" TUBING. LAND EOT @ 3052'. ND BOP. NU WELLHEAD. PREP FOR RODS. SWISDON.

TUBING INSTALLATION:

KB	6.00'	6.00'
97 JTS 2-3/8" GOOD BLUE BAND EUE 8RD TBG.	3045.71'	3051.71'
2-3/8" STANDARD SEATING NIPPLE	1.10'	3052.81'

NOTE: RUN PUMP AND RODS TOMORROW AM.

NOTE: CIRCULATED WELL 4 BPM @ 250 PSI. RETURNS WERE 50%. PUMPED 200 BBLS FW.

12/15/15

RIH WITH PUMP AND RODS. SPACED OUT RODS AND HWO. LOADED TUBING WITH 5 BBLS FW. PUMPED UP TO 500 PSI. RD PUMP TRUCK AND RIG. WELL PUMPING ON HAND TO BATTERY.

1-1/4" X 16.00' POLISH ROD WITH 1-1/2" LINER.	10.00'
2' X 3/4" PONY ROD.	2.00'
100 X 3/4" RODS	2500.00'
20 X 7/8" RODS	500.00'
2" X 1.5" X 10' RWBC PUMP	10.00'