

Submit 1 Copy To Appropriate District Office

District I - (575) 393-6161
1625 N. Freeway, Hobbs, NM 88240
District II - (575) 748-2255
811 S. First St., Artesia, NM 88210
District III - (505) 334-4178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources
OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103

Revised July 18, 2013

WELL API NO.
30-015-43723

5. Indicate Type of Lease
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name
PAUL 25 24S 28E RB

8. Well Number 225H

9. OGRID Number
228937

10. Pool name or Wildcat
PIERCE CROSSING; WOLFCAMP

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator
MATADOR PRODUCTION COMPANY

3. Address of Operator
5400 LBJ FREEWAY, STE. 1500, DALLAS, TX 75240

4. Well Location
Unit Letter D 359 feet from the NORTH line and 247 feet from the WEST line
Section 25 Township 24S Range 28E NMPM County EDDY6

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
2919' GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐
CLOSED-LOOP SYSTEM ☐
OTHER: CHANGE CSG_CMT PLAN ☒

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Please change casing and cement plan as per below;

FLUID TYPE	HOLE SZ	CSG SZ	CSG GRADE	CSG WT.	DEPTH SET	TOP CSG	TTL SX CEMENT	CLASS	EST TOC (CMT)	ADDITIONAL INFO FOR CSG/CMT PROGRAM (Optional)
FRESH WTR	17.5	13.375	J-55	54.50	605	0	500	C	0	
BRINE	12.25	9.625	J-55	40.00	2750	0	800	C	0	
CUT BRINE	8.75	7.625	P-110	29.70	9700	0	800	TXI/H	1650	Tapered String
CUT BRINE	8.75	7	P-110	29.00	10700	9700	800	TXI/H	1650	Tapered String
OIL-BASED MUD	6.125	5.5	P-110	20.00	9800	0	590	H	9500	Tapered String, 5.5" casing will not be run in OH
OIL-BASED MUD	6.125	4.5	P-110	13.50	15300	9800	590	H	9500	Tapered String

Spud Date:

PENDING

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Ava Monroe TITLE Sr. Engineering Technician DATE 06/13/2016

Type or print name Ava Monroe E-mail address: amonroe@matadorresources.com PHONE: 972-371-5218

For State Use Only:

APPROVED BY: [Signature] TITLE "Geologist" DATE 6/20/16

Conditions of Approval (if any):