



30-015-43419

Mewbourne Oil Company .

Eddy County, New Mexico

Section 12-24S-28E Journey 12 B2MP Fee 1H

Journey 12 B2MP Fee 1H

Original Hole

Design: Original Hole

Standard Survey Report

23 December, 2015

Provide signature page for survey





Stryker Directional Survey Report



Company:	Mewbourne Oil Company	Local Co-ordinate Reference:	Well Journey 12 B2MP Fee 1H
Project:	Eddy County, New Mexico	TVD Reference:	2975 + 27 @ 3002.0usft (Patterson #243)
Site:	Section 12-24S-28E Journey 12 B2MP Fee 1H	MD Reference:	2975 + 27 @ 3002.0usft (Patterson #243)
Well:	Journey 12 B2MP Fee 1H	North Reference:	Grid
Wellbore:	Original Hole	Survey Calculation Method:	Minimum Curvature
Design:	Original Hole	Database:	Stryker_EDM

Project	Eddy County, New Mexico		
Map System:	US State Plane 1927 (Exact solution)	System Datum:	Mean Sea Level
Geo Datum:	NAD 1927 (NADCON CONUS)		
Map Zone:	New Mexico East 3001		

Site	Section 12-24S-28E Journey 12 B2MP Fee 1H		
Site Position:	Northing:	446,119.80 usft	Latitude: 32° 13' 34.243 N
From: Map	Easting:	588,210.00 usft	Longitude: 104° 2' 53.081 W
Position Uncertainty: 0.0 usft	Slot Radius:	13-3/16 "	Grid Convergence: 0.15 °

Well	Journey 12 B2MP Fee 1H		
Well Position	+N/-S	0.0 usft	Northing: 446,119.80 usft
	+E/-W	0.0 usft	Easting: 588,210.00 usft
Position Uncertainty	0.0 usft	Wellhead Elevation:	27.0 usft
		Ground Level:	2,975.0 usft

Wellbore	Original Hole		
-----------------	---------------	--	--

Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)	Field Strength (nT)
	IGRF2015	12/2/2015	7.34	60.01	48,049

Design	Original Hole		
---------------	---------------	--	--

Audit Notes:				
Version: 1.0	Phase: ACTUAL	Tie On Depth:	0.0	

Vertical Section:	Depth From (TVD) (usft)	+N/-S (usft)	+E/-W (usft)	Direction (°)
	0.0	0.0	0.0	146.77

Survey Program		Date 12/23/2015		
From (usft)	To (usft)	Survey (Wellbore)	Tool Name	Description
100.0	7,576.0	Phoenix Gyro Survey (Original Hole)	SRG-GYRO-MS	surface readout gyro multishot
7,678.0	12,710.0	MWD Survey (Original Hole)	MWD	MWD v3:standard declination

Survey	Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
	0.0	0.00	0.00	0.0	0.0	0.0	0.0	0.00	0.00	0.00
	100.0	0.08	312.98	100.0	0.0	-0.1	-0.1	0.08	0.08	0.00
	200.0	0.38	149.28	200.0	-0.2	0.1	0.2	0.46	0.30	-163.70
	300.0	1.02	140.59	300.0	-1.2	0.8	1.4	0.65	0.64	-8.69
	400.0	1.78	155.00	400.0	-3.3	2.0	3.8	0.83	0.76	14.41
	500.0	1.53	134.44	499.9	-5.6	3.6	6.7	0.64	-0.25	-20.56
	600.0	2.11	132.37	599.9	-7.8	5.9	9.8	0.58	0.58	-2.07
	700.0	2.25	118.98	699.8	-10.0	9.0	13.3	0.53	0.14	-13.39
	800.0	1.99	111.39	799.7	-11.6	12.4	16.4	0.38	-0.26	-7.59
	900.0	1.93	123.00	899.7	-13.1	15.4	19.4	0.40	-0.06	11.61



Stryker Directional Survey Report



Company:	Mewbourne Oil Company .	Local Co-ordinate Reference:	Well Journey 12 B2MP Fee 1H
Project:	Eddy County, New Mexico	TVD Reference:	2975 + 27 @ 3002.0usft (Patterson #243)
Site:	Section 12-24S-28E Journey 12 B2MP Fee 1H	MD Reference:	2975 + 27 @ 3002.0usft (Patterson #243)
Well:	Journey 12 B2MP Fee 1H	North Reference:	Grid
Wellbore:	Original Hole	Survey Calculation Method:	Minimum Curvature
Design:	Original Hole	Database:	Stryker_EDM

Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
1,000.0	2.04	109.47	999.6	-14.6	18.5	22.3	0.48	0.11	-13.53
1,100.0	1.61	127.38	1,099.6	-16.1	21.3	25.1	0.71	-0.43	17.91
1,200.0	1.03	102.85	1,199.5	-17.1	23.3	27.1	0.80	-0.58	-24.53
1,300.0	1.13	122.39	1,299.5	-17.8	25.0	28.6	0.38	0.10	19.54
1,400.0	0.52	138.88	1,399.5	-18.7	26.1	30.0	0.65	-0.61	16.49
1,500.0	0.55	28.31	1,499.5	-18.6	26.6	30.2	0.88	0.03	-110.57
1,600.0	0.34	35.48	1,599.5	-18.0	27.0	29.8	0.22	-0.21	7.17
1,700.0	0.42	138.79	1,699.5	-18.0	27.4	30.1	0.60	0.08	103.31
1,800.0	0.55	264.37	1,799.5	-18.3	27.2	30.2	0.86	0.13	125.58
1,900.0	1.74	110.21	1,899.5	-18.9	28.2	31.2	2.25	1.19	-154.16
2,000.0	3.81	125.78	1,999.4	-21.4	32.3	35.6	2.18	2.07	15.57
2,100.0	3.81	135.10	2,099.1	-25.7	37.3	41.9	0.62	0.00	9.32
2,200.0	5.05	139.96	2,198.8	-31.4	42.5	49.5	1.29	1.24	4.86
2,300.0	6.64	130.36	2,298.3	-38.5	49.7	59.5	1.86	1.59	-9.60
2,400.0	7.14	124.38	2,397.6	-45.7	59.3	70.7	0.87	0.50	-5.98
2,500.0	6.26	121.56	2,496.9	-52.1	69.0	81.4	0.94	-0.88	-2.82
2,600.0	4.69	123.61	2,596.5	-57.2	77.1	90.1	1.58	-1.57	2.05
2,700.0	4.31	126.08	2,696.2	-61.7	83.5	97.4	0.43	-0.38	2.47
2,800.0	4.25	126.14	2,795.9	-66.1	89.6	104.4	0.06	-0.06	0.06
2,900.0	4.13	128.21	2,895.6	-70.5	95.4	111.3	0.19	-0.12	2.07
3,000.0	3.75	129.28	2,995.4	-74.8	100.7	117.8	0.39	-0.38	1.07
3,100.0	3.84	126.68	3,095.1	-78.9	106.0	124.1	0.19	0.09	-2.60
3,200.0	3.33	131.13	3,195.0	-82.8	110.8	130.0	0.58	-0.51	4.45
3,300.0	3.93	122.56	3,294.8	-86.5	115.9	135.9	0.81	0.60	-8.57
3,400.0	3.43	118.89	3,394.5	-89.8	121.4	141.7	0.55	-0.50	-3.67
3,500.0	2.26	124.14	3,494.4	-92.4	125.7	146.2	1.20	-1.17	5.25
3,600.0	2.01	121.92	3,594.4	-94.4	128.8	149.6	0.26	-0.25	-2.22
3,700.0	1.06	131.82	3,694.3	-96.0	131.0	152.0	0.98	-0.95	9.90
3,800.0	1.22	134.77	3,794.3	-97.3	132.4	154.0	0.17	0.16	2.95
3,900.0	1.12	140.27	3,894.3	-98.8	133.8	156.0	0.15	-0.10	5.50
4,000.0	1.18	107.97	3,994.3	-99.9	135.4	157.8	0.64	0.06	-32.30
4,100.0	1.04	127.19	4,094.2	-100.8	137.1	159.4	0.40	-0.14	19.22
4,200.0	0.75	142.05	4,194.2	-101.8	138.2	160.9	0.37	-0.29	14.86
4,300.0	0.81	140.39	4,294.2	-102.9	139.1	162.3	0.06	0.06	-1.66
4,400.0	0.14	132.33	4,394.2	-103.5	139.6	163.1	0.67	-0.67	-8.06
4,500.0	0.17	117.81	4,494.2	-103.7	139.8	163.4	0.05	0.03	-14.52
4,600.0	0.73	126.25	4,594.2	-104.1	140.5	164.1	0.56	0.56	8.44
4,700.0	0.23	116.46	4,694.2	-104.6	141.2	164.9	0.50	-0.50	-9.79
4,800.0	0.33	143.64	4,794.2	-104.9	141.5	165.3	0.16	0.10	27.18
4,900.0	0.65	134.39	4,894.2	-105.5	142.1	166.2	0.33	0.32	-9.25
5,000.0	0.90	207.00	4,994.2	-106.6	142.2	167.1	0.94	0.25	72.61
5,100.0	0.24	72.22	5,094.2	-107.3	142.0	167.5	1.08	-0.66	-134.78
5,200.0	0.33	6.35	5,194.2	-106.9	142.2	167.4	0.32	0.09	-65.87



Stryker Directional Survey Report



Company:	Mewbourne Oil Company	Local Co-ordinate Reference:	Well Journey 12 B2MP Fee 1H
Project:	Eddy County, New Mexico	TVD Reference:	2975 + 27 @ 3002.0usft (Patterson #243)
Site:	Section 12-24S-28E Journey 12 B2MP Fee 1H	MD Reference:	2975 + 27 @ 3002.0usft (Patterson #243)
Well:	Journey 12 B2MP Fee 1H	North Reference:	Grid
Wellbore:	Original Hole	Survey Calculation Method:	Minimum Curvature
Design:	Original Hole	Database:	Stryker_EDM

Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
5,300.0	0.87	200.33	5,294.2	-107.3	142.0	167.6	1.19	0.54	-166.02
5,400.0	0.98	202.33	5,394.2	-108.8	141.4	168.5	0.11	0.11	2.00
5,500.0	1.15	183.76	5,494.2	-110.6	141.0	169.8	0.38	0.17	-18.57
5,600.0	1.03	212.62	5,594.1	-112.4	140.5	171.0	0.56	-0.12	28.86
5,700.0	0.58	217.85	5,694.1	-113.6	139.7	171.5	0.46	-0.45	5.23
5,800.0	0.48	284.64	5,794.1	-113.8	139.0	171.4	0.59	-0.10	66.79
5,900.0	0.62	159.09	5,894.1	-114.2	138.7	171.6	0.98	0.14	-125.55
6,000.0	1.11	136.14	5,994.1	-115.5	139.6	173.1	0.59	0.49	-22.95
6,100.0	1.44	196.83	6,094.1	-117.4	139.9	174.8	1.32	0.33	60.69
6,200.0	1.06	186.76	6,194.1	-119.5	139.4	176.4	0.44	-0.38	-10.07
6,300.0	1.76	206.58	6,294.0	-121.8	138.6	177.8	0.84	0.70	19.82
6,400.0	2.58	173.04	6,394.0	-125.4	138.2	180.6	1.48	0.82	-33.54
6,500.0	3.00	157.77	6,493.8	-130.0	139.5	185.2	0.85	0.42	-15.27
6,600.0	2.02	178.74	6,593.8	-134.2	140.5	189.3	1.33	-0.98	20.97
6,700.0	1.83	178.06	6,693.7	-137.6	140.6	192.1	0.19	-0.19	-0.68
6,800.0	0.83	152.50	6,793.7	-139.8	141.0	194.2	1.14	-1.00	-25.56
6,900.0	0.38	239.49	6,893.7	-140.6	141.1	194.9	0.89	-0.45	86.99
7,000.0	1.52	272.07	6,993.7	-140.7	139.4	194.1	1.22	1.14	32.58
7,100.0	3.12	261.80	7,093.6	-141.1	135.4	192.2	1.65	1.60	-10.27
7,200.0	3.66	247.39	7,193.4	-142.7	129.8	190.5	1.00	0.54	-14.41
7,300.0	4.78	241.32	7,293.1	-145.9	123.2	189.6	1.20	1.12	-6.07
7,400.0	5.43	235.88	7,392.7	-150.6	115.6	189.3	0.81	0.65	-5.44
7,500.0	4.26	245.43	7,492.4	-154.8	108.3	188.8	1.42	-1.17	9.55
7,576.0	4.51	238.92	7,568.1	-157.5	103.2	188.3	0.73	0.33	-8.57
7576' MD Phoenix Gyro Survey									
7,678.0	2.70	233.00	7,669.9	-161.0	97.8	188.3	1.81	-1.77	-5.80
7,709.0	0.70	77.80	7,700.9	-161.4	97.4	188.4	10.80	-6.45	-500.65
7,741.0	3.40	59.00	7,732.9	-160.9	98.4	188.5	8.58	8.44	-58.75
7,773.0	6.60	58.10	7,764.8	-159.4	100.8	188.6	10.00	10.00	-2.81
7,805.0	9.90	55.20	7,796.4	-156.9	104.6	188.6	10.39	10.31	-9.06
7,836.0	13.60	57.00	7,826.8	-153.4	109.9	188.5	11.99	11.94	5.81
7,869.0	16.40	56.40	7,858.7	-148.7	117.0	188.5	8.50	8.48	-1.82
7,900.0	18.80	59.70	7,888.2	-143.7	125.0	188.7	8.38	7.74	10.65
7,931.0	20.70	60.80	7,917.4	-138.5	134.1	189.4	6.24	6.13	3.55
7,963.0	22.90	67.00	7,947.1	-133.3	144.7	190.9	9.94	6.88	19.38
7,994.0	23.90	69.70	7,975.5	-128.8	156.2	193.3	4.73	3.23	8.71
8,026.0	25.10	67.80	8,004.7	-124.0	168.6	196.1	4.49	3.75	-5.94
8,058.0	27.50	67.70	8,033.4	-118.6	181.7	198.8	7.50	7.50	-0.31
8,089.0	30.40	67.90	8,060.5	-113.0	195.6	201.7	9.36	9.35	0.65
8,121.0	33.70	68.40	8,087.6	-106.6	211.3	205.0	10.35	10.31	1.56
8,153.0	37.00	68.60	8,113.7	-99.9	228.5	208.8	10.32	10.31	0.63
8,184.0	40.30	67.00	8,137.9	-92.5	246.5	212.5	11.12	10.65	-5.16
8,216.0	43.70	68.30	8,161.7	-84.4	266.3	216.5	10.97	10.63	4.06



Stryker Directional Survey Report



Company:	Mewbourne Oil Company .	Local Co-ordinate Reference:	Well Journey 12 B2MP Fee 1H
Project:	Eddy County, New Mexico	TVD Reference:	2975 + 27 @ 3002.0usft (Patterson #243)
Site:	Section 12-24S-28E Journey 12 B2MP Fee 1H	MD Reference:	2975 + 27 @ 3002.0usft (Patterson #243)
Well:	Journey 12 B2MP Fee 1H	North Reference:	Grid
Wellbore:	Original Hole	Survey Calculation Method:	Minimum Curvature
Design:	Original Hole	Database:	Stryker_EDM

Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
8,247.0	47.70	69.80	8,183.3	-76.5	287.0	221.3	13.36	12.90	4.84
8,279.0	51.40	70.30	8,204.1	-68.2	309.9	226.9	11.62	11.56	1.56
8,311.0	55.20	72.10	8,223.2	-59.9	334.2	233.3	12.70	11.88	5.63
8,342.0	57.00	76.00	8,240.5	-52.9	358.9	240.9	11.95	5.81	12.58
8,374.0	59.30	79.30	8,257.4	-47.1	385.4	250.6	11.33	7.19	10.31
8,406.0	61.40	82.90	8,273.2	-42.8	412.9	262.1	11.77	6.56	11.25
8,437.0	65.50	85.40	8,287.1	-40.0	440.5	274.8	15.06	13.23	8.06
8,469.0	69.60	88.40	8,299.3	-38.4	470.0	289.7	15.47	12.81	9.38
8,496.1	71.97	89.33	8,308.2	-37.9	495.6	303.3	9.33	8.75	3.45
LP Journey 12 B2MP Fee 1H									
8,501.0	72.40	89.50	8,309.7	-37.8	500.3	305.8	9.33	8.76	3.39
8,532.0	74.10	90.00	8,318.6	-37.7	529.9	321.9	5.70	5.48	1.61
8,564.0	77.40	89.00	8,326.5	-37.4	561.0	338.7	10.75	10.31	-3.13
8,595.0	79.70	88.00	8,332.7	-36.6	591.3	354.7	8.06	7.42	-3.23
8,605.0	80.00	88.10	8,334.4	-36.3	601.2	359.8	3.16	3.00	1.00
8,674.0	83.10	92.00	8,344.6	-36.4	669.4	397.3	7.17	4.49	5.65
8,705.0	86.90	92.60	8,347.3	-37.6	700.2	415.2	12.41	12.26	1.94
8,768.0	89.50	93.90	8,349.3	-41.2	763.1	452.6	4.61	4.13	2.06
8,863.0	87.90	91.00	8,351.4	-45.2	858.0	508.0	3.49	-1.68	-3.05
8,958.0	88.10	90.60	8,354.7	-46.5	952.9	561.2	0.47	0.21	-0.42
9,053.0	88.40	90.00	8,357.6	-47.0	1,047.9	613.6	0.71	0.32	-0.63
9,148.0	88.90	89.70	8,359.9	-46.8	1,142.8	665.5	0.61	0.53	-0.32
9,242.0	98.40	88.90	8,353.9	-45.7	1,236.5	715.8	10.14	10.11	-0.85
9,332.0	89.90	88.80	8,347.4	-43.9	1,326.2	763.5	9.45	-9.44	-0.11
9,433.0	87.80	88.80	8,349.4	-41.7	1,427.1	817.0	2.08	-2.08	0.00
9,528.0	88.20	88.80	8,352.7	-39.7	1,522.1	867.4	0.42	0.42	0.00
9,622.0	88.50	88.80	8,355.4	-37.8	1,616.0	917.2	0.32	0.32	0.00
9,717.0	88.80	88.70	8,357.7	-35.7	1,711.0	967.5	0.33	0.32	-0.11
9,812.0	89.30	88.60	8,359.2	-33.5	1,805.9	1,017.7	0.54	0.53	-0.11
9,907.0	86.50	88.50	8,362.7	-31.1	1,900.8	1,067.7	2.95	-2.95	-0.11
10,002.0	86.50	88.50	8,368.5	-28.6	1,995.6	1,117.6	0.00	0.00	0.00
10,096.0	86.80	88.10	8,374.0	-25.8	2,089.4	1,166.6	0.53	0.32	-0.43
10,192.0	89.30	89.30	8,377.3	-23.6	2,185.3	1,217.4	2.89	2.60	1.25
10,286.0	90.00	90.00	8,377.9	-23.1	2,279.3	1,268.4	1.05	0.74	0.74
10,381.0	89.90	89.50	8,377.9	-22.6	2,374.3	1,320.1	0.54	-0.11	-0.53
10,476.0	90.10	89.50	8,377.9	-21.8	2,469.3	1,371.5	0.21	0.21	0.00
10,571.0	90.30	89.70	8,377.6	-21.1	2,564.3	1,423.0	0.30	0.21	0.21
10,666.0	88.20	89.30	8,378.9	-20.3	2,659.3	1,474.4	2.25	-2.21	-0.42
10,761.0	88.00	89.00	8,382.0	-18.9	2,754.2	1,525.2	0.38	-0.21	-0.32
10,855.0	88.90	89.60	8,384.5	-17.8	2,848.2	1,575.7	1.15	0.96	0.64
10,950.0	89.30	89.20	8,386.0	-16.8	2,943.2	1,627.0	0.60	0.42	-0.42
11,045.0	89.60	89.00	8,387.0	-15.3	3,038.1	1,677.8	0.38	0.32	-0.21
11,139.0	89.60	88.50	8,387.6	-13.2	3,132.1	1,727.6	0.53	0.00	-0.53
11,234.0	89.30	88.20	8,388.5	-10.5	3,227.1	1,777.3	0.45	-0.32	-0.32



Stryker Directional Survey Report



Company:	Mewbourne Oil Company .	Local Co-ordinate Reference:	Well Journey 12 B2MP Fee 1H
Project:	Eddy County, New Mexico	TVD Reference:	2975 + 27 @ 3002.0usft (Patterson #243)
Site:	Section 12-24S-28E Journey 12 B2MP Fee 1H	MD Reference:	2975 + 27 @ 3002.0usft (Patterson #243)
Well:	Journey 12 B2MP Fee 1H	North Reference:	Grid
Wellbore:	Original Hole	Survey Calculation Method:	Minimum Curvature
Design:	Original Hole	Database:	Stryker_EDM

Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
11,329.0	89.90	88.40	8,389.2	-7.7	3,322.0	1,827.0	0.67	0.63	0.21
11,424.0	90.20	88.20	8,389.1	-4.9	3,417.0	1,876.7	0.38	0.32	-0.21
11,519.0	89.50	87.50	8,389.4	-1.3	3,511.9	1,925.7	1.04	-0.74	-0.74
11,613.0	89.40	87.60	8,390.3	2.7	3,605.8	1,973.8	0.15	-0.11	0.11
11,708.0	89.40	87.40	8,391.2	6.9	3,700.7	2,022.4	0.21	0.00	-0.21
11,804.0	90.10	87.40	8,391.7	11.2	3,796.6	2,071.3	0.73	0.73	0.00
11,899.0	90.40	87.40	8,391.3	15.5	3,891.5	2,119.7	0.32	0.32	0.00
11,994.0	88.40	88.60	8,392.2	18.9	3,986.5	2,168.9	2.46	-2.11	1.26
12,089.0	89.00	89.50	8,394.4	20.4	4,081.4	2,219.7	1.14	0.63	0.95
12,184.0	88.70	90.90	8,396.3	20.1	4,176.4	2,272.0	1.51	-0.32	1.47
12,279.0	89.50	91.10	8,397.8	18.4	4,271.4	2,325.4	0.87	0.84	0.21
12,374.0	88.60	91.80	8,399.4	16.0	4,366.3	2,379.5	1.20	-0.95	0.74
12,468.0	90.00	92.20	8,400.5	12.8	4,460.3	2,433.7	1.55	1.49	0.43
12,563.0	87.80	94.30	8,402.3	7.4	4,555.1	2,490.2	3.20	-2.32	2.21
12,651.0	87.30	93.90	8,406.1	1.1	4,642.8	2,543.5	0.73	-0.57	-0.45
12,710.0	87.30	93.90	8,408.9	-2.9	4,701.6	2,579.1	0.00	0.00	0.00
12710' MD Projected to Bit - PBHL Journey 12 B2MP Fee #1H									

Design Annotations				
Measured Depth (usft)	Vertical Depth (usft)	Local Coordinates		Comment
		+N/-S (usft)	+E/-W (usft)	
7,576.0	7,568.1	-157.5	103.2	7576' MD Phoenix Gyro Survey
12,710.0	8,408.9	-2.9	4,701.6	12710' MD Projected to Bit



COMPANY: Mewbourne Oil Company
 WELL: Journey 12 B2MP Fee 1H
 COUNTY: Eddy County, New Mexico
 DATUM: NAD 1927 (NADCON CONUS)
 RIG: Patterson Patterson #243



GRID CORRECTION: To convert a Magnetic Direction to a Grid Direction, Add 7.19°

OFFICE: 936.582.7296

GEODETIC ZONE: New Mexico East 3001										
2975 + 27 @ 3002.0usft (Patterson #243)										
GROUND ELEVATION: 2975.0										
+N/-S	+E/-W	Northing	Easting	Latitude	Longitude	Slot				
0.0	0.0	446119.80	588210.00	32° 13' 34.243 N	104° 2' 53.081 W					
PLAN SECTIONS										
Sec	MD	Inc	Azi	TVD	+N/-S	+E/-W	Dleg	TFace	VSect	Target
1	7576.0	4.51	238.92	7568.1	-157.5	103.2	0.00	0.00	103.6	
2	7801.5	0.00	238.92	7793.4	-162.1	95.6	2.00	180.00	96.1	
3	7861.4	0.00	238.92	7853.3	-162.1	95.6	0.00	238.92	96.1	
4	8361.4	60.00	65.00	8266.8	-61.2	312.0	12.00	65.00	312.1	
5	8673.4	88.83	90.15	8351.0	-2.4	600.7	12.00	44.35	600.8	
6	12784.1	88.83	90.15	8435.0	-13.5	4710.5	0.00	0.00	4710.5	PBHL Journey 12 B2MP Fee #1H

SHL 470' FSL; 285 FWL
 Section 12-24S-28E
 PBHL 470' FSL; 330' FEL
 Section 12-24S-28E

451.5' FSL; 347.5' FEL

