

District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

RECEIVED Energy, Minerals and Natural Resources

Revised July 18, 2013

WELL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-43809
5. Indicate Type of Lease STATE [] FEE [x]
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Cedar Canyon 22-15 Fee
8. Well Number 31H
9. OGRID Number 16696
10. Pool name or Wildcat Pierce Crossing Bone Spring, East
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 2926' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)
1. Type of Well: Oil Well [x] Gas Well [] Other []
2. Name of Operator OXY USA INC.
3. Address of Operator P.O. BOX 50250 MIDLAND, TX 79710
4. Well Location Unit Letter C : 1108 feet from the NORTH line and 1603 feet from the WEST line
Section 22 Township 24S Range 29E NMPM County EDDY
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 2926' GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:
PERFORM REMEDIAL WORK [] PLUG AND ABANDON []
TEMPORARILY ABANDON [] CHANGE PLANS []
PULL OR ALTER CASING [] MULTIPLE COMPL []
DOWNHOLE COMMINGLE []
CLOSED-LOOP SYSTEM []
OTHER: []
SUBSEQUENT REPORT OF:
REMEDIAL WORK [] ALTERING CASING []
COMMENCE DRILLING OPNS [x] P AND A []
CASING/CEMENT JOB [x]
OTHER: []

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Spud 14-3/4" hole 7/16/16, drill to 450' 7/16/16. RIH & set 10-3/4" 45.5# J-55 BTC csg @ 443', pump 40BFW spacer w/ red dye then pump 200sx (60bbl) PPC w/ additives 14.2ppg 1.69 yield, followed by 270sx (65bbl) PPC w/ additives @ 14.8ppg 1.36 yield, full returns throughout job, circ 267sx (80bbl) cmt to surface. Pull wellhead landing joint & install valve & bull plug on wellhead & prepare to skid rig to Cedar Canyon 22-15 Fee 32H (30-015-43808).

Spud Date: 7/16/16

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE [Signature] TITLE Regulatory Coordinator DATE 7/20/2016

Type or print name Jana Mendiola E-mail address: janalyn_mendiola@oxy.com PHONE: 432-685-5936

For State Use Only

APPROVED BY: [Signature] TITLE Bus Op Spec-Adv DATE 7-27-16
Conditions of Approval (if any):