NM OIL CONSERVATION

ARTESIA DISTRICT

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

JAN 2 5 2017

Form C-141 Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Submit | Copy to appropriate District Office in Electrordance with 19.15.29 NMAC.

Release Notification and Corrective Action						
<u>NAB 1702741728</u>	OPERATO		🛛 Initia	l Report	☐ Final Report	
Name of Company Oxy Permian Ltd. //// Contact Casey Summers						
Address PO Box 4294; Houston, TX 77210 Telephone No. (575) 513-8289 Facility Name SDS 11 Federal #1 SWD Facility Facility Type SWD						
Surface Owner BLM Mineral Owner API No. 30-015-27627						
LOCATION OF RELEASE						
Unit Letter Section Township Range Feet from the No	rth/South Line	South Line Feet from the East/West Line County				
F 11 24S 31E		Eddy				
Latitude N 32.23339° Longitude W 103.75040°						
NATURE OF RELEASE						
Type of Release Produced water		Release 18 bbls	I Volume	Recovered	8 hbls	
Source of Release Nipple leak on disposal line		ur of Occurrenc		Date and Hour of Discovery		
Was Immediate Notice Given? If YES, To Whom?						
Yes No Not Requir		Mike Bratcher, Heather Patterson- NMOCD; Shelly Tucker- BLM				
By Whom? Kathy Purvis @ BBC International Inc. Was a Watercourse Reached?		Date and Hour 01/18/2017 @ 12:54 pm If YES, Volume Impacting the Watercourse.				
☐ Yes ⊠ No	ti 125, Visianis impliating the Walestonia					
If a Watercourse was Impacted, Describe Fully.*						
Describe Cause of Problem and Remedial Action Taken.*						
A nipple leak on the disposal line caused a leak of 18 bbls of produced	lwater Avacinin	i truck recovered	1 & bbls of produc	ed water an	d the ninnle was	
replaced.	Water. A vacaul	I Hack Iccordic	s d outs or produc	cu water an	a the inppie was	
Describe Area Affected and Cleanup Action Taken.*						
The affected area is approximately 80' x 55' on location. Remediation	will be complete	d in accordance	with the remediat	ion nlan an	proved by both	
NMOCD and the BLM.	. Will be complete			ion brain ab	,, a. c.	
I hereby certify that the information given above is true and complete	to the hest of my l	nowledge and u	nderstand that re-	renant to Mi	MOCD rules and	
regulations all operators are required to report and/or file certain releas	se notifications an	i perform correc	tive actions for re	leases whic	h may endanger	
public health or the environment. The acceptance of a C-141 report by should their operations have falled to adequately investigate and remedent	y the NMOCD ma	rked as "Final R	eport" does not re	lieve the op	perator of liability	
or the environment. In addition, NMOCD acceptance of a C-141 repo						
federal, state, or local laws and/or regulations.	·····	~	·····			
		OIL CONSERVATION DIVISION				
Signature: M		Signed Ru.				
Printed Name: Casey Summers Approved by Environmental Specialisti						
		1/27/17		_ 1/	IA	
Title: NM Environmental Advisor	Approval Date	: 1/2.111	Expiration	Date: N	un	
E-mail Address: Casey Summers@oxy.com	Conditions of	Approval;	•	Attache	ы П	
Date: 1-25-17 Phone: (575) 513-8289	$\int Q d$	attach	ed	ruacil	~ 🗀	
1 1010. (010/010-020)						

Operator/Responsible Party,

The OCD has received the form C-141 you provided on ______ regarding an unauthorized release. The information contained on that form has been entered into our incident database and remediation case number 269-4092 has been assigned. Please refer to this case number in all future correspondence.

It is the Division's obligation under both the Oil & Gas Act and Water Quality Act to provide for the protection of public health and the environment. Our regulations (19.15.29.11 NMAC) state the following,

The responsible person shall complete <u>division-approved corrective action</u> for releases that endanger public health or the environment. The responsible person shall address releases in accordance with a remediation plan submitted to and approved by the division or with an abatement plan submitted in accordance with 19.15.30 NMAC. [emphasis added]

Release characterization is the first phase of corrective action unless the release is ongoing or is of limited volume and all impacts can be immediately addressed. Proper and cost-effective remediation typically cannot occur without adequate characterization of the impacts of any release. Furthermore, the Division has the ability to impose reasonable conditions upon the efforts it oversees. As such, the Division is requiring a workplan for the characterization of impacts associated with this release be submitted to the OCD District of office in the submitted of the release characterization workplan is approved, there will be an associated deadline for submittal of the resultant investigation report. Modest extensions of time to these deadlines may be granted, but only with acceptable justification.

The goals of a characterization effort are: 1) determination of the lateral and vertical extents along with the magnitude of soil contamination. 2) determine if groundwater or surface waters have been impacted. 3) If groundwater or surface waters have been impacted, what are the extents and magnitude of that impact. 4) The characterization of any other adverse impacts that may have occurred (examples: impacts on vegetation, impacts on wildlife, air quality, loss of use of property, etc.). To meet these goals as quickly as possible, the following items must, at a minimum, be addressed in the release characterization workplan and subsequent reporting:

- Horizontal delineation of soil impacts in each of the four cardinal compass directions. Adsorbed soil contamination must be characterized for the following constituents using the associated laboratory methods: benzene, toluene, ethylbenzene, and total xylenes by either Method 8260 or 8021, total petroleum hydrocarbons by Method 8015 extended range (GRO+DRO+MRO; C₆ thru C₃₆), and for chloride by Method 300. This is not an exclusive list of potential contaminants. Analyzed parameters should be modified based on the nature of the released substance(s). Soil sampling must be both within the impacted area and beyond.
- Vertical delineation of soil impacts. Adsorbed soil contamination must be characterized for the following constituents using the associated laboratory methods: benzene, toluene, ethylbenzene, and total xylenes by either Method 8260 or 8021, total petroleum hydrocarbons by Method 8015 extended range (GRO+DRO+MRO; C₆ thru C₃₆), and for chloride by Method 300. As above, this is not an exclusive list of potential contaminants and can be modified. Vertical characterization samples should be taken at depth intervals no greater than five feet apart. Lithologic description of encountered soils must also be provided. At least ten vertical feet of soils with contaminant concentrations at or below these values must be demonstrated as existing above the water table.
- Nominal detection limits for field and laboratory analyses must be provided.
- Composite sampling is not generally allowed.
- Field screening and assessment techniques are acceptable (headspace, titration, EC [include algorithm for validation purposes], EM, etc.), but the sampling and assay procedures must be clearly defined. Copies of field notes are highly desirable. A statistically significant set of split samples must be submitted for confirmatory laboratory analysis, including the laterally farthest and vertically deepest sets of soil samples. Make sure there are at least two soil samples submitted

for laboratory analysis from each borehole or test pit (highest observed contamination and deepest depth investigated). Copies of the actual laboratory results must be provided including chain of custody documentation.

- •Probable depth to shallowest protectable groundwater and lateral distance to nearest surface water. If there is an estimate of groundwater depth, the information used to arrive at that estimate must be provided. If there is a reasonable assumption that the depth to protectable water is 50 feet or less, the responsible party should anticipate the need for at least one groundwater monitoring well to be installed in the area of likely maximum contamination.
- If groundwater contamination is encountered, an additional investigation workplan may be required to determine the extents of that contamination. Groundwater and/or surface water samples, if any, must be analyzed by a competent laboratory for volatile organic hydrocarbons (typically Method 8260 full list), total dissolved solids, pH, major anions and cations including chloride and sulfate, dissolved iron, and dissolved manganese. The investigation workplan must provide the groundwater sampling method(s) and sample handling protocols. To the fullest extent possible, aqueous analyses must be undertaken using nominal method detection limits. As with the soil analyses, copies of the actual laboratory results must be provided including chain of custody documentation.
- Accurately scaled and well-drafted site maps must be provided providing the location of borings, test pits, monitoring wells, potentially impacted areas, and significant surface features including roads and site infrastructure that might limit either the release characterization or remedial efforts. Field sketches may be included in subsequent reporting, but should not be considered stand-alone documentation of the site's layout. Digital photographic documentation of the location and fieldwork is recommended, especially if unusual circumstances are encountered.

Nothing herein should be interpreted to preclude emergency response actions or to imply immediate remediation by removal cannot proceed as warranted. Nonetheless, characterization of impacts and confirmation of the effectiveness of remedial efforts must still be provided to the OCD before any release incident will be closed.

Jim Griswold
OCD Environmental Bureau Chief
1220 South St. Francis Drive
Santa Fe, New Mexico 87505
505-476-3465
jim.griswold@state.nm.us