

Most Recent Job

Ground Elevation (ft)	Original KB Elevation (ft)	Total Depth (ft)	PSTD (All) (ft)
2,996.00	3,018.00	12,835.0	

Original Hole, 7/29/2015 11:08:58 AM

MD (ft)	TVD (ft)	Incl (°)	Vertical schematic (actual)
-11,980.0			1-1; Tubing; 2 3/8; 1,995; -11,980.0; 11,978.00; 4.60; N-80
-2.0			1-2; Nipple; 2 3/8; 1,785; -2.0; 1.00
-1.0			1-3; Notched collar; 2 3/8; 1,900; -1.0; 1.00
0.0			
22.0			1-1; Casing Joints; 13 3/8; 12,615; 22.0; 607.00; 54.50; K-55
628.9			1-2; Shoe; 13 3/8; 12,615; 629.0; 1.00
629.9			
630.9			2-1; Casing Joints; 9 5/8; 8,835; 22.0; 4,771.00; 40.00; N-80
4,793.0			
4,794.0			2-2; DV Tool; 9 5/8; 8,835; 4,793.0; 2.00
4,794.9			2-3; Casing Joints; 9 5/8; 8,835; 4,795.0; 5,129.00; 40.00; N-80
9,615.2			3-1; Liner Hanger; 8.84; 6,750; 9,615.0; 6.00
9,621.1			
9,923.9			2-4; Shoe; 9 5/8; 8,835; 9,924.0; 1.00
9,924.9			3-2; Casing Joints; 7 5/8; 6,765; 9,621.0; 2,124.00; 33.70; P-110
11,401.9			4-1; Liner Hanger; 6.77; 4,250; 11,402.0; 6.00
11,408.1			
11,527.9			Perforated; 11,528.0-11,538.0; 7/25/1991
11,538.1			Perforated; 11,720.0-11,728.0; 7/25/1991
11,720.1			Perforated; 11,720.0-11,728.0; 8/20/1978
11,728.0			
11,745.1			3-3; Float Collar; 7 5/8; 6,765; 11,745.0; 1.00
11,748.1			3-4; Casing Joints; 7 5/8; 6,765; 11,746.0; 39.00; 33.70; P-110
11,785.1			3-5; Float Shoe; 7 5/8; 6,765; 11,785.0; 1.00
11,788.1			
11,787.1			4-2; Casing Joints; 5; 4,276; 11,408.0; 1,382.00; 18.00; N-80
12,266.1			Perforated; 12,266.0-12,272.0; 9/25/2006
12,272.0			
12,306.1			Perforated; 12,306.0-12,311.0; 9/25/2006
12,311.0			
12,328.1			Perforated; 12,328.0-12,344.0; 9/25/2006
12,344.2			
12,396.0			Perforated; 12,396.0; 8/27/1976
12,396.9			Perforated; 12,399.0; 8/27/1976
12,401.9			Perforated; 12,402.0; 8/27/1976
12,562.0			Perforated; 12,562.0; 8/27/1976
12,566.9			Perforated; 12,567.0; 8/27/1976
12,571.8			Perforated; 12,572.0; 8/27/1976
12,790.0			
12,791.0			4-3; Float Collar; 5; 12,790.0; 1.00
12,834.0			4-4; Casing Joints; 5; 4,276; 12,791.0; 43.00; 18.00; N-80
12,835.0			4-5; Float Shoe; 5; 12,834.0; 1.00

PACKER 11465