

Submit 1 Copy To Appropriate District Office

District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
Revised July 18, 2013

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-015-25192
1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other P&A <input type="checkbox"/>		5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
2. Name of Operator EOG Y Resources, Inc.		6. State Oil & Gas Lease No. LG-3782
3. Address of Operator 104 South Fourth Street, Artesia, NM 88210		7. Lease Name or Unit Agreement Name Woodchuck ABW State Com
4. Well Location Unit Letter <u>K</u> : <u>1980</u> feet from the <u>South</u> line and <u>1980</u> feet from the <u>West</u> line Section <u>13</u> Township <u>17S</u> Range <u>28E</u> NMPM <u>Eddy</u> County		8. Well Number 1
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3697'GR		9. OGRID Number 025575
		10. Pool name or Wildcat Aid; Morrow

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐
CLOSED-LOOP SYSTEM ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS ☐ P AND A ☒
CASING/CEMENT JOB ☐
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

8/22/17 - MIRU. Opened well and bled off. ND wellhead and speared into 4-1/2" casing. Strip on BOP. POOH with 71 jts 4-1/2" casing.
8/23/17 - ND BOP. RIH with 1 jt 4-1/2" casing and overshot, grapple, strip on BOP and NU. RIH with 68 jts 4-1/2" casing. Attempted to fish, unable. Overshot fish then strip off BOP. Hang off and cut off 4-1/2" casing. NU BOP.
8/24/17 - RIH with tubing overshot, grapple and latch onto fish. Pulled up to 30,000 (parted). Stacked out at 3907'. Pumped 30 bbls brine. Stacked out at 4535' and worked down to 4545'.
8/25/17 - RIH and swedged down to 10,226'. RIH with tubing cutter down to 10,200' pulled up on tubing to 50,000 (tubing parted) and cut tubing. RIH and latched onto fish. Worked up and down until free. Set fish on slips.
8/28/17 - RIH and tagged bottom at 10,200'. Pumped 40 bbls brine. Spotted 100 sx Class "H" cement from 10,200'-9119'.

CONTINUED ON NEXT PAGE:

Spud Date:

Rig Release Date

Approved for plugging of well bore only.
Under bond to be retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms. www.emnrd.state.nm.us/ocd.

NM OIL CONSERVATION
ARTESIA DISTRICT

SEP 18 2017

RECEIVED

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Tina Huerta TITLE Regulatory Specialist DATE September 13, 2017

Type or print name Tina Huerta E-mail address: tina_huerta@eogresources.com PHONE: 575-748-4168

For State Use Only

APPROVED BY: Robert R. Byrd TITLE COMPLIANCE OFFICER DATE 9/18/2017

Conditions of Approval (if any):

FORM C-103 CONTINUED:


8/29/17 – Tagged TOC 9102'. Spotted 30 sx Class "H" cement 8440'-8040' calc TOC. WOC. Tagged TOC 8118'. Spotted 25 sx Class "C" cement from 7025'-6047' calc TOC. Perforated at 3785'. Spotted 45 sx Class "C" cement (200' inside/outside) from 3835'-3585' calc TOC.

8/30/17 – Tagged TOC 3483'. ND BOP. Speared into 4-1/2" casing, pulled slips, strip on BOP. LD 67 jts 4-1/2" casing, strip off BOP. LD last jt and 4-1/2" overshot. NU BOP. Spotted 30 sx Class "C" cement from 3072'-2941' calc TOC.

8/31/17 – Tagged TOC 2933'. Spotted 35 sx Class "C" cement from 2720'-2567' calc TOC. WOC. Tagged TOC 2588'. Spotted 40 sx Class "C" cement from 2432'-2285' calc TOC. NOTE: No 13-3/8" casing head. Did not perforate 8-5/8" casing below surface shoe. Ok'd from Bob Byrd Artesia-NMOCD. Spotted 45 sx Class "C" cement from 450'-284' calc TOC. ND BOP. Spotted 14 sx Class "C" cement from 60' up to surface. Topped off well with cement.

9/1/17 – Verified TOC. RD all equipment.

9/9/17 – Cut off wellhead and installed dry hole marker. Cut off anchors. **WELL IS PLUGGED AND ABANDONED.**



Regulatory Specialist
September 13, 2017