

District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3466
1220 S. St. Francis Dr., Santa Fe, NM 87505

Energy, Minerals and Natural Resources

OIL CO. ARTESIA DISTRICT
OIL CONSERVATION DIVISION
OCT 26 2017
RECEIVED

1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-43299
5. Indicate Type of Lease STATE [ ] FEE [X]
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name SIMPSON 15 B
8. Well Number #4
9. OGRID Number 277558
10. Pool name or Wildcat Atoka, Glorieta-Yeso (3250)
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3336' GL

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)
1. Type of Well: Oil Well [X] Gas Well [ ] Other [ ]
2. Name of Operator LIME ROCK RESOURCES II-A, L.P.
3. Address of Operator c/o Mike Pippin LLC, 3104 N. Sullivan, Farmington, NM 87401
4. Well Location Unit Letter B : 230 feet from the North line and 1760 feet from the East line
Section 15 Township 18-S Range 26-E NMPM Eddy County

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

- PERFORM REMEDIAL WORK [ ] PLUG AND ABANDON [ ]
TEMPORARILY ABANDON [ ] CHANGE PLANS [X]
PULL OR ALTER CASING [ ] MULTIPLE COMPL [ ]
DOWNHOLE COMMINGLE [ ]
CLOSED-LOOP SYSTEM [X]
OTHER: Drill Surface Hole to 1230' [X]

SUBSEQUENT REPORT OF:

- REMEDIAL WORK [ ] ALTERING CASING [ ]
COMMENCE DRILLING OPNS. [ ] P AND A [ ]
CASING/CEMENT JOB [ ]
OTHER: [ ]

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Lime Rock proposes to set the surface protection casing at a minimum of 1230', which is at least 50' below the base of the Artesian aquifer porosity that develops from 1160 to 1170' on the Lime Rock - Terry 14C #2 Neutron-Density log dated September 8, 2016. The surface hole will be drilled with a 12-1/4" bit, and the 8-5/8" csq cmted w/about 600 sx cm:

We plan to submit a NSL in the near future.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Mike Pippin TITLE Petroleum Engineer - Agent DATE 10/24/17

Type or print name Mike Pippin E-mail address: mike@pippinllc.com PHONE: 505-327-4573

For State Use Only

APPROVED BY: [Signature] TITLE Staff Mgr DATE 10-26-17
Conditions of Approval (if any):