

Submit 1 Copy To Appropriate District Office
 District I - (575) 393-6161
 1625 N. French Dr., Hobbs, NM 88240
 District II - (575) 748-1283
 811 S. First St., Artesia, NM 88210
 District III - (505) 334-6178
 1000 Rio Brazos Rd., Aztec, NM 87410
 District IV - (505) 476-3460
 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
 Energy, Minerals and Natural Resources

Form C-103
 Revised July 18, 2013

OIL CONSERVATION DIVISION
 1220 South St. Francis Dr.
 Santa Fe, NM 87505

WELL API NO.
30-015-44364

5. Indicate Type of Lease
STATE FEE

6. State Oil & Gas Lease No.
STATE

7. Lease Name or Unit Agreement Name
REMUDA SOUTH 25 STATE

8. Well Number
101H

9. OGRID Number
5380

10. Pool name or Wildcat
PURPLE SAGE; WOLFCAMP

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3062' GL

SUNDRY NOTICES AND REPORTS ON WELLS
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well Gas Well Other

2. Name of Operator
XTO ENERGY, INC

3. Address of Operator
6401 HOLIDAY HILL RD, BLDG 5, MIDLAND TX 79705

4. Well Location
Unit Letter E : 2280 feet from the NORTH line and 615 feet from the WEST line
Section 25 Township 23S Range 29E NMPM County EDDY

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

- PERFORM REMEDIAL WORK PLUG AND ABANDON
 TEMPORARILY ABANDON CHANGE PLANS
 PULL OR ALTER CASING MULTIPLE COMPL
 DOWNHOLE COMMINGLE
 CLOSED-LOOP SYSTEM
 OTHER:

SUBSEQUENT REPORT OF:

- REMEDIAL WORK ALTERING CASING
 COMMENCE DRILLING OPNS. P AND A
 CASING/CEMENT JOB
 OTHER:

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

XTO Energy, Inc requests permission to revise intermediate casing and cement as follows:

Casing Type	Hole Size	Casing Size	Casing Grade	Casing Weight	Setting Depth	Total Skcs Cement	TOC
Intermediate	12.25	9.625	J-55 LTC	40	7500	1765	0

DV tool will be set @ 3200' (~50' below base of salt).

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Kelly Kardos TITLE Regulatory Coordinator DATE 3/19/18

Type or print name Kelly Kardos E-mail address: kelly_kardos@xtoenergy.com PHONE: 432-620-4374

For State Use Only

APPROVED BY: [Signature] TITLE Staff Mgr DATE 3-21-18
 Conditions of Approval (if any):