Submit 1 Copy To Appropriate District	State of New Mexico			Form C-103	
Office <u>District 1</u> – (575) 393-6161	Energy, Minerals and Natural Resources		es	Revised July 18, 2013	
1625 N. French Dr., Hobbs, NM 88240 District II – (575) 748-1283			WELL AF 30-015-34		
811 S. First St., Artesia, NM 88210	OIL CONSERVATION DIVISION			te Type of Lease	
<u>District III</u> ← (505) 334-6178 1000 Rio Brazos Rd., Aztec, NM 87410	1220 South St. Francis Dr.			ATE FEE	
<u>District IV</u> – (505) 476-3460	Santa Fe, NM 87505		6. State C	Oil & Gas Lease No.	
1220 S. St. Francis Dr., Santa Fe, NM 87505					
SUNDRY NOTICES AND REPORTS ON WELLS				7. Lease Name or Unit Agreement Name	
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH			STALEY	STALEY STATE	
PROPOSALS.)  1. Type of Well: Oil Well  Gas Well  Othe Off OIL CONSERVATION			ON 8. Well N	8. Well Number #3	
2. Name of Operator			9. OGRII	9. OGRID Number 258350	
VANGUARD OPERATING. LLC  JUL 0 2 2018					
3. Address of Operator			<b> </b>	10. Pool name or Wildcat Red Lake, Glorieta-Yeso NE (96836)	
c/o Mike Pippin LLC, 3104 N. Sullivan, Farmington, NM 87401			Red Lake, Giorieta-Feso NE (90830)  Red Lake, Queen-Grayburg-San Andres (51300)		
4. Well Location		WEAP A PR	,		
Unit Letter I : 2310 feet from the South line and 330 feet from the East line					
Section 30	Township 17-S			IPM Eddy County	
	11. Elevation (Show wheth				
	3601' GL				
NOTICE OF INTENTION TO:  PERFORM REMEDIAL WORK   PLUG AND ABANDON   REMEDIAL WORK   PLUG AND ABANDON   CHANGE PLANS   COMMENCE DRILLING OPNS.   PAND A   PAND A   DOWNHOLE COMMINGLE   CLOSED-LOOP SYSTEM   OTHER: Recompleted to the San Andres   OTHER: Recompleted to the San Andres   OTHER: Recompleted this Yeso oil well to the San Andres as follows: On 6/11/18, MIRUSU. TOH w/rods, pump, & tbg. Set 5-1/2" CBP @ 3150' & PT 5-1/2" csg & CBP to 3000 psi-OK. Perfed middle San Andres @ 2619'-3032' w/36 holes. On 6/20/18, treated w/1000 gal 15% HCL acid & fraced w/29,508# 100 mesh & 351,109# 40/70 sand in slick water. Set 5-1/2" CBP @ 2610'. PT csg & CBP to 3000 psi-OK. Perfed middle San Andres @ 2120'-2569' w/35 holes. Treated perfs w/1500 gal 15% HCL acid & fraced w/29,508# 100 mesh & 351,109# 40/70 sand in slick water. Set 5-1/2" CBP @ 2050'. PT CBP & 5-1/2" csg to 3000 psi-OK. Perfed duper San Andres @ 1760'-1987' w/34 holes. Treated perfs w/1500 gal 15% HCL acid & fraced w/29,508# 100 mesh & 351,109# 40/70 sand in slick water. Set 5-1/2" CBP @ 2050'. PT CBP & 5-1/2" csg to 3000 psi-OK. Perfed upper San Andres @ 1760'-1987' w/34 holes. Treated perfs w/1500 gal 15% HCL acid & fraced w/30,343# 100 mesh & 189,950# 40/70 sand in slick water. On 6/22/18, MIRUSU. Drilled CBPs @ 2050' & 2610', & CO to CBP @ 3150'. On 6/26/18, landed 2-7/8" 6.5# J-55 tbg @ 2992'. Ran pump & rods. Released completion rig on 6/27/18. Completed the well as a single San Andres oil well. Following a test on the San Andres alone, the CBP @ 3150' will be removed and the well DHC as per State order ART-4609-CC.					
Spud Date: 6/22/05	1-1	ng Rig Release Date			
I hereby certify that the information above is true and complete to the best of my knowledge and belief.					
SIGNATURE	TITLE	Petroleum Engine	er - Agent	_DATE6/30/18	
Type or print nameMike Pip	ppin E-mail	address: <u>mike</u>	@pippinllc.com_	PHONE: <u>505-327-4573</u>	
For State Use Only				_	
APPROVED B K: Jumes Conditions of Approval (If any):	L St. Judany TITLE	Cacologi,	34	DATE 7-5-/8	