



RECEIVED

AUG 21 2018

DISTRICT II-ARTESIA O.C.D.

Mewbourne Oil Company

Eddy County, New Mexico

Section 26/35-25S-31E Armstrong 26-35 W1IP Fed Com

Armstrong 26-35 W1IP Fed Com #1H

Original Hole

30-015-43753

Design: Original Hole

Standard Survey Report

29 November, 2017



Company:	Mewbourne Oil Company	Local Co-ordinate Reference:	Well Armstrong 26-35 W1IP Fed Com #1H
Project:	Eddy County, New Mexico	TVD Reference:	3339 +27 @ 3366.0usft (Patterson 242)
Site:	Section 26/35-25S-31E Armstrong 26-35 W1IP Fed Com	MD Reference:	3339 +27 @ 3366.0usft (Patterson 242)
Well:	Armstrong 26-35 W1IP Fed Com #1H	North Reference:	Grid
Wellbore:	Original Hole	Survey Calculation Method:	Minimum Curvature
Design:	Original Hole	Database:	Stryker_EDM

Project	Eddy County, New Mexico		
Map System:	US State Plane 1927 (Exact solution)	System Datum:	Mean Sea Level
Geo Datum:	NAD 1927 (NADCON CONUS)		
Map Zone:	New Mexico East 3001		

Site	Section 26/35-25S-31E Armstrong 26-35 W1IP Fed Com		
Site Position:		Northing:	401,040.10 usft
From:	Map	Easting:	683,436.50 usft
Position Uncertainty:	0.0 usft	Slot Radius:	13-3/16 "
		Latitude:	32° 6' 4.284 N
		Longitude:	103° 44' 27.404 W
		Grid Convergence:	0.31 °

Well	Armstrong 26-35 W1IP Fed Com #1H		
Well Position	+N/-S	0.0 usft	Northing: 401,040.10 usft
	+E/-W	0.0 usft	Easting: 683,436.50 usft
Position Uncertainty	0.0 usft	Wellhead Elevation:	27.0 usft
		Latitude:	32° 6' 4.284 N
		Longitude:	103° 44' 27.404 W
		Ground Level:	3,339.0 usft

Wellbore	Original Hole		
-----------------	---------------	--	--

Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)	Field Strength (nT)
	IGRF2015	10/26/2017	6.98	59.92	47,810.93550377

Design	Original Hole		
---------------	---------------	--	--

Audit Notes:			
Version:	1.0	Phase:	ACTUAL
		Tie On Depth:	0.0

Vertical Section:	Depth From (TVD) (usft)	+N/-S (usft)	+E/-W (usft)	Direction (°)
	0.0	0.0	0.0	168.01

Survey Program	Date 11/29/2017		
From (usft)	To (usft)	Survey (Wellbore)	Tool Name
1,057.0	19,465.0	MWD Survey #1 (Original Hole)	

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
868.0	0.20	166.03	868.0	-2.5	-0.2	2.4	0.00	0.00	0.00
1,057.0	0.40	198.10	1,057.0	-3.5	-0.4	3.3	0.13	0.11	16.97
1,247.0	0.70	188.30	1,247.0	-5.3	-0.7	5.0	0.16	0.16	-5.16
1,437.0	0.70	195.50	1,437.0	-7.5	-1.2	7.1	0.05	0.00	3.79
1,627.0	1.00	202.60	1,626.9	-10.2	-2.2	9.5	0.17	0.16	3.74
1,818.0	1.50	203.20	1,817.9	-14.0	-3.8	12.9	0.26	0.26	0.31
2,005.0	2.20	213.50	2,004.8	-19.3	-6.7	17.4	0.41	0.37	5.51
2,191.0	1.70	262.50	2,190.7	-22.6	-11.5	19.7	0.90	-0.27	26.34
2,378.0	1.30	291.30	2,377.6	-22.2	-16.2	18.3	0.45	-0.21	15.40
2,565.0	1.30	29.30	2,564.6	-19.6	-17.1	15.6	1.05	0.00	52.41

Company:	Mewbourne Oil Company	Local Co-ordinate Reference:	Well Armstrong 26-35 W1IP Fed Com #1H
Project:	Eddy County, New Mexico	TVD Reference:	3339 +27 @ 3366.0usft (Patterson 242)
Site:	Section 26/35-25S-31E Armstrong 26-35 W1IP Fed Com	MD Reference:	3339 +27 @ 3366.0usft (Patterson 242)
Well:	Armstrong 26-35 W1IP Fed Com #1H	North Reference:	Grid
Wellbore:	Original Hole	Survey Calculation Method:	Minimum Curvature
Design:	Original Hole	Database:	Stryker_EDM

Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
2,752.0	1.50	11.50	2,751.6	-15.3	-15.6	11.7	0.25	0.11	-9.52
2,939.0	1.90	350.80	2,938.5	-9.9	-15.6	6.4	0.39	0.21	-11.07
3,126.0	1.10	40.80	3,125.4	-5.4	-14.9	2.2	0.78	-0.43	26.74
3,313.0	0.70	123.60	3,312.4	-4.7	-12.8	2.0	0.66	-0.21	44.28
3,500.0	1.40	174.50	3,499.4	-7.6	-11.6	5.0	0.59	0.37	27.22
3,687.0	2.60	164.20	3,686.3	-14.0	-10.3	11.5	0.67	0.64	-5.51
3,874.0	1.00	93.30	3,873.2	-18.2	-7.5	16.2	1.32	-0.86	-37.91
4,060.0	2.20	76.50	4,059.1	-17.4	-2.4	16.5	0.69	0.65	-9.03
4,199.0	2.80	93.40	4,198.0	-17.0	3.6	17.4	0.68	0.43	12.16
4,278.0	3.20	99.50	4,276.9	-17.5	7.7	18.7	0.65	0.51	7.72
4,340.0	2.20	114.80	4,338.8	-18.3	10.5	20.0	1.97	-1.61	24.68
4,433.0	0.30	208.30	4,431.8	-19.2	12.0	21.3	2.41	-2.04	100.54
4,620.0	1.20	303.30	4,618.8	-18.6	10.1	20.3	0.67	0.48	50.80
4,808.0	1.50	318.90	4,806.7	-15.6	6.9	16.7	0.25	0.16	8.30
4,994.0	1.40	307.50	4,992.6	-12.4	3.5	12.9	0.16	-0.05	-6.13
5,181.0	3.80	295.40	5,179.4	-8.4	-3.9	7.4	1.31	1.28	-6.47
5,368.0	4.70	291.30	5,365.9	-2.9	-16.7	-0.6	0.51	0.48	-2.19
5,555.0	4.80	291.90	5,552.3	2.8	-31.1	-9.2	0.06	0.05	0.32
5,742.0	5.10	289.70	5,738.6	8.5	-46.2	-17.9	0.19	0.16	-1.18
5,929.0	5.10	292.20	5,924.8	14.4	-61.7	-26.9	0.12	0.00	1.34
6,116.0	5.20	293.20	6,111.1	20.9	-77.2	-36.5	0.07	0.05	0.53
6,303.0	4.60	283.70	6,297.4	26.0	-92.2	-44.6	0.54	-0.32	-5.08
6,489.0	5.10	291.70	6,482.7	30.8	-107.2	-52.4	0.45	0.27	4.30
6,676.0	4.50	286.10	6,669.1	36.0	-121.9	-60.5	0.41	-0.32	-2.99
6,863.0	4.60	278.60	6,855.5	39.1	-136.4	-66.6	0.32	0.05	-4.01
7,050.0	5.30	268.70	7,041.8	40.0	-152.5	-70.8	0.59	0.37	-5.29
7,237.0	4.10	262.90	7,228.2	39.0	-167.7	-73.0	0.69	-0.64	-3.10
7,424.0	3.50	257.90	7,414.8	37.0	-179.9	-73.6	0.37	-0.32	-2.67
7,611.0	4.00	267.40	7,601.4	35.5	-192.0	-74.6	0.43	0.27	5.08
7,797.0	3.40	271.60	7,787.0	35.4	-204.0	-77.0	0.35	-0.32	2.26
7,984.0	4.20	266.80	7,973.6	35.1	-216.4	-79.3	0.46	0.43	-2.57
8,170.0	4.10	262.80	8,159.1	33.9	-229.8	-80.9	0.16	-0.05	-2.15
8,359.0	3.90	269.00	8,347.6	33.0	-242.9	-82.7	0.25	-0.11	3.28
8,545.0	3.10	270.30	8,533.3	32.9	-254.3	-85.0	0.43	-0.43	0.70
8,732.0	3.80	252.90	8,719.9	31.1	-265.3	-85.5	0.67	0.37	-9.30
8,919.0	4.50	254.80	8,906.4	27.3	-278.3	-84.5	0.38	0.37	1.02
9,106.0	4.20	266.20	9,092.9	25.0	-292.2	-85.1	0.49	-0.16	6.10
9,293.0	4.00	249.20	9,279.4	22.2	-305.1	-85.1	0.66	-0.11	-9.09
9,479.0	5.00	248.00	9,464.9	16.8	-318.7	-82.7	0.54	0.54	-0.65
9,666.0	5.40	251.60	9,651.1	11.0	-334.6	-80.3	0.28	0.21	1.93
9,853.0	4.30	263.00	9,837.4	7.4	-349.9	-79.9	0.78	-0.59	6.10
10,040.0	3.10	267.40	10,024.0	6.3	-361.9	-81.3	0.66	-0.64	2.35

Company:	Mewbourne Oil Company	Local Co-ordinate Reference:	Well Armstrong 26-35 W1IP Fed Com #1H
Project:	Eddy County, New Mexico	TVD Reference:	3339 +27 @ 3366.0usft (Patterson 242)
Site:	Section 26/35-25S-31E Armstrong 26-35 W1IP Fed Com	MD Reference:	3339 +27 @ 3366.0usft (Patterson 242)
Well:	Armstrong 26-35 W1IP Fed Com #1H	North Reference:	Grid
Wellbore:	Original Hole	Survey Calculation Method:	Minimum Curvature
Design:	Original Hole	Database:	Stryker_EDM

Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
10,226.0	4.00	248.50	10,209.7	3.7	-373.0	-81.1	0.79	0.48	-10.16
10,413.0	3.90	246.50	10,396.2	-1.2	-384.9	-78.7	0.09	-0.05	-1.07
10,600.0	5.60	245.50	10,582.6	-7.6	-399.0	-75.5	0.91	0.91	-0.53
10,788.0	4.10	210.30	10,769.9	-17.2	-410.8	-68.5	1.73	-0.80	-18.72
10,975.0	4.30	258.70	10,956.5	-24.3	-421.0	-63.7	1.84	0.11	25.88
11,162.0	1.60	223.00	11,143.2	-27.6	-429.7	-62.3	1.68	-1.44	-19.09
11,318.6	1.35	223.08	11,299.8	-30.5	-432.4	-60.0	0.16	-0.16	0.05
B.B. Armstrong 26-35 W1IP Fed Com 1H									
11,349.0	1.30	223.10	11,330.2	-31.1	-432.9	-59.6	0.16	-0.16	0.06
11,398.0	1.40	205.00	11,379.2	-32.0	-433.5	-58.8	0.89	0.20	-36.94
11,430.0	2.60	247.80	11,411.1	-32.6	-434.4	-58.3	5.74	3.75	133.75
11,462.0	5.40	269.10	11,443.1	-32.9	-436.5	-58.5	9.76	8.75	66.56
11,494.0	8.00	279.70	11,474.8	-32.6	-440.2	-59.6	8.96	8.13	33.13
11,525.0	10.60	276.70	11,505.4	-31.9	-445.2	-61.3	8.53	8.39	-9.68
11,557.0	14.20	274.80	11,536.7	-31.2	-452.0	-63.4	11.32	11.25	-5.94
11,589.0	17.30	271.50	11,567.5	-30.8	-460.7	-65.6	10.08	9.69	-10.31
11,621.0	19.80	260.60	11,597.8	-31.5	-470.8	-67.0	13.33	7.81	-34.06
11,653.0	22.20	248.00	11,627.7	-34.7	-481.8	-66.2	15.94	7.50	-39.38
11,684.0	24.60	236.50	11,656.2	-40.4	-492.6	-62.8	16.61	7.74	-37.10
11,716.0	26.90	224.50	11,685.0	-49.3	-503.2	-56.3	17.77	7.19	-37.50
11,748.0	29.10	212.90	11,713.3	-61.0	-512.5	-46.8	18.32	6.88	-36.25
11,780.0	31.50	205.10	11,740.9	-75.1	-520.3	-34.6	14.39	7.50	-24.38
11,812.0	33.70	199.60	11,767.9	-91.0	-526.8	-20.4	11.53	6.88	-17.19
11,844.0	35.50	197.00	11,794.2	-108.3	-532.5	-4.7	7.27	5.63	-8.13
11,876.0	37.40	196.00	11,820.0	-126.5	-537.9	12.0	6.22	5.94	-3.13
11,908.0	39.50	194.50	11,845.0	-145.7	-543.2	29.7	7.18	6.56	-4.69
11,940.0	41.30	193.00	11,869.4	-165.8	-548.1	48.4	6.39	5.63	-4.69
11,971.0	43.50	192.00	11,892.3	-186.3	-552.6	67.4	7.42	7.10	-3.23
12,003.0	46.20	190.80	11,915.0	-208.4	-557.1	88.1	8.84	8.44	-3.75
12,035.0	48.40	189.50	11,936.7	-231.5	-561.2	109.9	7.50	6.88	-4.06
12,067.0	49.90	189.00	11,957.6	-255.4	-565.1	132.5	4.83	4.69	-1.56
12,098.0	51.80	188.70	11,977.2	-279.2	-568.8	154.9	6.17	6.13	-0.97
12,130.0	54.80	188.30	11,996.3	-304.5	-572.6	179.0	9.43	9.38	-1.25
12,162.0	57.50	187.50	12,014.1	-330.9	-576.2	203.9	8.69	8.44	-2.50
12,194.0	59.80	187.00	12,030.8	-358.0	-579.7	229.7	7.31	7.19	-1.56
12,226.0	61.80	186.80	12,046.4	-385.7	-583.0	256.2	6.27	6.25	-0.63
12,257.0	63.10	185.70	12,060.7	-413.0	-586.0	282.3	5.24	4.19	-3.55
12,289.0	65.40	183.70	12,074.6	-441.7	-588.4	309.9	9.13	7.19	-6.25
12,320.0	68.70	181.30	12,086.7	-470.3	-589.6	337.5	12.81	10.65	-7.74
12,351.0	70.70	180.30	12,097.5	-499.3	-590.0	365.9	7.13	6.45	-3.23
12,380.0	72.20	180.00	12,106.7	-526.8	-590.1	392.7	5.26	5.17	-1.03
12,432.0	77.40	180.70	12,120.3	-577.0	-590.4	441.7	10.08	10.00	1.35
12,436.7	77.49	180.72	12,121.3	-581.6	-590.5	446.2	1.96	1.94	0.32

Company:	Mewbourne Oil Company	Local Co-ordinate Reference:	Well Armstrong 26-35 W1IP Fed Com #1H
Project:	Eddy County, New Mexico	TVD Reference:	3339 +27 @ 3366.0usft (Patterson 242)
Site:	Section 26/35-25S-31E Armstrong 26-35 W1IP Fed Com	MD Reference:	3339 +27 @ 3366.0usft (Patterson 242)
Well:	Armstrong 26-35 W1IP Fed Com #1H	North Reference:	Grid
Wellbore:	Original Hole	Survey Calculation Method:	Minimum Curvature
Design:	Original Hole	Database:	Stryker_EDM

Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
LP Armstrong 26-35 W1IP Fed Com 1H									
12,463.0	78.00	180.80	12,126.9	-607.3	-590.8	471.3	1.96	1.94	0.32
12,495.0	80.90	180.30	12,132.8	-638.7	-591.1	502.0	9.19	9.06	-1.56
12,526.0	83.70	179.60	12,136.9	-669.4	-591.1	532.0	9.31	9.03	-2.26
12,557.0	84.90	178.70	12,140.0	-700.3	-590.6	562.3	4.83	3.87	-2.90
12,588.0	85.20	178.50	12,142.7	-731.2	-589.9	592.7	1.16	0.97	-0.65
12,682.0	88.40	178.00	12,147.9	-825.0	-587.0	685.0	3.45	3.40	-0.53
12,775.0	91.70	178.20	12,147.9	-917.9	-583.9	776.6	3.55	3.55	0.22
12,869.0	90.50	179.30	12,146.0	-1,011.8	-581.9	868.9	1.73	-1.28	1.17
12,962.0	90.50	180.80	12,145.2	-1,104.8	-581.9	959.8	1.61	0.00	1.61
13,055.0	89.60	182.00	12,145.2	-1,197.8	-584.2	1,050.3	1.61	-0.97	1.29
13,242.0	89.50	182.60	12,146.6	-1,384.7	-591.7	1,231.5	0.33	-0.05	0.32
13,429.0	91.10	183.20	12,145.6	-1,571.4	-601.2	1,412.2	0.91	0.86	0.32
13,616.0	89.90	181.30	12,144.0	-1,758.2	-608.5	1,593.5	1.20	-0.64	-1.02
13,803.0	88.40	180.20	12,146.8	-1,945.2	-611.0	1,775.8	0.99	-0.80	-0.59
13,990.0	91.10	177.90	12,147.6	-2,132.1	-607.9	1,959.3	1.90	1.44	-1.23
14,177.0	93.00	178.60	12,140.9	-2,318.9	-602.2	2,143.2	1.08	1.02	0.37
14,364.0	89.30	179.20	12,137.2	-2,505.8	-598.6	2,326.8	2.00	-1.98	0.32
14,550.0	90.50	178.80	12,137.5	-2,691.8	-595.3	2,509.4	0.68	0.65	-0.22
14,737.0	92.30	180.20	12,132.9	-2,878.7	-593.7	2,692.6	1.22	0.96	0.75
14,924.0	88.10	179.90	12,132.3	-3,065.7	-593.9	2,875.4	2.25	-2.25	-0.16
15,110.0	88.90	179.50	12,137.1	-3,251.6	-592.9	3,057.5	0.48	0.43	-0.22
15,298.0	89.60	178.30	12,139.6	-3,439.5	-589.3	3,242.1	0.74	0.37	-0.64
15,485.0	92.20	177.70	12,136.7	-3,626.4	-582.7	3,426.2	1.43	1.39	-0.32
15,672.0	93.50	179.40	12,127.4	-3,813.1	-578.0	3,609.8	1.14	0.70	0.91
15,858.0	87.40	179.10	12,125.9	-3,999.0	-575.6	3,792.2	3.28	-3.28	-0.16
16,045.0	92.90	179.60	12,125.4	-4,185.9	-573.5	3,975.4	2.95	2.94	0.27
16,233.0	89.80	181.20	12,121.0	-4,373.8	-574.8	4,159.0	1.86	-1.65	0.85
16,419.0	88.90	182.80	12,123.1	-4,559.7	-581.3	4,339.5	0.99	-0.48	0.86
16,606.0	87.00	178.70	12,129.8	-4,746.5	-583.7	4,521.7	2.42	-1.02	-2.19
16,793.0	92.90	178.00	12,129.9	-4,933.3	-578.3	4,705.6	3.18	3.16	-0.37
16,979.0	91.40	179.50	12,123.0	-5,119.1	-574.3	4,888.2	1.14	-0.81	0.81
17,166.0	91.70	178.90	12,117.9	-5,306.1	-571.7	5,071.5	0.36	0.16	-0.32
17,353.0	91.10	181.20	12,113.3	-5,493.0	-571.8	5,254.4	1.27	-0.32	1.23
17,540.0	88.60	179.80	12,113.8	-5,680.0	-573.5	5,436.9	1.53	-1.34	-0.75
17,633.0	88.80	179.30	12,115.9	-5,772.9	-572.7	5,528.0	0.58	0.22	-0.54
17,727.0	91.50	179.00	12,115.7	-5,866.9	-571.3	5,620.2	2.89	2.87	-0.32
17,821.0	92.80	179.40	12,112.2	-5,960.8	-570.0	5,712.4	1.45	1.38	0.43
17,915.0	93.30	181.10	12,107.2	-6,054.7	-570.4	5,804.1	1.88	0.53	1.81
18,008.0	90.30	181.10	12,104.2	-6,147.6	-572.2	5,894.6	3.23	-3.23	0.00
18,102.0	88.70	179.20	12,105.1	-6,241.6	-572.5	5,986.5	2.64	-1.70	-2.02
18,195.0	88.30	180.10	12,107.5	-6,334.6	-571.9	6,077.6	1.06	-0.43	0.97

Company:	Mewbourne Oil Company	Local Co-ordinate Reference:	Well Armstrong 26-35 W1IP Fed Com #1H
Project:	Eddy County, New Mexico	TVD Reference:	3339 +27 @ 3366.0usft (Patterson 242)
Site:	Section 26/35-25S-31E Armstrong 26-35 W1IP Fed Com	MD Reference:	3339 +27 @ 3366.0usft (Patterson 242)
Well:	Armstrong 26-35 W1IP Fed Com #1H	North Reference:	Grid
Wellbore:	Original Hole	Survey Calculation Method:	Minimum Curvature
Design:	Original Hole	Database:	Stryker_EDM

Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
18,289.0	91.00	180.80	12,108.1	-6,428.6	-572.6	6,169.4	2.97	2.87	0.74
18,384.0	93.10	181.20	12,104.7	-6,523.5	-574.3	6,261.9	2.25	2.21	0.42
18,479.0	92.60	181.60	12,100.0	-6,618.3	-576.6	6,354.2	0.67	-0.53	0.42
18,575.0	91.70	180.90	12,096.4	-6,714.2	-578.7	6,447.5	1.19	-0.94	-0.73
18,670.0	89.90	181.70	12,095.0	-6,809.2	-580.9	6,540.0	2.07	-1.89	0.84
18,766.0	90.10	180.40	12,095.0	-6,905.2	-582.6	6,633.5	1.37	0.21	-1.35
18,861.0	88.50	179.60	12,096.2	-7,000.2	-582.6	6,726.4	1.88	-1.68	-0.84
18,957.0	90.00	180.90	12,097.4	-7,096.2	-583.0	6,820.2	2.07	1.56	1.35
19,052.0	84.80	179.00	12,101.8	-7,191.0	-583.0	6,913.0	5.83	-5.47	-2.00
19,148.0	88.80	179.00	12,107.1	-7,286.8	-581.3	7,007.1	4.17	4.17	0.00
19,243.0	94.50	179.60	12,104.4	-7,381.8	-580.1	7,100.2	6.03	6.00	0.63
19,338.0	93.80	178.80	12,097.5	-7,476.5	-578.8	7,193.2	1.12	-0.74	-0.84
19,413.0	93.50	178.50	12,092.7	-7,551.3	-577.0	7,266.7	0.57	-0.40	-0.40
19,465.0	93.50	178.50	12,089.5	-7,603.2	-575.7	7,317.8	0.00	0.00	0.00

19465' MD Projected to Bit - PBHL Armstrong 26-35 W1IP Fed com 1H

Design Annotations

Measured Depth (usft)	Vertical Depth (usft)	Local Coordinates		Comment
		+N/-S (usft)	+E/-W (usft)	
19,465.0	12,089.5	-7,603.2	-575.7	19465' MD Projected to Bit



COMPANY: Mewbourne Oil Company
WELL: Armstrong 26-35 W1IP Fed Com #1H
COUNTY: Eddy County, New Mexico
DATUM: NAD 1927 (NADCON CONUS)
RIG: Patterson Patterson 242



Grid Correction MWD: To convert a Magnetic Direction to a Grid Direction, Add 6.67°

OFFICE: 936.582.7296

GEODETTIC ZONE: New Mexico East 3001


3339 +27 @ 3366.0usft (Patterson 242)

GROUND ELEVATION: 3339.0

+N/-S	+E/-W	Northing	Easting	Latitude	Longitude	Slot
0.0	0.0	401040.10	683436.50	32° 6' 4.284 N	103° 44' 27.404 W	

PLAN SECTIONS

Sec	MD	Inc	Azi	TVD	+N/-S	+E/-W	Dleg	TFace	VSect	Target
1	0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.0	
2	5000.0	0.00	0.00	5000.0	0.0	0.0	0.00	0.00	0.0	
3	5285.3	4.28	269.85	5285.0	0.0	-10.6	1.50	269.85	0.8	
4	11031.3	4.28	269.85	11015.0	-1.2	-439.4	0.00	0.00	34.9	
5	11316.5	0.00	0.00	11300.0	-1.2	-450.0	1.50	180.00	35.7	B.B. Armstrong 26-35 W1IP Fed Com 1H
6	11455.0	0.00	0.00	11438.5	-1.2	-450.0	0.00	0.00	35.7	
7	11597.4	14.24	270.39	11579.4	-1.1	-467.7	10.00	270.39	36.9	
8	12502.5	90.37	179.81	12136.0	-578.2	-608.0	10.00	-90.47	623.1	LP Armstrong 26-35 W1IP Fed Com 1H
9	19535.4	90.37	179.81	12091.0	-7610.8	-585.2	0.00	0.00	7633.3	PBHL Armstrong 26-35 W1IP Fed com 1H



SHL 2625' FNL; 380' FEL
Section 26-25S-31E
PBHL 330' FSL; 990' FEL
Section 35-25S-31E

