Submit 1 Copy To Appropriate District Office	State of New Me	exico	Form C					
District I = (575) 393-6161	Energy, Minerals and Nati	ural Resources	Revised July 18	, 2013				
District II – (575) 748-1283 811 S. First St., Artesia, NM 88210 District III – (505) 334-6178 District III – (505) 334-6178 District IV – (505) 476-3460 1220 S. St. Francis Dr., Santa Fe, NM 87505 SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A		\ \varphi	ELL API NO.					
811 S. First St., Artesia, NM 88210, 9, 5 W OIL CONSERVATION DIVISION		NDIVISION $\frac{36}{5}$	0-015-00259					
District III – (505) 334-6178 OC 1220 South St. Francis Dr.		ncis Dr.	Indicate Type of Lease					
1000 Rio Brazos Rd., Aztec, NM 87410 Santa Fe NM 87505		7505	STATE FEE S					
District IV = (505) 476-3460	Santa 1 C, INIVI O	7505	State Oil & Gas Lease No.					
87505 AST Trailers Dr., Sunta 15 A								
SUNDRY NOTI	CES AND REPORTS ON WELLS	S 7.	Lease Name or Unit Agreement Na	me				
			leaveland					
DIFFERENT RESERVOIR. USE "APPLIC PROPOSALS.)	CATION FOR PERMIT" (FORM C-101) F	OR SUCH 8.	Well Number					
1. Type of Well: Oil Well	Gas Well Other	1						
2. Name of Operator	Cus Wen	9	9. OGRID Number					
EOG Y Resources, Inc.			025575					
3. Address of Operator	7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7		10. Pool name or Wildcat					
104 South Fourth Street, Artesia, N	M 88210		Atoka; Glorieta-Yeso					
4. Well Location			·					
	660 feet from the Nort	h line and 198	0 feet from the East	line				
Section 33			MPM Eddy County					
	11. Elevation (Show whether DR	•						
	3333	GR	l					
12. Check A	Appropriate Box to Indicate N	Vature of Notice, Re	port or Other Data					
NOTICE OF IN	TENTION TO	_ OUDOE	OUENT DEDODT OF					
			BSEQUENT REPORT OF:					
	PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WOR		☐ ALTERING CASING					
TEMPORARILY ABANDON	CHANGE PLANS	COMMENCE DRILLI		Ц				
PULL OR ALTER CASING	MULTIPLE COMPL	CASING/CEMENT JO)в П					
DOWNHOLE COMMINGLE								
CLOSED-LOOP SYSTEM		OTHER:		\Box				
OTHER:	eted operations (Clearly state all		ve pertinent dates including estimate	d date				
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of								
proposed completion or reco		c. Tor Multiple Compr	ctions. Attach wendere diagram of					
proposed completion of recompletion.								
8/9/18 - MIRU for workover. POOH wit	h rods. Pumped 40 bbls 2% KCL dow	n casing to kill well. NU E	OP. POOH with tubing, some joints had	holes.				
Ran back in hole with new 2-7/8" J-55 tu		5	5,					
8/10/18 - Opened up well. No pressure. I	Dropped 2 lbs dry corrosion inhibitor a		Flushed with 10 bbls 2% KCL. Ran rods	and				
pump. Flushed tubing with 20 bbls 2% K	CL before seating pump. Tried to seat	pump, would not seat.	The Amountain is	ı				
				9/1/18 – Found a leak around wellhead. Opened up well. 100 psi on casing, 50 psi on tubing. Bled down casing. Leak stopped. TOH with rods and pump. TIH and set an AS1-X RBP at 1324'. Loaded casing with 22 bbls 2% KCL. Bled down foam. TOOH laying down 40 jts 2-7/8" J-55 tubing onto racks.				
Dump 100# sand on RBP. Loaded casing			ing down 40 jts 2-7/6 3-33 tubing onto i					
	9/7/18 – Dug around wellhead. Found a pipe clamp on 5-1/2 inch casing. Leak was under clamp. Cut off 3' of 8-5/8" casing. Found some decent 5-							
1/2" casing to weld slip on coupling to. Loaded casing with 4 bbls 2% KCL. Well standing full. Weld on new 8' section of 5-1/2" 17# casing. Installed								
	Loaded casing with 4 bbls 2% KCL. V			t 5-				
5-1/2" x 2-7/8" Model R Larkin head. Ri	Loaded casing with 4 bbls 2% KCL. Vgged down.	Well standing full. Weld o	n new 8' section of 5-1/2" 17# casing. In	t 5-				
5-1/2" x 2-7/8" Model R Larkin head. Ri 10/5/18 – NU BOP. Tagged top of si	Loaded casing with 4 bbls 2% KCL. V gged down. and at 1310'. Reverse circulate sa:	Well standing full. Weld on the world of the weld on the well of the well well at 2 bbls min into was a second of the well well at 2 bbls min into was a second of the 2 bbls min into was a second of the 2 bbls min into was a second of the 2 b	n new 8' section of 5-1/2" 17# casing. In truck from 1310' to 1324'.	t 5- istalled				
5-1/2" x 2-7/8" Model R Larkin head. Ri 10/5/18 – NU BOP. Tagged top of si 10/6/18 – Tagged RBP at 1324'. Rele	Loaded casing with 4 bbls 2% KCL. Vigged down. and at 1310'. Reverse circulate saleased RBP. Set 2-7/8'' 6.5# J-55 to	Well standing full. Weld on the dat 2 bbls min into valubing at 3604'. Loaded	n new 8' section of 5-1/2" 17# casing. In a truck from 1310' to 1324'. Stubing with 8 bbls 2% KCL with biod	t 5- nstalled				
5-1/2" x 2-7/8" Model R Larkin head. Ri 10/5/18 – NU BOP. Tagged top of st 10/6/18 – Tagged RBP at 1324'. Releand 02 scavenger. Pressure tested to	Loaded casing with 4 bbls 2% KCL. Vigged down. and at 1310'. Reverse circulate saleased RBP. Set 2-7/8'' 6.5# J-55 to	Well standing full. Weld on the dat 2 bbls min into valubing at 3604'. Loaded	n new 8' section of 5-1/2" 17# casing. In a truck from 1310' to 1324'. Stubing with 8 bbls 2% KCL with biod	t 5- nstalled				
5-1/2" x 2-7/8" Model R Larkin head. Ri 10/5/18 – NU BOP. Tagged top of si 10/6/18 – Tagged RBP at 1324'. Rele	Loaded casing with 4 bbls 2% KCL. Vigged down. and at 1310'. Reverse circulate saleased RBP. Set 2-7/8'' 6.5# J-55 to	Well standing full. Weld on the dat 2 bbls min into valubing at 3604'. Loaded	n new 8' section of 5-1/2" 17# casing. In a truck from 1310' to 1324'. Stubing with 8 bbls 2% KCL with biod	t 5- nstalled				
5-1/2" x 2-7/8" Model R Larkin head. Ri 10/5/18 – NU BOP. Tagged top of st 10/6/18 – Tagged RBP at 1324'. Releand 02 scavenger. Pressure tested to	Loaded casing with 4 bbls 2% KCL. Vigged down. and at 1310'. Reverse circulate saleased RBP. Set 2-7/8'' 6.5# J-55 to	Well standing full. Weld on the dat 2 bbls min into valubing at 3604'. Loaded	n new 8' section of 5-1/2" 17# casing. In a truck from 1310' to 1324'. Stubing with 8 bbls 2% KCL with biod	t 5- nstalled				
5-1/2" x 2-7/8" Model R Larkin head. Ri 10/5/18 – NU BOP. Tagged top of si 10/6/18 – Tagged RBP at 1324'. Rela and 02 scavenger. Pressure tested to well to production.	Loaded casing with 4 bbls 2% KCL. Very gged down. and at 1310'. Reverse circulate same as a seased RBP. Set 2-7/8" 6.5# J-55 to 500 psi for 5 minutes, held good. I	Well standing full. Weld on at 2 bbls min into valubing at 3604'. Loaded Longstroke pump to 500	n new 8' section of 5-1/2" 17# casing. In a truck from 1310' to 1324'. Stubing with 8 bbls 2% KCL with biod	t 5- nstalled				
5-1/2" x 2-7/8" Model R Larkin head. Ri 10/5/18 – NU BOP. Tagged top of st 10/6/18 – Tagged RBP at 1324'. Releand 02 scavenger. Pressure tested to	Loaded casing with 4 bbls 2% KCL. Vigged down. and at 1310'. Reverse circulate saleased RBP. Set 2-7/8'' 6.5# J-55 to	Well standing full. Weld on at 2 bbls min into valubing at 3604'. Loaded Longstroke pump to 500	n new 8' section of 5-1/2" 17# casing. In a truck from 1310' to 1324'. Stubing with 8 bbls 2% KCL with biod	t 5- nstalled				
5-1/2" x 2-7/8" Model R Larkin head. Ri 10/5/18 – NU BOP. Tagged top of si 10/6/18 – Tagged RBP at 1324'. Rela and 02 scavenger. Pressure tested to well to production.	Loaded casing with 4 bbls 2% KCL. Very gged down. and at 1310'. Reverse circulate same as a seased RBP. Set 2-7/8" 6.5# J-55 to 500 psi for 5 minutes, held good. I	Well standing full. Weld on at 2 bbls min into valubing at 3604'. Loaded Longstroke pump to 500	n new 8' section of 5-1/2" 17# casing. In a truck from 1310' to 1324'. Stubing with 8 bbls 2% KCL with biod	t 5- nstalled				
5-1/2" x 2-7/8" Model R Larkin head. Ri 10/5/18 – NU BOP. Tagged top of si 10/6/18 – Tagged RBP at 1324'. Rela and 02 scavenger. Pressure tested to well to production.	Loaded casing with 4 bbls 2% KCL. Very gged down. and at 1310'. Reverse circulate same as the cased RBP. Set 2-7/8" 6.5# J-55 to 500 psi for 5 minutes, held good. I	Well standing full. Weld on at 2 bbls min into valubing at 3604'. Loaded Longstroke pump to 500 ate:	n new 8' section of 5-1/2" 17# casing. In truck from 1310' to 1324'. tubing with 8 bbls 2% KCL with biodesic psi twice, good. Hang well on. Turn	t 5- nstalled				
5-1/2" x 2-7/8" Model R Larkin head. Ri 10/5/18 – NU BOP. Tagged top of si 10/6/18 – Tagged RBP at 1324'. Rela and 02 scavenger. Pressure tested to well to production.	Loaded casing with 4 bbls 2% KCL. Very gged down. and at 1310'. Reverse circulate same as the cased RBP. Set 2-7/8" 6.5# J-55 to 500 psi for 5 minutes, held good. I	Well standing full. Weld on at 2 bbls min into valubing at 3604'. Loaded Longstroke pump to 500 ate:	n new 8' section of 5-1/2" 17# casing. In truck from 1310' to 1324'. tubing with 8 bbls 2% KCL with biodesic psi twice, good. Hang well on. Turn	t 5- nstalled				
5-1/2" x 2-7/8" Model R Larkin head. Ri 10/5/18 – NU BOP. Tagged top of si 10/6/18 – Tagged RBP at 1324'. Rele and 02 scavenger. Pressure tested to well to production. Spud Date:	Loaded casing with 4 bbls 2% KCL. Very gged down. and at 1310'. Reverse circulate same as the same as	Well standing full. Weld on at 2 bbls min into valubing at 3604'. Loaded Longstroke pump to 500 ate:	n new 8' section of 5-1/2" 17# casing. In truck from 1310' to 1324'. Itubing with 8 bbls 2% KCL with biodesis psi twice, good. Hang well on. Turn debt.	t 5- nstalled				
5-1/2" x 2-7/8" Model R Larkin head. Ri 10/5/18 – NU BOP. Tagged top of si 10/6/18 – Tagged RBP at 1324'. Rela and 02 scavenger. Pressure tested to well to production.	Loaded casing with 4 bbls 2% KCL. Very gged down. and at 1310'. Reverse circulate same as the same as	Well standing full. Weld on at 2 bbls min into valubing at 3604'. Loaded Longstroke pump to 500 ate:	n new 8' section of 5-1/2" 17# casing. In truck from 1310' to 1324'. tubing with 8 bbls 2% KCL with biodesic psi twice, good. Hang well on. Turn	t 5- nstalled				
5-1/2" x 2-7/8" Model R Larkin head. Ri 10/5/18 – NU BOP. Tagged top of si 10/6/18 – Tagged RBP at 1324'. Rele and 02 scavenger. Pressure tested to well to production. Spud Date: I hereby certify that the information a	Loaded casing with 4 bbls 2% KCL. Very gged down. and at 1310'. Reverse circulate same assed RBP. Set 2-7/8" 6.5# J-55 to 500 psi for 5 minutes, held good. I Rig Release Deabove is true and complete to the beginning the property of the second sec	Well standing full. Weld on at 2 bbls min into valubing at 3604'. Loaded Longstroke pump to 500 ate: Dest of my knowledge ar Regulatory Specialist	n new 8' section of 5-1/2" 17# casing. In the truck from 1310' to 1324'. Stubing with 8 bbls 2% KCL with biode psi twice, good. Hang well on. Turn debt belief. DATE October 22, 2018	t 5- estalled eide ned				
5-1/2" x 2-7/8" Model R Larkin head. Ri 10/5/18 – NU BOP. Tagged top of si 10/6/18 – Tagged RBP at 1324'. Rele and 02 scavenger. Pressure tested to well to production. Spud Date: I hereby certify that the information a SIGNATURE Type or print name Tina Huel	Loaded casing with 4 bbls 2% KCL. Very gged down. and at 1310'. Reverse circulate same assed RBP. Set 2-7/8" 6.5# J-55 to 500 psi for 5 minutes, held good. I Rig Release Deabove is true and complete to the beginning the property of the second sec	Well standing full. Weld on at 2 bbls min into valubing at 3604'. Loaded Longstroke pump to 500 ate:	n new 8' section of 5-1/2" 17# casing. In the truck from 1310' to 1324'. Stubing with 8 bbls 2% KCL with biode psi twice, good. Hang well on. Turn debt belief. DATE October 22, 2018	t 5- estalled eide ned				
5-1/2" x 2-7/8" Model R Larkin head. Ri 10/5/18 – NU BOP. Tagged top of si 10/6/18 – Tagged RBP at 1324'. Rele and 02 scavenger. Pressure tested to well to production. Spud Date: I hereby certify that the information a	Loaded casing with 4 bbls 2% KCL. Very gged down. and at 1310'. Reverse circulate same assed RBP. Set 2-7/8" 6.5# J-55 to 500 psi for 5 minutes, held good. I Rig Release Deabove is true and complete to the beginning the property of the second sec	Well standing full. Weld on at 2 bbls min into valubing at 3604'. Loaded Longstroke pump to 500 ate: Dest of my knowledge ar Regulatory Specialist	truck from 1310' to 1324'. tubing with 8 bbls 2% KCL with biod psi twice, good. Hang well on. Turn d belief. DATE October 22, 2018 es.com PHONE: _575-748-41	t 5- enstalled cide ened				
5-1/2" x 2-7/8" Model R Larkin head. Ri 10/5/18 – NU BOP. Tagged top of si 10/6/18 – Tagged RBP at 1324'. Rele and 02 scavenger. Pressure tested to well to production. Spud Date: I hereby certify that the information a SIGNATURE Type or print name Tina Huel	Loaded casing with 4 bbls 2% KCL. Very gged down. and at 1310'. Reverse circulate same assed RBP. Set 2-7/8" 6.5# J-55 to 500 psi for 5 minutes, held good. I Rig Release Deabove is true and complete to the beginning the property of the second sec	Well standing full. Weld on at 2 bbls min into valubing at 3604'. Loaded Longstroke pump to 500 ate: Dest of my knowledge ar Regulatory Specialist	n new 8' section of 5-1/2" 17# casing. In the truck from 1310' to 1324'. Stubing with 8 bbls 2% KCL with biode psi twice, good. Hang well on. Turn debt belief. DATE October 22, 2018	t 5- enstalled cide ened				