

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT  
OCD ArtesiaFORM APPROVED  
OMB NO. 1004-0137  
Expires: January 31, 2018**SUNDRY NOTICES AND REPORTS ON WELLS**  
*Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.*5. Lease Serial No.  
NMNM0399448

6. If Indian, Allottee or Tribe Name

7. If Unit or CA/Agreement, Name and/or No.  
NMNM853548. Well Name and No.  
MALONE ASA FEDERAL COM 29. API Well No.  
30-015-3076910. Field and Pool or Exploratory Area  
INDIAN BASIN; UP ASSOC11. County or Parish, State  
EDDY COUNTY, NM**SUBMIT IN TRIPLICATE - Other instructions on page 2**

## 1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other2. Name of Operator  
EOG Y RESOURCES, INC.Contact: TINA HUERTA  
E-Mail: tina\_huerta@eogresources.com3a. Address  
104 SOUTH FOURTH STREET  
ARTESIA, NM 882103b. Phone No. (include area code)  
Ph: 575-748-4168

## 4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Sec 12 T22S R23E NENE 660FNL 1310FEL

**12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA**

TYPE OF SUBMISSION	TYPE OF ACTION			
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Hydraulic Fracturing	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input type="checkbox"/> Other
	<input type="checkbox"/> Change Plans	<input checked="" type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.

EOG Y Resources, Inc. plans to plug and abandon this well as follows:

1. MIRU all safety equipment as needed. POOH with production equipment.
2. RIH with GR/JB to 7575 ft.
3. Set a CIBP at 7550 ft with 35# Class H cement on top. Fill hole with plugging mud.
4. Spot a 33 sx Class H cement plug from 6656 ft - 6824 ft. This will place a plug across Wolfcamp.
5. Spot a 26 sx Class C cement plug from 4649 ft - 4796 ft. This will assure <2000 ft of uncemented production casing.
6. Spot a 25 sx Class C cement plug from 2626 ft - 2768 ft. This will plug Bone Spring.
7. Spot a 25 sx Class C cement plug from 2078 ft - 2220 ft. This will plug Glorieta.
8. Perforate at 1247 ft. Attempt to establish circulation. Spot a 25 sx Class C cement plug from 1526 (Shoe @ 1476').

GC 12-17-18  
Accepted for record - NMOC

Spot cmf from 7550 - 7350 (CY)

SEE ATTACHED FOR  
CONDITIONS OF APPROVAL

NM OIL CONSERVATION

14. I hereby certify that the foregoing is true and correct.

Electronic Submission #444121 verified by the BLM Well Information System  
For EOG Y RESOURCES, INC., sent to the Carlsbad

ARTESIA DISTRICT

DEC 12 2018

Name (Printed/Typed) TINA HUERTA

Title REGULATORY SPECIALIST

Signature (Electronic Submission)

Date 11/14/2018

RECEIVED

**THIS SPACE FOR FEDERAL OR STATE OFFICE USE**

Approved By

Title

Date

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

\*\* OPERATOR-SUBMITTED \*\* OPERATOR-SUBMITTED \*\* OPERATOR-SUBMITTED

ENTERED

**Additional data for EC transaction #444121 that would not fit on the form**

**32. Additional remarks, continued**

*1400 - 1526*

*1105 ft - 1247 ft. This will plug the 9-5/8 inch casing shoe. WOC Tag.*

9. Spot a 10 sx Class C cement plug from 57 ft up to surface.

10. Cut off wellhead and install dry hole marker. Clean location.

Wellbore schematics attached

## 11/8/2018

### COMMENTS

14 3/4" hole

1' garf.

1474

8 3/4" lub

DIT@ 6181  
Both Stage  
circ.  
Surt

Perforations	7600-7640	✓
	7490-7540	✓

up

1

PSTD	7,828	MD
TD	8,000	MD

### Tubing

[illegible]

### CASING DETAIL

#	SIZE	WGHT	GRADE	Length	Top	Bottom	CMT
A	9 5/8	20 <del>36</del>	JK-55	1187	0	1187	2275 sxs circ
B	7	26 14 <del>13</del>	J-55	885	0	885	950 sx circ

### Formation Tops

San Andres	708	✓
Glorieta	2170	✓
Bone Spring	2718	✓
Wolfcamp	6774	✓
Canyon	7475	✓

Prepared by: MJM

[illegible]

### Tubing

[illegible]

### CASING DETAIL

#	SIZE	WGHT	GRADE	Length	Top	Bottom	CMT
A	9 5/8	20	K-55	1197	0	1197	2275 sxs circ
B	7	14	J-55	985	0	985	950 sx circ

### Formation Tops

San Andres	708
Glorieta	2170
Bone Spring	2718
Wolfcamp	6774
Canyon	7475

Prepared by: MJM

Date: 12-Nov-2018

**BUREAU OF LAND MANAGEMENT  
Carlsbad Field Office  
620 East Greene Street  
Carlsbad, New Mexico 88220  
575-234-5972**

**Permanent Abandonment of Federal Wells  
Conditions of Approval**

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within ninety (90) days from the approval date of this Notice of Intent to Abandon.

**If you are unable to plug the well by the 90<sup>th</sup> day provide this office, prior to the 90<sup>th</sup> day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.**

**The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.**

2. Notification: Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.

3. Blowout Preventers: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.

4. Mud Requirement: Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of brine water. Minimum nine (9) pounds per gallon.

5. Cement Requirement: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. **Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.**

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

6. **Dry Hole Marker:** All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). **The BLM is to be notified a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 10<sup>th</sup> day, the BLM is to be contacted with justification to receive an extension for completing the cut off.**

The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement, unless otherwise noted in COA (requirements will be attached). The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).

7. **Subsequent Plugging Reporting:** Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. **Show date well was plugged.**

8. **Trash:** All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation objectives.