

**NM OIL CONSERVATION  
ARTESIA DISTRICT**

Intent  As Drilled

DEC 12 2018

API #  
**30-015-45531**

**RECEIVED**

Operator Name: COG Operating LLC	Property Name: SRO 5 State Com	Well Number 504H
-------------------------------------	-----------------------------------	---------------------

**Kick Off Point (KOP)**

UL A	Section 5	Township 26S	Range 28E	Lot	Feet 314	From N/S North	Feet 645	From E/W East	County Eddy
Latitude <b>32.078067</b>					Longitude <b>-104.102895</b>			NAD <b>83</b>	

**First Take Point (FTP)**

UL A	Section 5	Township 26S	Range 28E	Lot	Feet 100	From N/S North	Feet 330	From E/W East	County Eddy
Latitude <b>32.078655</b>					Longitude <b>-104.101885</b>			NAD <b>83</b>	

**Last Take Point (LTP)**

UL P	Section 8	Township 26S	Range 28E	Lot	Feet 100	From N/S South	Feet 330	From E/W East	County Eddy
Latitude <b>32.050124</b>					Longitude <b>-104.102135</b>			NAD <b>83</b>	

Is this well the defining well for the Horizontal Spacing Unit?  Y

Is this well an infill well?  N

If infill is yes please provide API if available, Operator Name and well number for Defining well for Horizontal Spacing Unit.

API #	Operator Name: COG Operating LLC	Property Name: SRO 5 State Com	Well Number 504H
-------	-------------------------------------	-----------------------------------	---------------------

KZ 06/29/2018

## SRO 5 State Com #504H

### Casing and Cement

<u>String</u>	<u>Hole Size</u>	<u>Csg OD</u>	<u>PPF</u>	<u>Depth</u>	<u>Sx Cement</u>	<u>TOC</u>
Surface	17-1/2"	13-3/8"	54.5#	680'	500	0'
Intermediate 2	12-1/4"	9-5/8"	40#	2,500'	900	0'
Production	8-3/4"	5-1/2"	17#	18,160'	3,300	2,100'

### Well Plan

Drill 17-1/2" hole to 680' into the Rustler. Run 13-3/8" 54.5# J55 STC casing to TD and cement to surface in one stage. Will set in Rustler and cover water depth.

Drill 12-1/4" hole to ~2,500' with Brine. Run 9-5/8" 40# J-55 casing to TD and cement to surface in one stage.

Drill 8-3/4" vertical hole, curve & lateral to 18,160' with Cut Brine. Run 5-1/2" 17# P110 BTC casing to TD and cement to 2,100' in one stage.

### Well Control

After setting 13-3/8" casing and installing 3000 psi casing head, NU 13-5/8" Cameron BOP. Test annular and casing to 1500 psi and other BOP equipment to 3000 psi.

After setting 9-5/8" casing and installing 3000 psi casing spool, NU 13-5/8" Cameron BOP. Test annular to 1500 psi and other BOP equipment to 3000 psi.