

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
OMB NO. 1004-0137  
Expires: January 31, 2018

**SUNDRY NOTICES AND REPORTS ON WELLS**  
*Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.*

5. Lease Serial No.  
NMLC029392B

6. If Indian, Allottee or Tribe Name

7. If Unit or CA/Agreement, Name and/or No.

**SUBMIT IN TRIPLICATE - Other instructions on page 2**

8. Well Name and No.  
PRINCIPLE FEDERAL 4

9. API Well No.  
30-015-32894-00-S1

10. Field and Pool or Exploratory Area  
SHUGART

11. County or Parish, State  
EDDY COUNTY, NM

1. Type of Well  
 Oil Well  Gas Well  Other

2. Name of Operator  
CHEVRON USA INCORPORATED  
Contact: HOWIE LUCAS  
E-Mail: howie.lucas@chevron.com

3a. Address  
6301 DEAUVILLE BLVD  
MIDLAND, TX 79706

3b. Phone No. (include area code)  
Ph: 832-588-4044

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)  
Sec 27 T18S R31E SWNW 1920FNL 660FWL

**12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA**

TYPE OF SUBMISSION	TYPE OF ACTION			
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Hydraulic Fracturing	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input type="checkbox"/> Other
	<input type="checkbox"/> Change Plans	<input checked="" type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.

9 5/8" 40# 647' TOC surface, 5 1/2" 17# @ 6367' TOC 1480' via CBL, Perfs 6140'-6222', CIBP set at 6095' w/ 2 sx cmt, Perfs 5173'-5268'.

Chevron respectfully requests to abandon this well as follows:

1. Notify BLM 24 hrs. prior to starting work (575) 234-5909.
2. MIRU, NDWH, NU BOPE, test tubing  $\frac{1}{4}$  1000 psi  $\frac{1}{4}$  10 min, POOH w/ rods and tubing, bubble test all casing strings and share results w/ BLM and engineer. Chevron plans to utilize Zonite after plugging up to a designated depth agreed upon by Chevron and the BLM.
3. Set CIBP at 5120', test casing  $\frac{1}{4}$  1000 psi  $\frac{1}{4}$  10 min, spot MLF, spot 25 sx CL "C" cmt  $\frac{1}{4}$  5120'  $\frac{1}{4}$  4868', do not WOC & tag if casing passed pressure test (Perfs).
4. Spot 60 sx CL "C" cmt  $\frac{1}{4}$  4656'  $\frac{1}{4}$  4049' (Delaware, San Andres).

RECEIVED

GC 1/16/19  
Accepted for record - NMOCD

JAN 10 2019

DISTRICT II-ARTESIA O.C.D.

SEE ATTACHED FOR  
CONDITIONS OF APPROVAL

14. I hereby certify that the foregoing is true and correct.

Electronic Submission #446498 verified by the BLM Well Information System  
For CHEVRON USA INCORPORATED, sent to the Carlsbad  
Committed to AFMSS for processing by DEBORAH MCKINNEY on 12/06/2018 (19DLM0178SE)

Name (Printed/Typed) HOWIE LUCAS

Title ENGINEER

Signature (Electronic Submission)

Date 12/04/2018

**THIS SPACE FOR FEDERAL OR STATE OFFICE USE**

Approved By

*Jamaal Q. Jones*

Title

SPEET

Date

12-18-18

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

CFD

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

**\*\* BLM REVISED \*\* BLM REVISED \*\* BLM REVISED \*\* BLM REVISED \*\* BLM REVISED \*\***

**ENTERED**  
12-16-19

**Additional data for EC transaction #446498 that would not fit on the form**

**32. Additional remarks, continued**

- 5. Spot 25 sx CL "C" cmt f/ ~~2003~~ 1751' (B. Salt).
- 6. Perforate casing at 697' and squeeze 210 sx CL "C" cmt f/ Surface t/ 697' (Shoe, FW, Surf).
- 6. Cut off wellhead 3' below grade, Verify Cement To Surface, install required dry hole marker as per COA's, turn over to reclamation.

All cement plugs will be class "C" with a closed loop system used.

2200 - 2000, WOC Tag. Add Plug Perf.  
@ 1100, SQZ emt,  
To 1000, WOC Tag  
(T/Salt.)

Well: Principle F 4  
 Field: Shugart  
 Reservoir: Delaware

**Current**  
**Wellbore Diagram**

Location:  
 Section: 27  
 Township: 18  
 Range: 31  
 County: Eddy State: NM

Well ID Info:  
 Chevro: HN3642  
 API No: 3001532894  
 Spud Date: 12/2/03  
 Compl. Date: 1/15/04


Surface Csg: 9.625" 40#, J55  
 Set: @ 647'  
 Hole Size: 12.25"  
 Circ: Yes TOC: Surface  
 TOC By: Circulated

Prod. Csg: 5 1/2", 17#, J55  
 Set: @ 6367'  
 Hole Size: 8.75"  
 Circ: No TOC: 1480'  
 TOC By: CBL

Formation	TD, ft
Formation Top	
Rustler	620
Salado	851
Base of Salt	1,953
Bowers Sand	3,020
San Andres	4,162
Delaware	4,606

Cherry Canyon 5173'-5268'

Delaware 6140'-6222'



Tubing Strings		Planned Run?	Set Depth (MD) (FCS)	Set Depth (TVD) (FCS)
Tubing - Production		N	5,368.0	
Run Date	Run Job	Planned Date	Planned Job	
7/1/2008	Complete, 6/24/2008			

Job	Item Desc	OD (in)	ID (in)	WT (lb/ft)	Grade	Top Thread	Len (ft)	Top (FCS)	Bot (FCS)
161	Tubing	2 7/8	2.441	6.50	N-80	EUE	5,085.00	13.0	5,078.0
1	Anchor/catcher	2 7/8					3.00	5,078.0	5,081.0
8	Tubing	2 7/8	2.441	6.50	N-80	EUE	250.00	5,081.0	5,331.0
1	Seat Nipple: Cup Type	2 7/8					1.00	5,331.0	5,332.0
1	Perf Sub	2 7/8				EUE	4.00	5,332.0	5,336.0
1	Mud Anchor	2 7/8					31.00	5,336.0	5,367.0
1	Bull Plug	2 7/8				EUE	1.00	5,367.0	5,368.0

Rod Strings		Planned Run?	Set Depth (FCS)	Set Depth (TVD) (FCS)
Rod - Conventional		N	5,332.0	
Run Date	Run Job	Planned Date	Planned Job	
7/2/2008	Complete, 6/24/2008			

Job	Item Desc	OD (in)	Grade	M Size	Len (ft)	Top (FCS)	Bot (FCS)
1	Polished Rod	1 1/2			26.00	-9.0	17.0
1	Rod Sub	3/4			2.00	17.0	19.0
1	Rod Sub	3/4			6.00	19.0	25.0
1	Rod Sub	3/4			8.00	25.0	33.0
183	Sucker Rod	3/4	D	Grade 78	4,575.00	33.0	4,608.0
27	Sucker Rod	7/8	D	Grade 78	700.00	4,608.0	5,308.0
1	Rod Insert Pump	1 1/2			24.00	5,308.0	5,332.0

History:  
 -No known history of scale or damage. Well was recompleted in the Cherry Canyon zone in 2008 by Chesapeake prior to Chevron buying

CIBP set at 6095' w/ 2 sx cmr

PBTD: 6315'  
 TD: 6367'

Rustler 621  
 Salt 1050-2150  
 Yates 2187  
 7R 2677  
 Qu 3280  
 (SA) Capitan 4161  
 Blyn 4608  
 AS 6093

Well: **Principle F 4**  
 Field: **Shugart**  
 Reservoir: **Delaware**

**Location:**  
 Section: 27  
 Township: 18  
 Range: 31  
 County: Eddy State: NM

**Well ID Info:**  
 Chevno: HN3642  
 API No: 3001532894  
 Spud Date: 12/2/03  
 Compl. Date: 1/15/04

**Surface Csg:** 9.625" 40#, J55  
 Set: @ 647'  
 Hole Size: 12.25"  
 Circ: Yes **TOC:** Surface  
**TOC By:** Circulated


**Prod. Csg:** 5 1/2", 17#, J55  
 Set: @ 6367'  
 Hole Size: 8.75"  
 Circ: No **TOC:** 1480'  
**TOC By:** CBL

Formation	TD, ft
	Top
Rustler	620
Salado	851
Base of Salt	1,953
Bowers Sand	3,020
San Andres	4,162
Delaware	4,606

Perfs 5173'-5268'

Perfs 6140'-6222'

**Proposed Wellbore Diagram**



**BUREAU OF LAND MANAGEMENT**  
**Carlsbad Field Office**  
**620 East Greene Street**  
**Carlsbad, New Mexico 88220**  
**575-234-5972**

**Permanent Abandonment of Federal Wells**  
**Conditions of Approval (LPC Habitat)**

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within ninety (90) days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90<sup>th</sup> day provide this office, prior to the 90<sup>th</sup> day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

2. Notification: Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.

3. Blowout Preventers: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.

4. Mud Requirement: Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of brine water. Minimum nine (9) pounds per gallon.

5. Cement Requirement: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

6. Below Ground Level Cap (Lesser Prairie-Chicken Habitat): All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The BLM is to be notified a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 10<sup>th</sup> day, the BLM is to be contacted with justification to receive an extension for completing the cut off. Upon the plugging and subsequent abandonment of wells that are located in lesser prairie-chicken habitat, the casings shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The well bore shall then be covered with a metal plate at least ¼ inch thick and welded in place. A weep hole shall be left in the plate and/or casing.

NMOCD also requires the operator to notify NMOCD when this type of dry hole marker is used. This can be done on the subsequent report of abandonment which is submitted to the BLM after the well is plugged. State that a below ground cap was installed as required in the COA's from the BLM.

7. Subsequent Plugging Reporting: Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. Show date well was plugged.

8. Trash: All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation objectives.

Timing Limitation Stipulation/ Condition of Approval for Lesser Prairie-Chicken:

From March 1<sup>st</sup> through June 15<sup>th</sup> annually, abandonment activities will be allowed except between the hours from 3:00 am and 9:00 am. Normal vehicle use on existing roads will not be restricted