

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
Oil Cons.
N.M. Div. Dist. 2
1301 W. Grand Avenue
Arlington, NM 88210
(505) 748-4200
(Reverse Side)FORM APPROVED
OMB NO. 1004-0137
Expires: February 28, 1995

5. LEASE DESIGNATION AND SERIAL NO.

NMNM0467933

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME, WELL NO.

DALE H PARKE B TR C #15

9. API WELL NO.

30-015-32390 S1

10. FIELD AND POOL, OR WILDCAT

LOCO HILLS; PADDOCK

11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA

SEC. 15-T17S-R30E

12. COUNTY OR PARISH 13. STATE

EDDY

NM

15. DATE SPUDDED 16. DATE T.D. REACHED 17. DATE COMPL. (Ready to prod.)

4/29/03

5/8/03

6/27/03

18. ELEVATIONS (DF, RKB, RT, GE, ETC.)

3693' GL

19. ELEV. CASINGHEAD

20. TOTAL DEPTH, MD & TVD

5041'

21. PLUG, BACK T.D., MD & TVD

5018'

22. IF MULTIPLE COMPL., HOW MANY*

23. INTERVALS DRILLED BY

ROTARY TOOLS

CABLE TOOLS

0 - 5041'

24. PRODUCING INTERVAL(S), OF THIS COMPLETION-TOP, BOTTOM, NAME (MD AND TVD)*

4465' - 4764' PADDOCK

25. WAS DIRECTIONAL SURVEY MADE

NO

26. TYPE ELECTRIC AND OTHER LOGS RUN

DLL, CSNG

27. WAS WELL CORED

NO

28. CASING RECORD (Report all strings set in well)

CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD	AMOUNT PULLED
13 3/8" H40	48#	357'	17 1/2"	465 SX, CIRC	NONE
8 5/8" J55	24#	1210'	12 1/4"	600 SX, CIRC	NONE
5 1/2" J55	17#	5041'	7 7/8"	1185 SX, CIRC	NONE

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
					2 7/8"	4407'	

31. PERFORATION RECORD (Interval, size and number)

4465' - 4764' (20 SHOTS)

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)

4465' - 4764'

AMOUNT AND KIND OF MATERIAL USED

ACDZ W/ 2000 GAL 15% HCL ACID

33. *

PRODUCTION

DATE FIRST PRODUCTION

6/29/03

PRODUCTION METHOD (Flowing, gas lift, pumping--size and type of pump)

PUMPING

WELL STATUS (Producing or shut-in)

PROD

DATE OF TEST

6/30/03

HOURS TESTED

24

CHOKE SIZE

PROD'N FOR TEST PERIOD

OIL--BBL.

65

GAS--MCF.

110

WATER--BBL.

240

GAS-OIL RATIO

FLOW. TUBING PRESS.

CASING PRESSURE

CALCULATED 24-HOUR RATE

OIL--BBL.

GAS--MCF.

WATER--BBL.

OIL GRAVITY-API (CORR.)

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

SOLD

TEST WITNESSED BY

TITO AGUIRRE

35. LIST OF ATTACHMENTS

LOGS, DEVIATION SURVEY

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED

TITLE

AGENT

DATE 7/15/03

*(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill-stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):

38. GEOLOGICAL MARKERS			38. GEOLOGICAL MARKERS		
NAME	TOP		NAME	TOP	
	MEAS. DEPTH	TRUE VERT. DEPTH		MEAS. DEPTH	TRUE VERT. DEPTH
YATES	1304'				
QUEEN	2190'				
SAN ANDRES	2896'				
GLORIETA	4375'				

L & M DRILLING, INC.

OIL WELL DRILLING CONTRACTORS
PO BOX 1370 ARTESIA, NEW MEXICO 88211-1370
(505) 746-4405 746-3518 748-2205

May 15, 2003

Premier Oil & Gas
c/oMarbob Energy Corporation
PO Drawer 227
Artesia, NM 88211-0227


RE: Dale H. Parke B Trac C #15
990' FNL & 2310' FEL
Sec. 15, T17S, R30E
Eddy County, New Mexico

Gentlemen:

The following is a Deviation Survey for the above captioned well.

DEPTH	DEVIATION	DEPTH	DEVIATION
238'	1°	2742'	1°
320'	1°	3234'	3/4°
813'	1°	3734'	1 1/4°
1182'	2°	4228'	1°
1681'	1/4°	4717'	3/4°
2152'	1/4°	5041'	3/4°
2648'	1 1/2°		


Very truly yours,



Eddie C. LaRue
Vice President

STATE OF NEW MEXICO }
COUNTY OF EDDY }

The foregoing was acknowledged before me
this 15th day of May, 2003.


Notary Public

