

Office

Energy, Minerals and Natural Resources

Revised July 18, 2013

District I - (575) 393-6161

1625 N. French Dr., Hobbs, NM 88240

District II - (575) 748-1283

811 S. First St., Artesia, NM 88210

District III - (505) 334-6178

1000 Rio Brazos Rd., Aztec, NM 87410

District IV - (505) 476-3460

1220 S. St. Francis Dr., Santa Fe

87505

RECEIVED

MAR 13 2019

DISTRICT II-ARTESIA O.D.

OIL CONSERVATION DIVISION

1020 South St. Francis Dr.

Santa Fe, NM 87505

WELL API NO.

30-015-43938

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil &amp; Gas Lease No.

7. Lease Name or Unit Agreement Name

Rustler Breaks 26/23 W2ML Fee Com

8. Well Number 1H

9. OGRID Number 14744

10. Pool name or Wildcat

Purple Sage; Wolfcamp (gas)

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other

2. Name of Operator

Mewbourne Oil Company

3. Address of Operator

PO Box 5270, Hobbs NM 88241

4. Well Location

Unit Letter M : 210 feet from the North line and 370 feet from the West line

Section 35 Township 24S Range 28E NMPM Eddy County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

2969' GL

## 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

## NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐TEMPORARILY ABANDON ☐ CHANGE PLANS ☐PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐DOWNHOLE COMMINGLE ☐CLOSED-LOOP SYSTEM ☐OTHER: ☐

## SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐COMMENCE DRILLING OPNS. ☐ P AND A ☐CASING/CEMENT JOB ☒OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

02/22/19

TD'ed 8 3/4" hole @ 10875'. Ran 10860' of 7" 29# HCP110 LT&C Csg. Cemented 1<sup>st</sup> lead w/225 sks Class C w/additives. Mixed @ 10.0#/g w/3.88 yd. 2<sup>nd</sup> lead w/225 sks Class C (50:50:10) w/additives. Mixed @ 11.5#/g w/2.73 yd. Tail w/400 sks Class H w/additives. Mixed @ 15.6#/g w/1.18 yd. Displaced w/399 bbls OBM. Plug down @ 7:30 AM 02/23/19. Did not circ cmt. Est TOC @ 2305'. Lift PSI @ 250# @ 3 BPM. At 4:30 AM 02/24/19, tested csg to 1500# 30 mins, held OK. FIT test to 14.5 PPG EMW. Drilled out with 6 1/8" bit.

Spud Date: 02/10/19

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE R. Caballero TITLE Regulatory DATE 3/8/19Type or print name Ruby Caballero E-mail address: rcaballero@mewbourne.com PHONE: 575-393-5905**For State Use Only**APPROVED BY: [Signature] TITLE Staff DATE 3/14/19

Conditions of Approval (if any):