

District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO: 30-015-36348
5. Indicate Type of Lease STATE [X] FEE []
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Boyd 26L
8. Well Number #001
9. OGRID Number 371755
10. Pool name or Wildcat N. SEVEN RIVERS; GLORIETA-YESO

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well [X] Gas Well [] Other []
2. Name of Operator PERCUSSION PETROLEUM OPERATING, LLC
3. Address of Operator 919 Milam, Suite 2475, Houston, TX 77002
4. Well Location Unit Letter L: 1980 feet from the South line and 660 feet from the West line.
Section 26 Township 19S Range 25E NMPM Eddy County

11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3,466' GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:
PERFORM REMEDIAL WORK [] PLUG AND ABANDON []
TEMPORARILY ABANDON [] CHANGE PLANS []
PULL OR ALTER CASING [] MULTIPLE COMPL []
DOWNHOLE COMMINGLE []
CLOSED-LOOP SYSTEM []
OTHER: []
SUBSEQUENT REPORT OF:
REMEDIAL WORK [] ALTERING CASING []
COMMENCE DRILLING OPNS. [] P AND A []
CASING/CEMENT JOB []
OTHER: Add Perfs [X]

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

6/18/18: POOH with rods, pump, and tubing.

6/19/18: RIH with 3-1/8" slick guns to perf 3spf, 120degree phasing at the following depths: 2642' - 2884'. 2642', 70', 81', 92', 2724', 56', 80', 92', 2816', 33', 49', 63', 77' & 2884' (41 holes).

6/20/18: Run packer and acidize with 5000gal 15% NEFE HCL, dropping 7/8" 1.3sp gravity ball sealers until all balls and acid were gone. Flushed with 60 bbls fresh water displacing to bottom perf at 2884'.

6/21/18: RIH with rods, pump, and tubing. Put well back on production.

6/22/18: RDMO.

RECEIVED

APR 19 2019

Spud Date: 6/18/2018

Rig Release Date: 6/22/2018

DISTRICT II-ARTESIA O.C.D.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE [Signature] TITLE: Production Engineer DATE: 4/11/2019

Type or print name: Kenny Norton E-mail address: kenny@percussionpetroleum.com PHONE: 972-352-3602

For State Use Only

APPROVED BY: [Signature] TITLE: STA H M/C DATE: 4/25/19
Conditions of Approval (if any):