Form 3160-5 (June 2015)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB NO. 1004-0137 Expires: January 31, 2018

| SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals. | | | | | 5. Lease Serial No. NMLC064391B6. If Indian, Allottee or Tribe Name | | |
|--|--|--|--|--|--|----------------------|---|
| SUBMIT IN TRIPLICATE - Other instructions on page 2 | | | | | 7. If Unit or CA/Agreement, Name and/or No. | | |
| Type of Well Oil Well | | 8. Well Name and No. INDIAN HILLS UNIT 30 | | | | | |
| 2. Name of Operator OXY USA WTP LP | WART | | 9. API Well No. 30-015-31655 | | | | |
| 3a. Address P.O. BOX 50250 MIDLAND, TX 79710 | 3b. Phone No. (include area code) Ph: 432-685-5717 | | | 10. Field and Pool or Exploratory Area INDIAN BASIN MORROW | | | |
| 4. Location of Well <i>(Footage, Sec., T., R., M., or Survey Description)</i> Sec 20 T21S R24E NWSW 1494FSL 688FWL 32.461788 N Lat, 104.526825 W Lon | | | | | 11. County or Parish, State EDDY COUNTY, NM | | |
| 12. CHECK THE AF | PROPRIATE BOX(ES) | TO INDICA | TE NATURE O | F NOTICE, | REPORT, OR OTI | HER DATA | |
| TYPE OF SUBMISSION | TYPE OF ACTION | | | | | | |
| □ Notice of Intent □ Acidize □ Alter Casing □ Casing Repair □ Change Plans □ Convert to Injection 3. Describe Proposed or Completed Operation: Clearly state all pertinent If the proposal is to deepen directionally or recomplete horizontally, given Attach the Bond under which the work will be performed or provide the following completion of the involved operations. If the operation results | | ☐ Hyd☐ New☐ Plug☐ Plug☐ Plug☐ Int details, includ give subsurface the Bond No. Osults in a multiple subsurface | □ New Construction ☑ Plug and Abandon □ Plug Back t details, including estimated starting vive subsurface locations and measure he Bond No. on file with BLM/BIA. | | ed and true vertical depths of all pertinent markers and zones. Required subsequent reports must be filed within 30 days New York Company of the company o | | |
| testing has been completed. Final Ab determined that the site is ready for final 3/11/19 - MIRU PU, atttempt to 3/12/19 - NDWH, NUBOP. RII continue ro 9732', found csg or RIH & set CIBP @ 9660', POC | andonment Notices must be file nal inspection. b kill well , ran out of wate H w/ 5.75 gauge ring, fou bliar @ 9680' Notify BI N | ed only after all a er. nd FL @ +/- { M. approved s | requirements, including the following from the foll | ing reclamation Accepte ag at TOL (| n; have been completed a 3/28/19 d for record - NIM 3/28/19 3/ | and the operator has | |
| 3/13/19 - Cementing company cancelled job 3/14/19 - WO cement crew, establish circ, M&P 50sx Cl H cmt @ 9677', I | | | | | | n & & 2010 | , |
| 3/15/19 - RIH w/ tbg & tag cmt to 8543', M&P 130sx CL H cmt | @ 9427', pressure test to , PUH, WOC | _ | | M&P MLF, | DI IH | R 2 8 2019 | |
| 14. I hereby certify that the foregoing is | Electronic Submission #4 | 159063 verified USA WTP LP, | by the BLM Well sent to the Carls | Information bad | System | , | |
| Name (Printed/Typed) DAVID STEWART | | | Title SR. REGULATORY ADVISOR | | | | |
| Signature (Electronic Submission) | | | Date 03/25/20 | 019 | | | |
| | THIS SPACE FO | R FEDERA | L OR STATE (| OFFICE US | SE | | |
| Approved By | | | Title Office | | | Date | |

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Additional data for EC transaction #459063 that would not fit on the form

32. Additional remarks, continued

3/18/19 - RIH w/ tbg & tag cmt @ 7940', M&P MLF, PUH to 7789', M&P 65sx CL H cmt, PUH, WOC.

3/19/19 - RIH w/ tbg & tag cmt @ 7647', BLM on location. M&P MLF, PUH to 6908', M&P 115sx CL C cmt, PUH WOC.

3/20/19 - RIH w/ tbg & tag cmt @ 6559', BLM on location. M&P MLF, PUH to 6112', M&P 68sx CL C cmt w/ 1.5% CaCl2, PUH, WOC. RIH w/ tbg & tag cmt @ 5916', M&P MLF, PUH to 3715', M&P 60sx CL C cmt, PUH, WOC.

3/21/19 - RIH w/ tbg & tag cmt @ 3574'. M&P MLF, PUH to 2609', M&P 85sx CL C cmt, PUH, WOC. RIH w/ tbg & tag cmt @ 2350', M&P MLF, PUH to 1250', M&P 60sx Cl C cmt, PUH, WOC.

3/22/19 - RIH w/ tbg & tag cmt @ 1130'. M&P MLF, PUH to 250', M&P 110sx CL C cmt, circ cmt to surface. ND BOP, top off casing NU WH flange. Verify cement to surface on all casing string. Notify BLM, RDPU.