

District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

RECEIVED

JUN 21 2019

OIL CONSERVATION DIVISION
1220 South St. Francis Dr. Santa Fe, NM 87505

DISTRICT II-ARTESIA O.C.D.

WELL API NO. 30-015-34512
5. Indicate Type of Lease STATE [] FEE [x]
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name SS Snakebite Fee
8. Well Number 3
9. OGRID Number 229137
10. Pool name or Wildcat Esperanza; Delaware
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3117' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)
1. Type of Well: Oil Well [x] Gas Well [] Other []
2. Name of Operator COG Operating, LLC
3. Address of Operator 600 W. Illinois Ave, Midland, TX 79701
4. Well Location Unit Letter G : 2290 feet from the N line and 1675 feet from the E line
Section 9 Township 22S Range 27E NMPM County EDDY

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:
PERFORM REMEDIAL WORK [] PLUG AND ABANDON []
TEMPORARILY ABANDON [] CHANGE PLANS []
PULL OR ALTER CASING [] MULTIPLE COMPL []
DOWNHOLE COMMINGLE []
CLOSED-LOOP SYSTEM []
OTHER: []
SUBSEQUENT REPORT OF:
REMEDIAL WORK [] ALTERING CASING []
COMMENCE DRILLING OPNS. [] P AND A [x]
CASING/CEMENT JOB []
OTHER: []

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

10/17/18 MIRU Plugging equipment. ND pump jack head. Lock out/Tagged out, pump jack secure. Unseated pump, POH w/ 199 7/8" rods, 6 K-Bars, & pump. 10/18/18 Dug out cellar, NU BOP. POH w/ tbg & tbg anchor. Set 5 1/2" CIBP @ 5045'. Circulated hole w/ salt gel, pressure tested csg to 500 psi, did not hold. Spotted 25 sx class C cmt @ 5045-4795'. WOC. 10/19/18 Tagged plug @ 4785'. Pressure tested csg, held 500 psi. Spotted 25 sx class C cmt @ 4102-3852'. Spotted 25 sx class C cmt @ 2720-2470'. Spotted 25 sx class C cmt @ 2052-1802'. Spotted 25 sx class C cmt @ 1660-1410'. Perf'd csg @ 425'. Sqz'd 50 sx class C cmt @ 425' & displaced to 300'. WOC. 10/22/18 Tagged plug @ 270'. Spotted 30 sx class C cmt @ 270' & circulated to surface. Rugged down & moved off.

Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms. www.emnrd.state.nm.us/oed.

Spud Date: []

Rig Release Date: []

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE [Signature] TITLE SCADA Tech II DATE 6/20/19

Type or print name Brian Mariano E-mail address: bmariano@cmrco.com PHONE: 412-220-0467

APPROVED BY: [Signature] TITLE Staff Mgr DATE 6/24/19

Conditions of Approval (if any):