

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED

OCD Artesia

JUL 23 2019

FORM APPROVED
OMB NO. 1004-0137
Expires: January 31, 2018

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.

DISTRICT/ARTESIA/O.C.D.

SUBMIT IN TRIPLICATE - Other instructions on page 2

1. Type of Well <input checked="" type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other		7. If Unit or CA/Agreement, Name and/or No. 8910123980
2. Name of Operator COG OPERATING LLC Contact: ABIGAIL ANDERSON E-Mail: abbym@bcmmandassociates.com		8. Well Name and No. RJ UNIT 118
3a. Address 600 W ILLINOIS AVENUE MIDLAND, TX 79701	3b. Phone No. (include area code) Ph: 432-580-7161	9. API Well No. 30-015-03156-00-S1
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Sec 27 T17S R29E SESW Tract 2A 1295FSL 2615FWL		10. Field and Pool or Exploratory Area GRAYBURG
		11. County or Parish, State EDDY COUNTY, NM

12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Hydraulic Fracturing	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input type="checkbox"/> Other
	<input type="checkbox"/> Change Plans	<input checked="" type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.

- Set 7" CIBP @ 2700'. Spot 25 sx cmt on top. Circulate hole w/ MLF.
- Set 7" CIBP @ 2350'. Spot 25 sx cmt on top. Pressure test csg. to 500 psi. Circulate hole w/ MLF.
- Perf & Sqz 55 sx @ 760-660. WOC & Tag-
- Perf & Sqz 35 sx @ 60' to surface.
- Cut off wellhead and weld on ~~Below~~ Ground Dry-Hole Marker.

GC 7/24/19
Accepted for record - NMOCD

760-630 Shoe & Bleat. Add Plug. Spot
Cmt from 330-230

Note 3 & 4. Records indicate Remedial Sqz Job.
Cmt Braden head 900' - 20' cmt (CBL).

SEE ATTACHED FOR

CONDITIONS OF APPROVAL

14. I hereby certify that the foregoing is true and correct. Electronic Submission #463654 verified by the BLM Well Information System For COG OPERATING LLC, sent to the Carlsbad Committed to AFMSS for processing by DEBORAH MCKINNEY on 05/01/2019 (19DLM0455SE)	
Name (Printed/Typed) ABIGAIL ANDERSON	Title AGENT
Signature (Electronic Submission)	Date 05/01/2019

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved By <i>James R. [Signature]</i>	Title SALT	Date 5-12-19
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.		Office 110

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)


** BLM REVISED **

COG Operating LLC

Lease & Well # RJ Unit #118

Spud: 10/6/50

Elevation - 3547'



KB -

T/salt 280
 B/salt 680
 Qu 1810
 GB 2215
 SA 2575
 Lov 2680

8 5/8" csg 28# @ 710', 100 sx cmt.

Pumped 700 sx dn annulus, TOC 20', bottom @ 900'. ✓

Top of cmt est @ 1,452', survey. ✓

5 7/8" subs
 50 7/8" C-75 Rods
 86 3/4" T-66 Rods
 2"x1.5"x10' RWTC Pump

108 Jts 2-3/8"
 SN @ 3,439'

San Andres
 2414-2432'
 Acidized w/500 gal 15% HCL, frac w/???? gal, 50,000 # sd.

7" 23# csg @ 2778'. Cmt w/100 sx. TPC @ 1452, survey ✓

San Andres
 OH 2778 - 3500'.
 Acidized 2778-2970 w/7500 gal HCL, 5 treatments
 Fraced 3379-3500 w/40,000 gal gw, 1000 gal HCL, 50,000 # sd

6" OH to 3500'

COG Operating LLC

Lease & Well # RJ Unit #118

Spud: 10/6/50


Elevation -3547'

④ Perf csg 80-50 c
60 - surface

③ Perf csg 55-50 c
760 - 660 w/ TAG

② 7" CIBC 2350 w/ 25 SA

① 7" CIBC 2700 w/ 25 SA



KB -

8 5/8" csg 28# @ 710', 100 sx cmt.

Pumped 700 sx dn annulus, TOC 20', bottom @ 900'.

Top of cmt est @ 1.452', survey.

5 7/8" subs

50 7/8" C-75 Rods

86 3/4" T-66 Rods

108 Jts. 2-3/8"
SN @ 3,439'

2"x1.5"x10' RWTC Pump

San Andres

2414-2432'

Acidized w/500 gal 15% HCL, frac w/???? gal, 50,000 # sd.

7" 23# csg @ 2778'. Cmt w/100 sx. TPC @ 1452, survey

San Andres

OH 2778 - 3500'.

Acidized 2778-2970 w/7500 gal HCL, 5 treatments

Frac'd 3379-3500 w/40,000 gal gw, 1000 gal HCL, 50,000 # sd

6" OH to 3500'

BUREAU OF LAND MANAGEMENT
Carlsbad Field Office
620 East Greene Street
Carlsbad, New Mexico 88220
575-234-5972

Permanent Abandonment of Federal Wells
Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within ninety (90) days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90th day provide this office, prior to the 90th day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

2. Notification: Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.

3. Blowout Preventers: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.

4. Mud Requirement: Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of brine water. Minimum nine (9) pounds per gallon.

5. Cement Requirement: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

6. Dry Hole Marker: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The BLM is to be notified a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 10th day, the BLM is to be contacted with justification to receive an extension for completing the cut off.

The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement, unless otherwise noted in COA (requirements will be attached). The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).

7. Subsequent Plugging Reporting: Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. Show date well was plugged.

8. Trash: All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation objectives.