Submit 1 Copy To Appropriate District State of New Mexico	Form C-103
Office District 1 – (575) 393-6161 <b>RECEIVED</b> Minerals and Natural Resour	rces Revised July 18, 2013
1625 N. French Dr., Hobbs, NM 88240	WELL API NO.
	5. Indicate Type of Lease
1000 Rio Brazos Rd., Aztec, NM 87410	STATE 🛛 FEE 🗌
811 S. First St., Artesia, NM 88210 JAN USTICATION DIVISION   District III – (505) 334-6178 1220 South St. Francis Dr.   1000 Rio Brazos Rd., Aztec, NM 87410 1220 South St. Francis Dr.   District IV – (505) 476-3460 FMNRD-OCD ARTESIA, NM 87505   1220 S. St. Francis Dr., Santa Fe, NM	6. State Oil & Gas Lease No.
87505	325165
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO	7. Lease Name or Unit Agreement Name
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH	QUAIL 2 STATE COM
PROPOSALS.) 1. Type of Well: Oil Well 🔀 Gas Well 🗌 Other	8. Well Number #725H
2. Name of Operator	9. OGRID Number
EOG RESOURCES	10. Pool name or Wildcat
3. Address of Operator P O BOX 2267, MIDLAND TX 79702	[98220] PURPLE SAGE; WOLFCAMP (GAS
4. Well Location	
	and 1596 feet from the West line
Section 02 Township 26E Range 30E	NMPM County EDDY CO
11. Elevation (Show whether DR, RKB, RT,	GR, etc.)
3207 GL	
12. Check Appropriate Box to Indicate Nature of N	Notice Report or Other Data
	AL WORK
	CEMENT JOB
13. Describe proposed or completed operations. (Clearly state all pertinent de of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Mul	
proposed completion or recompletion.	
12/03/19 8-3/4" hole 12/03/19 Intermediate Hole @ 10,573' MD, 10,471' TVD	
Casing shoe @ 10,558' MD	2
Casing shoe @ 10,558' MD Ran 7-5/8'', 29.7#, HCP-110 BTC SC (0' - 1,046') Ran 7-5/8'', 29.7#, ECP-110 MO-FXL (1,046' - 10,558')	ret?
Casing shoe @ 10,558' MD Ran 7-5/8'', 29.7#, HCP-110 BTC SC (0' - 1,046') Ran 7-5/8'', 29.7#, ECP-110 MO-FXL (1,046' - 10,558') Stage 1: Lead Cement w/ 385 sx Class H (1.20 yld, 15.6 ppg) Test casing to 2,500 psi for 30 min - good Did not circ cement to surface. TOC @ 7.087 by Ca	ic set pt?
Casing shoe @ 10,558' MD Ran 7-5/8", 29,7#, HCP-110 BTC SC (0' - 1,046') Ran 7-5/8", 29,7#, ECP-110 MO-FXL (1,046' - 10,558') Stage 1: Lead Cement w/ 385 sx Class H (1.20 yld, 15.6 ppg) Test casing to 2,500 psi for 30 min - good Did not circ cement to surface, TOC @ 7,087 by Ca Stage 2: Bradenhead squeeze w/ 1,000 sx Class C (1.51 yld, 14.8 ppg) TOC @ 50' by Calc Stage 2: Toro out w/ 165 cx Class C (1.25 yld, 14.8 ppg) TOC @ 50' by Calc	ic cas set at?
Casing shoe @ 10,558' MD Ran 7-5/8", 29.7#, HCP-110 BTC SC (0' - 1,046') Ran 7-5/8", 29.7#, ECP-110 MO-FXL (1,046' - 10,558') Stage 1: Lead Cement w/ 385 sx Class H (1.20 yld, 15.6 ppg) Test casing to 2,500 psi for 30 min - good Did not circ cement to surface, TOC @ 7,087 by Ca Stage 2: Bradenhead squeeze w/ 1,000 sx Class C (1.51 yld, 14.8 ppg) TOC @ 50' by Calc Stage 3: Top out w/ 165 sx Class C (1.35 yld, 14.8 ppg) TOC @ surface Drilling 6-3/4" hole 12/08/19 6-3/4" hole	Devoth 's CBS Seit Art?
Casing shoe @ 10,558' MD Ran 7-5/8", 29.7#, HCP-110 BTC SC (0' - 1,046') Ran 7-5/8", 29.7#, ECP-110 MO-FXL (1,046' - 10,558') Stage 1: Lead Cement w/ 385 sx Class H (1.20 yld, 15.6 ppg) Test casing to 2,500 psi for 30 min - good Did not circ cement to surface, TOC @ 7,087 by Ca Stage 2: Bradenhead squeeze w/ 1,000 sx Class C (1.51 yld, 14.8 ppg) TOC @ 50' by Calc Stage 3: Top out w/ 165 sx Class C (1.35 yld, 14.8 ppg) TOC @ surface Drilling 6-3/4" hole 12/08/19 Production Hole @ 16,092' MD, 11,385' TVD	Depoth is CBS Set At?
Casing shoe @ 10,558' MD Ran 7-5/8", 29.7#, HCP-110 BTC SC (0' - 1,046') Ran 7-5/8", 29.7#, ECP-110 MO-FXL (1,046' - 10,558') Stage 1: Lead Cement w/ 385 sx Class H (1.20 yld, 15.6 ppg) Test casing to 2,500 psi for 30 min - good Did not circ cement to surface, TOC @ 7,087 by Ca Stage 2: Bradenhead squeeze w/ 1,000 sx Class C (1.51 yld, 14.8 ppg) TOC @ 50' by Calc Stage 3: Top out w/ 165 sx Class C (1.35 yld, 14.8 ppg) TOC @ surface Drilling 6-3/4" hole 12/08/19 Production Hole @ 16,092' MD, 11,385' TVD Casing shoe @ 16,078' MD, 11,385' TVD 5-1/2", 20#, EY HCP-110, RDT-BTX (MJ @ 612', 10,870', and 15,611')	Depoth is CBS Seit Art?
Casing shoe @ 10,558' MD Ran 7-5/8", 29.7#, HCP-110 BTC SC (0' - 1,046') Ran 7-5/8", 29.7#, ECP-110 MO-FXL (1,046' - 10,558') Stage 1: Lead Cement w/ 385 sx Class H (1.20 yld, 15.6 ppg) Test casing to 2,500 psi for 30 min - good Did not circ cement to surface, TOC @ 7,087 by Ca Stage 2: Bradenhead squeeze w/ 1,000 sx Class C (1.51 yld, 14.8 ppg) TOC @ 50' by Calc Stage 3: Top out w/ 165 sx Class C (1.35 yld, 14.8 ppg) TOC @ surface Drilling 6-3/4" hole 12/08/19 6-3/4" hole 12/08/19 Production Hole @ 16,092' MD, 11,385' TVD Casing shoe @ 16,078' MD, 11,385' TVD 5-1/2", 20#, EY HCP-110, RDT-BTX (MJ @ 612', 10,870', and 15,611') Cement w/ 525 sx Class C (1.19 yld, 14.5 ppg) Did not circ cement to surface, TOC @ 9,514' by Calc Waitingon CBL RR	Depoth is CBS Set At?
Casing shoe @ 10,558' MD Ran 7-5/8'', 29.7#, HCP-110 BTC SC (0' - 1,046') Ran 7-5/8'', 29.7#, HCP-110 MO-FXL (1,046' - 10,558') Stage 1: Lead Cement w/ 385 sx Class H (1.20 yld, 15.6 ppg) Test casing to 2,500 psi for 30 min - good Did not circ cement to surface, TOC @ 7,087 by Ca Stage 2: Bradenhead squeeze w/ 1,000 sx Class C (1.51 yld, 14.8 ppg) TOC @ 50' by Calc Stage 3: Top out w/ 165 sx Class C (1.35 yld, 14.8 ppg) TOC @ surface Drilling 6-3/4" hole 12/08/19 Production Hole @ 16,092' MD, 11,385' TVD Casing shoe @ 16,078' MD, 11,385' TVD 5-1/2'', 20#, EY HCP-110, RDT-BTX (MJ @ 612', 10,870', and 15,611') Cement w/ 525 sx Class C (1.19 yld, 14.5 ppg)	Depoth is CBS Set Bot?
Casing shoe @ 10,558' MD Ran 7-5/8'', 29.7#, HCP-110 BTC SC (0' - 1,046') Ran 7-5/8'', 29.7#, HCP-110 MO-FXL (1,046' - 10,558') Stage 1: Lead Cement w/ 385 sx Class H (1.20 yld, 15.6 ppg) Test casing to 2,500 psi for 30 min - good Did not circ cement to surface, TOC @ 7,087 by Ca Stage 2: Bradenhead squeeze w/ 1,000 sx Class C (1.51 yld, 14.8 ppg) TOC @ 50' by Calc Stage 3: Top out w/ 165 sx Class C (1.35 yld, 14.8 ppg) TOC @ surface Drilling 6-3/4" hole 12/08/19 Production Hole @ 16,092' MD, 11,385' TVD Casing shoe @ 16,078' MD, 11,385' TVD 5-1/2'', 20#, EY HCP-110, RDT-BTX (MJ @ 612', 10,870', and 15,611') Cement w/ 525 sx Class C (1.19 yld, 14.5 ppg)	Depoth 's CBS Seit Apt?
Casing shoe @ 10,558' MD Ran 7-5/8", 29.7#, HCP-110 BTC SC (0' - 1,046') Ran 7-5/8", 29.7#, ECP-110 MO-FXL (1,046' - 10,558') Stage 1: Lead Cement w/ 385 sx Class H (1.20 yld, 15.6 ppg) Test casing to 2,500 psi for 30 min - good Did not circ cement to surface, TOC @ 7,087 by Ca Stage 2: Bradenhead squeeze w/ 1,000 sx Class C (1.51 yld, 14.8 ppg) TOC @ 50' by Calc Stage 3: Top out w/ 165 sx Class C (1.35 yld, 14.8 ppg) TOC @ surface Drilling 6-3/4" hole 12/08/19 Production Hole @ 16,092' MD, 11,385' TVD Casing shoe @ 16,078' MD, 11,385' TVD 5-1/2", 20#, EY HCP-110, RDT-BTX (MJ @ 612', 10,870', and 15,611') Cement w/ 525 sx Class C (1.19 yld, 14.5 ppg) Did not circ cement to surface, TOC @ 9,514' by Calc Waitingon CBL RR	
Casing shoe @ 10,558' MD Ran 7-5/8", 29.7#, HCP-110 BTC SC (0' - 1,046') Ran 7-5/8", 29.7#, ECP-110 MO-FXL (1,046' - 10,558') Stage 1: Lead Cement w/ 385 sx Class H (1.20 yld, 15.6 ppg) Test casing to 2,500 psi for 30 min - good Did not circ cement to surface, TOC @ 7,087 by Ca Stage 2: Bradenhead squeeze w/ 1,000 sx Class C (1.51 yld, 14.8 ppg) TOC @ 50' by Calc Stage 3: Top out w/ 165 sx Class C (1.35 yld, 14.8 ppg) TOC @ surface Drilling 6-3/4" hole 12/08/19 Production Hole @ 16,092' MD, 11,385' TVD Casing shoe @ 16,078' MD, 11,385' TVD 5-1/2", 20#, EY HCP-110, RDT-BTX (MJ @ 612', 10,870', and 15,611') Cement w/ 525 sx Class C (1.19 yld, 14.5 ppg) Did not circ cement to surface, TOC @ 9,514' by Calc Waitingon CBL RR	Depoth 's CBS Seit Apt? 10/19
Casing shoe @ 10,558' MD Ran 7-5/8", 29.7#, HCP-110 BTC SC (0' - 1,046') Ran 7-5/8", 29.7#, ECP-110 MO-FXL (1,046' - 10,558') Stage 1: Lead Cement w/ 385 sx Class H (1.20 yld, 15.6 ppg) Test casing to 2,500 psi for 30 min - good Did not circ cement to surface, TOC @ 7,087 by Ca Stage 2: Bradenhead squeeze w/ 1,000 sx Class C (1.51 yld, 14.8 ppg) TOC @ 50' by Calc Stage 3: Top out w/ 165 sx Class C (1.35 yld, 14.8 ppg) TOC @ surface Drilling 6-3/4" hole 12/08/19 Production Hole @ 16,092' MD, 11,385' TVD Casing shoe @ 16,078' MD, 11,385' TVD 5-1/2", 20#, EY HCP-110, RDT-BTX (MJ @ 612', 10,870', and 15,611') Cement w/ 525 sx Class C (1.19 yld, 14.5 ppg) Did not circ cement to surface, TOC @ 9,514' by Calc Waitingon CBL RR Spud Date: 11/07/19 Rig Release Date: 12/12	10/19
Casing shoe @ 10,558' MD Ran 7-5/8", 29.7#, HCP-110 BTC SC (0' - 1,046') Ran 7-5/8", 29.7#, ECP-110 MO-FXL (1,046' - 10,558') Stage 1: Lead Cement w/ 385 sx Class H (1.20 yld, 15.6 ppg) Test casing to 2,500 psi for 30 min - good Did not circ cement to surface, TOC @ 7,087 by Ca Stage 2: Bradenhead squeeze w/ 1,000 sx Class C (1.51 yld, 14.8 ppg) TOC @ 50' by Calc Stage 3: Top out w/ 165 sx Class C (1.35 yld, 14.8 ppg) TOC @ surface Drilling 6-3/4" hole 12/08/19 Production Hole @ 16,092' MD, 11,385' TVD Casing shoe @ 16,078' MD, 11,385' TVD 5-1/2", 20#, EY HCP-110, RDT-BTX (MJ @ 612', 10,870', and 15,611') Cement w/ 525 sx Class C (1.19 yld, 14.5 ppg) Did not circ cement to surface, TOC @ 9,514' by Calc Waitingon CBL RR Spud Date: 11/07/19 Rig Release Date: 12/12	10/19
Casing shoe @ 10,558' MD Ran 7-5/8'', 29.7#, HCP-110 BTC SC (0' - 1,046') Ran 7-5/8'', 29.7#, ECP-110 MO-FXL (1,046' - 10,558') Stage 1: Lead Cement w/ 385 sx Class H (1.20 yld, 15.6 ppg) Test casing to 2,500 psi for 30 min - good Did not circ cement to surface, TOC @ 7,087 by Ca Stage 2: Bradenhead squeeze w/ 1,000 sx Class C (1.51 yld, 14.8 ppg) TOC @ 50' by Calc Stage 3: Top out w/ 165 sx Class C (1.35 yld, 14.8 ppg) TOC @ surface Drilling 6-3/4" hole 12/08/19 Production Hole @ 16,092' MD, 11,385' TVD Casing shoe @ 16,078' MD, 11,385' TVD Casing shoe @ 16,078' MD, 11,385' TVD S-1/2'', 20#, EY HCP-110, RDT-BTX (MJ @ 612', 10,870', and 15,611') Cement w/ 525 sx Class C (1.19 yld, 14.5 ppg) Did not circ cement to surface, TOC @ 9,514' by Calc Waitingon CBL RR Spud Date: 11/07/19 Rig Release Date: 12/14 I hereby certify that the information above is true and complete to the best of my kn	10/19 nowledge and belief.
Casing shoe @ 10,558' MD Ran 7-5/8'', 29.7#, HCP-110 BTC SC (0' - 1,046') Ran 7-5/8'', 29.7#, HCP-110 MO-FXL (1,046' - 10,558') Stage 1: Lead Cement w/ 385 sx Class H (1.20 yld, 15.6 ppg) Test casing to 2,500 psi for 30 min - good Did not circ cement to surface, TOC @ 7,087 by Ca Stage 2: Bradenhead squeeze w/ 1,000 sx Class C (1.51 yld, 14.8 ppg) TOC @ 50' by Calc Stage 3: Top out w/ 165 sx Class C (1.35 yld, 14.8 ppg) TOC @ surface Drilling 6-3/4" hole 12/08/19 Production Hole @ 16,092' MD, 11,385' TVD Casing shoe @ 16,078' MD, 11,385' TVD Shoe @ 16,078' MD, 11,385' TVD Sement w/ 525 sx Class C (1.19 yld, 14.5 ppg) Did not circ cement to surface, TOC @ 9,514' by Calc Waitingon CBL RR Spud Date: 11/07/19 I hereby certify that the information above is true and complete to the best of my kn	10/19 nowledge and belief.
Casing shoe @ 10,558' MD Ran 7-5/8", 29.7#, HCP-110 BTC SC (0' - 1,046') Ran 7-5/8", 29.7#, ECP-110 MO-FXL (1,046' - 10,558') Stage 1: Lead Cement w/ 385 sx Class H (1.20 yld, 15.6 ppg) Test casing to 2,500 psi for 30 min - good Did not circ cement to surface, TOC @ 7,087 by Ca Stage 2: Bradenhead squeeze w/ 1,000 sx Class C (1.51 yld, 14.8 ppg) TOC @ 50' by Calc Stage 3: Top out w/ 165 sx Class C (1.35 yld, 14.8 ppg) TOC @ surface Drilling 6-3/4" hole 12/08/19 Production Hole @ 16,092' MD, 11,385' TVD Casing shoe @ 16,078' MD, 11,385' TVD Casing shoe @ 16,078' MD, 11,385' TVD 5-1/2", 20#, EY HCP-110, RDT-BTX (MJ @ 612', 10,870', and 15,611') Cement w/ 525 sx Class C (1.19 yld, 14.5 ppg) Did not circ cement to surface, TOC @ 9,514' by Calc Waitingon CBL RR Spud Date: 11/07/19 Rig Release Date: 12/12 I hereby certify that the information above is true and complete to the best of my knows SIGNATURE MARCH SIGNATURE MARCH SIGNATURE MARCH SIGNATURE Casing Shoe @ 16,078 MD, 11,385' TVD Casing Shoe @ 16,078' MD, 11,385' TVD Signation of the completent to surface, TOC @ 9,514' by Calc Waitingon CBL RR Spud Date: 11/07/19 TITLE Sr. Regulatory	10/19 nowledge and belief. Administrator DATE 12/19/19
Casing shoe @ 10,558' MD Ran 7-5/8'', 29.7#, HCP-110 BTC SC (0' - 1,046') Ran 7-5/8'', 29.7#, HCP-110 MO-FXL (1,046' - 10,558') Stage 1: Lead Cement w/ 385 sx Class H (1.20 yld, 15.6 ppg) Test casing to 2,500 psi for 30 min - good Did not circ cement to surface, TOC @ 7,087 by Ca Stage 2: Bradenhead squeeze w/ 1,000 sx Class C (1.51 yld, 14.8 ppg) TOC @ 50' by Calc Stage 3: Top out w/ 165 sx Class C (1.35 yld, 14.8 ppg) TOC @ surface Drilling 6-3/4'' hole 12/08/19 Production Hole @ 16,092' MD, 11,385' TVD Casing shoe @ 16,078' MD, 11,385' TVD Casing shoe @ 16,078' MD, 11,385' TVD 5-1/2'', 20#, EY HCP-110, RDT-BTX (MJ @ 612', 10,870', and 15,611') Cement w/ 525 sx Class C (1.19 yld, 14.5 ppg) Did not circ cement to surface, TOC @ 9,514' by Calc Waitingon CBL RR Spud Date: 11/07/19 Rig Release Date: 12/12 I hereby certify that the information above is true and complete to the best of my kn SIGNATURE MM Join above is true and complete to the best of my kn SIGNATURE MM Join above is true and complete to the best of my kn SIGNATURE EMM Join above is true and complete to the best of my kn SIGNATURE EMM Join above is true and complete to the best of my kn SIGNATURE EMM Join above is true and complete to the best of my kn SIGNATURE EMM Join above is true and complete to the best of my kn SIGNATURE EMM Join above is true and complete to the best of my kn SIGNATURE EMM Join above is true and complete to the best of my kn SIGNATURE EMM Join above is true and complete to the best of my kn SIGNATURE EMM Join above is true and complete to the best of my kn SIGNATURE EMM Join ADV SIGNATURE E-mail address: Emmily_for	10/19 nowledge and belief. Administrator DATE 12/19/19 ollis@eogresources.comone: 432-848-9163
Casing shoe @ 10,558' MD Ran 7-5/8'', 29.7#, HCP-110 BTC SC (0' - 1,046') Ran 7-5/8'', 29.7#, HCP-110 MO-FXL (1,046' - 10,558') Stage 1: Lead Cement w/ 385 sx Class H (1.20 yld, 15.6 ppg) Test casing to 2,500 psi for 30 min - good Did not circ cement to surface, TOC @ 7,087 by Ca Stage 2: Bradenhead squeeze w/ 1,000 sx Class C (1.51 yld, 14.8 ppg) TOC @ 50' by Calc Stage 3: Top out w/ 165 sx Class C (1.35 yld, 14.8 ppg) TOC @ surface Drilling 6-3/4" hole 12/08/19 Production Hole @ 16,092' MD, 11,385' TVD Casing shoe @ 16,078' MD, 11,385' TVD Suff Casing shoe @ 16,078' MD, 11,385' TVD Casing shoe @ 16,078' MD, 11,385' TVD Suff Casing shoe @ 16,078' MD, 11,385' TVD Casing shoe @ 16,078' MD, 11,385' TVD Suff Casing shoe @ 16,078' MD	nowledge and belief. Administrator $DATE \frac{12}{19}$ ollis@eogresources.comONE: $\frac{432-848-9163}{2}$
Casing shoe @ 10,558' MD Ran 7-5/8'', 29.7#, HCP-110 BTC SC (0' - 1,046') Ran 7-5/8'', 29.7#, HCP-110 MO-FXL (1,046' - 10,558') Stage 1: Lead Cement wi 385 sx Class H (1.20 yld, 15.6 ppg) Test casing to 2,500 psi for 30 min - good Did not circ cement to surface, TOC @ 7,087 by Ca Stage 2: Bradenhead squeeze w/ 1,000 sx Class C (1.51 yld, 14.8 ppg) TOC @ 50' by Calc Stage 3: Top out w/ 165 sx Class C (1.35 yld, 14.8 ppg) TOC @ surface Drilling 6-3/4" hole 12/08/19 6-3/4" hole 12/08/19 Froduction Hole @ 16,092' MD, 11,385' TVD Casing shoe @ 16,078' MD, 14.5 ppg) Did not circ cement to surface, TOC @ 9,514' by Calc Waitingon CBL RR Spud Date: 11/07/19 I hereby certify that the information above is true and complete to the best of my kn SIGNATURE Multiply follis For State Use Only APPROVED BY: TITLE APPROVED BY: TITLE	10/19 nowledge and belief. Administrator DATE 12/19/19 ollis@eogresources.comone: 432-848-9163
Casing shoe @ 10,558' MD Ran 7-5/8'', 29.7#, HCP-110 BTC SC (0' - 1,046') Ran 7-5/8'', 29.7#, HCP-110 MO-FXL (1,046' - 10,558') Stage 1: Lead Cement w/ 385 sx Class H (1.20 yld, 15.6 ppg) Test casing to 2,500 psi for 30 min - good Did not circ cement to surface, TOC @ 7,087 by Ca Stage 2: Bradenhead squeeze w/ 1,000 sx Class C (1.51 yld, 14.8 ppg) TOC @ 50' by Calc Stage 3: Top out w/ 165 sx Class C (1.35 yld, 14.8 ppg) TOC @ surface Drilling 6-3/4" hole 12/08/19 6-3/4" hole 12/08/19 Production Hole @ 16,092' MD, 11,385' TVD Casing shoe @ 16,078' MD, 11,385' TVD Solut not circ cement to surface, TOC @ 9,514' by Calc Waitingon CBL RR Spud Date: 11/07/19 I hereby certify that the information above is true and complete to the best of my kn SIGNATURE Multiple Multiple Multiple Multiple Multiple Signa Case S	nowledge and belief. Administrator $DATE \frac{12}{19}$ ollis@eogresources.comONE: $\frac{432-848-9163}{2}$