

Submit 1 Copy To Appropriate District
Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-33939
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name SALT DRAW 10 STATE
8. Well Number 1
9. OGRID Number 372137
10. Pool name or Wildcat MORROW

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
CHISHOLM ENERGY OPERATING, LLC

3. Address of Operator 801 CHERRY STREET, SUITE 1200-UNIT 20
FORT WORTH, TX 76102

4. Well Location
Unit Letter T : 840 feet from the NORTH line and 660 feet from the EAST line
Section 10 Township 25S Range 28E NMPM County EDDY

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☒ CHANGE PLANS ☐
PULL OR ALTER CASING ☒ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐
CLOSED-LOOP SYSTEM ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: TEMPORARILY ABANDON ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

09/09/2019-PACKER LOCATED @12604'
09/10/2019-CUT TUBING @ 12,585'; POH LAID DOWN 279 JTS OF 2 3/8" TUBING
9/12/2019-SET CIBP @ 12530' MD, MADE TWO DUMP BAILER RUNS OF CLASS C CEMENT TO
SPOT 35' CMNT ON TOP OF CIBP W/TOC @ 12495' MD
10/30/2019-MIT SCHEDULED; MIT FAILED; D. SMOLIK ON LOCATION
PA PAPERWORK TO BE FILED ASAP

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jennifer Elrod TITLE SR. REGULATORY TECH DATE 01/24/2020

Type or print name JENNIFER ELROD E-mail address: jelrod@chisholmenergy.com PHONE: 817-953-3728
For State Use Only

APPROVED BY: "Denied" TITLE "Denied" DATE 1/23/20
Conditions of Approval (if any):

TEMORARILY ABANDONED WELLBORE DIAGRAM

LEASE: Salt Draw 10 State	WELL: 1	FIELD: Salt Draw	API: 30-015-33939
LOC: 840 FN & 660 FE	SEC: 10	BLK: T25S R28E	Reservoir: Morrow
SVY: 0	GL: 2961	CTY/ST: Eddy Co., NM	SPUD: 2/27/2005
CURRENT STATUS: Producing	KB: 2980	DF: 2979	TD DATE: 4/27/2005
			COMP. DATE: 1/10/2006

FRESH WATER
DEPTH:

HOLE SIZE: 0
 SURF CSG & SIZE: 13-3/8" 54.5# K-55
 SET @: 555'
 SXS CMT: 220 sx 35/65 Poz tail w/200 sx C
 CIRC: yes
 TOC AT: surface
 TOC BY: Circ.

*****GEOLOGY*****
 TOPS OF ALL ZONES
 PRODUCTIVE OF HYDRO-
 CARBONS:

TBG:
 JTS:
 SN:
 TAC:
 ROD SIZE:

TA-09/12/2019
 TOC @ 12495'
 35' DUMP BAIL CLASS C CMNT
 CIBP SET @ 12530
 CUT TBNG @ 12585
 PKR @ 12604'

PKR:
 TYPE:

HOLE SIZE:
 INT. CSG & SIZE: 9-5/8" 40# S&P & J-55
 SET @: 5015'
 SXS CMT: Lead=350 sx 35/65 Poz tail=200 sx C
 SXS CMT: Lead=1050 sx 35/65 Poz tail=100 sx C
 CIRC: Circ off DV tool 2nd to surface
 TOC AT: Surface
 TOC BY: circ.

SQUEEZE JOBS:

OH ID:
 COTD:
 PBDT: 12815
 TD: 13400

12689-12,697
 12,760-12,764
 CIBP @ 12,850 w/35' cmt on top
 12,864-12,884
 12,966-12,972
 12,997-13,000
 13,106-10'
 13170-74'
 13,180-84'
 13,214-24'

LINER:

HOLE SIZE: 0
 PROD. CSG & SIZE: 7" 26&29# P-110 & N-80
 SET @: 11,700'
 SXS CMT: lead=735 sx 35/65 Poz tail=400 sx
 CIRC: no
 TOC AT: 4100'
 TOC BY: TS

HOLE SIZE:
 PROD. CSG & SIZE: 4-1/2" 15.1# P-110
 Top @: 11,409'
 Btm @: 13398'
 SXS CMT: 300 sx H
 CIRC: Tested liner top to 1000#

OPEN HOLE: