Submit 1 Copy To Appropriate District	State of New Mexico		Form C-103
Office District I – (575) 393-6161	Energy, Minerals and Natural Re	sources	Revised July 18, 2013
1625 N. French Dr., Hobbs, NM 88240			WELL API NO.
<u>District II</u> – (575) 748-1283	OIL CONSERVATION DIV	ISION	30-015-46338
811 S. First St., Artesia, NM 88210			5. Indicate Type of Lease
<u>District III</u> – (505) 334-6178 1000 Rio Brazos Rd., Aztec, NM 87410	1220 South St. Francis D	'I]·	STATE FEE
District IV – (505) 476-3460	Santa Fe, NM 87505		6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM			
87505	The same property of the same same same same same same same sam	<u> </u>	7. I am Name and Huit Assessment Name
	CES AND REPORTS ON WELLS	TV TO A	7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPUS	ALS TO DRILL OR TO DEEPEN OR PLUG BAC ATION FOR PERMIT" (FORM C-101) FOR SUC	H	Styx 17 W0PA Fee
PROPOSALS.)	ATION TOKT ERWIT (LORGY C-101) LOK 30C	<b>`</b>	8. Well Number 2H
· · · · · · · · · · · · · · · · · · ·	Gas Well 🔯 Other		
2. Name of Operator			9. OGRID Number 14744
Mewbourne Oil Company			
3. Address of Operator			10. Pool name or Wildcat
PO Box 5270, Hobbs NM 88241			Purple Sage; Wolfcamp (gas)
	<del></del>		
4. Well Location	<i>/</i>		
Unit Letter _A:_29	4feet from theNorth line and		_feet from theEastline
Section 20	Township 23S Rang	e 28E	NMPM Eddy County
	11. Elevation (Show whether DR, RKB,	RT, GR, etc	2.)
	3037' GL	, , , , , ,	
	200. 32		
		CAT	D ( ) O(1 = ) D=4=
12. Check A	appropriate Box to Indicate Nature	of Notice	Report or Other Data
		0.11	DOEOUENT DEDOUT OF
NOTICE OF IN		1	BSEQUENT REPORT OF:
PERFORM REMEDIAL WORK 🗌	12007112712011	EDIAL WO	<del>_</del>
TEMPORARILY ABANDON	CHANGE PLANS	IMENCE DI	RILLING OPNS. P AND A
PULL OR ALTER CASING	MULTIPLE COMPL	ING/CEMEI	NT JOB 🛛
DOWNHOLE COMMINGLE	_		
<u> </u>			
CLOSED-LOOP SYSTEM U	П ОТН	FR·	
12 Describe represent or commit			nd give pertinent dates, including estimated date
			nd give pertment dates, merading estimated date
13. Describe proposed of compr	LANGE BLUE 10 15 7 14 NMAC For	Multiple C	ompletions. Attach wellhore diagram of
of starting any proposed wo	rk). SEE RULE 19.15.7.14 NMAC. For	Multiple C	ompletions: Attach wellbore diagram of
of starting any proposed wo proposed completion or reco	rk). SEE RULE 19.15.7.14 NMAC. For	Multiple C	ompletions: Attach wellbore diagram of
of starting any proposed wo proposed completion or reco	rk). SEE RULE 19.15.7.14 NMAC. For	Multiple C	ompletions: Attach wellbore diagram of
of starting any proposed wo proposed completion or reco	rk). SEE RULE 19.15.7.14 NMAC. For ompletion.	Multiple C	ompletions: Attach wellbore diagram of
of starting any proposed wo proposed completion or reconstruction of the starting any proposed wo proposed completion or reconstruction of the starting any proposed wo propos	rk). SEE RULE 19.15.7.14 NMAC. For ompletion.  of 13 3/8" 54.5# J55 ST&C Csg. Cemen	Multiple C	ompletions: Attach wellbore diagram of sks Class C w/2% CaCl2. Mixed @ 14.8#/g
of starting any proposed wo proposed completion or reconstruction of the second starting and proposed with the second starting any proposed work and second	rk). SEE RULE 19.15.7.14 NMAC. For ompletion.  of 13 3/8" 54.5# J55 ST&C Csg. Cement Plug down @ 6:15 PM 12/24/19. Circ 8	Multiple C  ed with 425 sks of cmt t	ompletions: Attach wellbore diagram of sks Class C w/2% CaCl2. Mixed @ 14.8#/g o the pit. Test BOPE to 5000# & Annular to
of starting any proposed wo proposed completion or reconstruction of the second starting and proposed with the second starting any proposed work and second	rk). SEE RULE 19.15.7.14 NMAC. For ompletion.  of 13 3/8" 54.5# J55 ST&C Csg. Cemen	Multiple C  ed with 425 sks of cmt t	ompletions: Attach wellbore diagram of sks Class C w/2% CaCl2. Mixed @ 14.8#/g o the pit. Test BOPE to 5000# & Annular to
of starting any proposed wo proposed completion or reconstruction of the second starting and proposed with the second starting any proposed work and second	rk). SEE RULE 19.15.7.14 NMAC. For ompletion.  of 13 3/8" 54.5# J55 ST&C Csg. Cement Plug down @ 6:15 PM 12/24/19. Circ 8	Multiple C  ed with 425 sks of cmt t	ompletions: Attach wellbore diagram of sks Class C w/2% CaCl2. Mixed @ 14.8#/g o the pit. Test BOPE to 5000# & Annular to
of starting any proposed wo proposed completion or reconstruction of reconstruction of the completion of reconstruction of the complete of the	rk). SEE RULE 19.15.7.14 NMAC. For ompletion.  of 13 3/8" 54.5# J55 ST&C Csg. Cemen Plug down @ 6:15 PM 12/24/19. Circ 8 I csg to 1500# for 30 mins, held OK. FIT	Multiple Control with 425 sks of cmt to 10.0 PPC	ompletions: Attach wellbore diagram of sks Class C w/2% CaCl2. Mixed @ 14.8#/g to the pit. Test BOPE to 5000# & Annular to EMW. Drilled out with 12 1/4" bit.
of starting any proposed wo proposed completion or reconstruction of reconstruction of the following proposed completion or reconstruction of the following proposed with the following proposed work with the following proposed with the	rk). SEE RULE 19.15.7.14 NMAC. For ompletion.  of 13 3/8" 54.5# J55 ST&C Csg. Cement Plug down @ 6:15 PM 12/24/19. Circ 8 d csg to 1500# for 30 mins, held OK. FIT	Multiple Control with 425 sks of cmt to 10.0 PPC	ompletions: Attach wellbore diagram of sks Class C w/2% CaCl2. Mixed @ 14.8#/g to the pit. Test BOPE to 5000# & Annular to GEMW. Drilled out with 12 1/4" bit.
of starting any proposed wo proposed completion or reconstruction of reconstruction of reconstruction of the starting and proposed work of the starting and proposed work of starting and starting	rk). SEE RULE 19.15.7.14 NMAC. For ompletion.  of 13 3/8" 54.5# J55 ST&C Csg. Cement Plug down @ 6:15 PM 12/24/19. Circ 8 d csg to 1500# for 30 mins, held OK. FIT 15' of 9 5/8" 40# HCL80 LT&C Csg. Ce 200 sks Class C Neat. Mixed @ 14.8#/g	Multiple Control with 425 sks of cmt to 10.0 PPC comented with w/1.32 yd. I	ompletions: Attach wellbore diagram of sks Class C w/2% CaCl2. Mixed @ 14.8#/g to the pit. Test BOPE to 5000# & Annular to G EMW. Drilled out with 12 1/4" bit.  The 400 sks Lite Class C (50:50:10) w/additives. Displaced w/180 bbl of FW. Plug down @ 6:45
of starting any proposed wo proposed completion or reconstruction of reconstruction of reconstruction of the starting and proposed work of the starting and proposed work of starting and starting	rk). SEE RULE 19.15.7.14 NMAC. For ompletion.  of 13 3/8" 54.5# J55 ST&C Csg. Cement Plug down @ 6:15 PM 12/24/19. Circ 8 d csg to 1500# for 30 mins, held OK. FIT 15' of 9 5/8" 40# HCL80 LT&C Csg. Ce 200 sks Class C Neat. Mixed @ 14.8#/g	Multiple Control with 425 sks of cmt to 10.0 PPC comented with w/1.32 yd. I	ompletions: Attach wellbore diagram of sks Class C w/2% CaCl2. Mixed @ 14.8#/g to the pit. Test BOPE to 5000# & Annular to G EMW. Drilled out with 12 1/4" bit.  The 400 sks Lite Class C (50:50:10) w/additives. Displaced w/180 bbl of FW. Plug down @ 6:45
of starting any proposed wo proposed completion or reconstruction of reconstruction of the completion of reconstruction of the complete of the	rk). SEE RULE 19.15.7.14 NMAC. For ompletion.  of 13 3/8" 54.5# J55 ST&C Csg. Cement Plug down @ 6:15 PM 12/24/19. Circ 8 d csg to 1500# for 30 mins, held OK. FIT 15' of 9 5/8" 40# HCL80 LT&C Csg. Ce 200 sks Class C Neat. Mixed @ 14.8#/g the pits. Set Cameron mandrel hanger the	Multiple Control with 425 sks of cmt to 10.0 PPC comented with w/1.32 yd. I rough BOP	is sks Class C w/2% CaCl2. Mixed @ 14.8#/g to the pit. Test BOPE to 5000# & Annular to EMW. Drilled out with 12 1/4" bit.  h 400 sks Lite Class C (50:50:10) w/additives. Displaced w/180 bbl of FW. Plug down @ 6:45 w/100k#. At 6:00 P.M. 12/27/19, tested csg to
of starting any proposed wo proposed completion or reconstruction of reconstruction of the completion of reconstruction of the complete of the	rk). SEE RULE 19.15.7.14 NMAC. For ompletion.  of 13 3/8" 54.5# J55 ST&C Csg. Cement Plug down @ 6:15 PM 12/24/19. Circ 8 d csg to 1500# for 30 mins, held OK. FIT 15' of 9 5/8" 40# HCL80 LT&C Csg. Ce 200 sks Class C Neat. Mixed @ 14.8#/g	Multiple Control with 425 sks of cmt to 10.0 PPC comented with w/1.32 yd. I rough BOP	is sks Class C w/2% CaCl2. Mixed @ 14.8#/g to the pit. Test BOPE to 5000# & Annular to EMW. Drilled out with 12 1/4" bit.  h 400 sks Lite Class C (50:50:10) w/additives. Displaced w/180 bbl of FW. Plug down @ 6:45 w/100k#. At 6:00 P.M. 12/27/19, tested csg to
of starting any proposed wo proposed completion or reconstruction of reconstruction of the complete of the proposed completion of reconstruction of the complete of the comple	rk). SEE RULE 19.15.7.14 NMAC. For ompletion.  of 13 3/8" 54.5# J55 ST&C Csg. Cemen Plug down @ 6:15 PM 12/24/19. Circ 8 d csg to 1500# for 30 mins, held OK. FIT  15' of 9 5/8" 40# HCL80 LT&C Csg. Ce 200 sks Class C Neat. Mixed @ 14.8#/g of the pits. Set Cameron mandrel hanger that to EMW of 9.7 PPG. Drilled out with 8	Multiple Control with 425 sks of cmt to 10.0 PPC control with 425 sks of cmt to 10.0 PPC control with 32 yd. I rough BOP 3/4" bit.	ompletions: Attach wellbore diagram of sks Class C w/2% CaCl2. Mixed @ 14.8#/g to the pit. Test BOPE to 5000# & Annular to G EMW. Drilled out with 12 1/4" bit.  The 400 sks Lite Class C (50:50:10) w/additives. Displaced w/180 bbl of FW. Plug down @ 6:45
of starting any proposed wo proposed completion or reconstruction of reconstruction of the completion of reconstruction of the complete of the	rk). SEE RULE 19.15.7.14 NMAC. For ompletion.  of 13 3/8" 54.5# J55 ST&C Csg. Cement Plug down @ 6:15 PM 12/24/19. Circ 8 d csg to 1500# for 30 mins, held OK. FIT 15' of 9 5/8" 40# HCL80 LT&C Csg. Ce 200 sks Class C Neat. Mixed @ 14.8#/g the pits. Set Cameron mandrel hanger the	Multiple Control with 425 sks of cmt to 10.0 PPC control with 425 sks of cmt to 10.0 PPC control with 32 yd. I rough BOP 3/4" bit.	is sks Class C w/2% CaCl2. Mixed @ 14.8#/g to the pit. Test BOPE to 5000# & Annular to GEMW. Drilled out with 12 1/4" bit.  h 400 sks Lite Class C (50:50:10) w/additives. Displaced w/180 bbl of FW. Plug down @ 6:45 w/100k#. At 6:00 P.M. 12/27/19, tested csg to
of starting any proposed wo proposed completion or reconstruction of reconstruction of the complete of the proposed completion of reconstruction of the complete of the comple	rk). SEE RULE 19.15.7.14 NMAC. For ompletion.  of 13 3/8" 54.5# J55 ST&C Csg. Cemen Plug down @ 6:15 PM 12/24/19. Circ 8 d csg to 1500# for 30 mins, held OK. FIT  15' of 9 5/8" 40# HCL80 LT&C Csg. Ce 200 sks Class C Neat. Mixed @ 14.8#/g of the pits. Set Cameron mandrel hanger that to EMW of 9.7 PPG. Drilled out with 8	Multiple Control with 425 sks of cmt to 10.0 PPC control with 425 sks of cmt to 10.0 PPC control with 32 yd. I rough BOP 3/4" bit.	is sks Class C w/2% CaCl2. Mixed @ 14.8#/g to the pit. Test BOPE to 5000# & Annular to EMW. Drilled out with 12 1/4" bit.  h 400 sks Lite Class C (50:50:10) w/additives. Displaced w/180 bbl of FW. Plug down @ 6:45 w/100k#. At 6:00 P.M. 12/27/19, tested csg to
of starting any proposed wo proposed completion or reconsideration of reconsideration of the proposed completion of reconsideration of the proposed with the	rk). SEE RULE 19.15.7.14 NMAC. For ompletion.  of 13 3/8" 54.5# J55 ST&C Csg. Cement Plug down @ 6:15 PM 12/24/19. Circ 8 it csg to 1500# for 30 mins, held OK. FIT 15' of 9 5/8" 40# HCL80 LT&C Csg. Ce 200 sks Class C Neat. Mixed @ 14.8#/g of the pits. Set Cameron mandrel hanger that to EMW of 9.7 PPG. Drilled out with 8 Rig Release Date	Multiple Control of the Multip	ompletions: Attach wellbore diagram of Sisks Class C w/2% CaCl2. Mixed @ 14.8#/g to the pit. Test BOPE to 5000# & Annular to GEMW. Drilled out with 12 1/4" bit.  The 400 sks Lite Class C (50:50:10) w/additives. Displaced w/180 bbl of FW. Plug down @ 6:45 w/100k#. At 6:00 P.M. 12/27/19, tested csg to RECEIVED  JAN 1 4 2020
of starting any proposed wo proposed completion or reconsideration of reconsideration of the proposed completion of reconsideration of the proposed with the	rk). SEE RULE 19.15.7.14 NMAC. For ompletion.  of 13 3/8" 54.5# J55 ST&C Csg. Cement Plug down @ 6:15 PM 12/24/19. Circ 8 it csg to 1500# for 30 mins, held OK. FIT 15' of 9 5/8" 40# HCL80 LT&C Csg. Ce 200 sks Class C Neat. Mixed @ 14.8#/g of the pits. Set Cameron mandrel hanger that to EMW of 9.7 PPG. Drilled out with 8 Rig Release Date	Multiple Control of the Multip	ompletions: Attach wellbore diagram of Sisks Class C w/2% CaCl2. Mixed @ 14.8#/g to the pit. Test BOPE to 5000# & Annular to GEMW. Drilled out with 12 1/4" bit.  The 400 sks Lite Class C (50:50:10) w/additives. Displaced w/180 bbl of FW. Plug down @ 6:45 w/100k#. At 6:00 P.M. 12/27/19, tested csg to RECEIVED  JAN 1 4 2020
of starting any proposed wo proposed completion or reconsideration of reconsideration of the proposed completion of reconsideration of the proposed with the	rk). SEE RULE 19.15.7.14 NMAC. For ompletion.  of 13 3/8" 54.5# J55 ST&C Csg. Cement Plug down @ 6:15 PM 12/24/19. Circ 8 it csg to 1500# for 30 mins, held OK. FIT 15' of 9 5/8" 40# HCL80 LT&C Csg. Ce 200 sks Class C Neat. Mixed @ 14.8#/g of the pits. Set Cameron mandrel hanger that to EMW of 9.7 PPG. Drilled out with 8 Rig Release Date	Multiple Control of the Multip	is sks Class C w/2% CaCl2. Mixed @ 14.8#/g to the pit. Test BOPE to 5000# & Annular to GEMW. Drilled out with 12 1/4" bit.  h 400 sks Lite Class C (50:50:10) w/additives. Displaced w/180 bbl of FW. Plug down @ 6:45 w/100k#. At 6:00 P.M. 12/27/19, tested csg to
of starting any proposed wo proposed completion or reconsideration of reconsideration of the proposed completion of reconsideration of the proposed with the	rk). SEE RULE 19.15.7.14 NMAC. For ompletion.  of 13 3/8" 54.5# J55 ST&C Csg. Cement Plug down @ 6:15 PM 12/24/19. Circ 8 d csg to 1500# for 30 mins, held OK. FIT 15' of 9 5/8" 40# HCL80 LT&C Csg. Ce 200 sks Class C Neat. Mixed @ 14.8#/g the pits. Set Cameron mandrel hanger that to EMW of 9.7 PPG. Drilled out with 8 Rig Release Date above is true and complete to the best of	Multiple Content with 425 sks of cmt to 10.0 PPC comented with w/1.32 yd. I rough BOP 3/4" bit.	Sign Sks Class C w/2% CaCl2. Mixed @ 14.8#/g to the pit. Test BOPE to 5000# & Annular to GEMW. Drilled out with 12 1/4" bit.  Sh 400 sks Lite Class C (50:50:10) w/additives. Displaced w/180 bbl of FW. Plug down @ 6:45 w/100k#. At 6:00 P.M. 12/27/19, tested csg to RECEIVED  JAN 1 4 2020
of starting any proposed wo proposed completion or reconsideration of reconsideration of the proposed completion of reconsideration of the proposed with the second	rk). SEE RULE 19.15.7.14 NMAC. For ompletion.  of 13 3/8" 54.5# J55 ST&C Csg. Cement Plug down @ 6:15 PM 12/24/19. Circ 8 it csg to 1500# for 30 mins, held OK. FIT 15' of 9 5/8" 40# HCL80 LT&C Csg. Ce 200 sks Class C Neat. Mixed @ 14.8#/g of the pits. Set Cameron mandrel hanger that to EMW of 9.7 PPG. Drilled out with 8 Rig Release Date	Multiple Content with 425 sks of cmt to 10.0 PPC comented with w/1.32 yd. I rough BOP 3/4" bit.	ompletions: Attach wellbore diagram of Sisks Class C w/2% CaCl2. Mixed @ 14.8#/g to the pit. Test BOPE to 5000# & Annular to GEMW. Drilled out with 12 1/4" bit.  The 400 sks Lite Class C (50:50:10) w/additives. Displaced w/180 bbl of FW. Plug down @ 6:45 w/100k#. At 6:00 P.M. 12/27/19, tested csg to RECEIVED  JAN 1 4 2020
of starting any proposed wo proposed completion or reconsideration of reconsideration of the proposed completion of reconsideration of the proposed with the	rk). SEE RULE 19.15.7.14 NMAC. For ompletion.  of 13 3/8" 54.5# J55 ST&C Csg. Cement Plug down @ 6:15 PM 12/24/19. Circ 8 d csg to 1500# for 30 mins, held OK. FIT 15' of 9 5/8" 40# HCL80 LT&C Csg. Ce 200 sks Class C Neat. Mixed @ 14.8#/g the pits. Set Cameron mandrel hanger that to EMW of 9.7 PPG. Drilled out with 8 Rig Release Date above is true and complete to the best of TITLE_Regulatory	Multiple Content with 425 sks of cmt to 10.0 PPC comented with w/1.32 yd. I rough BOP 3/4" bit.	ompletions: Attach wellbore diagram of sks Class C w/2% CaCl2. Mixed @ 14.8#/g to the pit. Test BOPE to 5000# & Annular to GEMW. Drilled out with 12 1/4" bit.  th 400 sks Lite Class C (50:50:10) w/additives. Displaced w/180 bbl of FW. Plug down @ 6:45 w/100k#. At 6:00 P.M. 12/27/19, tested csg to RECEIVED  JAN 1 4 2020  dge and belie EMNRD-OCD ARTESIA
of starting any proposed wo proposed completion or reconsistency of the proposed completion or reconsistency of the proposed completion or reconsistency of the proposed with	rk). SEE RULE 19.15.7.14 NMAC. For ompletion.  of 13 3/8" 54.5# J55 ST&C Csg. Cement Plug down @ 6:15 PM 12/24/19. Circ 8 it csg to 1500# for 30 mins, held OK. FIT 15' of 9 5/8" 40# HCL80 LT&C Csg. Ce 200 sks Class C Neat. Mixed @ 14.8#/g of the pits. Set Cameron mandrel hanger that to EMW of 9.7 PPG. Drilled out with 8 Rig Release Date above is true and complete to the best of	Multiple Content with 425 sks of cmt to 10.0 PPC comented with w/1.32 yd. I rough BOP 3/4" bit.	Sign Sks Class C w/2% CaCl2. Mixed @ 14.8#/g to the pit. Test BOPE to 5000# & Annular to GEMW. Drilled out with 12 1/4" bit.  Sh 400 sks Lite Class C (50:50:10) w/additives. Displaced w/180 bbl of FW. Plug down @ 6:45 w/100k#. At 6:00 P.M. 12/27/19, tested csg to RECEIVED  JAN 1 4 2020
of starting any proposed wo proposed completion or reconstruction of reconstruction of the completion of reconstruction of the complete of the	rk). SEE RULE 19.15.7.14 NMAC. For ompletion.  of 13 3/8" 54.5# J55 ST&C Csg. Cement Plug down @ 6:15 PM 12/24/19. Circ 8 it csg to 1500# for 30 mins, held OK. FIT 15' of 9 5/8" 40# HCL80 LT&C Csg. Ce 200 sks Class C Neat. Mixed @ 14.8#/g of the pits. Set Cameron mandrel hanger that to EMW of 9.7 PPG. Drilled out with 8 Rig Release Date above is true and complete to the best of	Multiple Content with 425 sks of cmt to 10.0 PPC comented with w/1.32 yd. I rough BOP 3/4" bit.	ompletions: Attach wellbore diagram of sks Class C w/2% CaCl2. Mixed @ 14.8#/g to the pit. Test BOPE to 5000# & Annular to GEMW. Drilled out with 12 1/4" bit.  th 400 sks Lite Class C (50:50:10) w/additives. Displaced w/180 bbl of FW. Plug down @ 6:45 w/100k#. At 6:00 P.M. 12/27/19, tested csg to RECEIVED  JAN 1 4 2020  dge and belie EMNRD-OCD ARTESIA
of starting any proposed wo proposed completion or reconsistency of the proposed completion or reconsistency of the proposed completion or reconsistency of the proposed with	rk). SEE RULE 19.15.7.14 NMAC. For ompletion.  of 13 3/8" 54.5# J55 ST&C Csg. Cement Plug down @ 6:15 PM 12/24/19. Circ 8 d csg to 1500# for 30 mins, held OK. FIT 15' of 9 5/8" 40# HCL80 LT&C Csg. Ce 200 sks Class C Neat. Mixed @ 14.8#/g the pits. Set Cameron mandrel hanger that to EMW of 9.7 PPG. Drilled out with 8 Rig Release Date above is true and complete to the best of E-mail address: _rojeda@means.	Multiple Content with 425 sks of cmt to 10.0 PPC comented with w/1.32 yd. I rough BOP 3/4" bit.	ompletions: Attach wellbore diagram of sks Class C w/2% CaCl2. Mixed @ 14.8#/g to the pit. Test BOPE to 5000# & Annular to GEMW. Drilled out with 12 1/4" bit.  th 400 sks Lite Class C (50:50:10) w/additives. Displaced w/180 bbl of FW. Plug down @ 6:45 w/100k#. At 6:00 P.M. 12/27/19, tested csg to  RECEIVED  JAN 1 4 2020  dige and belieEMNRD-OCD ARTESIA  DATE1/13/2020
of starting any proposed wo proposed completion or reconstruction of reconstruction of reconstruction of the completion of reconstruction of the complete of t	rk). SEE RULE 19.15.7.14 NMAC. For ompletion.  of 13 3/8" 54.5# J55 ST&C Csg. Cement Plug down @ 6:15 PM 12/24/19. Circ 8 d csg to 1500# for 30 mins, held OK. FIT 15' of 9 5/8" 40# HCL80 LT&C Csg. Ce 200 sks Class C Neat. Mixed @ 14.8#/g the pits. Set Cameron mandrel hanger that to EMW of 9.7 PPG. Drilled out with 8 Rig Release Date above is true and complete to the best of E-mail address: _rojeda@means.	Multiple Content with 425 sks of cmt to 10.0 PPC comented with w/1.32 yd. I rough BOP 3/4" bit.	ompletions: Attach wellbore diagram of sks Class C w/2% CaCl2. Mixed @ 14.8#/g to the pit. Test BOPE to 5000# & Annular to GEMW. Drilled out with 12 1/4" bit.  th 400 sks Lite Class C (50:50:10) w/additives. Displaced w/180 bbl of FW. Plug down @ 6:45 w/100k#. At 6:00 P.M. 12/27/19, tested csg to RECEIVED  JAN 1 4 2020  dge and belie EMNRD-OCD ARTESIA
of starting any proposed wo proposed completion or reconstruction of reconstruction of reconstruction of the completion of reconstruction of the complete of t	rk). SEE RULE 19.15.7.14 NMAC. For ompletion.  of 13 3/8" 54.5# J55 ST&C Csg. Cement Plug down @ 6:15 PM 12/24/19. Circ 8 it csg to 1500# for 30 mins, held OK. FIT 15' of 9 5/8" 40# HCL80 LT&C Csg. Ce 200 sks Class C Neat. Mixed @ 14.8#/g of the pits. Set Cameron mandrel hanger that to EMW of 9.7 PPG. Drilled out with 8 Rig Release Date above is true and complete to the best of	Multiple Content with 425 sks of cmt to 10.0 PPC comented with w/1.32 yd. I rough BOP 3/4" bit.	ompletions: Attach wellbore diagram of sks Class C w/2% CaCl2. Mixed @ 14.8#/g to the pit. Test BOPE to 5000# & Annular to GEMW. Drilled out with 12 1/4" bit.  th 400 sks Lite Class C (50:50:10) w/additives. Displaced w/180 bbl of FW. Plug down @ 6:45 w/100k#. At 6:00 P.M. 12/27/19, tested csg to  RECEIVED  JAN 1 4 2020  dige and belieEMNRD-OCD ARTESIA  DATE1/13/2020
of starting any proposed wo proposed completion or reconstruction of reconstruction of reconstruction of the completion of reconstruction of the complete of t	rk). SEE RULE 19.15.7.14 NMAC. For ompletion.  of 13 3/8" 54.5# J55 ST&C Csg. Cement Plug down @ 6:15 PM 12/24/19. Circ 8 d csg to 1500# for 30 mins, held OK. FIT 15' of 9 5/8" 40# HCL80 LT&C Csg. Ce 200 sks Class C Neat. Mixed @ 14.8#/g the pits. Set Cameron mandrel hanger that to EMW of 9.7 PPG. Drilled out with 8 Rig Release Date above is true and complete to the best of E-mail address: _rojeda@means.	Multiple Content with 425 sks of cmt to 10.0 PPC comented with w/1.32 yd. I rough BOP 3/4" bit.	ompletions: Attach wellbore diagram of sks Class C w/2% CaCl2. Mixed @ 14.8#/g to the pit. Test BOPE to 5000# & Annular to GEMW. Drilled out with 12 1/4" bit.  th 400 sks Lite Class C (50:50:10) w/additives. Displaced w/180 bbl of FW. Plug down @ 6:45 w/100k#. At 6:00 P.M. 12/27/19, tested csg to  RECEIVED  JAN 1 4 2020  dige and belieEMNRD-OCD ARTESIA  DATE1/13/2020

1/29/20 45