

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED

NOV 19 2019

Duplicate?

FORM APPROVED
OMB NO. 1004-0137
Expires: January 31, 2018**SUNDRY NOTICES AND REPORTS ON WELLS**
Do not use this form for proposals to drill or to re-enter an
abandoned well. Use form 3160-3 (APD) for such proposals.5. Lease Serial No.
NMLC062300

6. If Indian, Allottee or Tribe Name

7. If Unit or CA/Agreement, Name and/or No.

8. Well Name and No.
BIG SINKS DRAW 25-24 FED COM 710H9. API Well No.
30-015-45098-00-X110. Field and Pool or Exploratory Area
PURPLE SAGE-WOLFCAMP (GAS)11. County or Parish, State
EDDY COUNTY, NM**SUBMIT IN TRIPLICATE - Other instructions on page 2**

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other2. Name of Operator
DEVON ENERGY PRODUCTION COMPANY

Contact: JENNIFER HARMS

E-Mail: jennifer.harms@dvn.com

3a. Address
333 WEST SHERIDAN AVENUE
OKLAHOMA, OK 731023b. Phone No. (include area code)
Ph: 405-552-6560

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Sec 25 T25S R31E SWNW 2484FNL 925FWL
32.101704 N Lat, 103.737206 W Lon**12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA**

TYPE OF SUBMISSION

- ☒
- Notice of Intent
-
- ☐
- Subsequent Report
-
- ☐
- Final Abandonment Notice

- ☐
- Acidize
-
- ☐
- Alter Casing
-
- ☐
- Casing Repair
-
- ☐
- Change Plans
-
- ☐
- Convert to Injection

- ☐
- Deepen
-
- ☐
- Hydraulic Fracturing
-
- ☐
- New Construction
-
- ☐
- Plug and Abandon
-
- ☐
- Plug Back

TYPE OF ACTION

- ☐
- Production (Start/Resume)
-
- ☐
- Reclamation
-
- ☐
- Recomplete
-
- ☐
- Temporarily Abandon
-
- ☐
- Water Disposal
-
- ☐
- Water Shut-Off
-
- ☐
- Well Integrity
-
- ☒
- Other
-
- Change to Original APD

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.

NAME CHANGE/FORMATION CHANGE

Devon Energy Production Co., L.P. (Devon) respectfully requests to change the well name and depth on the subject well. Please see attached revised C102, Drill plan, directional plan.

-COTTON DRAW MDP 2
Permitted Well name: BIG SINKS DRAW 25-24 FED COM 331H
Proposed Well name: BIG SINKS DRAW 25-24 FED COM 710H
Permitted TVD/MD: 11268/18314-Jennings/Bonespring
Proposed TVD/MD: 11950/19279- Purple Sage/Wolfcamp**Carlsbad Field Office**
OCD Artesia

14. I hereby certify that the foregoing is true and correct.

Electronic Submission #483880 verified by the BLM Well Information System
For DEVON ENERGY PRODUCTION COMPANY, sent to the Carlsbad
Committed to AFMSS for processing by PRISCILLA PEREZ on 09/18/2019 (19PP3387SE)

Name (Printed/Typed) JENNIFER HARMS

Title REGULATORY COMPLIANCE ANALYST

Signature (Electronic Submission)

Date 09/18/2019

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved By LONG VO

Title PETROLEUM ENGINEER

Date 11/04/2019

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office Carlsbad

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

**** BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED ****

1/21/20 KS

PECOS DISTRICT DRILLING CONDITIONS OF APPROVAL

OPERATOR'S NAME:	Devon Energy Prod Co
LEASE NO.:	LC062300
WELL NAME & NO.:	710H – Big Sinks Draw 25-24 Fed
SURFACE HOLE FOOTAGE:	2484'/N & 925'/W
BOTTOM HOLE FOOTAGE:	330'/N & 330'/W, sec.24
LOCATION:	Section 25, T. 25 S., R.319 E.
COUNTY:	Eddy County, New Mexico

COA

H2S	<input type="radio"/> Yes	<input checked="" type="radio"/> No	
Potash	<input checked="" type="radio"/> None	<input type="radio"/> Secretary	<input type="radio"/> R-111-P
Cave/Karst Potential	<input checked="" type="radio"/> Low	<input type="radio"/> Medium	<input type="radio"/> High
Cave/Karst Potential	<input type="radio"/> Critical		
Variance	<input type="radio"/> None	<input checked="" type="radio"/> Flex Hose	<input type="radio"/> Other
Wellhead	<input type="radio"/> Conventional	<input type="radio"/> Multibowl	<input checked="" type="radio"/> Both
Other	<input type="checkbox"/> 4 String Area	<input type="checkbox"/> Capitan Reef	<input type="checkbox"/> WIPP
Other	<input checked="" type="checkbox"/> Fluid Filled	<input checked="" type="checkbox"/> Cement Squeeze	<input type="checkbox"/> Pilot Hole
Special Requirements	<input type="checkbox"/> Water Disposal	<input type="checkbox"/> COM	<input type="checkbox"/> Unit

All Previous COAs Still Apply

A. CASING

Primary Casing Design:

1. The 13-3/8 inch surface casing shall be set at approximately **1003 feet** (a minimum of **70 feet (Eddy County)** into the Rustler Anhydrite and above the salt) and cemented to the surface.
 - a. If cement does not circulate to the surface, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic type temperature survey with surface log readout will be used or a cement bond log shall be run to verify the top of the cement. Temperature survey will be run a minimum of six hours after pumping cement and ideally between 8-10 hours after completing the cement job.
 - b. Wait on cement (WOC) time for a primary cement job will be a minimum of **8 hours** or 500 pounds compressive strength, whichever is greater. (This is to include the lead cement)
 - c. Wait on cement (WOC) time for a remedial job will be a minimum of 4 hours after bringing cement to surface or 500 pounds compressive strength,

- whichever is greater.
- d. If cement falls back, remedial cementing will be done prior to drilling out that string.

Intermediate casing must be kept fluid filled to meet BLM minimum collapse requirement.

2. The minimum required fill of cement behind the 7-5/8 inch intermediate casing is:

Option 1 (Single Stage):

- Cement to surface. If cement does not circulate see B.1.a, c-d above.

Option 2:

Operator has proposed a DV tool, the depth may be adjusted as long as the cement is changed proportionally. The DV tool may be cancelled if cement circulates to surface on the first stage.

- a. First stage to DV tool: Cement to circulate. If cement does not circulate off the DV tool, contact the appropriate BLM office before proceeding with second stage cement job.
- b. Second stage above DV tool:
- Cement to surface. If cement does not circulate, contact the appropriate BLM office.

Operator has proposed to pump down 13-3/8" X 7-5/8" annulus. Operator must run a CBL from TD of the 7-5/8" casing to surface. Submit results to BLM.

3. The minimum required fill of cement behind the 5-1/2 inch production casing is:

- Cement should tie-back at least **200 feet** into previous casing string. Operator shall provide method of verification.
Cement excess is less than 25%, more cement might be required.

Alternate Casing Design:

4. The 13-3/8 inch surface casing shall be set at approximately **1003 feet** (a minimum of **70 feet (Eddy County)** into the Rustler Anhydrite and above the salt) and cemented to the surface.
- e. If cement does not circulate to the surface, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic type temperature survey with surface log readout will be used or a cement bond log shall be run

to verify the top of the cement. Temperature survey will be run a minimum of six hours after pumping cement and ideally between 8-10 hours after completing the cement job.

- f. Wait on cement (WOC) time for a primary cement job will be a minimum of **8 hours** or 500 pounds compressive strength, whichever is greater. (This is to include the lead cement)
- g. Wait on cement (WOC) time for a remedial job will be a minimum of 4 hours after bringing cement to surface or 500 pounds compressive strength, whichever is greater.
- h. If cement falls back, remedial cementing will be done prior to drilling out that string.

Intermediate casing must be kept fluid filled to meet BLM minimum collapse requirement.

5. The minimum required fill of cement behind the **8-5/8** inch intermediate casing is:

Option 1 (Single Stage):

- Cement to surface. If cement does not circulate see B.1.a, c-d above.
Cement excess is less than 25%, more cement might be required.

Option 2:

Operator has proposed a DV tool, the depth may be adjusted as long as the cement is changed proportionally. The DV tool may be cancelled if cement circulates to surface on the first stage.

- c. First stage to DV tool: Cement to circulate. If cement does not circulate off the DV tool, contact the appropriate BLM office before proceeding with second stage cement job.
- d. Second stage above DV tool:
 - Cement to surface. If cement does not circulate, contact the appropriate BLM office.
Cement excess is less than 25%, more cement might be required.

Operator has proposed to pump down 13-3/8" X 8-5/8" annulus. Operator must run a CBL from TD of the 8-5/8" casing to surface. Submit results to BLM.

The operator is approved to drill a 10.625" hole instead of 9.875" for intermediate 1 with a BTC connection.

6. The minimum required fill of cement behind the 5-1/2 inch production casing is:

- Cement should tie-back at least **200 feet** into previous casing string. Operator shall provide method of verification.
Cement excess is less than 25%, more cement might be required.

B. PRESSURE CONTROL

1. Variance approved to use flex line from BOP to choke manifold. Manufacturer's specification to be readily available. No external damage to flex line. Flex line to be installed as straight as possible (no hard bends).'

2.

Option 1:

- a. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be **5000 (5M)** psi.
- b. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the intermediate casing shoe shall be **5000 (5M)** psi.

Option 2:

1. Operator has proposed a multi-bowl wellhead assembly. This assembly will only be tested when installed on the surface casing. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be **5000 (5M)** psi.
 - a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
 - b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
 - c. Manufacturer representative shall install the test plug for the initial BOP test.
 - d. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
 - e. Whenever any seal subject to test pressure is broken, all the tests in OOGO2.III.A.2.i must be followed.

GENERAL REQUIREMENTS

The BLM is to be notified in advance for a representative to witness:

- a. Spudding well (minimum of 24 hours)
- b. Setting and/or Cementing of all casing strings (minimum of 4 hours)
- c. BOPE tests (minimum of 4 hours)

☒ Eddy County

Call the Carlsbad Field Office, 620 East Greene St., Carlsbad, NM 88220,
(575) 361-2822

☒ Lea County

Call the Hobbs Field Station, 414 West Taylor, Hobbs NM 88240, (575)
393-3612

1. Unless the production casing has been run and cemented or the well has been properly plugged, the drilling rig shall not be removed from over the hole without prior approval.
 - a. In the event the operator has proposed to drill multiple wells utilizing a skid/walking rig. Operator shall secure the wellbore on the current well, after installing and testing the wellhead, by installing a blind flange of like pressure rating to the wellhead and a pressure gauge that can be monitored while drilling is performed on the other well(s).
 - b. When the operator proposes to set surface casing with Spudder Rig
 - Notify the BLM when moving in and removing the Spudder Rig.
 - Notify the BLM when moving in the 2nd Rig. Rig to be moved in within 90 days of notification that Spudder Rig has left the location.
 - BOP/BOPE test to be conducted per Onshore Oil and Gas Order No. 2 as soon as 2nd Rig is rigged up on well.
2. Floor controls are required for 3M or Greater systems. These controls will be on the rig floor, unobstructed, readily accessible to the driller and will be operational at all times during drilling and/or completion activities. Rig floor is defined as the area immediately around the rotary table; the area immediately above the substructure on which the draw works are located, this does not include the dog house or stairway area.
3. The record of the drilling rate along with the GR/N well log run from TD to surface (horizontal well – vertical portion of hole) shall be submitted to the BLM office as well as all other logs run on the borehole 30 days from completion. If available, a digital copy of the logs is to be submitted in addition to the paper copies. The Rustler top and top and bottom of Salt are to be recorded on the Completion Report.

A. CASING

1. Changes to the approved APD casing program need prior approval if the items substituted are of lesser grade or different casing size or are Non-API. The Operator can exchange the components of the proposal with that of superior strength (i.e. changing from J-55 to N-80, or from 36# to 40#). Changes to the approved cement program need prior approval if the altered cement plan has less volume or strength or if the changes are substantial (i.e. Multistage tool, ECP, etc.). The initial wellhead installed on the well will remain on the well with spools used as needed.
2. Wait on cement (WOC) for Potash Areas: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi for all cement blends, 2) until cement has been in place at least 24 hours. WOC time will be recorded in the driller's log. The casing integrity test can be done (prior to the cement setting up) immediately after bumping the plug.
3. Wait on cement (WOC) for Water Basin: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi at the shoe, 2) until cement has been in place at least 8 hours. WOC time will be recorded in the driller's log. See individual casing strings for details regarding lead cement slurry requirements. The casing integrity test can be done (prior to the cement setting up) immediately after bumping the plug.
4. Provide compressive strengths including hours to reach required 500 pounds compressive strength prior to cementing each casing string. Have well specific cement details onsite prior to pumping the cement for each casing string.
5. No pea gravel permitted for remedial or fall back remedial without prior authorization from the BLM engineer.
6. On that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Formation at the shoe shall be tested to a minimum of the mud weight equivalent anticipated to control the formation pressure to the next casing depth or at total depth of the well. This test shall be performed before drilling more than 20 feet of new hole.
7. If hardband drill pipe is rotated inside casing, returns will be monitored for metal. If metal is found in samples, drill pipe will be pulled and rubber protectors which have a larger diameter than the tool joints of the drill pipe will be installed prior to continuing drilling operations.
8. Whenever a casing string is cemented in the R-111-P potash area, the NMOCD requirements shall be followed.

B. PRESSURE CONTROL

1. All blowout preventer (BOP) and related equipment (BOPE) shall comply with well control requirements as described in Onshore Oil and Gas Order No. 2 and API RP 53 Sec. 17.
2. If a variance is approved for a flexible hose to be installed from the BOP to the choke manifold, the following requirements apply: The flex line must meet the requirements of API 16C. Check condition of flexible line from BOP to choke manifold, replace if exterior is damaged or if line fails test. Line to be as straight as possible with no hard bends and is to be anchored according to Manufacturer's requirements. The flexible hose can be exchanged with a hose of equal size and equal or greater pressure rating. Anchor requirements, specification sheet and hydrostatic pressure test certification matching the hose in service, to be onsite for review. These documents shall be posted in the company man's trailer and on the rig floor.
3. 5M or higher system requires an HCR valve, remote kill line and annular to match. The remote kill line is to be installed prior to testing the system and tested to stack pressure.
4. If the operator has proposed a multi-bowl wellhead assembly in the APD. The following requirements must be met:
 - a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
 - b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
 - c. Manufacturer representative shall install the test plug for the initial BOP test.
 - d. Whenever any seal subject to test pressure is broken, all the tests in OOGO2.III.A.2.i must be followed.
 - e. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
5. The appropriate BLM office shall be notified a minimum of 4 hours in advance for a representative to witness the tests.
 - a. In a water basin, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. The casing cut-off and BOP installation can be initiated four hours after installing the slips, which will be approximately six hours after bumping the plug. For those casing strings not using slips, the minimum wait time before cut-off is eight hours after bumping the plug. BOP/BOPE testing can begin after cut-off or once cement reaches 500 psi compressive strength (including lead when specified), whichever is greater. However, if the float does not

hold, cut-off cannot be initiated until cement reaches 500 psi compressive strength (including lead when specified).

- b. In potash areas, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. For all casing strings, casing cut-off and BOP installation can be initiated at twelve hours after bumping the plug. However, **no tests** shall commence until the cement has had a minimum of 24 hours setup time, except the casing pressure test can be initiated immediately after bumping the plug (only applies to single stage cement jobs).
- c. The tests shall be done by an independent service company utilizing a test plug not a cup or J-packer. The operator also has the option of utilizing an independent tester to test without a plug (i.e. against the casing) pursuant to Onshore Order 2 with the pressure not to exceed 70% of the burst rating for the casing. Any test against the casing must meet the WOC time for water basin (8 hours) or potash (24 hours) or 500 pounds compressive strength, whichever is greater, prior to initiating the test (see casing segment as lead cement may be critical item).
- d. The test shall be run on a 5000 psi chart for a 2-3M BOP/BOP, on a 10000 psi chart for a 5M BOP/BOPE and on a 15000 psi chart for a 10M BOP/BOPE. If a linear chart is used, it shall be a one hour chart. A circular chart shall have a maximum 2 hour clock. If a twelve hour or twenty-four hour chart is used, tester shall make a notation that it is run with a two hour clock.
- e. The results of the test shall be reported to the appropriate BLM office.
- f. All tests are required to be recorded on a calibrated test chart. A copy of the BOP/BOPE test chart and a copy of independent service company test will be submitted to the appropriate BLM office.
- g. The BOP/BOPE test shall include a low pressure test from 250 to 300 psi. The test will be held for a minimum of 10 minutes if test is done with a test plug and 30 minutes without a test plug. This test shall be performed prior to the test at full stack pressure.
- h. BOP/BOPE must be tested by an independent service company within 500 feet of the top of the Wolfcamp formation if the time between the setting of the intermediate casing and reaching this depth exceeds 20 days. This test does not exclude the test prior to drilling out the casing shoe as per Onshore Order No. 2.

C. DRILLING MUD

Mud system monitoring equipment, with derrick floor indicators and visual and audio alarms, shall be operating before drilling into the Wolfcamp formation, and shall be used until production casing is run and cemented.

D. WASTE MATERIAL AND FLUIDS


All waste (i.e. drilling fluids, trash, salts, chemicals, sewage, gray water, etc.) created as a result of drilling operations and completion operations shall be safely contained and disposed of properly at a waste disposal facility. No waste material or fluid shall be disposed of on the well location or surrounding area.

Porto-johns and trash containers will be on-location during fracturing operations or any other crew-intensive operations.

SECTION 25, TOWNSHIP 25 SOUTH, RANGE 31 EAST, N.M.P.M.
EDDY COUNTY, STATE OF NEW MEXICO
SITE MAP

NOTE: LATITUDE AND LONGITUDE COORDINATES ARE SHOWN USING THE NORTH AMERICAN DATUM OF 1983 (NAD83) LISTED NEW MEXICO STATE PLANE EAST COORDINATES ARE GRID (NAD83). BASIS OF BEARING AND DISTANCES USED ARE NEW MEXICO STATE PLANE EAST COORDINATES MODIFIED TO THE SURFACE. VERTICAL DATUM NAVD88.

- A - BIG SINKS DRAW 25-24
FED COM 521H
- B - BIG SINKS DRAW 25-24
FED COM 531H
- C - BIG SINKS DRAW 25-24
FED COM 710H
- D - BIG SINKS DRAW 25-24
FED COM 611H
- E - BIG SINKS DRAW 25-24
FED COM 731H



012 60 120 240
SCALE 1" = 120'

DIRECTIONS TO LOCATION

FROM STATE HIGHWAY 128 AND CR 1 (ORLA ROAD) GO SOUTH ON CR 1 6.2 MILES, TURN RIGHT ON CALICHE ROAD (MONSANTO ROAD) AND GO WEST 2.1 MILES, TURN RIGHT AND GO NORTH 0.4 OF A MILE, CROSS A CATTLE GUARD, CONTINUE NORTH 0.4 OF A MILE, ROAD BENDS LEFT (WEST) CONTINUE WEST 2.0 MILES TO AN INTERSECTION, CONTINUE SOUTHWEST THROUGH INTERSECTION, ROAD BENDS SOUTH, CROSS A CATTLE GUARD, 3.45 MILES FROM INTERSECTION TURN LEFT ON CALICHE ROAD AND GO EAST 1.0 MILE TO AN EXISTING CALICHE ROAD AND GO NORTH 3500' THEN EAST 310' TO THE SOUTHWEST CORNER OF BIG SINKS DRAW 25 FED COM 1H, CONTINUE EAST 487' TO THE SOUTHWEST PAD CORNER FOR THIS LOCATION.

DEVON ENERGY PRODUCTION COMPANY, L.P.
BIG SINKS DRAW 25-24 FED COM 710H
LOCATED 2484 FT. FROM THE NORTH LINE
AND 925 FT. FROM THE WEST LINE OF
SECTION 25, TOWNSHIP 25 SOUTH,
RANGE 31 EAST, N.M.P.M.
EDDY COUNTY, STATE OF NEW MEXICO



AUGUST 1, 2019

SURVEY NO. 5659A


MADRON SURVEYING, INC. 301 SOUTH CANAL CARLSBAD, NEW MEXICO
(575) 234-3341

SECTION 25, TOWNSHIP 25 SOUTH, RANGE 31 EAST, N.M.P.M.
EDDY COUNTY, STATE OF NEW MEXICO
INTERIM SITE BUILD PLAN

- A - BIG SINKS DRAW 25-24
FED COM 521H
- B - BIG SINKS DRAW 25-24
FED COM 531H
- C - BIG SINKS DRAW 25-24
FED COM 710H
- D - BIG SINKS DRAW 25-24
FED COM 611H
- E - BIG SINKS DRAW 25-24
FED COM 731H



DENOTES INTERIM PAD
RECLAMATION AREA



DENOTES GRADING SITE
RECLAMATION AREA

0 12 60 120 240
SCALE 1" = 120'

2.264± ACRES INTERIM PAD RECLAMATION AREA
2.807± ACRES GRADING SITE RECLAMATION AREA
3.194± ACRES NON-RECLAIMED AREA
8.265± ACRES COTTON DRAW MDP2 BIG SINKS PAD 25-1

DEVON ENERGY PRODUCTION COMPANY, L.P.
BIG SINKS DRAW 25-24 FED COM 710H
LOCATED 2484 FT. FROM THE NORTH LINE
AND 925 FT. FROM THE WEST LINE OF
SECTION 25, TOWNSHIP 25 SOUTH,
RANGE 31 EAST, N.M.P.M.
EDDY COUNTY, STATE OF NEW MEXICO

AUGUST 1, 2019


SURVEY NO. 5659A

MADRON SURVEYING, INC.

301 SOUTH CANAL
(575) 234-3341

CARLSBAD, NEW MEXICO

SECTION 25, TOWNSHIP 25 SOUTH, RANGE 31 EAST, N.M.P.M.
EDDY COUNTY, STATE OF NEW MEXICO
LOCATION VERIFICATION MAP



USGS/4UAD MAP:
PADUCA BREAKS WEST

NOT TO SCALE


DEVON ENERGY PRODUCTION COMPANY, L.P.
BIG SINKS DRAW 25-24 FED COM 710H
LOCATED 2484 FT. FROM THE NORTH LINE
AND 925 FT. FROM THE WEST LINE OF
SECTION 25, TOWNSHIP 25 SOUTH,
RANGE 31 EAST, N.M.P.M.
EDDY COUNTY, STATE OF NEW MEXICO

AUGUST 1, 2019

SURVEY NO. 5659A

MADRON SURVEYING, INC. 301 SOUTH CANAL (575) 234-3341 CARLSBAD, NEW MEXICO

SECTION 25, TOWNSHIP 25 SOUTH, RANGE 31 EAST, N.M.P.M.
EDDY COUNTY, STATE OF NEW MEXICO
VICINITY MAP



DISTANCES IN MILES

NOT TO SCALE

DEVON ENERGY PRODUCTION COMPANY, L.P.
BIG SINKS DRAW 25-24 FED COM 710H
LOCATED 2484 FT. FROM THE NORTH LINE
AND 925 FT. FROM THE WEST LINE OF
SECTION 25, TOWNSHIP 25 SOUTH,
RANGE 31 EAST, N.M.P.M.
EDDY COUNTY, STATE OF NEW MEXICO

AUGUST 1, 2019


DIRECTIONS TO LOCATION

FROM STATE HIGHWAY 128 AND CR 1 (ORLA ROAD) GO SOUTH ON CR 1 6.2 MILES, TURN RIGHT ON CALICHE ROAD (MONSANTO ROAD) AND GO WEST 2.1 MILES, TURN RIGHT AND GO NORTH 0.4 OF A MILE, CROSS A CATTLE GUARD, CONTINUE NORTH 0.4 OF A MILE, ROAD BENDS LEFT (WEST) CONTINUE WEST 2.0 MILES TO AN INTERSECTION, CONTINUE SOUTHWEST THROUGH INTERSECTION, ROAD BENDS SOUTH, CROSS A CATTLE GUARD, 3.45 MILES FROM INTERSECTION TURN LEFT ON CALICHE ROAD AND GO EAST 1.0 MILE TO AN EXISTING CALICHE ROAD AND GO NORTH 3500' THEN EAST 310' TO THE SOUTHWEST CORNER OF BIG SINKS DRAW 25 FED COM 1H, CONTINUE EAST 487' TO THE SOUTHWEST PAD CORNER FOR THIS LOCATION.

SURVEY NO. 5659A

MADRON SURVEYING, INC. 301 SOUTH CANAL (575) 234-3341 CARLSBAD, NEW MEXICO

SECTION 25, TOWNSHIP 25 SOUTH, RANGE 31 EAST, N.M.P.M.
EDDY COUNTY, STATE OF NEW MEXICO
AERIAL PHOTO



NOT TO SCALE
AERIAL PHOTO:
GOOGLE EARTH
NOVEMBER 2015


DEVON ENERGY PRODUCTION COMPANY, L.P.
BIG SINKS DRAW 25-24 FED COM 710H
LOCATED 2484 FT. FROM THE NORTH LINE
AND 925 FT. FROM THE WEST LINE OF
SECTION 25, TOWNSHIP 25 SOUTH,
RANGE 31 EAST, N.M.P.M.
EDDY COUNTY, STATE OF NEW MEXICO

AUGUST 1, 2019

SURVEY NO. 5659A

MADRON SURVEYING, INC. 301 SOUTH CANAL (575) 234-3341 CARLSBAD, NEW MEXICO

EDDY COUNTY, STATE OF NEW MEXICO
ACCESS AERIAL ROUTE MAP



LOCATED 2484 FT. FROM THE NORTH LINE
AND 925 FT. FROM THE WEST LINE OF
SECTION 25, TOWNSHIP 25 SOUTH,
RANGE 31 EAST, N.M.P.M.
EDDY COUNTY, STATE OF NEW MEXICO

MADRON SURVEYING, INC. 301 SOUTH CANAL CARLSBAD, NEW MEXICO
(575) 234-3341

301 SOUTH CANAL
(575) 234-3341

PLAN VIEW

**COTTON DRAW MDP2,
BIG SINKS PAD 25-1
EL. = 3339.0'**

**LIMITS OF EARTHWORK
3:1 SLOPE (TYP.)**

**DRILLING PAD
BIG SINKS DRAW 25-24
FED COM.
521H, 531H, 710H, 611H, 731H**

PAD CENTER POINT

**LIMITS OF EARTHWORK
3:1 SLOPE (TYP.)**

EXISTING CALICHE ROAD

PROPOSED 30' ACCESS ROAD

**BIG SINKS DRAW 25-24
FED COM 521H
BIG SINKS DRAW 25-24
FED COM 531H
BIG SINKS DRAW 25-24
FED COM 710H
BIG SINKS DRAW 25-24
FED COM 611H
BIG SINKS DRAW 25-24
FED COM 731H**

**SECTION 25, TOWNSHIP 25 SOUTH,
RANGE 31 EAST, N.M.P.M.
EDDY COUNTY, STATE OF NEW MEXICO**

**DEVON ENERGY PRODUCTION COMPANY, L.P.
GRADING PLAN AND CROSS SECTIONS
FOR BIG SINKS DRAW 25-24 FED COM 710H**

AUGUST 1, 2019

MADRON SURVEYING, INC.

SCALE 1" = 120'

CUT	FILL	NET
5422 CU. YD	11752 CU. YD	6330 CU. YD (FILL)

EARTHWORK QUANTITIES ARE ESTIMATED

SHEET 1-2
SURVEY NO. 5659A

I, FILMON F. JARAMILLO, A NEW MEXICO REGISTERED PROFESSIONAL SURVEYOR CERTIFY THAT I DIRECTED AND AM RESPONSIBLE FOR THIS SURVEY, THAT THIS SURVEY IS TRUE AND CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF, AND THIS SURVEY AND PLAT MEET THE MINIMUM STANDARDS FOR SURVEYING IN NEW MEXICO.

FILMON F. JARAMILLO PLS. 12345 DATE 8/1/19

DEVON ENERGY PRODUCTION COMPANY, L.P.
GRADING PLAN AND CROSS SECTIONS
FOR BIG SINKS DRAW 25-24 FED COM 710H
SECTION 25, TOWNSHIP 25 SOUTH,
RANGE 31 EAST, N.M.P.M.
EDDY COUNTY, STATE OF NEW MEXICO

AUGUST 1, 2019

MADRON SURVEYING, INC. 301 SOUTH CANAL (575) 234-3341 CARLSBAD, NEW MEXICO

0 60 120 240





SCALE 1" = 120'

CUT	FILL	NET
5422 CU. YD	11752 CU. YD	6330 CU. YD (FILL)

EARTHWORK QUANTITIES ARE ESTIMATED

SHEET 1-2
SURVEY NO. 5659A ☒

CROSS SECTIONS



I, FILIMON F. JARAMILLO, A NEW MEXICO REGISTERED PROFESSIONAL SURVEYOR CERTIFY THAT I DIRECTED AND AM RESPONSIBLE FOR THIS SURVEY, THAT THIS SURVEY IS TRUE AND CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF, AND THIS SURVEY AND PLAT MEET THE MINIMUM STANDARDS FOR SURVEYING IN NEW MEXICO.

DEVON ENERGY PRODUCTION COMPANY, L.P.
GRADING PLAN AND CROSS SECTIONS
FOR BIG SINKS DRAW 25-24 FED COM 710H
 SECTION 25, TOWNSHIP 25 SOUTH,
 RANGE 31 EAST, N.M.P.M.
 EDDY COUNTY, STATE OF NEW MEXICO

012 60 120 240
 SCALE 1" = 120' - 1" = 20' VER

CUT	FILL	NET
5422 CU. YD	11752 CU. YD	6330 CU. YD (FILL)

EARTHWORK QUANTITIES ARE ESTIMATED

AUGUST 1, 2019

MADRON SURVEYING, INC. 301 SOUTH CANAL (575) 234-3341 **CARLSBAD, NEW MEXICO**

SHEET 2-2
 SURVEY NO. 5659A

Big Sinks Draw 25-24 Fed Com 710H

1. Geologic Formations

TVD of target	11950	Pilot hole depth	N/A
MD at TD:	19279	Deepest expected fresh water	

Basin

[illegible]

*H₂S, water flows, loss of circulation, abnormal pressures, etc.

2. Casing Program (Primary Design)

Hole Size	Casing Interval		Csg. Size	Wt (PPF)	Grade	Conn	Min SF Collapse	Min SF Burst	Min SF Tension
	From	To							
17 1/2	0	975 TVD 1045	13 3/8	48.0	H40	STC	1.125	1.25	1.6
9 7/8	0	10480 TVD	7 5/8	29.7	P110	Flushmax III	1.125	1.25	1.6
6 3/4	0	TD	5 1/2	20.0	P110	Vam SG	1.125	1.25	1.6
19278 MD 11950 TVD				BLM Minimum Safety Factor			1.125	1	1.6 Dry 1.8 Wet

Fluid Filled

- All casing strings will be tested in accordance with Onshore Oil and Gas Order #2 IILB.1.h Must have table for contingency casing.
- Rustler top will be validated via drilling parameters (i.e. reduction in ROP) and surface casing setting depth revised accordingly if needed.
- A variance is requested for collapse rating on intermediate casing. Operator will keep pipe full while running casing.
- Int casing shoe will be selected based on drilling data/gamma, setting depth with be revised accordingly if needed.
- A variance is requested to wave the centralizer requirement for the Intermediate casing and production casing.
- A variance is requested to set intermediate casing in the curve if hole conditions dictate that a higher shoe strength is required.

Casing Program (Alternative Design)

Hole Size	Casing Interval		Csg. Size	Wt (PPF)	Grade	Conn	Min SF Collapse	Min SF Burst	Min SF Tension
	From	To							
17 1/2	0	1005 975 TVD	13 3/8	48.0	H40	STC	1.125	1.25	1.6
9 7/8	0	10480 TVD	8 5/8	32.0	P110	TLW	1.125	1.25	1.6
7 7/8	0	TD	5 1/2	17.0	P110	BTC	1.125	1.25	1.6
				BLM Minimum Safety Factor			1.125	1	1.6 Dry 1.8 Wet

Fluid Filled

- All casing strings will be tested in accordance with Onshore Oil and Gas Order #2 IILB.1.h Must have table for contingency casing.
- Rustler top will be validated via drilling parameters (i.e. reduction in ROP) and surface casing setting depth revised accordingly if needed.
- A variance is requested for collapse rating on intermediate casing. Operator will keep pipe full while running casing.
- Int casing shoe will be selected based on drilling data/gamma, setting depth with be revised accordingly if needed.
- A variance is requested to wave the centralizer requirement for the Intermediate casing and production casing.
- Variance requested to drill 10.625" hole instead of 9.875" for intermediate 1, the 8.625" connection will change from TLW to BTC.
- A variance is requested to set intermediate casing in the curve if hole conditions dictate that a higher shoe strength is required.

OK

	Y or N
Is casing new? If used, attach certification as required in Onshore Order #1	Y
Does casing meet API specifications? If no, attach casing specification sheet.	Y
Is premium or uncommon casing planned? If yes attach casing specification sheet.	N
Does the above casing design meet or exceed BLM's minimum standards? If not provide justification (loading assumptions, casing design criteria).	Y
Will the intermediate pipe be kept at a minimum 1/3 fluid filled to avoid approaching the collapse pressure rating of the casing?	Y
Is well located within Capitan Reef?	N
If yes, does production casing cement tie back a minimum of 50' above the Reef?	
Is well within the designated 4 string boundary.	
Is well located in SOPA but not in R-111-P?	N
If yes, are the first 2 strings cemented to surface and 3 rd string cement tied back 500' into previous casing?	
Is well located in R-111-P and SOPA?	N
If yes, are the first three strings cemented to surface?	
Is 2 nd string set 100' to 600' below the base of salt?	
Is well located in high Cave/Karst?	N
If yes, are there two strings cemented to surface?	
(For 2 string wells) If yes, is there a contingency casing if lost circulation occurs?	
Is well located in critical Cave/Karst?	N
If yes, are there three strings cemented to surface?	

3. Cementing Program (Primary Design)

Casing	# Sks	TOC	Wt. (lb/gal)	Yld. (ft ³ /sack)	Slurry Description
Surface	744	Surf	13.2	1.44	Lead: Class C Cement + additives
Int 1	638	Surf	9	3.27	Lead: Class C Cement + additives
	783	4000' above shoe	13.2	1.44	Tail: Class H / C + additives
Int 1 Two Stage w/ DV @ TVD of Delaware	819	Surf	9	3.27	1st stage Lead: Class C Cement + additives
	93	500' above shoe	13.2	1.44	1st stage Tail: Class H / C + additives
	404	Surf	9	3.27	2nd stage Lead: Class C Cement + additives
	93	500' above DV	13.2	1.44	2nd stage Tail: Class H / C + additives
Int 1 Intermediate Squeeze	As Needed	Surf	9	1.44	Squeeze Lead: Class C Cement + additives
	638	Surf	9	3.27	Lead: Class C Cement + additives
	783	4000' above shoe	13.2	1.44	Tail: Class H / C + additives
Production	60	9406	9.0	3.3	Lead: Class H / C + additives
	502	11406	13.2	1.4	Tail: Class H / C + additives

ok

100% Run
85% excess

If a DV tool is ran the depth(s) will be adjusted based on hole conditions and cement volumes will be adjusted proportionally. Slurry weights will be adjusted based on estimated fracture gradient of the formation. DV tool will be set a minimum of 50 feet below previous casing and a minimum of 200 feet above current shoe. If cement is not returned to surface during the primary cement job on the surface casing string, a planned top job will be conducted immediately after completion of the primary job.

Casing String	% Excess
Surface	50%
Intermediate 1	30%
Intermediate 1 (Two Stage)	25%
Prod	10%

3. Cementing Program (Alternative Design)

Casing	# Sk	TOC	Wt. ppg.	Yld (ft ³ /sack)	Slurry Description
Surface	744	Surf	13.2	1.44	Lead: Class C Cement + additives
Int 1	418	Surf	9	3.27	Lead: Class C Cement + additives
	465	4000' above shoe	13.2	1.44	Tail: Class H / C + additives
Int 1 Two Stage w DV @ ~4500	481	Surf	9	3.27	1st stage Lead: Class C Cement + additives
	55	500' above shoe	13.2	1.44	1st stage Tail: Class H / C + additives
	281	Surf	9	3.27	2nd stage Lead: Class C Cement + additives
	55	500' above DV	13.2	1.44	2nd stage Tail: Class H / C + additives
Int 1 Intermediate Squeeze	As Needed	Surf	13.2	1.44	Squeeze Lead: Class C Cement + additives
	418	Surf	9	3.27	Lead: Class C Cement + additives
	465	4000' above shoe	13.2	1.44	Tail: Class H / C + additives
Int 1 (10.625" Hole Size)	601	Surf	9	3.27	Lead: Class C Cement + additives
	768	4000' above shoe	13.2	1.44	Tail: Class H / C + additives
Production	117	9406	9.0	3.3	Lead: Class H / C + additives
	1042	11406	13.2	1.4	Tail: Class H / C + additives

less than 25% excess

ok

less than 25% excess

If a DV tool is ran the depth(s) will be adjusted based on hole conditions and cement volumes will be adjusted proportionally. Slurry weights will be adjusted based on estimated fracture gradient of the formation. DV tool will be set a minimum of 50 feet below previous casing and a minimum of 200 feet above current shoe. If cement is not returned to surface during the primary cement job on the surface casing string, a planned top job will be conducted immediately after completion of the primary job.

Casing String	% Excess
Surface	50%
Intermediate 1	30%
Intermediate 1 (Two Stage)	25%
Prod	10%

4. Pressure Control Equipment (Three String Design) ^{ok}

BOP installed and tested before drilling which hole?		Size?	Min. Required WP	Type	✓	Tested to:
Int 1	13-58"	5M	Annular		X	50% of rated working pressure
			Blind Ram		X	5M
			Pipe Ram			
			Double Ram		X	
			Other*			
Production	13-5/8"	5M	Annular (5M)		X	50% of rated working pressure
			Blind Ram		X	5M
			Pipe Ram			
			Double Ram		X	
			Other*			
			Annular (5M)			
			Blind Ram			
			Pipe Ram			
			Double Ram			
			Other*			
N	A variance is requested for the use of a diverter on the surface casing. See attached for schematic.					
Y	A variance is requested to run a 5 M annular on a 10M system					

ok

5. Mud Program (Three String Design)

Section	Type	Weight (ppg)
Surface	FW Gel	8.5-9
Intermediate	DBE / Cut Brine	10-10.5
Production	OBM	10-10.5

Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirements will be kept on location at all times.

What will be used to monitor the loss or gain of fluid?	PVT/Pason/Visual Monitoring
---	-----------------------------

6. Logging and Testing Procedures

Logging, Coring and Testing	
X	Will run GR/CNL from TD to surface (horizontal well - vertical portion of hole). Stated logs run will be in the Completion Report and submitted to the BLM.
	No logs are planned based on well control or offset log information.
	Drill stem test? If yes, explain.
	Coring? If yes, explain.

Additional logs planned	Interval
Resistivity	Int. shoe to KOP
Density	Int. shoe to KOP
X CBL	Production casing
X Mud log	Intermediate shoe to TD
PEX	

7. Drilling Conditions

Condition	Specify what type and where?
BH pressure at deepest TVD	6525
Abnormal temperature	No

Mitigation measure for abnormal conditions. Describe. Lost circulation material/sweeps/mud scavengers.

Hydrogen Sulfide (H₂S) monitors will be installed prior to drilling out the surface shoe. If H₂S is detected in concentrations greater than 100 ppm, the operator will comply with the provisions of Onshore Oil and Gas Order #6. If Hydrogen Sulfide is encountered measured values and formations will be provided to the BLM.

N	H ₂ S is present
Y	H ₂ S plan attached.

8. Other facets of operation

Is this a walking operation? Potentially

- 1 If operator elects, drilling rig will batch drill the surface holes and run/cement surface casing; walking the rig to next wells on the pad.
- 2 The drilling rig will then batch drill the intermediate sections and run/cement intermediate casing; the wellbore will be isolated with a blind flange and pressure gauge installed for monitoring the well before walking to the next well.
- 3 The drilling rig will then batch drill the production hole sections on the wells with OBM, run/cement production casing, and install TA caps or tubing heads for completions.

NOTE: During batch operations the drilling rig will be moved from well to well however, it will not be removed from the pad until all wells have production casing run/cemented.

Will be pre-setting casing? Potentially

- 1 Spudder rig will move in and batch drill surface hole.
 - a. Rig will utilize fresh water based mud to drill surface hole to TD. Solids control will be handled entirely on a closed loop basis.,
- 2 After drilling the surface hole section, the spudder rig will run casing and cement following all of the applicable rules and regulations (OnShore Order 2, all COAs and NMOCD regulations).
- 3 The wellhead will be installed and tested once the surface casing is cut off and the WOC time has been reached.
- 4 A blind flange with the same pressure rating as the wellhead will be installed to seal the wellbore. Pressure will be monitored with a pressure gauge installed on the wellhead.
- 5 Spudder rig operations is expected to take 4-5 days per well on a multi-well pad.
- 6 The NMOCD will be contacted and notified 24 hours prior to commencing spudder rig operations.
- 7 Drilling operations will be performed with drilling rig. At that time an approved BOP stack will be nipped up and tested on the wellhead before drilling operations commences on each well.
 - a. The NMOCD will be contacted / notified 24 hours before the drilling rig moves back on to the pad with the pre-set surface casing.

Attachments

X Directional Plan
 Other, describe

WCDSC Permian NM

Eddy County (NAD 83 NM Eastern)

Sec 25-T25S-R31E

Big Sinks Draw 25-24 Fed Com 710H

Wellbore #1

Plan: Permit Plan 1

Standard Planning Report - Geographic

11 September, 2019

Planning Report - Geographic

Database:	EDM r5000.141_Prod US	Local Co-ordinate Reference:	Well Big Sinks Draw 25-24 Fed Com 710H
Company:	WCDSC Permian NM	TVD Reference:	RKB @ 3362.50ft
Project:	Eddy County (NAD 83 NM Eastern)	MD Reference:	RKB @ 3362.50ft
Site:	Sec 25-T25S-R31E	North Reference:	Grid
Well:	Big Sinks Draw 25-24 Fed Com 710H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Permit Plan 1		

Project:	Eddy County (NAD 83 NM Eastern)		
Map System:	US State Plane 1983	System Datum:	Mean Sea Level
Geo Datum:	North American Datum 1983		
Map Zone:	New Mexico Eastern Zone		

Site:	Sec 25-T25S-R31E		
Site Position:		Northing:	403,723.39 usft
From:	Map	Easting:	724,993.28 usft
Position Uncertainty:	5.00 ft	Slot Radius:	13-3/16"
		Latitude:	32.108526
		Longitude:	-103.740178
		Grid Convergence:	0.32 °

Well:	Big Sinks Draw 25-24 Fed Com 710H		
Well Position	+N/-S	0.00 ft	Northing:
	+E/-W	0.00 ft	Easting:
Position Uncertainty		0.50 ft	Wellhead Elevation:
			Latitude:
			Longitude:
			Ground Level:

Wellbore:	Wellbore #1		
Magnetics	Model Name	Sample Date	Declination
	IGRF2015	9/11/2019	6.78
			Dip Angle
			Field Strength
			(nT)
			59.90
			47,619.34289445

Design:	Permit Plan 1		
Audit Notes:			
Version:	Phase:	PROTOTYPE	Tie On Depth:
			0.00
Vertical Section:	Depth From (TVD)	+N/-S	+E/-W
	(ft)	(ft)	(ft)
	0.00	0.00	0.00
			Direction
			(°)
			355.26

Plan Survey Tool Program	Date	9/11/2019		
Depth From	Depth To	Survey (Wellbore)	Tool Name	Remarks
(ft)	(ft)			
1	0.00	19,278.21 Permit Plan 1 (Wellbore #1)	MWD+HDGM	
			OWSG MWD + HDGM	

Plan Sections										
Measured	Inclination	Azimuth	Vertical	+N/-S	+E/-W	Dogleg	Build	Turn	TFO	Target
Depth	(°)	(°)	Depth	(ft)	(ft)	Rate	Rate	Rate	(°)	
(ft)			(ft)			(°/100usft)	(°/100usft)	(°/100usft)		
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
2,000.00	0.00	0.00	2,000.00	0.00	0.00	0.00	0.00	0.00	0.00	
2,468.65	4.69	261.39	2,468.13	-2.87	-18.94	1.00	1.00	0.00	261.39	
10,743.10	4.69	261.39	10,714.91	-104.09	-687.37	0.00	0.00	0.00	0.00	
11,055.54	0.00	0.00	11,027.00	-106.00	-700.00	1.50	-1.50	0.00	180.00	
11,405.58	0.00	0.00	11,377.04	-106.00	-700.00	0.00	0.00	0.00	0.00	
11,855.10	45.83	17.54	11,780.14	56.47	-648.64	10.20	10.20	0.00	17.54	
12,315.11	90.00	359.84	11,950.00	466.96	-596.62	10.20	9.60	-3.85	-24.62	
19,278.52	90.00	359.84	11,950.00	7,430.34	-616.33	0.00	0.00	0.00	0.00	PBHL - Big Sinks Dra

Planning Report - Geographic

Database:	EDM r5000.141_Prod US	Local Co-ordinate Reference:	Well Big Sinks Draw 25-24 Fed Com 710H
Company:	WCDSC Permian NM	TVD Reference:	RKB @ 3362.50ft
Project:	Eddy County (NAD 83 NM Eastern)	MD Reference:	RKB @ 3362.50ft
Site:	Sec 25-T25S-R31E	North Reference:	Grid
Well:	Big Sinks Draw 25-24 Fed Com 710H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Permit Plan 1		

Planned Survey									
Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Map Northing (usft)	Map Easting (usft)	Latitude	Longitude
0.00	0.00	0.00	0.00	0.00	0.00	401,246.29	725,926.51	32.101703	-103.737208
100.00	0.00	0.00	100.00	0.00	0.00	401,246.29	725,926.51	32.101703	-103.737208
200.00	0.00	0.00	200.00	0.00	0.00	401,246.29	725,926.51	32.101703	-103.737208
300.00	0.00	0.00	300.00	0.00	0.00	401,246.29	725,926.51	32.101703	-103.737208
400.00	0.00	0.00	400.00	0.00	0.00	401,246.29	725,926.51	32.101703	-103.737208
500.00	0.00	0.00	500.00	0.00	0.00	401,246.29	725,926.51	32.101703	-103.737208
600.00	0.00	0.00	600.00	0.00	0.00	401,246.29	725,926.51	32.101703	-103.737208
700.00	0.00	0.00	700.00	0.00	0.00	401,246.29	725,926.51	32.101703	-103.737208
800.00	0.00	0.00	800.00	0.00	0.00	401,246.29	725,926.51	32.101703	-103.737208
900.00	0.00	0.00	900.00	0.00	0.00	401,246.29	725,926.51	32.101703	-103.737208
1,000.00	0.00	0.00	1,000.00	0.00	0.00	401,246.29	725,926.51	32.101703	-103.737208
1,100.00	0.00	0.00	1,100.00	0.00	0.00	401,246.29	725,926.51	32.101703	-103.737208
1,200.00	0.00	0.00	1,200.00	0.00	0.00	401,246.29	725,926.51	32.101703	-103.737208
1,300.00	0.00	0.00	1,300.00	0.00	0.00	401,246.29	725,926.51	32.101703	-103.737208
1,400.00	0.00	0.00	1,400.00	0.00	0.00	401,246.29	725,926.51	32.101703	-103.737208
1,500.00	0.00	0.00	1,500.00	0.00	0.00	401,246.29	725,926.51	32.101703	-103.737208
1,600.00	0.00	0.00	1,600.00	0.00	0.00	401,246.29	725,926.51	32.101703	-103.737208
1,700.00	0.00	0.00	1,700.00	0.00	0.00	401,246.29	725,926.51	32.101703	-103.737208
1,800.00	0.00	0.00	1,800.00	0.00	0.00	401,246.29	725,926.51	32.101703	-103.737208
1,900.00	0.00	0.00	1,900.00	0.00	0.00	401,246.29	725,926.51	32.101703	-103.737208
2,000.00	0.00	0.00	2,000.00	0.00	0.00	401,246.29	725,926.51	32.101703	-103.737208
2,100.00	1.00	261.39	2,099.99	-0.13	-0.86	401,246.16	725,925.64	32.101702	-103.737211
2,200.00	2.00	261.39	2,199.96	-0.52	-3.45	401,245.77	725,923.06	32.101701	-103.737219
2,300.00	3.00	261.39	2,299.86	-1.18	-7.76	401,245.11	725,918.74	32.101700	-103.737233
2,400.00	4.00	261.39	2,399.68	-2.09	-13.80	401,244.20	725,912.71	32.101697	-103.737253
2,468.65	4.69	261.39	2,468.13	-2.87	-18.94	401,243.42	725,907.57	32.101695	-103.737269
2,500.00	4.69	261.39	2,499.37	-3.25	-21.47	401,243.04	725,905.03	32.101694	-103.737277
2,600.00	4.69	261.39	2,599.04	-4.47	-29.55	401,241.81	725,896.96	32.101691	-103.737304
2,700.00	4.69	261.39	2,698.70	-5.70	-37.63	401,240.59	725,888.88	32.101688	-103.737330
2,800.00	4.69	261.39	2,798.37	-6.92	-45.71	401,239.37	725,880.80	32.101684	-103.737356
2,900.00	4.69	261.39	2,898.04	-8.14	-53.79	401,238.14	725,872.72	32.101681	-103.737382
3,000.00	4.69	261.39	2,997.70	-9.37	-61.86	401,236.92	725,864.64	32.101678	-103.737408
3,100.00	4.69	261.39	3,097.37	-10.59	-69.94	401,235.70	725,856.56	32.101675	-103.737434
3,200.00	4.69	261.39	3,197.03	-11.81	-78.02	401,234.47	725,848.49	32.101671	-103.737460
3,300.00	4.69	261.39	3,296.70	-13.04	-86.10	401,233.25	725,840.41	32.101668	-103.737486
3,400.00	4.69	261.39	3,396.36	-14.26	-94.18	401,232.03	725,832.33	32.101665	-103.737512
3,500.00	4.69	261.39	3,496.03	-15.48	-102.26	401,230.80	725,824.25	32.101662	-103.737539
3,600.00	4.69	261.39	3,595.70	-16.71	-110.33	401,229.58	725,816.17	32.101658	-103.737565
3,700.00	4.69	261.39	3,695.36	-17.93	-118.41	401,228.36	725,808.09	32.101655	-103.737591
3,800.00	4.69	261.39	3,795.03	-19.15	-126.49	401,227.13	725,800.02	32.101652	-103.737617
3,900.00	4.69	261.39	3,894.69	-20.38	-134.57	401,225.91	725,791.94	32.101649	-103.737643
4,000.00	4.69	261.39	3,994.36	-21.60	-142.65	401,224.69	725,783.86	32.101645	-103.737669
4,100.00	4.69	261.39	4,094.02	-22.82	-150.72	401,223.46	725,775.78	32.101642	-103.737695
4,200.00	4.69	261.39	4,193.69	-24.05	-158.80	401,222.24	725,767.70	32.101639	-103.737721
4,300.00	4.69	261.39	4,293.35	-25.27	-166.88	401,221.02	725,759.63	32.101636	-103.737747
4,400.00	4.69	261.39	4,393.02	-26.49	-174.96	401,219.80	725,751.55	32.101632	-103.737773
4,500.00	4.69	261.39	4,492.69	-27.72	-183.04	401,218.57	725,743.47	32.101629	-103.737800
4,600.00	4.69	261.39	4,592.35	-28.94	-191.12	401,217.35	725,735.39	32.101626	-103.737826
4,700.00	4.69	261.39	4,692.02	-30.16	-199.19	401,216.13	725,727.31	32.101623	-103.737852
4,800.00	4.69	261.39	4,791.68	-31.39	-207.27	401,214.90	725,719.23	32.101620	-103.737878
4,900.00	4.69	261.39	4,891.35	-32.61	-215.35	401,213.68	725,711.16	32.101616	-103.737904
5,000.00	4.69	261.39	4,991.01	-33.83	-223.43	401,212.46	725,703.08	32.101613	-103.737930
5,100.00	4.69	261.39	5,090.68	-35.06	-231.51	401,211.23	725,695.00	32.101610	-103.737956
5,200.00	4.69	261.39	5,190.35	-36.28	-239.59	401,210.01	725,686.92	32.101607	-103.737982
5,300.00	4.69	261.39	5,290.01	-37.50	-247.66	401,208.79	725,678.84	32.101603	-103.738008

Planning Report - Geographic

Database:	EDM r5000.141_Prod US	Local Co-ordinate Reference:	Well Big Sinks Draw 25-24 Fed Com 710H
Company:	WCDSC Permian NM	TVD Reference:	RKB @ 3362.50ft
Project:	Eddy County (NAD 83 NM Eastern)	MD Reference:	RKB @ 3362.50ft
Site:	Sec 25-T25S-R31E	North Reference:	Grid
Well:	Big Sinks Draw 25-24 Fed Com 710H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Permit Plan 1		

Planned Survey										
Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Map Northing (usft)	Map Easting (usft)	Latitude	Longitude	
5,400.00	4.69	261.39	5,389.68	-38.73	-255.74	401,207.56	725,670.76	32.101600	-103.738035	
5,500.00	4.69	261.39	5,489.34	-39.95	-263.82	401,206.34	725,662.69	32.101597	-103.738061	
5,600.00	4.69	261.39	5,589.01	-41.17	-271.90	401,205.12	725,654.61	32.101594	-103.738087	
5,700.00	4.69	261.39	5,688.67	-42.40	-279.98	401,203.89	725,646.53	32.101590	-103.738113	
5,800.00	4.69	261.39	5,788.34	-43.62	-288.06	401,202.67	725,638.45	32.101587	-103.738139	
5,900.00	4.69	261.39	5,888.01	-44.84	-296.13	401,201.45	725,630.37	32.101584	-103.738165	
6,000.00	4.69	261.39	5,987.67	-46.07	-304.21	401,200.22	725,622.29	32.101581	-103.738191	
6,100.00	4.69	261.39	6,087.34	-47.29	-312.29	401,199.00	725,614.22	32.101577	-103.738217	
6,200.00	4.69	261.39	6,187.00	-48.51	-320.37	401,197.78	725,606.14	32.101574	-103.738243	
6,300.00	4.69	261.39	6,286.67	-49.74	-328.45	401,196.55	725,598.06	32.101571	-103.738270	
6,400.00	4.69	261.39	6,386.33	-50.96	-336.53	401,195.33	725,589.98	32.101568	-103.738296	
6,500.00	4.69	261.39	6,486.00	-52.18	-344.60	401,194.11	725,581.90	32.101564	-103.738322	
6,600.00	4.69	261.39	6,585.67	-53.41	-352.68	401,192.88	725,573.82	32.101561	-103.738348	
6,700.00	4.69	261.39	6,685.33	-54.63	-360.76	401,191.66	725,565.75	32.101558	-103.738374	
6,800.00	4.69	261.39	6,785.00	-55.85	-368.84	401,190.44	725,557.67	32.101555	-103.738400	
6,900.00	4.69	261.39	6,884.66	-57.08	-376.92	401,189.21	725,549.59	32.101551	-103.738426	
7,000.00	4.69	261.39	6,984.33	-58.30	-385.00	401,187.99	725,541.51	32.101548	-103.738452	
7,100.00	4.69	261.39	7,083.99	-59.52	-393.07	401,186.77	725,533.43	32.101545	-103.738478	
7,200.00	4.69	261.39	7,183.66	-60.75	-401.15	401,185.54	725,525.36	32.101542	-103.738505	
7,300.00	4.69	261.39	7,283.32	-61.97	-409.23	401,184.32	725,517.28	32.101539	-103.738531	
7,400.00	4.69	261.39	7,382.99	-63.19	-417.31	401,183.10	725,509.20	32.101535	-103.738557	
7,500.00	4.69	261.39	7,482.66	-64.42	-425.39	401,181.87	725,501.12	32.101532	-103.738583	
7,600.00	4.69	261.39	7,582.32	-65.64	-433.46	401,180.65	725,493.04	32.101529	-103.738609	
7,700.00	4.69	261.39	7,681.99	-66.86	-441.54	401,179.43	725,484.96	32.101526	-103.738635	
7,800.00	4.69	261.39	7,781.65	-68.09	-449.62	401,178.20	725,476.89	32.101522	-103.738661	
7,900.00	4.69	261.39	7,881.32	-69.31	-457.70	401,176.98	725,468.81	32.101519	-103.738687	
8,000.00	4.69	261.39	7,980.98	-70.53	-465.78	401,175.76	725,460.73	32.101516	-103.738713	
8,100.00	4.69	261.39	8,080.65	-71.76	-473.86	401,174.53	725,452.65	32.101513	-103.738740	
8,200.00	4.69	261.39	8,180.32	-72.98	-481.93	401,173.31	725,444.57	32.101509	-103.738766	
8,300.00	4.69	261.39	8,279.98	-74.20	-490.01	401,172.09	725,436.49	32.101506	-103.738792	
8,400.00	4.69	261.39	8,379.65	-75.43	-498.09	401,170.86	725,428.42	32.101503	-103.738818	
8,500.00	4.69	261.39	8,479.31	-76.65	-506.17	401,169.64	725,420.34	32.101500	-103.738844	
8,600.00	4.69	261.39	8,578.98	-77.87	-514.25	401,168.42	725,412.26	32.101496	-103.738870	
8,700.00	4.69	261.39	8,678.64	-79.10	-522.33	401,167.19	725,404.18	32.101493	-103.738896	
8,800.00	4.69	261.39	8,778.31	-80.32	-530.40	401,165.97	725,396.10	32.101490	-103.738922	
8,900.00	4.69	261.39	8,877.98	-81.54	-538.48	401,164.75	725,388.02	32.101487	-103.738948	
9,000.00	4.69	261.39	8,977.64	-82.76	-546.56	401,163.52	725,379.95	32.101483	-103.738975	
9,100.00	4.69	261.39	9,077.31	-83.99	-554.64	401,162.30	725,371.87	32.101480	-103.739001	
9,200.00	4.69	261.39	9,176.97	-85.21	-562.72	401,161.08	725,363.79	32.101477	-103.739027	
9,300.00	4.69	261.39	9,276.64	-86.43	-570.80	401,159.85	725,355.71	32.101474	-103.739053	
9,400.00	4.69	261.39	9,376.30	-87.66	-578.87	401,158.63	725,347.63	32.101470	-103.739079	
9,500.00	4.69	261.39	9,475.97	-88.88	-586.95	401,157.41	725,339.56	32.101467	-103.739105	
9,600.00	4.69	261.39	9,575.64	-90.10	-595.03	401,156.18	725,331.48	32.101464	-103.739131	
9,700.00	4.69	261.39	9,675.30	-91.33	-603.11	401,154.96	725,323.40	32.101461	-103.739157	
9,800.00	4.69	261.39	9,774.97	-92.55	-611.19	401,153.74	725,315.32	32.101458	-103.739183	
9,900.00	4.69	261.39	9,874.63	-93.77	-619.27	401,152.51	725,307.24	32.101454	-103.739209	
10,000.00	4.69	261.39	9,974.30	-95.00	-627.34	401,151.29	725,299.16	32.101451	-103.739236	
10,100.00	4.69	261.39	10,073.96	-96.22	-635.42	401,150.07	725,291.09	32.101448	-103.739262	
10,200.00	4.69	261.39	10,173.63	-97.44	-643.50	401,148.84	725,283.01	32.101445	-103.739288	
10,300.00	4.69	261.39	10,273.29	-98.67	-651.58	401,147.62	725,274.93	32.101441	-103.739314	
10,400.00	4.69	261.39	10,372.96	-99.89	-659.66	401,146.40	725,266.85	32.101438	-103.739340	
10,500.00	4.69	261.39	10,472.63	-101.11	-667.73	401,145.18	725,258.77	32.101435	-103.739366	
10,600.00	4.69	261.39	10,572.29	-102.34	-675.81	401,143.95	725,250.69	32.101432	-103.739392	
10,700.00	4.69	261.39	10,671.96	-103.56	-683.89	401,142.73	725,242.62	32.101428	-103.739418	
10,743.10	4.69	261.39	10,714.91	-104.09	-687.37	401,142.20	725,239.13	32.101427	-103.739430	

Planning Report - Geographic

Database	EDM r5000.141_Prod US	Local Co-ordinate Reference	Well Big Sinks Draw 25-24 Fed Com 710H
Company	WCDSC Permian NM	TVD Reference	RKB @ 3362.50ft
Project	Eddy County (NAD 83 NM Eastern)	MD Reference	RKB @ 3362.50ft
Site	Sec 25-T25S-R31E	North Reference	Grid
Well	Big Sinks Draw 25-24 Fed Com 710H	Survey Calculation Method	Minimum Curvature
Wellbore	Wellbore #1		
Design	Permit Plan 1		

Planned Survey									
Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	N/S (ft)	E/W (ft)	Map Northing (usft)	Map Easting (usft)	Latitude	Longitude
10,800.00	3.83	261.39	10,771.66	-104.72	-691.55	401,141.57	725,234.96	32.101425	-103.739443
10,900.00	2.33	261.39	10,871.51	-105.53	-696.87	401,140.76	725,229.64	32.101423	-103.739460
11,000.00	0.83	261.39	10,971.47	-105.94	-699.60	401,140.35	725,226.91	32.101422	-103.739469
11,055.54	0.00	0.00	11,027.00	-106.00	-700.00	401,140.29	725,226.51	32.101422	-103.739470
11,100.00	0.00	0.00	11,071.47	-106.00	-700.00	401,140.29	725,226.51	32.101422	-103.739470
11,200.00	0.00	0.00	11,171.47	-106.00	-700.00	401,140.29	725,226.51	32.101422	-103.739470
11,300.00	0.00	0.00	11,271.47	-106.00	-700.00	401,140.29	725,226.51	32.101422	-103.739470
11,400.00	0.00	0.00	11,371.47	-106.00	-700.00	401,140.29	725,226.51	32.101422	-103.739470
11,405.58	0.00	0.00	11,377.05	-106.00	-700.00	401,140.29	725,226.51	32.101422	-103.739470
KOP @ 11406' MD, 2590' FNL, 225' FWL									
11,500.00	9.63	17.54	11,471.02	-98.45	-697.61	401,147.83	725,228.89	32.101443	-103.739463
11,600.00	19.82	17.54	11,567.61	-74.25	-689.96	401,172.04	725,236.54	32.101509	-103.739437
11,700.00	30.02	17.54	11,658.18	-34.13	-677.28	401,212.16	725,249.23	32.101619	-103.739396
11,800.00	40.21	17.54	11,739.87	20.64	-659.96	401,266.93	725,266.54	32.101769	-103.739339
11,855.10	45.83	17.54	11,780.14	56.47	-648.64	401,302.76	725,277.87	32.101868	-103.739302
11,900.00	50.02	15.06	11,810.23	88.46	-639.31	401,334.74	725,287.20	32.101955	-103.739271
12,000.00	59.50	10.46	11,867.88	168.03	-621.48	401,414.32	725,305.02	32.102174	-103.739212
12,100.00	69.12	6.70	11,911.19	257.03	-608.18	401,503.32	725,318.33	32.102418	-103.739167
12,160.00	74.93	4.67	11,929.70	313.79	-602.54	401,560.08	725,323.97	32.102574	-103.739148
FTP @ 12160' MD, 2171' FNL, 330' FWL									
12,200.00	78.81	3.39	11,938.79	352.64	-599.81	401,598.93	725,326.70	32.102681	-103.739139
12,300.00	88.53	0.30	11,949.81	451.85	-596.64	401,698.14	725,329.87	32.102954	-103.739127
12,315.11	90.00	359.84	11,950.00	466.96	-596.62	401,713.25	725,329.89	32.102995	-103.739126
12,400.00	90.00	359.84	11,950.00	551.85	-596.86	401,798.13	725,329.65	32.103229	-103.739126
12,500.00	90.00	359.84	11,950.00	651.85	-597.14	401,898.13	725,329.36	32.103503	-103.739125
12,600.00	90.00	359.84	11,950.00	751.85	-597.43	401,998.13	725,329.08	32.103778	-103.739124
12,700.00	90.00	359.84	11,950.00	851.85	-597.71	402,098.13	725,328.80	32.104053	-103.739123
12,800.00	90.00	359.84	11,950.00	951.85	-597.99	402,198.13	725,328.51	32.104328	-103.739122
12,900.00	90.00	359.84	11,950.00	1,051.84	-598.28	402,298.13	725,328.23	32.104603	-103.739121
13,000.00	90.00	359.84	11,950.00	1,151.84	-598.56	402,398.13	725,327.95	32.104878	-103.739120
13,100.00	90.00	359.84	11,950.00	1,251.84	-598.84	402,498.13	725,327.67	32.105153	-103.739120
13,200.00	90.00	359.84	11,950.00	1,351.84	-599.12	402,598.13	725,327.38	32.105428	-103.739119
13,300.00	90.00	359.84	11,950.00	1,451.84	-599.41	402,698.13	725,327.10	32.105703	-103.739118
13,400.00	90.00	359.84	11,950.00	1,551.84	-599.69	402,798.13	725,326.82	32.105977	-103.739117
13,500.00	90.00	359.84	11,950.00	1,651.84	-599.97	402,898.13	725,326.53	32.106252	-103.739116
13,600.00	90.00	359.84	11,950.00	1,751.84	-600.26	402,998.13	725,326.25	32.106527	-103.739115
13,700.00	90.00	359.84	11,950.00	1,851.84	-600.54	403,098.13	725,325.97	32.106802	-103.739114
13,800.00	90.00	359.84	11,950.00	1,951.84	-600.82	403,198.13	725,325.68	32.107077	-103.739114
13,900.00	90.00	359.84	11,950.00	2,051.84	-601.11	403,298.13	725,325.40	32.107352	-103.739113
14,000.00	90.00	359.84	11,950.00	2,151.84	-601.39	403,398.13	725,325.12	32.107627	-103.739112
14,100.00	90.00	359.84	11,950.00	2,251.84	-601.67	403,498.12	725,324.83	32.107902	-103.739111
14,200.00	90.00	359.84	11,950.00	2,351.84	-601.96	403,598.12	725,324.55	32.108177	-103.739110
14,300.00	90.00	359.84	11,950.00	2,451.84	-602.24	403,698.12	725,324.27	32.108451	-103.739109
14,332.00	90.00	359.84	11,950.00	2,483.84	-602.33	403,730.12	725,324.18	32.108539	-103.739109
Cross section @ 14332' MD, 0' FSL, 330' FWL									
14,400.00	90.00	359.84	11,950.00	2,551.84	-602.52	403,798.12	725,323.99	32.108726	-103.739108
14,500.00	90.00	359.84	11,950.00	2,651.84	-602.81	403,898.12	725,323.70	32.109001	-103.739107
14,600.00	90.00	359.84	11,950.00	2,751.84	-603.09	403,998.12	725,323.42	32.109276	-103.739107
14,700.00	90.00	359.84	11,950.00	2,851.84	-603.37	404,098.12	725,323.14	32.109551	-103.739106
14,800.00	90.00	359.84	11,950.00	2,951.84	-603.65	404,198.12	725,322.85	32.109826	-103.739105
14,900.00	90.00	359.84	11,950.00	3,051.84	-603.94	404,298.12	725,322.57	32.110101	-103.739104
15,000.00	90.00	359.84	11,950.00	3,151.84	-604.22	404,398.12	725,322.29	32.110376	-103.739103
15,100.00	90.00	359.84	11,950.00	3,251.84	-604.50	404,498.12	725,322.00	32.110650	-103.739102
15,200.00	90.00	359.84	11,950.00	3,351.84	-604.79	404,598.12	725,321.72	32.110925	-103.739101

Planning Report - Geographic

Database:	EDM r5000.141_Prod US	Local Co-ordinate Reference:	Well Big Sinks Draw 25-24 Fed Com 710H
Company:	WCDSC Permian NM	TVD Reference:	RKB @ 3362.50ft
Project:	Eddy County (NAD 83 NM Eastern)	MD Reference:	RKB @ 3362.50ft
Site:	Sec 25-T25S-R31E	North Reference:	Grid
Well:	Big Sinks Draw 25-24 Fed Com 710H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Permit Plan 1		

Planned Survey										
Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Map Northing (usft)	Map Easting (usft)	Latitude	Longitude	
15,300.00	90.00	359.84	11,950.00	3,451.84	-605.07	404,698.12	725,321.44	32.111200	-103.739101	
15,400.00	90.00	359.84	11,950.00	3,551.83	-605.35	404,798.12	725,321.15	32.111475	-103.739100	
15,500.00	90.00	359.84	11,950.00	3,651.83	-605.64	404,898.12	725,320.87	32.111750	-103.739099	
15,600.00	90.00	359.84	11,950.00	3,751.83	-605.92	404,998.12	725,320.59	32.112025	-103.739098	
15,700.00	90.00	359.84	11,950.00	3,851.83	-606.20	405,098.11	725,320.31	32.112300	-103.739097	
15,800.00	90.00	359.84	11,950.00	3,951.83	-606.49	405,198.11	725,320.02	32.112575	-103.739096	
15,900.00	90.00	359.84	11,950.00	4,051.83	-606.77	405,298.11	725,319.74	32.112850	-103.739095	
16,000.00	90.00	359.84	11,950.00	4,151.83	-607.05	405,398.11	725,319.46	32.113124	-103.739094	
16,100.00	90.00	359.84	11,950.00	4,251.83	-607.33	405,498.11	725,319.17	32.113399	-103.739094	
16,200.00	90.00	359.84	11,950.00	4,351.83	-607.62	405,598.11	725,318.89	32.113674	-103.739093	
16,300.00	90.00	359.84	11,950.00	4,451.83	-607.90	405,698.11	725,318.61	32.113949	-103.739092	
16,400.00	90.00	359.84	11,950.00	4,551.83	-608.18	405,798.11	725,318.32	32.114224	-103.739091	
16,500.00	90.00	359.84	11,950.00	4,651.83	-608.47	405,898.11	725,318.04	32.114499	-103.739090	
16,600.00	90.00	359.84	11,950.00	4,751.83	-608.75	405,998.11	725,317.76	32.114774	-103.739089	
16,700.00	90.00	359.84	11,950.00	4,851.83	-609.03	406,098.11	725,317.47	32.115049	-103.739088	
16,800.00	90.00	359.84	11,950.00	4,951.83	-609.32	406,198.11	725,317.19	32.115323	-103.739088	
16,900.00	90.00	359.84	11,950.00	5,051.83	-609.60	406,298.11	725,316.91	32.115598	-103.739087	
17,000.00	90.00	359.84	11,950.00	5,151.83	-609.88	406,398.11	725,316.63	32.115873	-103.739086	
17,100.00	90.00	359.84	11,950.00	5,251.83	-610.17	406,498.11	725,316.34	32.116148	-103.739085	
17,200.00	90.00	359.84	11,950.00	5,351.83	-610.45	406,598.11	725,316.06	32.116423	-103.739084	
17,300.00	90.00	359.84	11,950.00	5,451.83	-610.73	406,698.11	725,315.78	32.116698	-103.739083	
17,400.00	90.00	359.84	11,950.00	5,551.83	-611.01	406,798.10	725,315.49	32.116973	-103.739082	
17,500.00	90.00	359.84	11,950.00	5,651.83	-611.30	406,898.10	725,315.21	32.117248	-103.739081	
17,600.00	90.00	359.84	11,950.00	5,751.83	-611.58	406,998.10	725,314.93	32.117523	-103.739081	
17,700.00	90.00	359.84	11,950.00	5,851.83	-611.86	407,098.10	725,314.64	32.117797	-103.739080	
17,800.00	90.00	359.84	11,950.00	5,951.83	-612.15	407,198.10	725,314.36	32.118072	-103.739079	
17,900.00	90.00	359.84	11,950.00	6,051.82	-612.43	407,298.10	725,314.08	32.118347	-103.739078	
18,000.00	90.00	359.84	11,950.00	6,151.82	-612.71	407,398.10	725,313.79	32.118622	-103.739077	
18,100.00	90.00	359.84	11,950.00	6,251.82	-613.00	407,498.10	725,313.51	32.118897	-103.739076	
18,200.00	90.00	359.84	11,950.00	6,351.82	-613.28	407,598.10	725,313.23	32.119172	-103.739075	
18,300.00	90.00	359.84	11,950.00	6,451.82	-613.56	407,698.10	725,312.95	32.119447	-103.739075	
18,400.00	90.00	359.84	11,950.00	6,551.82	-613.85	407,798.10	725,312.66	32.119722	-103.739074	
18,500.00	90.00	359.84	11,950.00	6,651.82	-614.13	407,898.10	725,312.38	32.119997	-103.739073	
18,600.00	90.00	359.84	11,950.00	6,751.82	-614.41	407,998.10	725,312.10	32.120271	-103.739072	
18,700.00	90.00	359.84	11,950.00	6,851.82	-614.69	408,098.10	725,311.81	32.120546	-103.739071	
18,800.00	90.00	359.84	11,950.00	6,951.82	-614.98	408,198.10	725,311.53	32.120821	-103.739070	
18,900.00	90.00	359.84	11,950.00	7,051.82	-615.26	408,298.10	725,311.25	32.121096	-103.739069	
19,000.00	90.00	359.84	11,950.00	7,151.82	-615.54	408,398.10	725,310.96	32.121371	-103.739068	
19,100.00	90.00	359.84	11,950.00	7,251.82	-615.83	408,498.09	725,310.68	32.121646	-103.739068	
19,200.00	90.00	359.84	11,950.00	7,351.82	-616.11	408,598.09	725,310.40	32.121921	-103.739067	
19,278.51	90.00	359.84	11,950.00	7,430.33	-616.33	408,676.60	725,310.18	32.122136	-103.739066	
PBHL & LTP @ 19279' MD, 330' FNL, 330' FWL										
19,278.52	90.00	359.84	11,950.00	7,430.34	-616.33	408,676.62	725,310.18	32.122137	-103.739066	

Design Targets										
Target Name	hit/miss target	Dip Angle (°)	Dip Dir. (°)	TVD (ft)	+N/-S (ft)	+E/-W (ft)	Map Northing (usft)	Map Easting (usft)	Latitude	Longitude
PBHL - Big Sinks Draw		0.00	0.00	0.00	7,430.35	-616.30	408,676.62	725,310.21	32.122137	-103.739066
- plan misses target center by 7455.86ft at 0.00ft MD (0.00 TVD, 0.00 N, 0.00 E)										
- Point										

Planning Report - Geographic

Database:	EDM r5000.141_Prod US	Local Co-ordinate Reference:	Well Big Sinks Draw 25-24 Fed Com 710H
Company:	WCDSC Permian NM	TVD Reference:	RKB @ 3362.50ft
Project:	Eddy County (NAD 83 NM Eastern)	MD Reference:	RKB @ 3362.50ft
Site:	Sec 25-T25S-R31E	North Reference:	Grid
Well:	Big Sinks Draw 25-24 Fed Com 710H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Permit Plan 1		

Plan Annotations				
Measured Depth (ft)	Vertical Depth (ft)	Local Coordinates		Comment
		+N/-S (ft)	+E/-W (ft)	
11,405.58	11,377.05	-106.00	-700.00	KOP @ 11406' MD, 2590' FNL, 225' FWL
12,160.00	11,929.70	313.79	-602.54	FTP @ 12160' MD, 2171' FNL, 330' FWL
14,332.00	11,950.00	2,483.84	-602.33	Cross section @ 14332' MD, 0' FSL, 330' FWL
19,278.51	11,950.00	7,430.33	-616.33	PBHL & LTP @ 19279' MD, 330' FNL, 330' FWL