

Submit Copy To Appropriate District Office
 District I - (575) 393-6161
 1625 N. French Dr., Hobbs, NM 88240
 District II - (575) 748-1283
 811 S. First St., Artesia, NM 88210
 District III - (505) 334-6178
 1000 Rio Brazos Rd., Aztec, NM 87410
 District IV - (505) 476-3460
 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
 Energy, Minerals and Natural Resources

Form C-103
 Revised August 1, 2011

OIL CONSERVATION DIVISION
 1220 South St. Francis Dr.
 Santa Fe, NM 87505

WELL API NO. 30-025-29350
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. V-648
7. Lease Name or Unit Agreement Name FORT RANCH STATE
8. Well Number 1
9. OGRID Number 190595
10. Pool name or Wildcat SAUNDERS, UPPER PERMO-PENN
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 4206' KB

SUNDRY NOTICES AND REPORTS ON WELLS
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well Gas Well Other

2. Name of Operator
 ENDEAVOR ENERGY RESOURCES, LP

3. Address of Operator
 110 NORTH MARIENFELD, SUITE 200, MIDLAND, TX 79701

4. Well Location
 Unit Letter P : 330 feet from the SOUTH line and 600 feet from the EAST line
 Section 11 Township 14S Range 33E NMPM: LEA County

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

- PERFORM REMEDIAL WORK PLUG AND ABANDON
 TEMPORARILY ABANDON CHANGE PLANS
 PULL OR ALTER CASING MULTIPLE COMPL
 DOWNHOLE COMMINGLE

SUBSEQUENT REPORT OF:

- REMEDIAL WORK ALTERING CASING
 COMMENCE DRILLING OPNS. P AND A
 CASING/CEMENT JOB

OTHER: OTHER:

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Need Current & Proposed WBD

- NOTIFY NMOCD 24 HRS. BEFORE MIRU.
- MIRU. ND WH, NU BOPE.
- SET CIBP@9700' AND SPOT 25SX OF CLASS "H" CEMENT FROM 9700'-9600'. (PERFS)
- CIRCULATE 9.5 PPG MLF AND TEST CASING.
- PERF AND SQUEEZE 60SX OF CLASS "C" CEMENT FROM 7011'6811'. WOC&TAG. (TUBB)
- PERF AND SQUEEZE 55SX OF CLASS "C" CEMENT FROM 4200'-4000'. WOC&TAG. (SHOE/SA)
- PERF AND SQUEEZE 35SX OF CLASS "C" CEMENT FROM 2665'.2565'. WOC&TAG. (B.SALT)
- PERF AND SQUEEZE 35SX OF CLASS "C" CEMENT FROM 1733'-1633'. WOC&TAG. (T.SALT)
- PERF AND SQUEEZE 60SX OF CLASS "C" CEMENT FROM 518'-318. WOC&TAG. (FW/SHOE)
- SPOT 10SX OF CLASS "C" CEMENT FROM 15'-SURFACE. (SURFACE).
- CUTOFF WELLHEAD, ANCHORS 3' BELOW SURFACE AND INSTALL DRYHOLE MARKER. TURN OVER FOR RECLAMATION.
 CLOSED LOOP CONTAINMENT SYSTEM WILL BE USED FOR FLUIDS.

Spud Date:

[Empty box for Spud Date]

Rig Release Date:

[Empty box for Rig Release Date]

RECEIVED

FEB 05 2020

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

EMNRD-OCD ARTESIA

SIGNATURE [Signature] TITLE SR. REGULATORY ANALYST DATE 02/04/20

Type or print name JAN SOUTH E-mail address: JSOUTH@EERONLINE.COM PHONE: (432)687-1575

For State Use Only

APPROVED BY: _____ TITLE _____ DATE _____

Conditions of Approval (if any):

DENIED

DENIED