

Submit 3 Copies To Appropriate District
Office

District I

1625 N. French Dr., Hobbs, NM 88240

District II

811 South First, Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

Form C-103

Revised March 25, 1999

WELL API NO.

30-015-32527

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

V-1673

7. Lease Name or Unit Agreement Name:

Lost Tank AIS State

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well:

Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator

Yates Petroleum Corporation

3. Address of Operator

105 S. 4th Street Artesia, NM 88210

4. Well Location

Unit Letter F : 2310 feet from the North line and 2310 feet from the West line

Section 36 Township 21S Range 31E NMPM Eddy County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

3578' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

MULTIPLE
COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING
CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND
ABANDONMENT ☐

CASING TEST AND
CEMENT JOB ☐

OTHER: Completion operation ☒

Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

6/16/03 - TOC 5533' (CBL). Perforate Brushy 8288'-8306' (19), 8322'-8326' (5) for a total of 24 holes. Frac with 62,000# Ottawa and 63,000 20/40 Super LC, 1500g 7-1/2% IC/HCL acid.

6/18/03 - Perforate Brushy Canyon 8166'-8174' (9). Acidize with 1000g 7-1/2% IC HCL.

6/19/03 - Squeeze perfs 8166'-8174' with 225 sx "H" Neat cement.

6/23/03 - Perforate Brushy 7508'-7516' (9), 7664'-7668' (5), 7794'-7797' (4), 7860'-7864' (5) for a total of 23 holes. Acidize 7860'-7864' with 500g 7-1/2% IC HCL.

6/25/03 - Acidize 7794'-7797' with 500g 7-1/2% IC HCL.

6/26/03 - Acidize 7664'-7668' with 500g 7-1/2% IC HCL acid. Acidize 7508'-7516' with 800g 7-1/2% IC HCL acid.

7/1/03 - Perforate Cherry Canyon 6834'-6852' (19), 6868'-6874' (7), 6940'-6950' (11).

7/2/03 - Frac with 71,400g 20 x-linked gel and Spear head 2000g 7-1/2% IC HCL acid. Pumped 90,000# 20/40 Ottawa sand, 50,000# 20/40 Super LC, 49,500# 16/30 Super LC.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Tina Huerta TITLE Regulatory Compliance Supervisor DATE July 10, 2003

Type or print name Tina Huerta

Telephone No. 505-748-1471

(This space for State use)

APPROVED BY [Signature]

TITLE District Supervisor

DATE JUL 11 2003

Conditions of approval, if any: