| Submit 3 Copies To Appropriate District Office District I | State of New Mexico Energy, Minerals and Natural Resource | Form C-103 es May 27, 2004 |
|---|--|--|
| 1625 N. French Dr., Hobbs, NM 88240 <u>District II</u> 1301 W. Grand Ave., Artesia, NM 88210 <u>District III</u> 1000 Rio Brazos Rd., Aztec, NM 87410 <u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM 87505 | OIL CONSERVATION DIVISION 1220 South St. Francis Dr. Santa Fe, NM 87505 | 5. Indicate Type of bease STATE FEE 6. State Oil & Gas Lease 100 2000 |
| (DO NOT USE THIS FORM FOR PROPO | TICES AND REPORTS ON WELLS DSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A ICATION FOR PERMIT" (FORM C-101) FOR SUCH Gas Well Other | 7. Lease Name of Unit Agree And Name of Rio Repasco OJ 8. Well Number |
| Name of Operator Yates Petroleum Corporat Address of Operator 105 S. 4 th Street, Artesia, | | 9. OGRID Number 025575 10. Pool name or Wildcat Penasco Draw; Atoka |
| 4. Well Location Unit Letter J: 1980 feet from the South line and 1980 feet from the East line Section 34 Township 18S Range 25E NMPM Eddy County 11. Elevation (Show whether DR, RKB, RT, GR, etc.) | | |
| 3485'GR Pit or Below-grade Tank Application □ or Closure □ Pit type Depth to Groundwater Distance from nearest fresh water well Distance from nearest surface water Pit Liner Thickness: mil Below-Grade Tank: Volume bbls; Construction Material | | |
| 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data | | |
| NOTICE OF II PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING | CHANGE PLANS COMMEN | SUBSEQUENT REPORT OF: L WORK |
| | | ails, and give pertinent dates, including estimated date ons: Attach wellbore diagram of proposed completion |
| Yates Petroleum Corporation plans to plug and abandon this well as follows: 1. RU safety equipment as needed. No casing recovery will be attempted. 2. Set 5-1/2" CIBP at 5619' with 35' cement on top. 3. Perforate 4 squeeze holes at 4253'. Squeeze with 40 sx Class "C" cement with additives and displace the cement down to 4203'. This well leave a plug across the Abo top. WOC and tag. 4. Perforate 4 squeeze holes at 2253'. Squeeze with 75 sx Class "C" cement with additives and displace the cement down to 1954'. This will leave a plug across the Glorieta top. WOC and tag. 5. Perforate 4 squeeze holes at 1124'. Squeeze with 40 sx Class "C" cement with additives and displace the cement down to 1024'. This will leave a plug across the intermediate casing shoe. WOC and tag. 6. Perforate 4 squeeze holes at 502'. Squeeze with 40 sx Class "C" cement with additives and displace the cement down to 402'. This well leave a plug across the surface casing shoe. WOC and tag. 7. Perforate 4 squeeze holes at 150'. Squeeze with 40 sx Class "C" cement with additives and do not displace cement. This will leave a plug from 0-150' in the production casing and in the intermediate casing forming a surface plug. WOC and tag. 8. Remove all surface equipment and weld dry hole marker per regulation. | | |
| NOTE: Yates Petroleum Corporation will use steel pits and no earth pits | | |
| | | |
| I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit or an (attached) alternative OCD-approved plan. | | |
| SIGNATURE () | | iance Supervisor DATE August 4, 2006 |
| | erta E-mail address: <u>tinah@y</u> | pcnm.com Telephone No. <u>505-748-1471</u> |
| For State Use Only APPROVED BY: Conditions of Approval (if any): | TITLE | AUG 0 8 2006DATE |



