District I
1625 N. French Dr., Hobbs, NM 88240
District II
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

THE TERMY VERMEN

State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 For drilling and production facilities, submit to appropriate NMOCD District Office.

For downstream facilities, submit to Santa Fe office

Form C-144 June 1, 2004

Pit or Below-Grade Tank Registration or Closure

Is pit or below-grade tank cov Type of action: Registration of a pit or below	ered by a "general plan"? Yes No No w-grade tank Closure of a pit or below-grade tank	
Operator: CBS OPERATING CORPORATION Telephon		STRES@AOL.COM
Address: PO Box 2236; Midland, TX 79702		
Facility or well name: NORTH SOUARE LAKE UNIT #197 API	#: 30-015-33068 U/I. or Otr/Otr A	Sec 30 T 16S R 31E
	e N32°53,989' Longitude W103°	
Surface Owner: Federal State Private Indian		NAD. 1727 1965 2
Pit	Dates and talk	
1	Below-grade tank	
Type: Drilling 🗵 Production 🗌 Disposal 🗍	Volume:bbl Type of fluid:	
Workover Emergency	Construction material: Double-walled, with leak detection? Yes If not, explain why not.	
Lined 🖾 Unlined 🗌		
Liner type: Synthetic Thickness 20 mil Clay		
Pit Volume 5000 bbl		
Depth to ground water (vertical distance from bottom of pit to seasonal	Less than 50 feet	(20 points)
high water elevation of ground water.)	50 feet or more, but less than 100 feet	(10 points)
	100 feet or more ✓	(0 points) V
	Yes	(20 points)
Wellhead protection area: (Less than 200 feet from a private domestic water source, or less than 1000 feet from all other water sources.)	No 🗸	(0 points) ✓
water source, or less than 1000 reet from an oney water sources.)	Less than 200 feet	(20 points)
Distance to surface water: (horizontal distance to all wetlands, playas,	200 feet or more, but less than 1000 feet	(10 points)
irrigation canals, ditches, and perennial and ephemeral watercourses.)	1	
	1000 feet or more ✓	(0 points)
'	Ranking Score (Total Points)	0 points
If this is a pit closure: (1) Attach a diagram of the facility showing the pit's	s relationship to other equipment and tanks. (2) Indica	ate disposal location: (check the
onsite box if you are burying in place) onsite offsite If offsite, name	of facility(3) Attach	a general description of remedial
action taken including remediation start date and end date. (4) Groundwater		
and attach sample results.	,,,,,	
(5) Attach soil sample results and a diagram of sample locations and excaval	tions.	
Additional Comments:		
A 106' X 60' 20-mil woven liner will be placed on top of the drilling pi	t (liner dimension allows 5-ft overlap on all sides). A	After liner placement, 3-ft of clean top soil
will be placed over the installed top liner.		
	. , a	
SFE A+	tached	
	raction	
I hereby certify that the information above is true and complete to the best has been/will be constructed or closed according to NMOCD guideline	of my knowledge and belief. I further certify that the SXL a general permit [], or an (attached) alternal	te above-described pit or below-grade tank
5	as Ed. a Bonorum bor mus Ed. or ma (armonos) missi and	i
Date: August 1, 2006	/ \n/ 91	' (
Printed Name/Title John Good, Consultant to CBS Operating Corp.*	Signature Stun Africa	-24
Your certification and NMOCD approval of this application/closure does not otherwise endanger public health or the environment. Nor does it relieve to regulations. *505-631-3277; jcgood4614@aol.com	not relieve the operator of liability should the contents the operator of its responsibility for compliance with an	of the pit or tank contaminate ground water or ny other federal, state, or local laws and/or
Approval:		
Printed Name/Title	Signature	Date: AUG 0 8 2006
1 1		

CBS-06-013 (North Square Lake #199)

Based on the proximity of the site to area water wells, surface water bodies, and depth to ground water from the lower most contamination, the NMOCD ranking score for the site is 0 points as presented in the table below.

NMOCD Site Ranking Table

1. GROUND WATER	2. WELLHEAD PROTECTION	3. DISTANCE TO SURFACE WATER
DEPTH TO GW <50 FEET: 20 POINTS	IF <1000' FROM WATER SOURCE, OR; <200' FROM PRIVATE	<200 HORIZONTAL FEET: 20 POINTS
DEPTH TO GW 50 TO 99 FEET: 10 POINTS	DOMESTIC WATER SOURCE: 20 POINTS	200-1000 HORIZONTAL FEET: 10 POINTS
DEPTH TO GW >100 FEET: 0 POINTS	IF >1000' FROM WATER SOURCE, OR; >200' FROM PRIVATE DOMESTIC WATER SOURCE: 0 POINTS	>1000 HORIZONTAL FEET: 0 POINTS
GROUND WATER SCORE = 0	WELLHEAD PROTECTION SCORE= 0	SURFACE WATER SCORE= 0

4.0 Ground Water Investigation

No ground water investigation was conducted, nor will be necessary as a result of this drilling pit closure process.

5.0 Proposed Pit Closure Process

3-ft of clean topsoil previously placed on top of the pit will be removed to the sides of the drilling pit utilizing a bulldozer. A 106-ft X 60-ft; 20-mil woven liner will be placed over the exposed drilling pit surface (liner dimensions provide for 5-ft overlap on all sides). After liner placement, the clean top soil will be pushed back over the drilling pit.